

# TIP TOP CEMENT BC 3004

## Safety Data Sheet

according to the Model Work Health and Safety Regulations



Issue date:19/11/2015 Revision date:31/08/2020 Supersedes:14/07/2020 Version: 2.4

SDS No: 00156-0210

### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Product name : TIP TOP CEMENT BC 3004  
Product code : 525 4088, 525 4095, 525 4105, 525 4106, 525 4130, 525 4143

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

#### 1.4. Details of manufacturer or importer

**Supplier**  
REMA TIP TOP AG  
65 Gruber Strasse  
Poing 85586  
Germany  
T +49 (0) 8121 / 707 - 100  
[info@tiptop.de](mailto:info@tiptop.de)

**Importer**  
REMA TIP TOP Australia Pty Ltd.  
3/20 Worth Street  
Chullora NSW 2190  
Australia  
T +61 2 8755 8400  
[www.rema-tiptop.com.au](http://www.rema-tiptop.com.au)

E-mail address of competent person responsible for the SDS: [sds@gbk-ingelheim.de](mailto:sds@gbk-ingelheim.de)

#### 1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

### SECTION 2: Hazard identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

|  |      |
|--|------|
| Flammable liquids, Category 2  | H225 |
| Skin corrosion/irritation, Category 2                                  | H315 |
| Serious eye damage/eye irritation, Category 2A                         | H319 |
| Specific target organ toxicity — Single exposure, Category 3, Narcosis | H336 |
| Hazardous to the aquatic environment — Chronic Hazard, Category 1      | H410 |

#### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame Exclamation mark Environment

Signal word (GHS AU) :

Danger

Contains

: Ethylacetate (30 - < 40 %); Cyclohexane (30 - < 40 %); Other substances (not contributing to the classification of this product) (≥ 10 - < 30 %); Rosin; colophony (< 1 %)

# TIP TOP CEMENT BC 3004

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0210



|                                   |  |
|-----------------------------------|--|
| Hazard statements (GHS AU)        | : H225 - Highly flammable liquid and vapour<br>H315 - Causes skin irritation<br>H319 - Causes serious eye irritation<br>H336 - May cause drowsiness or dizziness<br>H410 - Very toxic to aquatic life with long lasting effects  |
| Precautionary statements (GHS AU) | : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.<br>P264 - Wash hands thoroughly after handling.<br>P271 - Use only outdoors or in a well-ventilated area.<br>P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.<br>P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .<br>P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.<br>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.<br>P312 - Call a POISON CENTER or doctor if you feel unwell.<br>P403+P233 - Store in a well-ventilated place. Keep container tightly closed.<br>P501 - Dispose of in accordance with local and national regulations to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. |

### 2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Vapours may form explosive mixture with air.

## SECTION 3: Composition and information on ingredients

Comments : Preparation in organic solvents.

| Name  | CAS-No.    | %           | Classification according to the model Work Health and Safety Regulations (WHS Regulations)  |
|---|------------|-------------|---|
| Ethylacetate  | 141-78-6   | 30 - < 40   | Flam. Liq. 2, H225<br>Eye Irrit. 2A, H319<br>STOT SE 3, H336  |
| Cyclohexane   | 110-82-7   | 30 - < 40   | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 |
| Other substances (not contributing to the classification of this product) | -          | ≥ 10 – < 30 | Not classified  |
| Zinc oxide  | 1314-13-2  | < 5         | Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410  |
| Rosin; colophony  | 8050-09-7  | < 1         | Skin Sens. 1, H317  |
| Titanium dioxide  | 13463-67-7 | < 1         | Carc. 2, H351   |

# TIP TOP CEMENT BC 3004

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0210



### SECTION 4: First aid measures

#### 4.1. Description of necessary first-aid measures

|                                       |  |
|---------------------------------------|--|
| First-aid measures general            | : Take off immediately all contaminated clothing. Move the affected person away from the contaminated area. Call a poison center or a doctor if you feel unwell. |
| First-aid measures after inhalation   | : Move to fresh air in case of accidental inhalation of vapours or decomposition products. Call a physician immediately.   |
| First-aid measures after skin contact | : Wash off immediately with soap and plenty of water. Get medical advice if skin irritation persists.  |
| First-aid measures after eye contact  | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist.  |
| First-aid measures after ingestion    | : Do not induce vomiting. Call a physician immediately. Do not induce vomiting without medical advice.   |

#### 4.2. Symptoms caused by exposure

|                                    |                                      |
|------------------------------------|--------------------------------------|
| Symptoms/effects                   | : May cause drowsiness or dizziness. |
| Symptoms/effects after eye contact | : Causes serious eye irritation.     |
| Symptoms/effects after ingestion   | : Aspiration hazard.                 |

#### 4.3. Medical attention and special treatment

|           |                          |
|-----------|--------------------------|
| Treatment | : Treat symptomatically. |
|-----------|--------------------------|

### SECTION 5: Fire-fighting measures

#### 5.1. Extinguishing media

|                                |  |
|--------------------------------|--|
| Suitable extinguishing media   | : Water spray. Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : high volume water jet.                         |

#### 5.2. Specific hazards arising from the chemical

|  |   |
|--|---|
| General measures                                 | : In case of vapour formation use adequate respirator. Explosion free apparatus have to be used. Ensure adequate air ventilation. Evacuate personnel to a safe area. Remove ignition sources. Wear personal protective equipment. |
| Hazardous decomposition products in case of fire | : Carbon monoxide. Carbon dioxide. Hydrogen chloride gas.   |

#### 5.3. Special protective equipment and precautions for fire-fighters

|                                |  |
|--------------------------------|--|
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.   |
| Other information              | : The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Cool containers / tanks with spray water if possible. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations. |

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

|                  |   |
|------------------|---|
| General measures | : In case of vapour formation use adequate respirator. Explosion free apparatus have to be used. Ensure adequate air ventilation. Evacuate personnel to a safe area. Remove ignition sources. Wear personal protective equipment. |
|------------------|---|

##### 6.1.1. For non-emergency personnel

|                      |  |
|----------------------|--|
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours. Avoid contact with skin and eyes. |
|----------------------|--|

# TIP TOP CEMENT BC 3004

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0210



### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

### 6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Shovel or sweep up and put in a closed container for disposal.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use explosion-proof equipment. Avoid contact with skin, eyes and clothing. Vapours are heavier than air and may spread along floors.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Pay attention to explosion protection guidelines.  
Storage conditions : Keep container tightly closed in a dry, cool and well-ventilated place.  
Incompatible materials : oxidizing materials.  
Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

## SECTION 8: Exposure controls and personal protection

### 8.1. Control parameters - exposure standards

| Cyclohexane (110-82-7)                   |   |
|--|---|
| Australia - Occupational Exposure Limits |   |
| Local name                               | Cyclohexane   |
| OES TWA [1]                              | 350 mg/m <sup>3</sup>   |
| OES TWA [2]                              | 100 ppm   |
| OES STEL                                 | 1050 mg/m <sup>3</sup>  |
| OES STEL [ppm]                           | 300 ppm   |
| Regulatory reference                     | Workplace exposure standards for airborne contaminants (2019) |
| Ethylacetate (141-78-6)                  |   |
| Australia - Occupational Exposure Limits |   |
| Local name                               | Ethyl acetate (Acetic acid ethyl ester; Acetic ester)         |
| OES TWA [1]                              | 720 mg/m <sup>3</sup>   |
| OES TWA [2]                              | 200 ppm   |
| OES STEL                                 | 1440 mg/m <sup>3</sup>  |
| OES STEL [ppm]                           | 400 ppm   |
| Regulatory reference                     | Workplace exposure standards for airborne contaminants (2019) |

# TIP TOP CEMENT BC 3004

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0210



| <b>Zinc oxide (1314-13-2)</b>                   |  |
|---|--|
| <b>Australia - Occupational Exposure Limits</b> |  |
| Local name                                      | Zinc oxide   |
| OES TWA [1]                                     | 10 mg/m <sup>3</sup> dust<br>5 mg/m <sup>3</sup> fume                                    |
| OES STEL  | 10 mg/m <sup>3</sup> fume  |
| Remark (AU)                                     | (a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica. |
| Regulatory reference                            | Workplace exposure standards for airborne contaminants (2019)                            |

| <b>Silicon dioxide, amorphous (7631-86-9)</b>   |   |
|---|---|
| <b>Australia - Occupational Exposure Limits</b> |   |
| Local name                                      | Fumed silica [Silica – Amorphous]                             |
| OES TWA [1]                                     | 2 mg/m <sup>3</sup> respirable dust                           |
| Regulatory reference                            | Workplace exposure standards for airborne contaminants (2019) |

| <b>Titanium dioxide (13463-67-7)</b>            |  |
|---|--|
| <b>Australia - Occupational Exposure Limits</b> |  |
| Local name                                      | Titanium dioxide   |
| OES TWA [1]                                     | 10 mg/m <sup>3</sup> (containing no asbestos and <1% crystalline silica-inhalable dust)  |
| Remark (AU)                                     | (a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica. |
| Regulatory reference                            | Workplace exposure standards for airborne contaminants (2019)                            |

### 8.2. Biological Monitoring

No additional information available

### 8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Splash protection. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

| Type              | Material     | Permeation       | Thickness (mm) | Penetration | Standard   |
|-------------------|--------------|------------------|----------------|-------------|------------|
| protective gloves | Butyl rubber | 2 (> 30 minutes) | ≥0.7           |             | EN ISO 374 |

Eye protection : Eyewash bottle with clean water (EN 15154). Protective goggles (EN 166)

Skin and body protection : Solvent-resistant apron. EN 467

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

| Device  | Filter type | Condition | Standard |
|---|-------------|-----------|----------|
| Respiratory protective device with a gas filter | Type A      |           | EN 14387 |

Environmental exposure controls : Avoid release to the environment.

Other information : Do not inhale vapour. Wash hands before breaks and at the end of workday. Wash hands immediately after handling the product. Remove and wash contaminated clothing before re-use. Avoid contact with skin, eyes and clothing. Treat subsequently with skin cream.

# TIP TOP CEMENT BC 3004

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0210



### SECTION 9: Physical and chemical properties

|  |  |
|--|--|
| Physical state                             | : Liquid   |
| Appearance                                 | : No data available  |
| Colour                                     | : Blue   |
| Odour                                      | : Fruity   |
| Odour threshold                            | : No data available  |
| pH   | : No data available  |
| Relative evaporation rate (butylacetate=1) | : No data available  |
| Melting point / Freezing point             | : Melting point: < 30 °C   |
| Boiling point                              | : > 76 °C  |
| Flash point                                | : -18 °C   |
| Auto-ignition temperature                  | : 260 °C   |
| Flammability (solid, gas)                  | : No data available  |
| Vapour pressure                            | : Vapour pressure: 104 hPa @ 20 °C                                     |
| Relative density                           | : No data available  |
| Density                                    | : Density: 0.9 g/cm <sup>3</sup> @ 20 °C                               |
| Solubility                                 | : Not miscible. at 20 °C.  |
| Log Pow                                    | : No data available  |
| Viscosity, kinematic                       | : > 20.5 mm <sup>2</sup> /s @ 40 °C                                    |
| Viscosity, dynamic                         | : 2000 mPa·s   |
| Explosive properties                       | : No data available  |
| Explosive limits                           | : No data available  |
| Minimum ignition energy                    | : No data available  |
| VOC content                                | : 70 – 75 % VOC Directive 2004/42/EC - Decorative paints and varnishes |
| Fat solubility                             | : No data available  |
| Flow time                                  | : > 30 sec, 3 mm DIN/ISO 2431  |
| Solvent content                            | : < 80 %   |

### SECTION 10: Stability and reactivity

|                                    |  |
|------------------------------------|--|
| Reactivity                         | : No decomposition if stored normally.   |
| Chemical stability                 | : Stable under normal conditions.  |
| Possibility of hazardous reactions | : Reacts with oxidants.  |
| Conditions to avoid                | : To avoid thermal decomposition, do not overheat. Vapour/air-mixtures are explosive at intense warming. Heating can release vapours which can be ignited. |
| Incompatible materials             | : Strong oxidizing agent.  |
| Hazardous decomposition products   | : Hydrogen chloride gas. Carbon monoxide. Carbon dioxide.  |

### SECTION 11: Toxicological information

|                             |                  |
|-----------------------------|------------------|
| Acute toxicity (oral)       | : Not classified |
| Acute toxicity (dermal)     | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

| <b>Cyclohexane (110-82-7)</b>       |   |
|-------------------------------------|---|
| LD50 oral rat                       | > 12705 mg/kg                             |
| <b>Zinc oxide (1314-13-2)</b>       |   |
| LD50 oral rat                       | > 5000 mg/kg (OECD 401 method)            |
| LD50 dermal rat                     | > 2000 mg/kg bodyweight (OECD 402 method) |
| LC50 Inhalation - Rat               | > 5.7 mg/l/4h                             |
| <b>Rosin; colophony (8050-09-7)</b> |   |
| LD50 dermal                         | 2500 mg/kg                                |
| LC50 Inhalation - Rat (Dust/Mist)   | 2.3 mg/l/4h                               |

# TIP TOP CEMENT BC 3004

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0210



| <b>Titanium dioxide (13463-67-7)</b> |                                      |
|--------------------------------------|--------------------------------------|
| LD50 oral rat                        | > 10000 mg/kg                        |
| Skin corrosion/irritation            | : Causes skin irritation.            |
| Serious eye damage/irritation        | : Causes serious eye irritation.     |
| Respiratory or skin sensitisation    | : Not classified                     |
| Germ cell mutagenicity               | : Not classified                     |
| Carcinogenicity                      | : Not classified                     |
| Reproductive toxicity                | : Not classified                     |
| STOT-single exposure                 | : May cause drowsiness or dizziness. |

| <b>Cyclohexane (110-82-7)</b> |                                    |
|-------------------------------|------------------------------------|
| STOT-single exposure          | May cause drowsiness or dizziness. |

| <b>Ethylacetate (141-78-6)</b>                      |   |
|---|---|
| STOT-single exposure                                | May cause drowsiness or dizziness.  |
| STOT-repeated exposure                              | : Not classified  |
| Aspiration hazard                                   | : Not classified  |
| Potential adverse human health effects and symptoms | : Irritation of mucous membranes. High concentration of vapours may induce: headache, nausea, dizziness |

## SECTION 12: Ecological information

### 12.1. Ecotoxicity

|   |   |
|---|---|
| Hazardous to the aquatic environment, short-term (acute)  | : Not classified  |
| Hazardous to the aquatic environment, long-term (chronic) | : Very toxic to aquatic life with long lasting effects. |
| Other information   | : Do not flush into surface water or sewer system.      |

| <b>Cyclohexane (110-82-7)</b> |   |
|-------------------------------|---|
| LC50 fish 1                   | > 4 mg/l 72h, Selenastrum capricornutum |
| EC50 Daphnia 1                | 0.9 mg/l                                |
| NOEC chronic algae            | 0.94 mg/l                               |
| BCF - Fish [2]                | 31 – 129 Cyprinus carpio (Common carp)  |

| <b>Rosin; colophony (8050-09-7)</b> |          |
|-------------------------------------|----------|
| EC50 Daphnia 1                      | 4.5 mg/l |

### 12.2. Persistence and degradability

| <b>TIP TOP CEMENT BC 3004</b> |                    |
|-------------------------------|--------------------|
| Persistence and degradability | No data available. |

| <b>Zinc oxide (1314-13-2)</b> |  |
|-------------------------------|--|
| Not rapidly degradable        |  |

| <b>Rosin; colophony (8050-09-7)</b> |  |
|-------------------------------------|--|
| Not rapidly degradable              |  |

# TIP TOP CEMENT BC 3004

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0210



### 12.3. Bioaccumulative potential

#### TIP TOP CEMENT BC 3004

|                           |                    |
|---------------------------|--------------------|
| Bioaccumulative potential | No data available. |
|---------------------------|--------------------|

#### Cyclohexane (110-82-7)

|                |  |
|----------------|--|
| BCF - Fish [2] | 31 – 129 Cyprinus carpio (Common carp) |
|----------------|--|

### 12.4. Mobility in soil

#### TIP TOP CEMENT BC 3004

|                |                    |
|----------------|--------------------|
| Ecology - soil | No data available. |
|----------------|--------------------|

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : Significantly hazardous to water.

#### TIP TOP CEMENT BC 3004

|                              |       |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

#### Cyclohexane (110-82-7)

|                              |       |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

#### Ethylacetate (141-78-6)

|                              |       |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

#### Zinc oxide (1314-13-2)

|                              |       |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

#### Rosin; colophony (8050-09-7)

|                              |       |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

#### Titanium dioxide (13463-67-7)

|                              |       |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

#### Other substances (not contributing to the classification of this product)

|                              |       |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

## SECTION 13: Disposal considerations

Waste treatment methods : Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Empty containers should be taken for local recycling, recovery or waste disposal. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed of like the product.



# TIP TOP CEMENT BC 3004

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0210



### SECTION 14: Transport information

| ADG                                     | IMDG  | IATA                               |
|---|---|------------------------------------|
| <b>14.1. UN number</b>                  |   |                                    |
| Not applicable                          | 1133  | 1133                               |
| <b>14.2. UN Proper Shipping Name</b>    |   |                                    |
| Not applicable                          | ADHESIVES (Cyclohexane)                                     | Adhesives                          |
| <b>14.3. Transport hazard class(es)</b> |   |                                    |
| Not applicable                          | 3   | 3                                  |
| Not applicable                          |   |                                    |
| <b>14.4. Packing group</b>              |   |                                    |
| Not applicable                          | II  | II                                 |
| <b>14.5. Environmental hazards</b>      |   |                                    |
| Not applicable                          | Dangerous for the environment: Yes<br>Marine pollutant: Yes | Dangerous for the environment: Yes |

### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : No supplementary information available

### Transport by road and rail

Not applicable

### Transport by sea

UN-No. (IMDG) : 1133  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E2  
Packing instructions (IMDG) : P001  
Special packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC02  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1, TP8  
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS  
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS  
Stowage category (IMDG) : B

### Air transport

UN-No. (IATA) : 1133  
PCA Excepted quantities (IATA) : E2  
PCA Limited quantities (IATA) : Y341  
PCA limited quantity max net quantity (IATA) : 1L  
PCA packing instructions (IATA) : 353  
PCA max net quantity (IATA) : 5L  
CAO packing instructions (IATA) : 364  
CAO max net quantity (IATA) : 60L

# TIP TOP CEMENT BC 3004

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0210



Special provisions (IATA) : A3  
ERG code (IATA) : 3L

### 14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

#### Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : All components of this mixture are listed on or exempted from AICIS

#### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

Revision date : 31/08/2020

| Classification    |      |
|-------------------|------|
| Flam. Liq. 2      | H225 |
| Skin Irrit. 2     | H315 |
| Eye Irrit. 2A     | H319 |
| STOT SE 3         | H336 |
| Aquatic Chronic 1 | H410 |

| Full text of H-statements |  |
|---------------------------|--|
| Aquatic Acute 1           | Hazardous to the aquatic environment — Acute Hazard, Category 1        |
| Aquatic Chronic 1         | Hazardous to the aquatic environment — Chronic Hazard, Category 1      |
| Asp. Tox. 1               | Aspiration hazard, Category 1  |
| Carc. 2                   | Carcinogenicity, Category 2  |
| Eye Irrit. 2A             | Serious eye damage/eye irritation, Category 2A                         |
| Flam. Liq. 2              | Flammable liquids, Category 2  |
| Skin Irrit. 2             | Skin corrosion/irritation, Category 2                                  |
| Skin Sens. 1              | Skin sensitisation, Category 1   |
| STOT SE 3                 | Specific target organ toxicity — Single exposure, Category 3, Narcosis |
| H225                      | Highly flammable liquid and vapour                                     |
| H304                      | May be fatal if swallowed and enters airways                           |
| H315                      | Causes skin irritation   |

# TIP TOP CEMENT BC 3004

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0210



| Full text of H-statements |  |
|---------------------------|--|
| H317                      | May cause an allergic skin reaction                  |
| H319                      | Causes serious eye irritation                        |
| H336                      | May cause drowsiness or dizziness                    |
| H351                      | Suspected of causing cancer                          |
| H400                      | Very toxic to aquatic life                           |
| H410                      | Very toxic to aquatic life with long lasting effects |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.