

TIP TOP CEMENT OTR

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Issue date:16/05/2017 Revision date:22/09/2020 Version: 1.3

SDS No: 00156-0359



SECTION 1: Identification : Product identifier and chemical identity

1.1. Product identifier

Product form : Mixture
Product name : TIP TOP CEMENT OTR
Product code : 515 9430, 515 9431, 515 9440

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

1.4. Supplier's details

Supplier

REMA TIP TOP AG
65 Gruber Strasse
85586 Poing - Germany
T +49 (0) 8121 / 707 - 100

Importer

REMA TIP TOP Australia Pty Ltd.
3 - 7 Ironbark Close
Warabrook NSW 2304 - Australia
T +61-2-4935-0200
www.rema-tiptop.com.au

E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2 H225
Serious eye damage/eye irritation, Category 2A H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411

2.2. Label elements

Hazard pictograms (GHS AU) :



Flame Exclamation mark Environment

Signal word (GHS AU) : Danger

Contains : ethylacetate ($\geq 60 - < 65$ %); Hydrocarbons, C6-C7, isoalkanes, cycloalkanes, $< 3\%$ n-hexane ($\geq 20 - < 25$ %); Other substances (not contributing to the classification of this product) ($\geq 10 - < 20$ %); Zinc bis(N-ethyl-N-phenyldithiocarbamate) ($\geq 1 - < 3$ %); N-Cyclohexyl-N-ethylamine ($\geq 0.5 - < 1$ %); Zinc oxide ($\geq 0.3 - < 0.5$ %)

Hazard statements (GHS AU) : H225 - Highly flammable liquid and vapour
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (GHS AU) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

TIP TOP CEMENT OTR

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0359



P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER/doctor if you feel unwell.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P391 - Collect spillage
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P235 - Keep cool.

Additional hazard statements (GHS AU) : AUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Other hazards not contributing to the classification : Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

Comments : Preparation in organic solvents.
Ethyl acetate.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
ethylacetate	141-78-6	≥ 60 – < 65	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Hydrocarbons, C6-C7, isoalkanes, cycloalkanes, < 3% n-hexane	92062-15-2	≥ 20 – < 25	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Other substances (not contributing to the classification of this product)		≥ 10 – < 20	Not classified
Natural Rubber	9006-04-6	≥ 10 – < 15	Not classified
Zinc bis(N-ethyl-N-phenyldithiocarbamate)	14634-93-6	≥ 1 – < 3	Not classified
Titanium dioxide	13463-67-7	< 1	Carc. 2, H351
N-Cyclohexyl-N-ethylamine	5459-93-8	≥ 0.5 – < 1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Aquatic Chronic 3, H412
Silica, amorphous, fumed, crystalline-free	112945-52-5	≥ 0.3 – < 0.5	Not classified
Zinc oxide	1314-13-2	≥ 0.3 – < 0.5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Poly(1,2-dihydro-2,2,4-trimethylquinoline)	26780-96-1	≥ 0.1 – < 0.3	Aquatic Chronic 3, H412

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Take off immediately all contaminated clothing. In the event of persistent symptoms receive medical treatment. Move the affected person away from the contaminated area.

First-aid measures after inhalation : Move to fresh air in case of accidental inhalation of vapours or decomposition products. Call a physician immediately.

First-aid measures after skin contact : Wash off immediately with soap and plenty of water. Get medical advice if skin irritation persists.

First-aid measures after eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist.

First-aid measures after ingestion : Do not induce vomiting. Rinse mouth out with water. Drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician immediately. Do not induce vomiting without medical advice.

4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Aspiration hazard. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

TIP TOP CEMENT OTR

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0359



SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Water spray. Dry powder. Carbon dioxide.
Unsuitable extinguishing media : high volume water jet.

5.2. Special hazards arising from the substance or mixture

General measures : In case of vapour formation use adequate respirator. Ensure adequate air ventilation. Use personal protective clothing. Use explosion-proof equipment.
Hazardous decomposition products in case of fire : In case of fire: Carbon monoxide. Carbon dioxide.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Hazchem Code : * 3Y
Other information : Vapours are heavier than air and may spread along floors. Cool containers / tanks with spray water if possible. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations. The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : In case of vapour formation use adequate respirator. Ensure adequate air ventilation. Use personal protective clothing. Use explosion-proof equipment.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Shovel or sweep up and put in a closed container for disposal.

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

Precautions for safe handling : Use explosion-proof equipment. Take precautionary measures against static discharge. Do not smoke. Keep away from heat and sources of ignition. Vapours are heavier than air and may spread along floors. Use only outdoors or in a well-ventilated area. Keep container tightly closed.
Hygiene measures : Do not inhale vapour. Treat subsequently with skin cream. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Pay attention to explosion protection guidelines. Ground/bond container and receiving equipment.
Storage conditions : Keep away from sources of ignition. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Incompatible materials : Refer to Section 10 on Incompatible Materials.
Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

ethylacetate (141-78-6)	
Australia - Occupational Exposure Limits	
Local name	Ethyl acetate (Acetic acid ethyl ester; Acetic ester)
TWA (mg/m ³)	720 mg/m ³
TWA (ppm)	200 ppm

TIP TOP CEMENT OTR

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0359



ethylacetate (141-78-6)	
STEL (mg/m ³)	1440 mg/m ³
STEL (ppm)	400 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
Zinc oxide (1314-13-2)	
Australia - Occupational Exposure Limits	
Local name	Zinc oxide
TWA (mg/m ³)	10 mg/m ³ dust 5 mg/m ³ fume
STEL (mg/m ³)	10 mg/m ³ fume
Remark (AU)	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
Titanium dioxide (13463-67-7)	
Australia - Occupational Exposure Limits	
Local name	Titanium dioxide
TWA (mg/m ³)	10 mg/m ³ (containing no asbestos and <1% crystalline silica-inhalable dust)
Remark (AU)	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls : Pay attention to explosion protection guidelines. Ensure good ventilation of the work station.

8.4. Personal protective equipment

Hand protection : This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Natural rubber	1 (> 10 minutes)	≥0.6		
Chemically resistant protective gloves	Butyl rubber	3 (> 60 minutes)	≥ 0.7		

Eye protection : Tightly fitting goggles (EN 166). Eyewash bottle with clean water (EN 15154)

Skin and body protection : Solvent-resistant apron. EN 467

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A		EN 14387

Environmental exposure controls : Avoid release to the environment.

Other information : Do not inhale vapour. Wash hands before breaks and at the end of workday. Wash hands immediately after handling the product. Do not eat, drink or smoke during use. Treat subsequently with skin cream.

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Blue
Odour	: Ester like
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: No data available

TIP TOP CEMENT OTR

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0359



Boiling point	: > 35 °C
Flash point	: -20 °C DIN EN ISO 3679
Auto-ignition temperature	: 460 °C
Flammability (solid, gas)	: No data available
Vapour pressure	: Vapour pressure : 100 hPa @ 20 °C
Relative density	: No data available
Density	: Density : 0.88 g/cm ³ @ 20 °C
Solubility	: Water: Not miscible
Log Pow	: No data available
Viscosity, kinematic	: 3740 – 3820 mm ² /s @ 40 °C
Viscosity, dynamic	: 4500 – 6500 mPa·s
Explosive properties	: Product is not explosive. May form flammable/explosive vapour-air mixture.
Oxidising properties	: Non oxidizing
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 80 – 85 %
Fat solubility	: No data available
Additional information	: Flow time 385 s @23°C, 6 DIN EN ISO 2431. Solvent content <85%. Solvent separation test (%) < 3

SECTION 10: Stability and reactivity

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: oxidizing materials.
Conditions to avoid	: Vapour/air-mixtures are explosive at intense warming. Heating can release vapours which can be ignited. To avoid thermal decomposition, do not overheat.
Incompatible materials	: Nitrous acid and other nitrosating agents. Oxidizing agent.
Hazardous decomposition products	: Carbon monoxide. Carbon dioxide. An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

SECTION 11: Toxicological information

Acute toxicity	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Zinc oxide (1314-13-2)

LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402 method)
LC50 Inhalation - Rat	> 5.7 mg/l/4h

Silica, amorphous, fumed, crystalline-free (112945-52-5)

LD50 oral rat	3160 mg/kg
---------------	------------

Titanium dioxide (13463-67-7)

LD50 oral rat	> 10000 mg/kg
---------------	---------------

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified.

TIP TOP CEMENT OTR

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0359



Potential adverse human health effects and symptoms	: Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product. High concentration of vapours may induce: headache, nausea, dizziness
Other information	: An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.
Other information	: Do not flush into surface water or sewer system.

12.2. Persistence and degradability

TIP TOP CEMENT OTR	
Persistence and degradability	No data available.
Zinc oxide (1314-13-2)	
Not rapidly degradable	
Hydrocarbons, C6-C7, isoalkanes, cycloalkanes, < 3% n-hexane (92062-15-2)	
Not rapidly degradable	

12.3. Bioaccumulative potential

TIP TOP CEMENT OTR	
Bioaccumulative potential	No data available.

12.4. Mobility in soil

TIP TOP CEMENT OTR	
Ecology - soil	No data available.

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: Slightly hazardous to water.

TIP TOP CEMENT OTR	
Fluorinated greenhouse gases	False
ethylacetate (141-78-6)	
Fluorinated greenhouse gases	False
Zinc bis(N-ethyl-N-phenyldithiocarbamate) (14634-93-6)	
Fluorinated greenhouse gases	False
N-Cyclohexyl-N-ethylamine (5459-93-8)	
Fluorinated greenhouse gases	False
Zinc oxide (1314-13-2)	
Fluorinated greenhouse gases	False
Poly(1,2-dihydro-2,2,4-trimethylquinoline) (26780-96-1)	
Fluorinated greenhouse gases	False
Silica, amorphous, fumed, crystalline-free (112945-52-5)	
Fluorinated greenhouse gases	False
Hydrocarbons, C6-C7, isoalkanes, cycloalkanes, < 3% n-hexane (92062-15-2)	
Fluorinated greenhouse gases	False
Natural Rubber (9006-04-6)	
Fluorinated greenhouse gases	False
Titanium dioxide (13463-67-7)	
Fluorinated greenhouse gases	False

TIP TOP CEMENT OTR

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0359



Other substances (not contributing to the classification of this product)

Fluorinated greenhouse gases False

SECTION 13: Disposal considerations

- Waste treatment methods : Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Product/Packaging disposal recommendations : Packaging that cannot be cleaned should be disposed of like the product. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Empty containers should be taken for local recycling, recovery or waste disposal.
- Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

ADG	IMDG	IATA
14.1. UN number		
1133	1133	1133
14.2. UN proper shipping name		
ADHESIVES	ADHESIVES	Adhesives
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		
III - substances presenting low danger	III	III
14.5. Environmental hazards		
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes

14.6. Special precautions for user

- Specific storage requirement : No data available
- Shock sensitivity : No data available

14.7. Additional information

- Other information : No supplementary information available

Transport by road and rail

- UN-No. (ADG) : 1133
- Special provision (ADG) : 223
- Limited quantities (ADG) : 5l
- Packing instructions (ADG) : P001, IBC03, LP01
- Special packing provisions (ADG) : PP1
- Portable tank and bulk container instructions (ADG) : T2
- Portable tank and bulk container special provisions (ADG) : TP1

Transport by sea

- UN-No. (IMDG) : 1133
- Transport regulations (IMDG) : Transport in accordance with section 2.3.2.5 of the IMDG (viscous substance) may be applied
- Special provisions (IMDG) : 223, 955
- Limited quantities (IMDG) : 5 L
- Excepted quantities (IMDG) : E1
- Packing instructions (IMDG) : P001, LP01
- EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
- EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
- Properties and observations (IMDG) : Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

TIP TOP CEMENT OTR

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0359



Air transport

UN-No. (IATA)	: 1133
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 3Y

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

Australian Inventory of Chemical Substances (AICS) status : All the chemicals contained in this product are listed on the AICS

15.2. International agreements

No additional information available

SECTION 16: Any other relevant information

Abbreviations and acronyms	: ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways IATA - International Air Transport Association IMDG - International Maritime Dangerous Goods RID - Regulations concerning the International Carriage of Dangerous Goods by Rail DOT - Department of Transport TDG - Transportation of Dangerous Goods REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 GHS - Globally Harmonized System of Classification, Labelling and Packaging of Chemicals IARC - International Agency for Research on Cancer vPvB - Very Persistent and Very Bioaccumulative PBT - Persistent Bioaccumulative Toxic PNEC - Predicted No-Effect Concentration CAS - CAS (Chemical Abstracts Service) number IBC-Code - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk ATE - Acute Toxicity Estimate CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 BCF - Bioconcentration factor MARPOL 73/78 - MARPOL 73/78: International Convention for the Prevention of Pollution From Ships ADG - Transport of Australian Dangerous Goods
Revision date	: 22/09/2020
Other information	: Data of sections 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge. The delivery specifications are contained in the corresponding product sheet. This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

Classification:

Flam. Liq. 2	H225
--------------	------

TIP TOP CEMENT OTR

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0359



Eye Irrit. 2A	H319
STOT SE 3	H336
Aquatic Chronic 2	H411

Full text of H-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.