

# TIP TOP CEMENT SC-BL-NF

## Safety Data Sheet

according to the WHS Regulations  
Issue date: 19/04/2023 Version: 1.0  
SDS No: 00156-0523



### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Product name : TIP TOP CEMENT SC-BL-NF  
Product code : 515 0035, 515 0815, 515 0358, 515 0341, 515 0372, 515 0373, 515 0387, 515 0389, 515 0406, 515 0407, 515 0506, 515 0507, 515 0508, 515 0509

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

#### 1.4. Details of manufacturer or importer

##### Supplier

REMA TIP TOP AG  
65 Gruber Strasse  
Poing 85586  
Germany  
T +49 (0) 8121 / 707 - 100  
[info@tiptop.de](mailto:info@tiptop.de)

##### Importer

REMA TIP TOP Australia Pty Ltd.  
3/20 Worth Street  
Chullora NSW 2190  
Australia  
T +61 2 8755 8400  
[www.rema-tiptop.com.au](http://www.rema-tiptop.com.au)

E-mail address of competent person responsible for the SDS: [sds@gbk-ingelheim.de](mailto:sds@gbk-ingelheim.de)

#### 1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

### SECTION 2: Hazard identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Skin sensitisation, Category 1	H317
Germ cell mutagenicity, Category 2	H341
Carcinogenicity, Category 1B	H350
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

#### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Exclamation mark    Health hazard

Signal word (GHS AU) :

Danger

Contains :

Trichloroethylene (< 95 %)

Hazard statements (GHS AU) :

H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H341 - Suspected of causing genetic defects

# TIP TOP CEMENT SC-BL-NF

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0523

### Precautionary statements (GHS AU)

H350 - May cause cancer  
H412 - Harmful to aquatic life with long lasting effects  
: P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P261 - Avoid breathing vapours.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 - Call a POISON CENTER, a doctor if you feel unwell.  
P333+P313 - If skin irritation or rash occurs: Get medical attention.  
P337+P313 - If eye irritation persists: Get medical attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition and information on ingredients

Comments : Preparation based on :  
Trichloroethylene.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Trichloroethylene	79-01-6	< 95	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350 STOT SE 3, H336 Aquatic Chronic 3, H412
Other substances (not contributing to the classification of this product)	-	< 10	Not classified
Zinc bis(N-ethyl-N-phenyldithiocarbamate)	14634-93-6	< 2,5	Not classified
N-Cyclohexyl-N-ethylamine	5459-93-8	< 1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Aquatic Chronic 3, H412
Zinc oxide	1314-13-2	< 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

# TIP TOP CEMENT SC-BL-NF

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0523

### SECTION 4: First aid measures

#### 4.1. Description of necessary first-aid measures

First-aid measures general	: Take off immediately all contaminated clothing. Move the affected person away from the contaminated area. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Move to fresh air in case of accidental inhalation of vapours or decomposition products. Call a physician immediately.
First-aid measures after skin contact	: Wash off immediately with soap and plenty of water. Get medical advice if skin irritation persists.
First-aid measures after eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately. Do not induce vomiting without medical advice. Give a slurry of activated charcoal in water to drink. Attention. Beware, danger of aspiration.

#### 4.2. Symptoms caused by exposure

Symptoms/effects after inhalation	: Aspiration hazard. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Chronic symptoms	: May cause cancer. Suspected of causing genetic defects.

#### 4.3. Medical attention and special treatment

Treatment	: Treat symptomatically.
-----------	--------------------------

### SECTION 5: Fire-fighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide. Product does not burn, fire-extinguishing activities according to surrounding.
Unsuitable extinguishing media	: high volume water jet.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Non flammable.
Explosion hazard	: Product is not explosive.
General measures	: In case of vapour formation use adequate respirator. Ensure adequate air ventilation. Remove ignition sources.
Hazardous decomposition products in case of fire	: Carbon monoxide. Carbon dioxide. Chlorine. Hydrogen chloride gas. Traces of. Phosgene.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Hazchem Code	: 2Z
Other information	: Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations. Collect contaminated firefighting water separately, must not be discharged into the drains.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: In case of vapour formation use adequate respirator. Ensure adequate air ventilation. Remove ignition sources.
------------------	--

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Do not breathe vapours. Avoid contact with skin, eyes and clothing.
----------------------	---

# TIP TOP CEMENT SC-BL-NF

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0523

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Do not discharge into the subsoil/soil. Do not discharge into the drains/surface waters/groundwater.

### 6.3. Methods and materials for containment and cleaning up

For containment : Dike and contain spill.  
Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Shovel or sweep up and put in a closed container for disposal.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin, eyes and clothing. Keep container tightly closed. Vapours are heavier than air and may spread along floors. Keep away from heat and sources of ignition.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed in a dry, cool and well-ventilated place.  
Incompatible materials : oxidizing materials. Aluminium. Metallic powders. alkali metals. alkaline earth metals.  
Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

## SECTION 8: Exposure controls and personal protection

### 8.1. Control parameters - exposure standards

Zinc oxide (1314-13-2)	
Australia - Occupational Exposure Limits	
Local name	Zinc oxide
OES TWA [1]	5 mg/m <sup>3</sup> fume 10 mg/m <sup>3</sup> dust
OES STEL	10 mg/m <sup>3</sup> fume
Remark (AU)	Dust: (a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

### 8.2. Biological Monitoring

Monitoring methods : A specific exposure sampling method is not available.

### 8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
protective gloves	Viton	6 (> 480 minutes)	≥0.7		EN ISO 374

# TIP TOP CEMENT SC-BL-NF

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0523

Eye protection : Eyewash bottle with clean water (EN 15154)

Type	Field of application	Characteristics	Standard
Protective goggles (EN 166)	Liquid splashes may occur		EN 166

Skin and body protection :

Type	Standard
Long sleeved protective clothing	EN ISO 6530

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A - High-boiling (>65 °C) organic compounds	In case of inadequate ventilation wear	EN 14387

Environmental exposure controls : Avoid release to the environment.

Other information : Do not inhale vapour. Avoid contact with skin and eyes. Wash hands before breaks and at the end of workday. Wash hands immediately after handling the product. Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Blue
Odour	: Sweet
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: -86.4 °C Trichloroethylene
Boiling point	: 87 °C Trichloroethylene
Flash point	: Not applicable According to PTB instructions, trichloroethylene has no flashpoint; however, vapour and air mixtures are flammable under a stronger energy influx.
Auto-ignition temperature	: 410 °C Trichloroethylene
Flammability (solid, gas)	: No data available
Vapour pressure	: Vapour pressure: 77 hPa Trichloroethylene
Relative density	: Relative vapour density at 20°C: 4.54 Trichloroethylene
Density	: Density: 1.41 g/cm <sup>3</sup> @ 20 °C
Solubility	: Water: Not miscible ,20°C
Log Pow	: No data available
Viscosity, dynamic	: 11000 mPa·s
Explosive properties	: Product is not explosive.
Oxidising properties	: Not oxidising
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 90 – 95 %
Fat solubility	: No data available
Additional information	: Solvent content 90-95%

## SECTION 10: Stability and reactivity

Reactivity	: No decomposition if stored normally.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Reacts with oxidants. alkali metals.
Conditions to avoid	: Above 120°C, a thermic decomposition may take place.
Incompatible materials	: Strong oxidizing agent. alkali metals. Aluminium. Metallic powders.
Hazardous decomposition products	: No hazardous decomposition products known. Thermal decomposition generates : Carbon oxides (CO, CO <sub>2</sub> ). Chlorine. Hydrogen chloride gas. Traces of. Phosgene.

# TIP TOP CEMENT SC-BL-NF

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0523

### SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

<b>Zinc oxide (1314-13-2)</b>	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 oral	5000 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402 method)
LD50 dermal	5000 mg/kg
LC50 Inhalation - Rat	> 5.7 mg/l/4h
LC50 Inhalation - Rat (Dust/Mist)	5.7 mg/l/4h

<b>Trichloroethylene (79-01-6)</b>	
LD50 oral rat	5400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	12500 ppm/4h
ATE AU (oral)	5400 mg/kg bodyweight
ATE AU (vapours)	12500 mg/l/4h
ATE AU (dust,mist)	12500 mg/l/4h

<b>N-Cyclohexyl-N-ethylamine (5459-93-8)</b>	
ATE AU (oral)	500 mg/kg bodyweight
ATE AU (dermal)	300 mg/kg bodyweight
ATE AU (gases)	4500 ppmv/4h
ATE AU (vapours)	11 mg/l/4h
ATE AU (dust,mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Suspected of causing genetic defects.  
Carcinogenicity : May cause cancer.  
Reproductive toxicity : Not classified  
STOT-single exposure : May cause drowsiness or dizziness.

<b>Trichloroethylene (79-01-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified  
Aspiration hazard : Not classified

<b>Zinc oxide (1314-13-2)</b>	
Animal studies and expert judgment for classification	False

<b>Trichloroethylene (79-01-6)</b>	
Animal studies and expert judgment for classification	False

<b>Zinc bis(N-ethyl-N-phenyldithiocarbamate) (14634-93-6)</b>	
Animal studies and expert judgment for classification	False

# TIP TOP CEMENT SC-BL-NF

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0523

<b>N-Cyclohexyl-N-ethylamine (5459-93-8)</b>	
Animal studies and expert judgment for classification	False
<b>Other substances (not contributing to the classification of this product)</b>	
Animal studies and expert judgment for classification	False

Potential adverse human health effects and symptoms : Components of the product may be absorbed into the body through the skin. High concentration of vapours may induce: headache, nausea, dizziness. Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product. Risk of lungs oedema. Skin contact or inhalation of solvents contained in this product may cause

## SECTION 12: Ecological information

### 12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.  
Other information : Do not flush into surface water or sewer system.

<b>Trichloroethylene (79-01-6)</b>	
LC50 fish 1	42.4 mg/l (96 h), Pimephales promelas
EC50 Daphnia 1	47 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Log Pow	2.53

### 12.2. Persistence and degradability

<b>TIP TOP CEMENT SC-BL-NF</b>	
Persistence and degradability	No data available.
<b>Zinc oxide (1314-13-2)</b>	
Not rapidly degradable	
<b>Trichloroethylene (79-01-6)</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	2.4 % (14 d) (OECD 301C method)

### 12.3. Bioaccumulative potential

<b>TIP TOP CEMENT SC-BL-NF</b>	
Bioaccumulative potential	No data available.
<b>Trichloroethylene (79-01-6)</b>	
Log Pow	2.53
Bioaccumulative potential	Low bio-accumulation can be estimated because of low log Po/w.

### 12.4. Mobility in soil

<b>TIP TOP CEMENT SC-BL-NF</b>	
Ecology - soil	No data available.

# TIP TOP CEMENT SC-BL-NF

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0523

Trichloroethylene (79-01-6)	
Ecology - soil	Expected to be highly mobile in soil.
Log Pow	2.53

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : Significantly hazardous to water.

TIP TOP CEMENT SC-BL-NF	
Fluorinated greenhouse gases	False
Zinc oxide (1314-13-2)	
Fluorinated greenhouse gases	False
Trichloroethylene (79-01-6)	
Fluorinated greenhouse gases	False
Zinc bis(N-ethyl-N-phenyldithiocarbamate) (14634-93-6)	
Fluorinated greenhouse gases	False
N-Cyclohexyl-N-ethylamine (5459-93-8)	
Fluorinated greenhouse gases	False
Other substances (not contributing to the classification of this product)	
Fluorinated greenhouse gases	False

## SECTION 13: Disposal considerations

Waste treatment methods : Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Empty containers should be taken for local recycling, recovery or waste disposal. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed of like the product.

## SECTION 14: Transport information

### 14.1. UN number

UN-No. (ADG) : 1710  
UN-No. (IMDG) : 1710  
UN-No. (IATA) : 1710

### 14.2. UN Proper Shipping Name

Proper Shipping Name (ADG) : TRICHLOROETHYLENE (SOLUTION)  
Proper Shipping Name (IMDG) : TRICHLOROETHYLENE (SOLUTION)  
Proper Shipping Name (IATA) : Trichloroethylene (SOLUTION)

### 14.3. Transport hazard class(es)

**ADG**  
Transport hazard class(es) (ADG) : 6.1  
Danger labels (ADG) : 6.1



# TIP TOP CEMENT SC-BL-NF

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0523



### IMDG

Transport hazard class(es) (IMDG) : 6.1  
Danger labels (IMDG) : 6.1



### IATA

Transport hazard class(es) (IATA) : 6.1  
Danger labels (IATA) : 6.1



### 14.4. Packing group

Packing group (ADG) : III - Substances presenting low danger  
Packing group (IMDG) : III  
Packing group (IATA) : III

### 14.5. Environmental hazards

Marine pollutant : No  
Dangerous for the environment : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : No supplementary information available

### Transport by road and rail

UN-No. (ADG) : 1710  
Limited quantities (ADG) : 5L  
Excepted quantities (ADG) : E1  
Packing instructions (ADG) : P001, IBC03, LP01  
Portable tank and bulk container instructions (ADG) : T4  
Portable tank and bulk container special provisions (ADG) : TP1

### Transport by sea

UN-No. (IMDG) : 1710  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : P001, LP01  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1  
EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE  
EmS-No. (Spillage) : S-A - SPILLAGE SCHEDULE Alfa - TOXIC SUBSTANCES  
Stowage category (IMDG) : A

# TIP TOP CEMENT SC-BL-NF

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0523

Stowage and handling (IMDG) : SW2  
Segregation (IMDG) : SGG10

### Air transport

UN-No. (IATA) : 1710  
PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y642  
PCA limited quantity max net quantity (IATA) : 2L  
PCA packing instructions (IATA) : 655  
PCA max net quantity (IATA) : 60L  
CAO packing instructions (IATA) : 663  
CAO max net quantity (IATA) : 220L  
ERG code (IATA) : 6A

### 14.8. Hazchem or Emergency Action Code

Hazchem Code : 2Z

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

#### Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : All components of this mixture are listed on or exempted from AICIS

#### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

Abbreviations and acronyms : ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
IATA - International Air Transport Association  
IMDG - International Maritime Dangerous Goods  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
DOT - Department of Transport  
TDG - Transportation of Dangerous Goods  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
GHS - Globally Harmonized System of Classification, Labelling and Packaging of Chemicals  
IARC - International Agency for Research on Cancer  
vPvB - Very Persistent and Very Bioaccumulative  
PBT - Persistent Bioaccumulative Toxic  
PNEC - Predicted No-Effect Concentration  
CAS - CAS (Chemical Abstracts Service) number  
IBC-Code - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk  
ATE - Acute Toxicity Estimate  
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
BCF - Bioconcentration factor  
MARPOL 73/78 - MARPOL 73/78: International Convention for the Prevention of Pollution From Ships  
ADG - Transport of Australian Dangerous Goods

# TIP TOP CEMENT SC-BL-NF

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0523

Other information : Data of sections 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge. The delivery specifications are contained in the corresponding product sheet. This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

Classification	
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Skin Sens. 1	H317
Muta. 2	H341
Carc. 1B	H350
STOT SE 3	H336
Aquatic Chronic 3	H412

Full text of H-statements	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Carc. 1B	Carcinogenicity, Category 1B
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects

# TIP TOP CEMENT SC-BL-NF

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0523

Full text of H-statements	
H350	May cause cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects