

# TIP TOP CEMENT SC 4000

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Issue date:20/11/2015 Revision date:23/07/2021 Version: 2.6

SDS No: 00156-0119



### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Product name : TIP TOP CEMENT SC 4000  
Product code : 5517 8009, 525 2509; 525 2516; 525 2523; 525 2530; 525 2554; 525 2592; 525 2602; 525 2619; 525 2633; 525 2657; 525 2688; 525 2695; 525 2704; 525 2705; 525 2712; 525 2729, 525 3254

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesive

#### 1.4. Details of manufacturer or importer

##### Supplier

REMA TIP TOP AG  
65 Gruber Strasse  
Poing 85586  
Germany  
T +49 (0) 8121 / 707 - 100  
[info@tiptop.de](mailto:info@tiptop.de)

E-mail address of competent person responsible for the SDS: [sds@gbk-ingelheim.de](mailto:sds@gbk-ingelheim.de)

##### Importer

REMA TIP TOP Australia Pty Ltd.  
3/20 Worth Street  
Chullora NSW 2190  
Australia  
T +61 2 8755 8400  
[www.rema-tiptop.com.au](http://www.rema-tiptop.com.au)

#### 1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

### SECTION 2: Hazard identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment — Chronic Hazard, Category 1	H410

#### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation  
mark

Environment

Signal word (GHS AU) :

Danger

Contains :

Ethyl acetate ( $\geq 30 - < 60$  %); Cyclohexane ( $\geq 35 - < 40$  %); Other substances (not contributing to the classification of this product) ( $\geq 10 - < 30$  %)

Hazard statements (GHS AU) :

H225 - Highly flammable liquid and vapour  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H410 - Very toxic to aquatic life with long lasting effects

# TIP TOP CEMENT SC 4000

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0119



Precautionary statements (GHS AU) :

- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 - Wash hands thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
- P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 - Call a POISON CENTER or doctor if you feel unwell.
- P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
- P501 - Dispose of an approved waste disposal plant to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Vapours may form explosive mixture with air.

## SECTION 3: Composition and information on ingredients

Comments : Preparation in organic solvents.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Ethyl acetate	141-78-6	≥ 30 – < 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Cyclohexane	110-82-7	≥ 35 – < 40	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Other substances (not contributing to the classification of this product)	-	≥ 10 – < 30	Not classified
Zinc oxide	1314-13-2	< 5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
silicon dioxide crystalline-free	112926-00-8	< 5	Not classified
Rosin; colophony	8050-09-7	< 1	Skin Sens. 1, H317

## SECTION 4: First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general : Take off immediately all contaminated clothing. In the event of persistent symptoms receive medical treatment. Move the affected person away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a physician immediately.

First-aid measures after skin contact : Wash off immediately with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist.

# TIP TOP CEMENT SC 4000

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0119



First-aid measures after ingestion : Do not induce vomiting without medical advice. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician immediately.

### 4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after inhalation : Aspiration hazard.  
Symptoms/effects after skin contact : Causes skin irritation.  
Symptoms/effects after eye contact : Causes serious eye irritation.

### 4.3. Medical attention and special treatment

Treatment : Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Water spray. Dry powder. Carbon dioxide.  
Unsuitable extinguishing media : high volume water jet.

### 5.2. Specific hazards arising from the chemical

General measures : In case of vapour formation use adequate respirator. Ensure adequate air ventilation. Evacuate personnel to a safe area. Use explosion-proof equipment.  
Hazardous decomposition products in case of fire : In case of fire: Carbon monoxide. Carbon dioxide. Hydrogen chloride gas.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.  
Hazchem Code : \* 3Y  
Other information : The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Cool containers / tanks with spray water if possible. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : In case of vapour formation use adequate respirator. Ensure adequate air ventilation. Evacuate personnel to a safe area. Use explosion-proof equipment.

#### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

### 6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Shovel or sweep up and put in a closed container for disposal.

# TIP TOP CEMENT SC 4000

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0119



### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep the container tightly closed. Vapours are heavier than air and may spread along floors. Ensure good ventilation of the work station. Avoid contact with skin, eyes and clothing. Do not smoke. Keep away from heat and sources of ignition. Take precautionary measures against static discharge. Use explosion-proof equipment.
- Hygiene measures : Do not inhale vapour. Treat subsequently with skin cream. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Pay attention to explosion protection guidelines.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.
- Incompatible materials : oxidizing materials.
- Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

### SECTION 8: Exposure controls and personal protection

#### 8.1. Control parameters - exposure standards

##### Ethyl acetate (141-78-6)

###### Australia - Occupational Exposure Limits

Local name	Ethyl acetate (Acetic acid ethyl ester; Acetic ester)
OES TWA [1]	720 mg/m <sup>3</sup>
OES TWA [2]	200 ppm
OES STEL	1440 mg/m <sup>3</sup>
OES STEL [ppm]	400 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

##### Zinc oxide (1314-13-2)

###### Australia - Occupational Exposure Limits

Local name	Zinc oxide
OES TWA [1]	10 mg/m <sup>3</sup> dust 5 mg/m <sup>3</sup> fume
OES STEL	10 mg/m <sup>3</sup> fume
Remark (AU)	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

##### Cyclohexane (110-82-7)

###### Australia - Occupational Exposure Limits

Local name	Cyclohexane
OES TWA [1]	350 mg/m <sup>3</sup>
OES TWA [2]	100 ppm
OES STEL	1050 mg/m <sup>3</sup>
OES STEL [ppm]	300 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

# TIP TOP CEMENT SC 4000

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0119



### 8.2. Biological Monitoring

No additional information available

### 8.3. Engineering controls

Appropriate engineering controls : Pay attention to explosion protection guidelines. Ensure good ventilation of the work station.

### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Splash protection. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Nitrile rubber (NBR)	1 (> 10 minutes)	≥0.4		
Chemically resistant protective gloves	Butyl rubber	2 (> 30 minutes)	≥ 0.7		

Eye protection : Eyewash bottle with clean water (EN 15154). Safety goggles with side protection (EN 166). Protective goggles (EN 166)

Skin and body protection : Long sleeved protective clothing (DIN EN ISO 6530)

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A		EN 14387

Environmental exposure controls : Avoid release to the environment.

Other information : Do not inhale vapour. Wash hands before breaks and at the end of workday. Wash hands immediately after handling the product. Do not eat, drink or smoke during use. Treat subsequently with skin cream.

## SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Green Black White
Odour	: Fruity
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: No data available
Boiling point	: 77 – 81 °C
Flash point	: -19 °C
Auto-ignition temperature	: > 250 °C
Flammability (solid, gas)	: No data available
Vapour pressure	: Vapour pressure: ≈ 100 hPa @ 20 °C
Relative density	: No data available
Density	: Density: 0.9 g/cm <sup>3</sup> @ 20 °C
Solubility	: immiscible. at 20 °C.
Log Pow	: No data available
Viscosity, kinematic	: > 20.5 mm <sup>2</sup> /s @ 40 °C
Viscosity, dynamic	: ≈ 2000 mPa·s
Explosive properties	: Product is not explosive. May form flammable/explosive vapour-air mixture.
Oxidising properties	: Not oxidising
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 75 – 80 %
Fat solubility	: No data available

# TIP TOP CEMENT SC 4000

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0119



Additional information : Flow time 116 s @23°C, 6 DIN EN ISO 2431. Solvent separation test (%) 0. Solvent content < 80%

### SECTION 10: Stability and reactivity

Reactivity : No decomposition if stored normally. Highly flammable liquid and vapour.  
Chemical stability : Stable under normal conditions.  
Possibility of hazardous reactions : oxidizing materials.  
Conditions to avoid : Vapour/air-mixtures are explosive at intense warming. Heating can release vapours which can be ignited. To avoid thermal decomposition, do not overheat.  
Incompatible materials : Oxidizing agent.  
Hazardous decomposition products : Carbon monoxide. Carbon dioxide. Hydrogen chloride gas.

### SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Ethyl acetate (141-78-6)

LD50 oral rat	4935 mg/kg
LC50 Inhalation - Rat	1600 mg/l/4h

#### Zinc oxide (1314-13-2)

LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402 method)
LC50 Inhalation - Rat	> 5.7 mg/l/4h

#### Rosin; colophony (8050-09-7)

LD50 dermal	2500 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	2.3 mg/l/4h

#### Cyclohexane (110-82-7)

LD50 oral rat	> 12705 mg/kg
---------------	---------------

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : May cause drowsiness or dizziness.

#### Ethyl acetate (141-78-6)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

#### Cyclohexane (110-82-7)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified  
Aspiration hazard : Not classified  
Potential adverse human health effects and symptoms : Irritation of mucous membranes. High concentration of vapours may induce: headache, nausea, dizziness. Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product

# TIP TOP CEMENT SC 4000

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0119



### SECTION 12: Ecological information

#### 12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Very toxic to aquatic life with long lasting effects.  
Other information : Do not flush into surface water or sewer system.

##### Ethyl acetate (141-78-6)

LC50 fish 1	> 100 mg/l
-------------	------------

##### Rosin; colophony (8050-09-7)

EC50 Daphnia 1	4.5 mg/l
----------------	----------

##### Cyclohexane (110-82-7)

LC50 fish 1	> 4 mg/l 72h, Selenastrum capricornutum
EC50 Daphnia 1	0.9 mg/l
NOEC chronic algae	0.94 mg/l
BCF - Fish [2]	31 – 129 Cyprinus carpio (Common carp)

##### silicon dioxide crystalline-free (112926-00-8)

LC50 fish 1	10000 mg/l
-------------	------------

#### 12.2. Persistence and degradability

##### TIP TOP CEMENT SC 4000

Persistence and degradability	No data available.
-------------------------------	--------------------

##### Zinc oxide (1314-13-2)

Not rapidly degradable

##### Rosin; colophony (8050-09-7)

Not rapidly degradable

##### silicon dioxide crystalline-free (112926-00-8)

Not rapidly degradable

#### 12.3. Bioaccumulative potential

##### TIP TOP CEMENT SC 4000

Bioaccumulative potential	No data available.
---------------------------	--------------------

##### Cyclohexane (110-82-7)

BCF - Fish [2]	31 – 129 Cyprinus carpio (Common carp)
----------------	--

#### 12.4. Mobility in soil

##### TIP TOP CEMENT SC 4000

Ecology - soil	No data available.
----------------	--------------------

#### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : Slightly hazardous to water.

# TIP TOP CEMENT SC 4000

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0119



TIP TOP CEMENT SC 4000	
Fluorinated greenhouse gases	False
Ethyl acetate (141-78-6)	
Fluorinated greenhouse gases	False
Zinc oxide (1314-13-2)	
Fluorinated greenhouse gases	False
Rosin; colophony (8050-09-7)	
Fluorinated greenhouse gases	False
Cyclohexane (110-82-7)	
Fluorinated greenhouse gases	False
silicon dioxide crystalline-free (112926-00-8)	
Fluorinated greenhouse gases	False
Other substances (not contributing to the classification of this product)	
Fluorinated greenhouse gases	False

### SECTION 13: Disposal considerations

- Waste treatment methods : Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Product/Packaging disposal recommendations : Packaging that cannot be cleaned should be disposed of like the product. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Empty containers should be taken for local recycling, recovery or waste disposal.

### SECTION 14: Transport information

ADG	IMDG	IATA
<b>14.1. UN number</b>		
1133	1133	1133
<b>14.2. UN Proper Shipping Name</b>		
ADHESIVES	ADHESIVES	Adhesives
<b>14.3. Transport hazard class(es)</b>		
3	3	3
<b>14.4. Packing group</b>		
III - substances presenting low danger	III	III
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes



# TIP TOP CEMENT SC 4000

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0119



### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : (Packing group III, if content of packaging <= 450l, according 2.3.2.2 IMDG). (Packing group III, if content of packaging <= 30l, according 3.3.3.1.1 IATA)

#### Transport by road and rail

UN-No. (ADG) : 1133  
Special provision (ADG) : 223  
Limited quantities (ADG) : 5l  
Packing instructions (ADG) : P001, IBC03, LP01  
Special packing provisions (ADG) : PP1  
Portable tank and bulk container instructions (ADG) : T2  
Portable tank and bulk container special provisions (ADG) : TP1

#### Transport by sea

UN-No. (IMDG) : 1133  
Transport regulations (IMDG) : Transport in accordance with section 2.3.2.5 of the IMDG (viscous substance) may be applied  
Special provisions (IMDG) : 223, 955  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : P001, LP01  
Special packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T2  
Tank special provisions (IMDG) : TP1  
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS  
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS  
Stowage category (IMDG) : A

#### Air transport

UN-No. (IATA) : 1133  
PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y344  
PCA limited quantity max net quantity (IATA) : 10L  
PCA packing instructions (IATA) : 355  
PCA max net quantity (IATA) : 60L  
CAO packing instructions (IATA) : 366  
CAO max net quantity (IATA) : 220L  
Special provisions (IATA) : A3  
ERG code (IATA) : 3L

### 14.8. Hazchem or Emergency Action Code

Hazchem Code : \* 3Y

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

#### Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : All components of this mixture are listed on or exempted from AICIS

# TIP TOP CEMENT SC 4000

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0119



### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

Abbreviations and acronyms : ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
IATA - International Air Transport Association  
IMDG - International Maritime Dangerous Goods  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
DOT - Department of Transport  
TDG - Transportation of Dangerous Goods  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
GHS - Globally Harmonized System of Classification, Labelling and Packaging of Chemicals  
IARC - International Agency for Research on Cancer  
vPvB - Very Persistent and Very Bioaccumulative  
PBT - Persistent Bioaccumulative Toxic  
PNEC - Predicted No-Effect Concentration  
CAS - CAS (Chemical Abstracts Service) number  
IBC-Code - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk  
ATE - Acute Toxicity Estimate  
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
BCF - Bioconcentration factor  
MARPOL 73/78 - MARPOL 73/78: International Convention for the Prevention of Pollution From Ships  
ADG - Transport of Australian Dangerous Goods

Revision date : 23/07/2021

Other information : Data of sections 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge. The delivery specifications are contained in the corresponding product sheet. This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

Classification	
Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
Aquatic Chronic 1	H410

Full text of H-statements	
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1

# TIP TOP CEMENT SC 4000

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0119



Full text of H-statements	
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.