

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the WHS Regulations

Issue date:17/04/2015 Revision date:06/10/2023 Supersedes:07/09/2023 Version: 4.2

SDS No: 00156-0029



### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Product name : TIP TOP CEMENT SVS VULC  
Product code : 90008, 90009, 90010, 020004, 020009, 020010, 020011, 020540, 020541, 020542, 020543, 505 0196, 505 4037, 505 4051, 505 9010, 505 9017, 505 9018, 505 9025, 505 9032, 505 9035, 505 9036, 505 9037, 505 9038, 505 9050, 505 9055, 505 9056, 505 9127, 505 9128, 505 9142, 505 9145, 505 9159, 505 9197, 505 9198, 505 9245, 505 9246, 505 9252, 505 9253, 506 0000, 506 0006, 506 0007, 506 0021, 506 0045, 506 0048, 506 0100, 506 0103, 506 0117, 506 0193, 506 0194, 506 0203, 506 0306, 506 0308, 506 0375, 506 0376, 506 0518, 506 0519, 506 0605, 506 0900, 506 0911, 506 0912, 506 1500, 506 4003, 506 4004, 506 4005, 506 4027, 506 4041, 506 4106, 506 4190, 506 4191, 506 4195, 506 4199, 506 4200, 506 4201, 506 4209, 506 4254, 506 4302, 506 4371, 506 4515, 506 4601, 506 8100, 506 9015, 506 9022, 506 9030, 506 9053, 506 9060, 506 9061, 506 9101, 506 9118, 506 9120, 506 9132, 506 9133, 506 9148, 506 9149, 506 9150, 506 9163, 506 9170, 506 9190, 506 9500, 506 9510, 506 9520, 506 9521, 506 9534, 506 9637, 506 9716, 506 9724, 506 9730, 506 9740, 506 9741, 506 9749, 506 9750, 506 9751, 506 9760, 506 9770, 507 0011, 507 0012, 507 0310, 507 0311, 507 0602, 507 0603, 507 9706, 507 9892, 507 9971, 514 8790, 514 8820, 514 8870, 514 8890, 546 2313, 552 3190, 552 3197, 552 3198, 552 3199, 552 4196, 596 4354, 5042, 5042-10, 5054, 5952, 5952-10, 5098-10, 5086, 5087, 5088, 5097, 5098, 5096, 5106, 8823, 8824

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesive

#### 1.4. Details of manufacturer or importer

##### Supplier

REMA TIP TOP AG  
65 Gruber Strasse  
Poing 85586  
Germany  
T +49 (0) 8121 / 707 - 100  
[info@tiptop.de](mailto:info@tiptop.de)

E-mail address of competent person responsible for the SDS: [sds@gbk-ingelheim.de](mailto:sds@gbk-ingelheim.de)

##### Importer

REMA TIP TOP Australia Pty Ltd.  
3/20 Worth Street  
Chullora NSW 2190  
Australia  
T +61 2 8755 8400  
[www.rema-tiptop.com.au](http://www.rema-tiptop.com.au)

#### 1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

### SECTION 2: Hazard identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0029

### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation  
mark

Environment

Signal word (GHS AU) :

Danger

Contains :

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 3% normal hexane (< 70 %);  
Hydrocarbons, C6, iso, < 3% normal hexane (< 25 %)

Hazard statements (GHS AU) :

H225 - Highly flammable liquid and vapour  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS AU) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.  
P240 - Ground and bond container and receiving equipment.  
P241 - Use explosion-proof equipment.  
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 - Wash hands thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 - Call a doctor, a POISON CENTER if you feel unwell.  
P332+P313 - If skin irritation occurs: Get medical attention.  
P337+P313 - If eye irritation persists: Get medical attention.  
P391 - Collect spillage.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents and container to an approved waste disposal plant.

### 2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance. Vapours may form explosive mixture with air.

## SECTION 3: Composition and information on ingredients

Comments :

Preparation solved in petroleum spirit.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 3% normal hexane	64742-49-0	< 70	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0029

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Hydrocarbons, C6, iso, < 3% normal hexane	64742-49-0	< 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
N-Cyclohexyl-N-ethylamine	5459-93-8	< 2.5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Aquatic Chronic 3, H412

### SECTION 4: First aid measures

#### 4.1. Description of necessary first-aid measures

First-aid measures general	: Immediately remove contaminated clothing or footwear. In the event of persistent symptoms receive medical treatment. Take affected person away from danger area. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Move to fresh air in case of accidental inhalation of vapours or decomposition products. Get immediate medical advice/attention.
First-aid measures after skin contact	: Get medical advice if skin irritation persists. Treat subsequently with skin cream. Wash off immediately with soap and plenty of water. Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist immediately. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Symptoms caused by exposure

Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation.
Symptoms/effects after ingestion	: Aspiration hazard.

#### 4.3. Medical attention and special treatment

Treatment	: Treat symptomatically.
-----------	--------------------------

### SECTION 5: Fire-fighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: high volume water jet.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: Product is not explosive. Explosive vapour/air mixtures may be formed.
General measures	: In case of vapour formation use adequate respirator. Use explosion-proof equipment. Avoid contact with skin, eyes and clothing. Use personal protective clothing. Ensure adequate ventilation.
Hazardous decomposition products in case of fire	: Thermal decomposition generates : Carbon oxides (CO, CO <sub>2</sub> ). Nitrogen oxides.

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0029

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Hazchem Code	: * 3Y
Other information	: Vapours are heavier than air and may spread along floors. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Collect contaminated firefighting water separately, must not be discharged into the drains. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: In case of vapour formation use adequate respirator. Use explosion-proof equipment. Avoid contact with skin, eyes and clothing. Use personal protective clothing. Ensure adequate ventilation.
<b>6.1.1. For non-emergency personnel</b>	
Emergency procedures	: Ventilate spillage area.
<b>6.1.2. For emergency responders</b>	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Do not discharge into drains or the environment.

### 6.3. Methods and materials for containment and cleaning up

For containment	: Dam up the liquid spill.
Methods for cleaning up	: Take up liquid spill into absorbent material. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Shovel or sweep up and put in a closed container for disposal. Notify authorities if product enters sewers or public waters.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Keep container tightly closed. Vapours are heavier than air and may spread along floors. Use only outdoors or in a well-ventilated area. Avoid contact with skin, eyes and clothing. Keep away from heat and sources of ignition. Do not smoke. Take precautionary measures against static discharge.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment. Pay attention to explosion protection guidelines.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls and personal protection

### 8.1. Control parameters - exposure standards

No additional information available

### 8.2. Biological Monitoring

Monitoring methods	: A specific exposure sampling method is not available.
--------------------	---

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0029

### 8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥0.4		EN ISO 374

Eye protection : Eyewash bottle with clean water (EN 15154)

Type	Field of application	Characteristics	Standard
Protective goggles (EN 166)	Liquid splashes may occur		EN 166

Skin and body protection :

Type	Standard
Chemical resistant apron	EN 467

Respiratory protection :

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A - High-boiling (>65 °C) organic compounds	In case of inadequate ventilation wear	EN 14387

Environmental exposure controls : Avoid release to the environment.

Other information : Take off contaminated clothing and wash it before reuse. Do not inhale vapour. Wash hands before breaks and at the end of workday. Wash hands immediately after handling the product. Avoid contact with skin, eyes and clothing. Treat subsequently with skin cream. Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

Physical state : Liquid  
Appearance : No data available  
Colour : Colourless  
Odour : Hydrocarbon-like  
Odour threshold : No data available  
pH : No data available  
pH solution : No data available  
Relative evaporation rate (butylacetate=1) : No data available  
Melting point / Freezing point : Melting point: < -50 Hydrocarbons, C6-C7  
Boiling point : > 60 °C  
Flash point : -25 °C DIN EN ISO 3679  
Auto-ignition temperature : 260 °C Hydrocarbons, C6-C7  
Flammability (solid, gas) : No data available  
Vapour pressure : Vapour pressure: 190 hPa @20°C, Hydrocarbons, C6-C7  
Relative density : No data available  
Density : Density: 0.72 g/cm<sup>3</sup> @20°C  
Solubility : Not miscible. at 20 °C.  
Log Pow : No data available  
Viscosity, kinematic : 2485 – 2535 mm<sup>2</sup>/s @40°C  
Viscosity, dynamic : 2900 – 3500 mPa·s  
Explosive properties : Product is not explosive. May form flammable/explosive vapour-air mixture.  
Oxidising properties : Not oxidising  
Explosive limits : No data available  
Minimum ignition energy : No data available  
VOC content : < 95 %

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0029

Fat solubility	: No data available
Flow time	: 108 s (6 DIN EN ISO 2431)
Solvent separation test (%)	: 0 %
Solvent content	: > 90 %

### SECTION 10: Stability and reactivity

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Reactions with oxidizing agents.
Conditions to avoid	: Heating can release vapours which can be ignited. Vapour/air-mixtures are explosive at intense warming. To avoid thermal decomposition, do not overheat.
Incompatible materials	: Oxidizing agent.
Hazardous decomposition products	: An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces. Thermal decomposition generates : Carbon oxides (CO, CO <sub>2</sub> ). Nitrogen oxides.

### SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>N-Cyclohexyl-N-ethylamine (5459-93-8)</b>	
ATE AU (oral)	500 mg/kg bodyweight
ATE AU (dermal)	300 mg/kg bodyweight
ATE AU (gases)	4500 ppmv/4h
ATE AU (vapours)	11 mg/l/4h
ATE AU (dust,mist)	1.5 mg/l/4h

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt; 3% normal hexane (64742-49-0)</b>	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h

<b>Hydrocarbons, C6, iso, &lt; 3% normal hexane (64742-49-0)</b>	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified.
Potential adverse human health effects and symptoms	: High concentration of vapours may induce: headache, nausea, dizziness. A longer or repeated contact may lead to irritation of eyes and mucous membranes. Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product. An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0029

### SECTION 12: Ecological information

#### 12.1. Ecotoxicity

Ecology - general : Toxic to aquatic life with long lasting effects.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.  
Other information : Do not flush into surface water or sewer system.

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 3% normal hexane (64742-49-0)

LC50 fish 1	1 – 10 mg/l
-------------	-------------

EC50 Daphnia 1	1 – 10 mg/l
----------------	-------------

#### Hydrocarbons, C6, iso, < 3% normal hexane (64742-49-0)

LC50 fish 1	1 – 10 mg/l
-------------	-------------

EC50 Daphnia 1	1 – 10 mg/l
----------------	-------------

#### 12.2. Persistence and degradability

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 3% normal hexane (64742-49-0)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

#### 12.3. Bioaccumulative potential

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 3% normal hexane (64742-49-0)

Bioaccumulative potential	Potentially bioaccumulable.
---------------------------	-----------------------------

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : Low hazard to waters.

### SECTION 13: Disposal considerations

Waste treatment methods : Can be incinerated according to local regulations. Recycling is preferred to disposal or incineration.  
Product/Packaging disposal recommendations : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed of like the product. Empty containers should be taken for local recycling, recovery or waste disposal.

### SECTION 14: Transport information







In accordance with ADG / IMDG / IATA

ADG	IMDG	IATA
<b>14.1. UN number</b>		
1133	1133	1133
<b>14.2. UN Proper Shipping Name</b>		
ADHESIVES	ADHESIVES	Adhesives

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0029

ADG	IMDG	IATA
<b>14.3. Transport hazard class(es)</b>		
3	3	3
 	 	 
<b>14.4. Packing group</b>		
III - Substances presenting low danger	III	III
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes

### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : No supplementary information available

### Transport by road and rail

UN-No. (ADG) : 1133  
Special provision (ADG) : 223  
Limited quantities (ADG) : 5I  
Excepted quantities (ADG) : E1  
Packing instructions (ADG) : P001, IBC03, LP01  
Special packing provisions (ADG) : PP1  
Portable tank and bulk container instructions (ADG) : T2  
Portable tank and bulk container special provisions (ADG) : TP1

### Transport by sea

UN-No. (IMDG) : 1133  
Special provisions (IMDG) : 223, 955  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : P001, LP01  
Special packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T2  
Tank special provisions (IMDG) : TP1  
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS  
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS  
Stowage category (IMDG) : A

### Air transport

UN-No. (IATA) : 1133  
PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y344  
PCA limited quantity max net quantity (IATA) : 10L  
PCA packing instructions (IATA) : 355  
PCA max net quantity (IATA) : 60L  
CAO packing instructions (IATA) : 366  
CAO max net quantity (IATA) : 220L  
Special provisions (IATA) : A3



# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0029

ERG code (IATA) : 3L

### 14.8. Hazchem or Emergency Action Code

Hazchem Code : \* 3Y

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

#### Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS) : All the chemicals contained in this product are listed introductions  
Inventory) status

#### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Schedule 5

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

Revision date : 6/10/2023

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0029

Abbreviations and acronyms:	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Classification	
Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
Aquatic Chronic 2	H411

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the WHS Regulations  
SDS No: 00156-0029

Full text of H-statements	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.