

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

Issue date:17/04/2015 Revision date:16/12/2020 Supersedes:22/07/2020 Version: 3.7

SDS No: 00156-0029



### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Product name : TIP TOP CEMENT SVS VULC  
Product code : 020004, 020009, 020010, 020011, 020540, 020541, 020542, 020543, 505 0196, 505 4037, 505 4051, 505 9010, 505 9017, 505 9018, 505 9025, 505 9032, 505 9035, 505 9036, 505 9037, 505 9038, 505 9050, 505 9055, 505 9056, 505 9127, 505 9128, 505 9142, 505 9145, 505 9159, 505 9197, 505 9198, 505 9245, 505 9246, 505 9252, 505 9253, 506 0000, 506 0006, 506 0007, 506 0021, 506 0045, 506 0048, 506 0100, 506 0103, 506 0117, 506 0193, 506 0194, 506 0203, 506 0306, 506 0308, 506 0375, 506 0376, 506 0518, 506 0519, 506 0605, 506 0900, 506 0911, 506 0912, 506 1500, 506 4003, 506 4004, 506 4005, 506 4027, 506 4041, 506 4106, 506 4190, 506 4191, 506 4195, 506 4199, 506 4200, 506 4201, 506 4209, 506 4254, 506 4302, 506 4371, 506 4515, 506 4601, 506 8100, 506 9015, 506 9022, 506 9030, 506 9053, 506 9060, 506 9061, 506 9101, 506 9118, 506 9120, 506 9132, 506 9133, 506 9148, 506 9149, 506 9150, 506 9163, 506 9170, 506 9190, 506 9500, 506 9510, 506 9520, 506 9521, 506 9534, 506 9637, 506 9716, 506 9724, 506 9730, 506 9740, 506 9749, 506 9750, 506 9760, 506 9770, 507 0011, 507 0012, 507 0310, 507 0311, 507 0602, 507 0603, 507 9706, 507 9892, 507 9971, 514 8790, 514 8820, 514 8870, 514 8890, 546 2313, 552 3190, 552 3197, 552 3198, 552 3199, 552 4196, 596 4354, 5042, 5042-10, 5054, 5952, 5952-10, 5098-10, 5086, 5087, 5088, 5097, 5098, 5096, 5106

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesive

#### 1.4. Details of manufacturer or importer

##### Supplier

REMA TIP TOP AG  
65 Gruber Strasse  
Poing 85586  
Germany  
T +49 (0) 8121 / 707 - 100  
[info@tiptop.de](mailto:info@tiptop.de)

E-mail address of competent person responsible for the SDS: [sds@gbk-ingelheim.de](mailto:sds@gbk-ingelheim.de)

##### Importer

REMA TIP TOP Australia Pty Ltd.  
3/20 Worth Street  
Chullora NSW 2190  
Australia  
T +61 2 8755 8400  
[www.rema-tiptop.com.au](http://www.rema-tiptop.com.au)

#### 1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

### SECTION 2: Hazard identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0029



### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation  
mark

Environment

Signal word (GHS AU) :

Danger

Contains

Hydrocarbons, C6-C7 (> 90 %); Other substances (not contributing to the classification of this product) (< 5 %); N-Cyclohexyl-N-ethylamine (< 2.5 %)

Hazard statements (GHS AU) :

H225 - Highly flammable liquid and vapour  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS AU) :

P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 - Ground and bond container and receiving equipment.  
P241 - Use explosion-proof equipment.  
P242 - Use non-sparking tools.  
P243 - Take action to prevent static discharges.  
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 - Wash hands thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 - Call a doctor, a POISON CENTER if you feel unwell.  
P332+P313 - If skin irritation occurs: Get medical attention.  
P337+P313 - If eye irritation persists: Get medical attention.  
P235 - Keep cool.  
P391 - Collect spillage.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P501 - Dispose of contents/container to in accordance with local and national regulations.

### 2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification :

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance. Vapours may form explosive mixture with air.

## SECTION 3: Composition and information on ingredients

Comments

: Preparation solved in petroleum spirit.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Hydrocarbons, C6-C7	64742-49-0	> 90	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0029



Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Other substances (not contributing to the classification of this product)	-	< 5	Not classified
N-Cyclohexyl-N-ethylamine	5459-93-8	< 2.5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Aquatic Chronic 3, H412

### SECTION 4: First aid measures

#### 4.1. Description of necessary first-aid measures

- First-aid measures general : Immediately remove contaminated clothing or footwear. In the event of persistent symptoms receive medical treatment. Take affected person away from danger area. Call a poison center or a doctor if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Move to fresh air in case of accidental inhalation of vapours or decomposition products. Get immediate medical advice/attention.
- First-aid measures after skin contact : Get medical advice if skin irritation persists. Treat subsequently with skin cream. Wash off immediately with soap and plenty of water. Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist immediately. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

#### 4.2. Symptoms caused by exposure

- Symptoms/effects : May cause drowsiness or dizziness.
- Symptoms/effects after skin contact : May cause skin irritation.
- Symptoms/effects after eye contact : May cause eye irritation.
- Symptoms/effects after ingestion : Aspiration hazard.

#### 4.3. Medical attention and special treatment

- Treatment : Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : high volume water jet.

#### 5.2. Specific hazards arising from the chemical

- General measures : In case of vapour formation use adequate respirator. Use explosion-proof equipment. Avoid contact with skin, eyes and clothing. Use personal protective clothing. Ensure adequate ventilation.
- Hazardous decomposition products in case of fire : Thermal decomposition generates : Carbon dioxide. Carbon monoxide. Nitrogen oxides.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
- Hazchem Code : 3Y

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0029



Other information : Vapours are heavier than air and may spread along floors. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Cool containers at risk with water spray jet. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : In case of vapour formation use adequate respirator. Use explosion-proof equipment. Avoid contact with skin, eyes and clothing. Use personal protective clothing. Ensure adequate ventilation.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Do not discharge into drains or the environment.

### 6.3. Methods and materials for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Shovel or sweep up and put in a closed container for disposal. Notify authorities if product enters sewers or public waters.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep container tightly closed. Vapours are heavier than air and may spread along floors. Use only outdoors or in a well-ventilated area. Avoid contact with skin, eyes and clothing. Keep away from heat and sources of ignition. Do not smoke. Take precautionary measures against static discharge.  
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment. Pay attention to explosion protection guidelines.  
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

## SECTION 8: Exposure controls and personal protection

### 8.1. Control parameters - exposure standards

No additional information available

### 8.2. Biological Monitoring

No additional information available

### 8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0029



### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥0.4		EN ISO 374

Eye protection : Tightly fitting goggles (EN 166). Safety glasses

Skin and body protection : Solvent-resistant apron. EN 467

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A		EN 14387

### Personal protective equipment symbol(s)



Environmental exposure controls

: Avoid release to the environment.

Other information

: Take off contaminated clothing and wash it before reuse. Do not inhale vapour. Wash hands before breaks and at the end of workday. Wash hands immediately after handling the product. Avoid contact with skin, eyes and clothing. Treat subsequently with skin cream. Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

Physical state : Liquid

Appearance : No data available

Colour : Colourless

Odour : Hydrocarbon-like

Odour threshold : No data available

pH : No data available

Relative evaporation rate (butylacetate=1) : No data available

Melting point / Freezing point : Melting point: < -50 Hydrocarbons, C6-C7

Boiling point : > 60 °C

Flash point : -25 °C DIN EN ISO 3679

Auto-ignition temperature : 260 °C Hydrocarbons, C6-C7

Flammability (solid, gas) : No data available

Vapour pressure : Vapour pressure: 190 hPa @20°C, Hydrocarbons, C6-C7

Relative density : No data available

Density : Density: 0.72 g/cm<sup>3</sup> @20°C

Solubility : Not miscible. at 20 °C.

Log Pow : No data available

Viscosity, kinematic : 2485 – 2535 mm<sup>2</sup>/s @40°C

Viscosity, dynamic : 2900 – 3500 mPa·s

Explosive properties : Product is not explosive. May form flammable/explosive vapour-air mixture.

Oxidising properties : Non oxidizing

Explosive limits : No data available

Minimum ignition energy : No data available

VOC content : < 95 %

Fat solubility : No data available

Flow time : 108 s (6 DIN EN ISO 2431)

Solvent separation test (%) : 0 %

Solvent content : > 90 %

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0029



### SECTION 10: Stability and reactivity

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Reactions with oxidizing agents.
Conditions to avoid	: Heating can release vapours which can be ignited. Vapour/air-mixtures are explosive at intense warming. To avoid thermal decomposition, do not overheat.
Incompatible materials	: Oxidizing agent.
Hazardous decomposition products	: Carbon dioxide. Carbon monoxide. Nitrogen oxides. An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

### SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Hydrocarbons, C6-C7 (64742-49-0)

LD50 oral rat	> 5840 mg/kg
LD50 dermal rat	> 2920 mg/kg
LC50 Inhalation - Rat	> 25.2 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

#### Hydrocarbons, C6-C7 (64742-49-0)

STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: High concentration of vapours may induce: headache, nausea, dizziness. A longer or repeated contact may lead to irritation of eyes and mucous membranes. Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product. An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces

### SECTION 12: Ecological information

#### 12.1. Ecotoxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.
Other information	: Do not flush into surface water or sewer system.

#### Hydrocarbons, C6-C7 (64742-49-0)

LC50 fish 1	11.4 mg/l
EC50 Daphnia 1	3 mg/l
ErC50 algae	30 mg/l

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0029



### Hydrocarbons, C6-C7 (64742-49-0)

BCF - Fish [1]	242 – 253
----------------	-----------

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

### Hydrocarbons, C6-C7 (64742-49-0)

BCF - Fish [1]	242 – 253
----------------	-----------

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : Low hazard to waters.

### TIP TOP CEMENT SVS VULC

Fluorinated greenhouse gases	False
------------------------------	-------

### N-Cyclohexyl-N-ethylamine (5459-93-8)

Fluorinated greenhouse gases	False
------------------------------	-------

### Hydrocarbons, C6-C7 (64742-49-0)

Fluorinated greenhouse gases	False
------------------------------	-------

### Other substances (not contributing to the classification of this product)

Fluorinated greenhouse gases	False
------------------------------	-------

## SECTION 13: Disposal considerations

Waste treatment methods : Can be incinerated according to local regulations. Recycling is preferred to disposal or incineration.

Product/Packaging disposal recommendations : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed of like the product. Empty containers should be taken for local recycling, recovery or waste disposal.

## SECTION 14: Transport information

ADG	IMDG	IATA
<b>14.1. UN number</b>		
3295	3295	3295
<b>14.2. UN Proper Shipping Name</b>		
HYDROCARBONS, LIQUID, N.O.S.	HYDROCARBONS, LIQUID, N.O.S.	Hydrocarbons, liquid, n.o.s.
<b>14.3. Transport hazard class(es)</b>		
3	3	3

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0029



ADG	IMDG	IATA
<b>14.4. Packing group</b>		
III - substances presenting low danger	III	III
<b>14.5. Environmental hazards</b>		
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes

### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : No supplementary information available

#### Transport by road and rail

UN-No. (ADG) : 3295  
Special provision (ADG) : 223  
Limited quantities (ADG) : 5I  
Packing instructions (ADG) : P001, IBC03, LP01  
Portable tank and bulk container instructions (ADG) : T4  
Portable tank and bulk container special provisions (ADG) : TP1, TP29

#### Transport by sea

UN-No. (IMDG) : 3295  
Special provisions (IMDG) : 223  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : P001, LP01  
IBC packing instructions (IMDG) : IBC03  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1, TP29  
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS  
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS  
Stowage category (IMDG) : A

#### Air transport

UN-No. (IATA) : 3295  
PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y344  
PCA limited quantity max net quantity (IATA) : 10L  
PCA packing instructions (IATA) : 355  
PCA max net quantity (IATA) : 60L  
CAO packing instructions (IATA) : 366  
CAO max net quantity (IATA) : 220L  
Special provisions (IATA) : A3, A224  
ERG code (IATA) : 3L



# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0029



**Other applicable information** : (Packing group III, if content of packaging ≤ 450l, according 2.2.3.1.4 ADR, RID, ADN)  
(Packing group III, if content of packaging ≤ 450l, according 2.3.2.2 IMDG)  
(Packing group III, if content of packaging ≤ 30l, according 3.3.3.1.1 IATA)

### 14.8. Hazchem or Emergency Action Code

Hazchem Code : 3Y

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

#### Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS : All the chemicals contained in this product are listed introductions Inventory) status

#### Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Schedule 5

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

Abbreviations and acronyms : ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE - Acute Toxicity Estimate  
BLV - Biological limit value  
CAS-No. - Chemical Abstract Service number  
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
DMEL - Derived Minimal Effect level  
DNEL - Derived-No Effect Level  
EC50 - Median effective concentration  
EC-No. - European Community number  
EN - European Standard  
IATA - International Air Transport Association  
IMDG - International Maritime Dangerous Goods  
LC50 - Median lethal concentration  
LD50 - Median lethal dose  
LOAEL - Lowest Observed Adverse Effect Level  
NOAEC - No-Observed Adverse Effect Concentration  
NOAEL - No-Observed Adverse Effect Level  
NOEC - No-Observed Effect Concentration  
OEL - Occupational Exposure Limit  
PBT - Persistent Bioaccumulative Toxic  
PNEC - Predicted No-Effect Concentration  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
SDS - Safety Data Sheet  
vPvB - Very Persistent and Very Bioaccumulative  
WGK - Water Hazard Class

Revision date : 16/12/2020

### Classification

Flam. Liq. 2	H225
Skin Irrit. 2	H315

# TIP TOP CEMENT SVS VULC

## Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0029



Classification	
Eye Irrit. 2A	H319
STOT SE 3	H336
Aquatic Chronic 2	H411

Full text of H-statements	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.