

ESKANOL CLEANER

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Issue date: 31/03/2021 Version: 1.1

SDS No: 00359-1319



SECTION 1: Product identifier

1.1. Product identifier

Product form : Mixture
Product name : ESKANOL CLEANER
Product code : 10000, 10002

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

No additional information available

1.4. Supplier's details

TIP TOP Oberflächenschutz Elbe GmbH
4 Heuweg
6886 Wittenberg - Germany
T +49(0)3491/635-50 - F +49(0)3491/635-552

1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2 H225
Serious eye damage/eye irritation, Category 2A H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336

2.2. Label elements

Hazard pictograms (GHS AU) :



Flame

Exclamation mark

Signal word (GHS AU) : Danger
Contains : Acetone (> 95 %)
Hazard statements (GHS AU) : H225 - Highly flammable liquid and vapour
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness
Precautionary statements (GHS AU) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing vapours.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER/doctor if you feel unwell.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to in accordance with local and national regulations.

ESKANOL CLEANER

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00359-1319



2.3. Other hazards

Other hazards not contributing to the classification : In use, may form flammable/explosive vapour-air mixture.

SECTION 3: Composition/information on ingredients

Comments : Mixture of the substances listed below with harmless additives.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Acetone	67-64-1	> 95	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Take off immediately all contaminated clothing. In the event of persistent symptoms receive medical treatment.

First-aid measures after inhalation : Move to fresh air in case of accidental inhalation of vapours or decomposition products. In the event of symptoms refer for medical treatment.

First-aid measures after skin contact : Wash off immediately with soap and plenty of water. Get medical advice if skin irritation persists.

First-aid measures after eye contact : Contact lenses should be removed. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist.

First-aid measures after ingestion : Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician immediately. Do not induce vomiting without medical advice.

4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Water spray. Dry powder.

Unsuitable extinguishing media : high volume water jet.

5.2. Special hazards arising from the substance or mixture

General measures : Avoid contact with skin, eyes and clothing. In case of vapour formation use adequate respirator. Use personal protective clothing. Remove ignition sources.

Hazardous decomposition products in case of fire : Carbon monoxide. Carbon dioxide.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Hazchem Code : * 2YE

Other information : Cool containers / tanks with spray water if possible. Vapour/air-mixtures are explosive at intense warming. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin, eyes and clothing. In case of vapour formation use adequate respirator. Use personal protective clothing. Remove ignition sources.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe Vapours. Avoid contact with skin and eyes.

ESKANOL CLEANER

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00359-1319



6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Shovel or sweep up and put in a closed container for disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Ensure good ventilation of the work station. Do not breathe vapours. Do not eat, drink or smoke when using this product. Keep away from heat and sources of ignition. Take precautionary measures against static discharge. Use explosion-proof equipment. Use only non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed in a dry, cool and well-ventilated place. Keep only in original container. Do not use metal containers.

Incompatible materials : Bases, oxidizing materials.

Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

Acetone (67-64-1)	
Australia - Occupational Exposure Limits	
Local name	Acetone
OES TWA [1]	1185 mg/m ³
OES TWA [2]	500 ppm
OES STEL	2375 mg/m ³
OES STEL [ppm]	1000 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls : Pay attention to explosion protection guidelines. Ensure good ventilation of the work station.

8.4. Personal protective equipment

Hand protection : This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves. Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Butyl rubber	5 (> 240 minutes)	≥ 0.7		EN ISO 374

Eye protection : Tightly fitting goggles (EN 166). Eyewash bottle with clean water (EN 15154)

Skin and body protection : Long sleeved protective clothing. EN ISO 6530

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A		EN 14387

Environmental exposure controls : Avoid release to the environment.

ESKANOL CLEANER

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00359-1319



Other information : Do not breathe vapours. Wash hands before breaks and at the end of workday. Wash hands immediately after handling the product. Do not eat, drink or smoke during use. Take off contaminated clothing and wash it before reuse. Avoid contact with eyes, skin or mucous membrane.

SECTION 9: Physical and chemical properties

Physical state : Liquid
Appearance : No data available
Colour : Colourless
Odour : aromatic
Odour threshold : No data available
pH : Not determined
Relative evaporation rate (butylacetate=1) : No data available
Melting point / Freezing point : Melting point : -94.7 °C Acetone
Boiling point : 56 °C Acetone
Flash point : -18 °C Acetone
Auto-ignition temperature : 540 °C Acetone
Flammability (solid, gas) : No data available
Vapour pressure : Vapour pressure : 247 hPa @20°C
Relative density : No data available
Density : Density : 0.79 g/cm³ @20°C
Solubility : Miscible. at 20 °C.
Log Pow : No data available
Viscosity, dynamic : 0.33 mPa·s @ 20°C, Acetone
Explosive properties : Product is not explosive. May form flammable/explosive vapour-air mixture.
Oxidising properties : Not fire-promoting.
Explosive limits : No data available
Lower explosive limit (LEL) : 2.5 vol %
Upper explosive limit (UEL) : 13 vol %
Minimum ignition energy : No data available
VOC content : > 95 %
Fat solubility : No data available
Additional information : Solvent content > 95 %

SECTION 10: Stability and reactivity

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : alkalis. oxidizing materials.
Conditions to avoid : Heating can release vapours which can be ignited. Vapour/air-mixtures are explosive at intense warming.
Incompatible materials : Bases. Oxidizing agent.
Hazardous decomposition products : Carbon monoxide. Carbon dioxide. Phosphorus oxides.

SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Not classified
pH: Not determined
Serious eye damage/irritation : Causes serious eye irritation.
pH: Not determined
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified

ESKANOL CLEANER

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00359-1319



Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

ESKANOL CLEANER	
Viscosity, kinematic	0.418 mm ² /s
Potential adverse human health effects and symptoms	: Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product. At high concentrations, the vapours can be irritating to the respiratory system

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Other information	: Do not flush into surface water or sewer system.

12.2. Persistence and degradability

Acetone (67-64-1)	
Not rapidly degradable	

12.3. Bioaccumulative potential

ESKANOL CLEANER	
Bioaccumulative potential	Not potentially bioaccumulable.

12.4. Mobility in soil

ESKANOL CLEANER	
Ecology - soil	No data available.

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: Low hazard to waters.

ESKANOL CLEANER	
Fluorinated greenhouse gases	False
Acetone (67-64-1)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Waste treatment methods	: Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Packaging that cannot be cleaned should be disposed of like the product. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Empty containers should be taken for local recycling, recovery or waste disposal.

SECTION 14: Transport information

ADG	IMDG	IATA
14.1. UN number		
1090	1090	1090
14.2. UN proper shipping name		
ACETONE	ACETONE	Acetone
14.3. Transport hazard class(es)		
3	3	3

ESKANOL CLEANER

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00359-1319



ADG	IMDG	IATA
14.4. Packing group		
II - substances presenting medium danger	II	II
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1090
Limited quantities (ADG) : 1I
Packing instructions (ADG) : P001, IBC02
Portable tank and bulk container instructions (ADG) : T4
Portable tank and bulk container special provisions (ADG) : TP1

Transport by sea

UN-No. (IMDG) : 1090
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG) : E
Flash point (IMDG) : -20°C to -18°C c.c.

Air transport

UN-No. (IATA) : 1090
PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
ERG code (IATA) : 3H

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 2YE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

Australian Inventory of Chemical Substances (AICS) status : Listed on the AICS (Australian Inventory of Chemical Substances)

15.2. International agreements

No additional information available

SECTION 16: Other information

ESKANOL CLEANER

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00359-1319



Classification:

Flam. Liq. 2	H225
Eye Irrit. 2A	H319
STOT SE 3	H336

Full text of H-statements:

Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.