



## Safety Data Sheet

According to the Model WHS Regulations and the ADG code

### ESKANOL VE TOPCOAT

Revision date: 16.12.2018

Product code: 00359-1320\_AUS

Page 1 of 10

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

ESKANOL VE TOPCOAT

Art.-No.

10075

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coating

##### 1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP Australia Pty Ltd.  
Street: 3 - 7 Ironbark Close  
Place: Warabrook  
NSW 2304 / Australia  
Telephone: +61-2-4935-0200  
Internet: www.rema-tiptop.com.au  
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de  
1.4. Emergency telephone number: +61-280735031, Infotrac/GBK GmbH-ID: 93591

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS CHEMICAL ACCORDING TO SAFE WORK AUSTRALIA AND WHS CRITERIA  
CLASSIFIED AS DANGEROUS GOODS ACCORDING TO THE ADG CODE  
POISON SCHEDULE: 5

##### Classification according to WHS

Hazard categories:  
Flammable liquid: Flam. Liq. 3  
Acute toxicity: Acute Tox. 4  
Skin corrosion/irritation: Skin Irrit. 2  
Serious eye damage/eye irritation: Eye Irrit. 2A  
Respiratory or skin sensitisation: Skin Sens. 1B  
Reproductive toxicity: Repr. 2  
Specific target organ toxicity - single exposure: STOT SE 3  
Specific target organ toxicity - repeated exposure: STOT RE 1  
Hazardous to the aquatic environment: Aquatic Chronic 3  
Hazard Statements:  
Flammable liquid and vapour.  
Harmful if inhaled.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
Suspected of damaging the unborn child.  
May cause respiratory irritation.  
Causes damage to organs through prolonged or repeated exposure.  
Harmful to aquatic life with long lasting effects.

##### 2.2. Label elements

##### Component(s) to be indicated on the label

styrene 30 - < 45 %  
2-phenylpropene, alpha-methylstyrene < 2.5 %  
non hazardous ingredients 30 - 60 %

## Safety Data Sheet

According to the Model WHS Regulations and the ADG code

### ESKANOL VE TOPCOAT

Revision date: 16.12.2018

Product code: 00359-1320\_AUS

Page 2 of 10

**Signal word:** Danger**Pictograms:**

flame



exclamation mark



health hazard

**Hazard statements**

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe vapour.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P362+P364	Take off contaminated clothing and wash it before reuse.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P233	Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to approved disposal company or local collection.

**2.3. Other hazards**

Vapours may form explosive mixture with air.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Mixture containing following substances with additives



## Safety Data Sheet

According to the Model WHS Regulations and the ADG code

### ESKANOL VE TOPCOAT

Revision date: 16.12.2018

Product code: 00359-1320\_AUS

Page 3 of 10

#### Hazardous components

CAS No	Chemical name	Quantity
EC No	Classification according to WHS criteria	
100-42-5	styrene	30 - < 45 %
202-851-5	Flam. Liq. 3, Repr. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2A, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 3; H226 H361d H332 H315 H319 H335 H372 H304 H412	
98-83-9	2-phenylpropene, alpha-methylstyrene	< 2.5 %
202-705-0	Flam. Liq. 3, Repr. 2, Eye Irrit. 2A, Skin Sens. 1B, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H361 H319 H317 H335 H304 H411	
	non hazardous ingredients	30 - 60 %

Full text of H and AUH phrases: see section 16.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

Remove contaminated soaked clothing immediately.  
In the event of persistent symptoms receive medical treatment.  
Take away from danger area and lay down affected person.

###### After inhalation

Move to fresh air in case of accidental inhalation of vapours.  
Seek medical treatment immediately.

###### After contact with skin

Wash off immediately with soap and plenty of water.  
Treat subsequently with skin cream.  
Consult a doctor if skin irritation persists.

###### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Consult (eye) doctor immediately.

###### After ingestion

Do not induce vomiting.  
Summon a doctor immediately.  
Rinse out mouth and give plenty of water to drink.  
Never give anything by mouth to an unconscious person.  
Induce vomiting only upon the advice of a physician.

##### 4.2. Most important symptoms and effects, both acute and delayed

Harmful if inhaled.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause respiratory irritation.  
Causes damage to organs through prolonged or repeated exposure. (the ear)  
Suspected of damaging the unborn child.

##### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media



## Safety Data Sheet

According to the Model WHS Regulations and the ADG code

### ESKANOL VE TOPCOAT

Revision date: 16.12.2018

Product code: 00359-1320\_AUS

Page 4 of 10

#### **Suitable extinguishing media**

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

#### **Unsuitable extinguishing media**

Full water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Fire may produce:

carbon monoxide and carbon dioxide

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

#### **5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective suit.

HAZCHEM: •3Y

#### **Additional information**

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

#### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

#### **6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

#### **6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Use only in thoroughly ventilated areas.

Provide suitable extraction at the processing machines.

##### **Advice on protection against fire and explosion**

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.



## Safety Data Sheet

According to the Model WHS Regulations and the ADG code

### ESKANOL VE TOPCOAT

Revision date: 16.12.2018

Product code: 00359-1320\_AUS

Page 5 of 10

Pay attention to anti-explosion rules.  
Avoid temperatures above 50°C.

#### Hints on joint storage

Incompatible with:  
Oxidizing agents, Metal halogenides, Peroxides

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

#### 7.3. Specific end use(s)

Coating

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational Exposure Limits (OEL) - Australia

CAS No	Substance	ppm	mg/m <sup>3</sup>	Category
100-42-5	Styrene, monomer	50	213	TWA
100-42-5	Styrene, monomer	100	426	STEL
98-83-9	alpha-Methyl styrene	50	242	TWA
98-83-9	alpha-Methyl styrene	100	483	STEL

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
98-83-9	2-Phenylpropene	50	246		TWA (8 h)	WEL
		100	491		STEL (15 min)	WEL
100-42-5	Styrene	100	430		TWA (8 h)	WEL
		250	1080		STEL (15 min)	WEL

#### 8.2. Exposure controls

##### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.  
Pay attention to explosion protection guidelines.

##### Protective and hygiene measures

Do not inhale vapours.  
Wash hands before breaks and immediately after handling the product.  
When using do not eat, drink or smoke.  
Treat subsequently with skin cream.  
Remove and wash contaminated clothes before re-use.

##### Eye/face protection

Eye wash bottle with pure water.  
Tightly fitting goggles.

##### Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.  
This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.  
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.  
Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

##### Skin protection

Long sleeved clothing.



## Safety Data Sheet

According to the Model WHS Regulations and the ADG code

### ESKANOL VE TOPCOAT

Revision date: 16.12.2018

Product code: 00359-1320\_AUS

Page 6 of 10

Solvent-resistant apron.

#### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Yellowish
Odour:	Pungent

#### Test method

pH-Value: No information available.

#### Changes in the physical state

Melting point:	- 31 °C *)
Initial boiling point and boiling range:	145 °C *)
Flash point:	31 °C

#### Flammability

Solid:	No information available.
Gas:	No information available.

#### Explosive properties

No information available.

Lower explosion limits:	1.1 vol. % *)
Upper explosion limits:	6.0 vol. % *)
Ignition temperature:	490 °C *)

#### Auto-ignition temperature

Solid:	No information available.
Gas:	No information available.

Decomposition temperature: No information available.

#### Oxidizing properties

No information available.

Vapour pressure: 6.7 hPa \*)  
(at 20 °C)Density (at 25 °C): 1.1 g/cm<sup>3</sup>Water solubility: Immiscible  
(at 20 °C)

#### Solubility in other solvents

No information available.

Partition coefficient: No information available.

Viscosity / dynamic: 2500 - 3500 mPa·s  
(at 25 °C)Viscosity / kinematic: > 20.5 mm<sup>2</sup>/s  
(at 40 °C)

Vapour density: No information available.

Evaporation rate: No information available.

#### 9.2. Other information

\*) Styrene



## Safety Data Sheet

According to the Model WHS Regulations and the ADG code

### ESKANOL VE TOPCOAT

Revision date: 16.12.2018

Product code: 00359-1320\_AUS

Page 7 of 10

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

No decomposition if stored and applied as directed.

##### 10.2. Chemical stability

Stable under normal conditions.

##### 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.  
Reactions with peroxides.

##### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.  
Vapour/air mixtures are explosive at intensive warming.  
Heating can release vapours which can be ignited.  
Avoid temperatures above 50°C.  
If heating up polymerisation.

##### 10.5. Incompatible materials

Oxidizing agents, Metal halogenides, Peroxides

##### 10.6. Hazardous decomposition products

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).  
Carbon monoxide and carbon dioxide

#### SECTION 11: Toxicological information

##### 11.1. Information on toxicological effects

###### **Acute toxicity**

Harmful if inhaled.  
No toxicological data available.  
Styrene  
LD50/oral/rat: 5000 mg/kg  
LD50/dermal/rat: > 2000 mg/kg  
LC50/inhalation/rat: 11.8 mg/l/4h

###### **Irritation and corrosivity**

Causes skin irritation.  
Causes serious eye irritation.

###### **Sensitising effects**

May cause an allergic skin reaction. (2-phenylpropene, alpha-methylstyrene)

###### **Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of damaging the unborn child. (styrene)  
Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.

###### **STOT-single exposure**

May cause respiratory irritation. (styrene)

###### **STOT-repeated exposure**

Causes damage to organs through prolonged or repeated exposure. (styrene)

###### **Aspiration hazard**

Based on available data, the classification criteria are not met.

###### **Practical experience**

###### **Other observations**

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.



## Safety Data Sheet

According to the Model WHS Regulations and the ADG code

### ESKANOL VE TOPCOAT

Revision date: 16.12.2018

Product code: 00359-1320\_AUS

Page 8 of 10

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

#### SECTION 12: Ecological information

##### 12.1. Toxicity

Ecological data are not available.  
Harmful to aquatic life with long lasting effects.  
Styrene  
LC50/Pimephales promelas/96 h = 4.02 mg/kg  
EC50/Daphnia magna/48 h = 4.7 mg/kg  
EC50/Pseudokirchneriela subcapitata/72 h > 4.9 mg/kg

##### 12.2. Persistence and degradability

No data available

##### 12.3. Bioaccumulative potential

No data available

##### 12.4. Mobility in soil

No data available

##### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

##### 12.6. Other adverse effects

Hazardous water pollutant.  
Product is toxic to fish and their nutrient animals.

##### Further information

Do not flush into surface water or sanitary sewer system.

#### SECTION 13: Disposal considerations

##### 13.1. Waste treatment methods

###### **Advice on disposal**

Can be incinerated, when in compliance with local regulations.  
Where possible recycling is preferred to disposal.  
Waste disposal according to local regulations.

###### **Contaminated packaging**

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.  
Packaging that cannot be cleaned should be disposed of like the product.  
Waste disposal according to local regulations.

#### SECTION 14: Transport information



##### **Land transport (ADG)**

<b><u>14.1. UN number:</u></b>	UN 1866
<b><u>14.2. UN proper shipping name:</u></b>	Resin solution
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	III
Hazard label:	3





## Safety Data Sheet

According to the Model WHS Regulations and the ADG code

### ESKANOL VE TOPCOAT

Revision date: 16.12.2018

Product code: 00359-1320\_AUS

Page 9 of 10

Special Provisions: 223  
Limited quantity: 5 L

**Other applicable information (land transport)**

HAZCHEM: •3Y

**Marine transport (IMDG)**

**14.1. UN number:** UN 1866  
**14.2. UN proper shipping name:** Resin solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3  
Special Provisions: 223, 955  
Limited quantity: 5 L  
Excepted quantity: E1  
EmS: F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN 1866  
**14.2. UN proper shipping name:** Resin solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3  
Special Provisions: A3  
Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**14.6. Special precautions for user**

Handle in accordance with good industrial hygiene and safety practice.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

The transport takes place only in approved and appropriate packaging.

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information****Additional information**

No information available.

**National regulatory information**

Water contaminating class (D): 2 - clearly water contaminating

**Additional information**

Poison Schedule: 5

Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

AICS: All components of this mixture are listed on or exempted from AICS.



## Safety Data Sheet

According to the Model WHS Regulations and the ADG code

### ESKANOL VE TOPCOAT

Revision date: 16.12.2018

Product code: 00359-1320\_AUS

Page 10 of 10

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### Changes

Changes in chapter: -

#### Abbreviations and acronyms

ADG = Australian Code for the Transport of Dangerous Goods by Road & Rail

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

HAZCHEM = HAZardous CHEMicals

WHS = Work Health and Safety

NOHSC = National Occupational Health and Safety Commission (Australia)

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

#### Relevant H and AUH phrases (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*