

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Issue date:16/06/2017 Revision date:15/06/2021 Version: 2.4

SDS No: 00156-0030



SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Product name : TIP TOP PRIMER PR 200
Product code : 525 2406, 525 2451, 525 2743, 525 2744, 529 8109

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Primer

1.4. Details of manufacturer or importer

Manufacturer

REMA TIP TOP AG
65 Gruber Strasse
Poing 85586
Germany
T +49 (0) 8121 / 707 - 100

Distributor

REMA TIP TOP Australia Pty Ltd.
3 - 7 Ironbark Close
Warabrook NSW 2304
Australia
T +61-2-4935-0200
www.rema-tiptop.com.au

E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2	H225
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Skin sensitisation, Category 1	H317
Germ cell mutagenicity, Category 2	H341
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation
mark

Health hazard

Signal word (GHS AU) :

Danger

Contains :

4-methylpentan-2-one (< 75 %); Reaction mass of ethylbenzene and xylene (< 10 %); Phenol formaldehyde resin (< 5 %); Phenol (< 3 %); Formaldehyde (< 0,1 %)

Hazard statements (GHS AU) :

H225 - Highly flammable liquid and vapour
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0030



Precautionary statements (GHS AU)

H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H341 - Suspected of causing genetic defects
H412 - Harmful to aquatic life with long lasting effects

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P281 - Use personal protective equipment as required.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER or doctor if you feel unwell.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Vapours may form explosive mixture with air.

SECTION 3: Composition and information on ingredients

Comments : Preparation with polymers in xylene and 4-methylpentan-2-one.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
4-methylpentan-2-one	108-10-1	< 75	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319 STOT SE 3, H335
Reaction mass of ethylbenzene and xylene	-	< 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Phenol formaldehyde resin	9003-35-4	< 5	Skin Sens. 1, H317

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0030



Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Phenol	108-95-2	< 3	Muta. 2, H341 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 STOT RE 2, H373 Skin Corr. 1B, H314
Zinc oxide	1314-13-2	< 2,5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Toluene	108-88-3	< 2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Formaldehyde	50-00-0	< 0,1	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Muta. 2, H341 Carc. 1B, H350

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Take off immediately all contaminated clothing. Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours. In the event of persistent symptoms receive medical treatment.
First-aid measures after inhalation	: Move to fresh air in case of accidental inhalation of vapours or decomposition products. Call a physician immediately.
First-aid measures after skin contact	: Wash off immediately with soap and plenty of water. Possible risk of resorption through skin. If you feel unwell, seek medical advice.
First-aid measures after eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do not induce vomiting. Rinse mouth out with water. Never give anything by mouth to an unconscious person. Call a physician immediately.

4.2. Symptoms caused by exposure

Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation.

4.3. Medical attention and special treatment

Treatment	: Treat symptomatically.
-----------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0030



Unsuitable extinguishing media : high volume water jet.

5.2. Specific hazards arising from the chemical

General measures : In case of vapour formation use adequate respirator. Explosion free apparatus have to be used. Ensure adequate air ventilation. Evacuate personnel to a safe area. Concerning personal protective equipment to use, see section 8. Remove ignition sources.

Hazardous decomposition products in case of fire : Fire may produce: Carbon monoxide. Carbon dioxide. Hydrogen chloride.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Hazchem Code : * 3YE

Other information : Vapours are heavier than air and may spread along floors. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Cool containers / tanks with spray water if possible. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : In case of vapour formation use adequate respirator. Explosion free apparatus have to be used. Ensure adequate air ventilation. Evacuate personnel to a safe area. Concerning personal protective equipment to use, see section 8. Remove ignition sources.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Shovel or sweep up and put in a closed container for disposal. Clean contaminated surface thoroughly.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Ensure good ventilation of the work station. Vapours are heavier than air. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use explosion-proof equipment. Wear personal protective equipment. Do not handle until all safety precautions have been read and understood.

Hygiene measures : Do not inhale vapour. Always wash hands after handling the product. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0030



7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Pay attention to explosion protection guidelines. Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Incompatible materials	: oxidizing materials.
Information on mixed storage	: Keep away from food, drink and animal feeding stuffs.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

4-methylpentan-2-one (108-10-1)	
Australia - Occupational Exposure Limits	
Local name	Methyl isobutyl ketone (MIBK; 4-Methyl-2-pentanone; Hexone)
OES TWA [1]	205 mg/m ³
OES TWA [2]	50 ppm
OES STEL	307 mg/m ³
OES STEL [ppm]	75 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
Phenol (108-95-2)	
Australia - Occupational Exposure Limits	
Local name	Phenol
OES TWA [1]	4 mg/m ³
OES TWA [2]	1 ppm
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
Zinc oxide (1314-13-2)	
Australia - Occupational Exposure Limits	
Local name	Zinc oxide
OES TWA [1]	10 mg/m ³ dust 5 mg/m ³ fume
OES STEL	10 mg/m ³ fume
Remark (AU)	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
Formaldehyde (50-00-0)	
Australia - Occupational Exposure Limits	
Local name	Formaldehyde
OES TWA [1]	1.2 mg/m ³
OES TWA [2]	1 ppm
OES STEL	2.5 mg/m ³
OES STEL [ppm]	2 ppm

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0030



Formaldehyde (50-00-0)	
Remark (AU)	Carcinogenicity Category 2 – Suspected human carcinogen. The classification of a chemical into this category is on the basis of evidence from human and animal studies, where the evidence is not sufficiently convincing to place the chemical into Category 1 or from limited evidence of carcinogenicity in human or animal studies; Sen - Respiratory and/or Skin Sensitiser.
Chemical category	Probable carcinogen
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

Toluene (108-88-3)	
Australia - Occupational Exposure Limits	
Local name	Toluene
OES TWA [1]	191 mg/m ³
OES TWA [2]	50 ppm
OES STEL	574 mg/m ³
OES STEL [ppm]	150 ppm
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
Chemical category	Skin notation
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Splash protection. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Butyl rubber	5 (> 240 minutes)	≥0.7		

Eye protection : Tightly fitting goggles (EN 166). Eyewash bottle with clean water (EN 15154)

Skin and body protection : Solvent-resistant apron. EN 467

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A		EN 14387

Environmental exposure controls : Avoid release to the environment.

Other information : Do not inhale vapour. Do not eat, drink or smoke when using this product. Wash hands immediately after handling the product. Avoid contact with skin, eyes and clothing.

SECTION 9: Physical and chemical properties

Physical state : Liquid
Appearance : No data available
Colour : Grey
Odour : aromatic

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0030



Odour threshold	: No data available
pH	: Not determined
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: Not determined Freezing point: Not determined
Boiling point	: ≈ 117 °C
Flash point	: 17 °C
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not determined
Flammability (solid, gas)	: No data available
Vapour pressure	: Vapour pressure: 7 – 9 hPa @20°C
Relative density	: No data available
Density	: Density: 0.93 g/cm ³ @ 20 °C
Solubility	: immiscible. at 20 °C. Water: Not miscible
Log Pow	: Not determined
Viscosity, dynamic	: 500 mPa·s
Explosive properties	: Product is not explosive. May form flammable/explosive vapour-air mixture.
Oxidising properties	: Non oxidizing
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: < 70 %
Fat solubility	: No data available
Additional information	: Solvent content < 90%

SECTION 10: Stability and reactivity

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Reactions with oxidizing agents.
Conditions to avoid	: To avoid thermal decomposition, do not overheat. Vapour/air mixtures are explosive. Heating can release vapours which can be ignited.
Incompatible materials	: Strong oxidizing agent.
Hazardous decomposition products	: Carbon monoxide. Carbon dioxide. Hydrogen chloride.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.

ATE AU (dust,mist)	1.684 mg/l/4h
Zinc oxide (1314-13-2)	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402 method)
LC50 Inhalation - Rat	> 5.7 mg/l/4h
Toluene (108-88-3)	
LD50 oral	5000 mg/kg
LC50 Inhalation - Rat (Vapours)	12.5 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. pH: Not determined
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not determined
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Suspected of causing genetic defects.
Carcinogenicity	: Not classified

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0030



Reproductive toxicity : Not classified
STOT-single exposure : May cause respiratory irritation.

4-methylpentan-2-one (108-10-1)

STOT-single exposure : May cause respiratory irritation.

Reaction mass of ethylbenzene and xylene

STOT-single exposure : May cause respiratory irritation.

Toluene (108-88-3)

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Phenol (108-95-2)

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Reaction mass of ethylbenzene and xylene

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Toluene (108-88-3)

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified
Potential adverse human health effects and symptoms : High concentration of vapours may induce: headache, nausea, dizziness. Inhalation may cause irritation, cough, shortness of breath. Repeated exposure may cause skin dryness or cracking. Possible risk of resorption through skin

SECTION 12: Ecological information

12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.
Other information : Do not flush into surface water or sewer system.

TIP TOP PRIMER PR 200

Partition coefficient n-octanol/water (Log Kow) : Not determined

Log Pow : Not determined

Phenol (108-95-2)

EC50 Daphnia 1 : 7.83 mg/l

NOEC chronic fish : 0.75 mg/l

Toluene (108-88-3)

EC50 Daphnia 1 : 3.78 mg/l

NOEC chronic crustacea : 0.74 mg/l

12.2. Persistence and degradability

TIP TOP PRIMER PR 200

Persistence and degradability : No data available.

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0030



12.3. Bioaccumulative potential

TIP TOP PRIMER PR 200	
Log Pow	Not determined
Partition coefficient n-octanol/water (Log Kow)	Not determined
Bioaccumulative potential	No data available.

12.4. Mobility in soil

TIP TOP PRIMER PR 200	
Ecology - soil	No data available.

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : Significantly hazardous to water.

TIP TOP PRIMER PR 200	
Fluorinated greenhouse gases	False
4-methylpentan-2-one (108-10-1)	
Fluorinated greenhouse gases	False
Phenol formaldehyde resin (9003-35-4)	
Fluorinated greenhouse gases	False
Phenol (108-95-2)	
Fluorinated greenhouse gases	False
Zinc oxide (1314-13-2)	
Fluorinated greenhouse gases	False
Formaldehyde (50-00-0)	
Fluorinated greenhouse gases	False
Reaction mass of ethylbenzene and xylene	
Fluorinated greenhouse gases	False
Toluene (108-88-3)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Waste treatment methods : Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Packaging that cannot be cleaned should be disposed of like the product. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Empty containers should be taken for local recycling, recovery or waste disposal.

TIP TOP PRIMER PR 200




Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0030



SECTION 14: Transport information

ADG	IMDG	IATA
14.1. UN number		
1263	1263	1263
14.2. UN Proper Shipping Name		
PAINT	PAINT	Paint
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group		
II - substances presenting medium danger	II	II
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1263
Special provision (ADG) : 163, 367
Limited quantities (ADG) : 5l
Packing instructions (ADG) : P001, IBC02
Special packing provisions (ADG) : PP1
Portable tank and bulk container instructions (ADG) : T4
Portable tank and bulk container special provisions (ADG) : TP1, TP8, TP28

Transport by sea

UN-No. (IMDG) : 1263
Special provisions (IMDG) : 163, 367
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP8, TP28
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG) : B

Air transport

UN-No. (IATA) : 1263
PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0030



PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 3YE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS : All components of this mixture are listed on or exempted from AICS Inventory) status

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Schedule 6

15.2. International agreements

No additional information available

SECTION 16: Other information

Abbreviations and acronyms	: ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways IATA - International Air Transport Association IMDG - International Maritime Dangerous Goods RID - Regulations concerning the International Carriage of Dangerous Goods by Rail DOT - Department of Transport TDG - Transportation of Dangerous Goods REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 GHS - Globally Harmonized System of Classification, Labelling and Packaging of Chemicals IARC - International Agency for Research on Cancer vPvB - Very Persistent and Very Bioaccumulative PBT - Persistent Bioaccumulative Toxic PNEC - Predicted No-Effect Concentration CAS - CAS (Chemical Abstracts Service) number IBC-Code - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk ATE - Acute Toxicity Estimate CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 BCF - Bioconcentration factor MARPOL 73/78 - MARPOL 73/78: International Convention for the Prevention of Pollution From Ships ADG - Transport of Australian Dangerous Goods
Revision date	: 15/06/2021

Classification

Flam. Liq. 2	H225
Acute Tox. 4 (Inhalation:dust,mist)	H332

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0030



Classification	
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Skin Sens. 1	H317
Muta. 2	H341
STOT SE 3	H335
Aquatic Chronic 3	H412

Full text of H-statements	
Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage

TIP TOP PRIMER PR 200

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0030



Full text of H-statements	
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H350	May cause cancer
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.