

TIP TOP PRIMER PR 304

Safety Data Sheet

according to the Model Work Health and Safety Regulations
Issue date:08/05/2019 Revision date:23/03/2022 Supersedes:01/09/2020 Version: 2.5
SDS No: 00156-0211



SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Product name : TIP TOP PRIMER PR 304
Product code : 525 4112, 525 4150

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesives
Industrial use

1.4. Details of manufacturer or importer

Supplier

REMA TIP TOP AG
65 Gruber Strasse
Poing 85586
Germany
T +49 (0) 8121 / 707 - 100
info@tiptop.de

Importer

REMA TIP TOP Australia Pty Ltd.
3/20 Worth Street
Chullora NSW 2190
Australia
T +61 2 8755 8400
www.rema-tiptop.com.au

E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2	H225
Acute toxicity (dermal), Category 4	H312
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity — Repeated exposure, Category 2	H373
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame Exclamation mark Health hazard

Signal word (GHS AU) :

Danger

Contains :

Reaction mass of ethylbenzene and xylene ($\geq 35 - < 40\%$); Butanone ($< 30\%$); Other substances (not contributing to the classification of this product) ($30 - 40\%$); Toluene ($< 1\%$)

TIP TOP PRIMER PR 304

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0211

Hazard statements (GHS AU)	: H225 - Highly flammable liquid and vapour H312+H332 - Harmful in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness H373 - May cause damage to organs through prolonged or repeated exposure H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS AU)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P260 - Do not breathe vapours. P264 - Wash hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a doctor, a POISON CENTER if you feel unwell. P332+P313 - If skin irritation occurs: Get medical attention. P337+P313 - If eye irritation persists: Get medical attention. P362 - Take off contaminated clothing. P363 - Wash contaminated clothing before reuse. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents and container to an approved waste disposal plant.
Additional hazard statements (GHS AU)	: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Vapours may form explosive mixture with air.

SECTION 3: Composition and information on ingredients

Comments : Preparation in organic solvents.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Reaction mass of ethylbenzene and xylene	-	≥ 35 – < 40	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Butanone	78-93-3	< 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

TIP TOP PRIMER PR 304

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0211

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Titanium dioxide	13463-67-7	≥ 1 – < 3	Carc. 2, H351
Zinc oxide	1314-13-2	< 2,5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Other substances (not contributing to the classification of this product)	-	30 - 40	Not classified
Trizinc bis(orthophosphate)	7779-90-0	< 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Toluene	108-88-3	< 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

Comments : Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter < = 10 µm.

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Take off immediately all contaminated clothing. Move the affected person away from the contaminated area. In the event of persistent symptoms receive medical treatment.

First-aid measures after inhalation : Move to fresh air in case of accidental inhalation of vapours or decomposition products. In the event of symptoms refer for medical treatment.

First-aid measures after skin contact : Wash off immediately with soap and plenty of water. Get medical advice if skin irritation persists.

First-aid measures after eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist.

First-aid measures after ingestion : Do not induce vomiting. Rinse mouth out with water. Drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician immediately. Do not induce vomiting without medical advice.

4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

Symptoms/effects after inhalation : May cause respiratory irritation. Harmful if inhaled.

Symptoms/effects after skin contact : May cause skin irritation. Harmful in contact with skin.

Symptoms/effects after eye contact : Causes serious eye irritation.

Chronic symptoms : Suspected of damaging the unborn child.

4.3. Medical attention and special treatment

Treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : high volume water jet.

TIP TOP PRIMER PR 304

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0211

5.2. Specific hazards arising from the chemical

- General measures : In case of vapour formation use adequate respirator. Explosion free apparatus have to be used. Ensure adequate air ventilation. Use personal protective clothing.
- Hazardous decomposition products in case of fire : Chlorine compounds. Carbon monoxide. Carbon dioxide.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
- Hazchem Code : * 3YE
- Other information : Vapours are heavier than air and may spread along floors. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Cool containers / tanks with spray water if possible. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : In case of vapour formation use adequate respirator. Explosion free apparatus have to be used. Ensure adequate air ventilation. Use personal protective clothing.

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe vapours. Avoid contact with skin, eyes and clothing.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and materials for containment and cleaning up

- Methods for cleaning up : Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Shovel or sweep up and put in a closed container for disposal. Clean contaminated surface thoroughly.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Ensure good ventilation of the work station. Avoid contact with skin, eyes and clothing. Take precautionary measures against static discharge. Pay attention to explosion protection guidelines. Keep away from heat and sources of ignition. Do not smoke.
- Hygiene measures : Do not inhale vapour. Avoid contact with skin, eyes and clothing. Always wash hands after handling the product. Apply emollient cream. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Pay attention to explosion protection guidelines. Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Incompatible materials : oxidizing materials.
- Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

TIP TOP PRIMER PR 304

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0211

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Butanone (78-93-3)	
Australia - Occupational Exposure Limits	
Local name	Methyl ethyl ketone (MEK; 2-Butanone)
OES TWA [1]	445 mg/m ³
OES TWA [2]	150 ppm
OES STEL	890 mg/m ³
OES STEL [ppm]	300 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
Titanium dioxide (13463-67-7)	
Australia - Occupational Exposure Limits	
Local name	Titanium dioxide
OES TWA [1]	10 mg/m ³
Remark (AU)	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
Zinc oxide (1314-13-2)	
Australia - Occupational Exposure Limits	
Local name	Zinc oxide
OES TWA [1]	10 mg/m ³ dust 5 mg/m ³ fume
OES STEL	10 mg/m ³ fume
Remark (AU)	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
Toluene (108-88-3)	
Australia - Occupational Exposure Limits	
Local name	Toluene
OES TWA [1]	191 mg/m ³
OES TWA [2]	50 ppm
OES STEL	574 mg/m ³
OES STEL [ppm]	150 ppm
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
Chemical category	Skin notation
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Pay attention to explosion protection guidelines.

TIP TOP PRIMER PR 304

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0211

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Splash protection. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
protective gloves	Butyl rubber	2 (> 30 minutes)	≥0.7		EN ISO 374

Eye protection : Tightly fitting goggles (EN 166). Eyewash bottle with clean water (EN 15154)

Skin and body protection : Long sleeved protective clothing (DIN EN ISO 6530)

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A		EN 14387

Environmental exposure controls : Avoid release to the environment.

Other information : Do not inhale vapour. Avoid contact with skin and eyes. Wash hands before breaks and at the end of workday. Wash hands immediately after handling the product. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

Physical state : Liquid
Appearance : No data available
Colour : red
Odour : Like ketone
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point / Freezing point : No data available
Boiling point : ≈ 80 °C
Flash point : -14 °C
Auto-ignition temperature : > 460 °C
Flammability (solid, gas) : No data available
Vapour pressure : Vapour pressure: ≈ 101 hPa @ 20 °C
Relative density : No data available
Density : Density: 1.02 g/cm³ @ 20 °C
Solubility : Water: partly miscible
Log Pow : No data available
Viscosity, kinematic : > 20.5 mm²/s @ 40 °C
Viscosity, dynamic : ≈ 860 mPa.s
Explosive properties : No data available
Explosive limits : No data available
Minimum ignition energy : No data available
VOC content : 60 – 65 % VOC Directive 2004/42/EC - Decorative paints and varnishes
Fat solubility : No data available
Solvent content : < 70 %

SECTION 10: Stability and reactivity

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Reacts with oxidants.
Conditions to avoid : To avoid thermal decomposition, do not overheat. Vapour/air mixtures are explosive.
Incompatible materials : Strong oxidizing agent.
Hazardous decomposition products : Thermal decomposition generates : Chlorine compounds. Carbon monoxide. Carbon dioxide.

TIP TOP PRIMER PR 304

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0211

SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Harmful in contact with skin.
Acute toxicity (inhalation) : Harmful if inhaled.

ATE AU (dermal)	1100 mg/kg bodyweight
ATE AU (dust,mist)	3.829 mg/l/4h

Zinc oxide (1314-13-2)

LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402 method)
LC50 Inhalation - Rat	> 5.7 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

Butanone (78-93-3)

STOT-single exposure : May cause drowsiness or dizziness.

Toluene (108-88-3)

STOT-single exposure : May cause drowsiness or dizziness.

Reaction mass of ethylbenzene and xylene

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Toluene (108-88-3)

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Reaction mass of ethylbenzene and xylene

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified
Potential adverse human health effects and symptoms : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance. High concentration of vapours may induce: headache, nausea, dizziness. May have a narcotic effect at high concentrations

SECTION 12: Ecological information

12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.
Other information : Do not flush into surface water or sewer system.

12.2. Persistence and degradability

TIP TOP PRIMER PR 304

Persistence and degradability : No data available.

TIP TOP PRIMER PR 304

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0211

Zinc oxide (1314-13-2)

Not rapidly degradable

12.3. Bioaccumulative potential

TIP TOP PRIMER PR 304

Bioaccumulative potential | No data available.

12.4. Mobility in soil

TIP TOP PRIMER PR 304

Ecology - soil | No data available.

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : Significantly hazardous to water.

TIP TOP PRIMER PR 304

Fluorinated greenhouse gases | False

Butanone (78-93-3)

Fluorinated greenhouse gases | False

Titanium dioxide (13463-67-7)

Fluorinated greenhouse gases | False

Zinc oxide (1314-13-2)

Fluorinated greenhouse gases | False

Trizinc bis(orthophosphate) (7779-90-0)

Fluorinated greenhouse gases | False

Toluene (108-88-3)

Fluorinated greenhouse gases | False

Reaction mass of ethylbenzene and xylene

Fluorinated greenhouse gases | False

Other substances (not contributing to the classification of this product)

Fluorinated greenhouse gases | False

SECTION 13: Disposal considerations

Waste treatment methods : Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations.

Product/Packaging disposal recommendations : Packaging that cannot be cleaned should be disposed of like the product. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Empty containers should be taken for local recycling, recovery or waste disposal.

TIP TOP PRIMER PR 304

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0211

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) : 1133
UN-No. (IMDG) : 1133
UN-No. (IATA) : 1133

14.2. UN Proper Shipping Name

Proper Shipping Name (ADG) : ADHESIVES
Proper Shipping Name (IMDG) : ADHESIVES
Proper Shipping Name (IATA) : Adhesives

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 3
Danger labels (ADG) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3



14.4. Packing group

Packing group (ADG) : II - Substances presenting medium danger
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Marine pollutant : No
Dangerous for the environment : No
Other information : No supplementary information available

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1133

TIP TOP PRIMER PR 304

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0211

Limited quantities (ADG) : 5l
Packing instructions (ADG) : P001, IBC02
Special packing provisions (ADG) : PP1
Portable tank and bulk container instructions (ADG) : T4
Portable tank and bulk container special provisions (ADG) : TP1, TP8

Transport by sea

UN-No. (IMDG) : 1133
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP8
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG) : B

Air transport

UN-No. (IATA) : 1133
PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 3YE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : All the chemicals contained in this product are listed introductions

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 23/03/2022

Classification	
Flam. Liq. 2	H225
Acute Tox. 4 (Dermal)	H312

TIP TOP PRIMER PR 304

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0211

Classification	
Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 3	H412

Full text of H-statements	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

TIP TOP PRIMER PR 304

Safety Data Sheet

according to the Model Work Health and Safety Regulations
SDS No: 00156-0211

Full text of H-statements	
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.