

TIP TOP PRIMER PR 805

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
Issue date:19/03/2026 Revision date:25/03/2026 Supersedes:19/03/2026 Version: 1.1
SDS No: 00156-0546



SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Product name : TIP TOP PRIMER PR 805
Product code : 525 2422, 525 2431, 525 2732

1.2. Other means of identification

No additional information available.

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Primer

1.4. Details of manufacturer or importer

Manufacturer

REMA TIP TOP AG
65 Gruber Strasse
Poing 85586
Germany
T +49 (0) 8121 / 707 - 100
info@tiptop.de
E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

Distributor

REMA TIP TOP Australia Pty Ltd.
3/20 Worth Street
Chullora NSW 2190
Australia
T +61 2 8755 8400
www.rema-tiptop.com.au

1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 1	H224
Acute toxicity (inhal.), Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Carcinogenicity, Category 2	H351
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity – Repeated exposure, Category 2	H373
Hazardous to the aquatic environment – Acute Hazard, Category 3	H402
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame



Exclamation mark



Health hazard

Signal word (GHS AU) :

Danger

Contains

: Reaction mass of ethylbenzene and xylene (< 25 %); Butanone (< 5 %); 4-methylpentan-2-one (< 50 %)

TIP TOP PRIMER PR 805

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0546

Hazard statements (GHS AU)	: H224 - Extremely flammable liquid and vapour H315 - Causes skin irritation H319 - Causes serious eye irritation H332 - Harmful if inhaled H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness H351 - Suspected of causing cancer H373 - May cause damage to organs through prolonged or repeated exposure H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS AU)	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground and bond container and receiving equipment. P260 - Do not breathe vapours. P264 - Wash hands, forearms and face thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER, a doctor if you feel unwell. P332+P313 - If skin irritation occurs: Get medical attention. P337+P313 - If eye irritation persists: Get medical attention. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents and container to a hazardous or special waste collection point.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Vapours may form explosive mixture with air.

SECTION 3: Composition and information on ingredients

Comments : Preparation with polymers in xylene and 4-methylpentan-2-one.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
4-methylpentan-2-one	108-10-1	< 50	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H336
Reaction mass of ethylbenzene and xylene	no CAS number	< 25	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
Titanium dioxide	13463-67-7	≥ 3 – < 5	Not classified

TIP TOP PRIMER PR 805

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0546

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Butanone	78-93-3	< 5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Toluene	108-88-3	< 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Other substances (not contributing to the classification of this product)	-	Up to 100%	-

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Reaction mass of ethylbenzene and xylene	CAS-No.: no CAS number	(10 ≤ C ≤ 100) STOT RE 2; H373

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Take off immediately all contaminated clothing. Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours. In the event of persistent symptoms receive medical treatment.
First-aid measures after inhalation	: Move to fresh air in case of accidental inhalation of vapours or decomposition products. Call a physician immediately.
First-aid measures after skin contact	: Wash off immediately with soap and plenty of water. Possible risk of resorption through skin. If you feel unwell, seek medical advice.
First-aid measures after eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do not induce vomiting. Rinse mouth out with water. Never give anything by mouth to an unconscious person. Call a physician immediately.

4.2. Symptoms caused by exposure

Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Chronic symptoms	: Suspected of causing cancer.

4.3. Medical attention and special treatment

Treatment	: Treat symptomatically.
-----------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: high volume water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour.
-------------	---------------------------------------

TIP TOP PRIMER PR 805

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0546

Explosion hazard	: Product is not explosive. Explosive vapour/air mixtures may be formed.
General measures	: In case of vapour formation use adequate respirator. Explosion free apparatus have to be used. Ensure adequate air ventilation. Evacuate personnel to a safe area. Concerning personal protective equipment to use, see section 8. Remove ignition sources.
Hazardous decomposition products in case of fire	: Fire may produce: Carbon oxides (CO, CO ₂). Hydrogen chloride.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Hazchem Code	: * 3YE
Other information	: Vapours are heavier than air and may spread along floors. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: In case of vapour formation use adequate respirator. Explosion free apparatus have to be used. Ensure adequate air ventilation. Evacuate personnel to a safe area. Concerning personal protective equipment to use, see section 8. Remove ignition sources.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours. Avoid contact with skin and eyes.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and materials for containment and cleaning up

For containment	: Dike and contain spill.
Methods for cleaning up	: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Shovel or sweep up and put in a closed container for disposal. Clean contaminated surface thoroughly.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Ensure good ventilation of the work station. Vapours are heavier than air. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use explosion-proof equipment. Wear personal protective equipment. Do not handle until all safety precautions have been read and understood.
Hygiene measures	: Do not inhale vapour. Always wash hands after handling the product. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Pay attention to explosion protection guidelines. Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

TIP TOP PRIMER PR 805

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0546

Incompatible materials : oxidizing materials.
Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Toluene (108-88-3)	
Australia - Occupational Exposure Limits	
Chemical category	Skin notation
Butanone (78-93-3)	
Australia - Occupational Exposure Limits	
Local name	Methyl ethyl ketone (MEK; 2-Butanone)
OES TWA	445 mg/m ³
	150 ppm
OES STEL	890 mg/m ³
	300 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2025)
4-methylpentan-2-one (108-10-1)	
Australia - Occupational Exposure Limits	
Local name	Methyl isobutyl ketone (2-Pentanone, 4-methyl-; MIBK; 4-Methyl-2-pentanone; Hexone)
OES TWA	205 mg/m ³
	50 ppm
OES STEL	307 mg/m ³
	75 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2025)
Titanium dioxide (13463-67-7)	
Australia - Occupational Exposure Limits	
Local name	Titanium dioxide
OES TWA	10 mg/m ³
Remark (AU)	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Regulatory reference	Workplace exposure standards for airborne contaminants (2025)

8.2. Biological Monitoring

Monitoring methods : A specific exposure sampling method is not available.

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Splash protection. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

TIP TOP PRIMER PR 805

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0546

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Butyl rubber	5 (> 240 minutes)	≥0.7		

Eye protection : Eyewash bottle with clean water (EN 15154)

Type	Field of application	Characteristics	Standard
Protective goggles (EN 166)	Liquid splashes may occur		EN 166

Type	Standard
Chemical resistant apron	EN 467

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A - High-boiling (>65 °C) organic compounds		EN 14387

Environmental exposure controls : Avoid release to the environment.

Other information : Do not inhale vapour. Do not eat, drink or smoke when using this product. Wash hands immediately after handling the product. Avoid contact with skin, eyes and clothing.

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Grey
Odour	: aromatic
Odour threshold	: No data available.
pH	: No data available.
pH solution	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point / Freezing point	: No data available.
Boiling point	: 70 °C
Flash point	: 15 °C
Auto-ignition temperature	: No data available.
Flammability	: No data available.
Vapour pressure	: Vapour pressure: 7 – 9 hPa @20°C
Relative density	: No data available.
Density	: Density: 0.87 – 0.92 g/cm ³ @ 20 °C
Solubility	: Water: Not miscible
Log Pow	: No data available.
Viscosity, kinematic	: > 20.5 mm ² /s @ 40 °C
Viscosity, dynamic	: 10 – 300 mPa·s
Explosive properties	: Product is not explosive. May form flammable/explosive vapour-air mixture.
Oxidising properties	: Not oxidising
Explosive limits	: 1.4 Vol-% 4-methylpentan-2-one 7.5 Vol-% 4-methylpentan-2-one
Minimum ignition energy	: No data available.
VOC content	: < 75 %
Fat solubility	: No data available.
Additional information	: Solvent content < 75%

SECTION 10: Stability and reactivity

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Reactions with oxidizing agents.
Conditions to avoid	: To avoid thermal decomposition, do not overheat. Vapour/air mixtures are explosive. Heating can release vapours which can be ignited.

TIP TOP PRIMER PR 805

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0546

Incompatible materials : Strong oxidizing agent.
Hazardous decomposition products : No hazardous decomposition products known. Thermal decomposition generates : Carbon oxides (CO, CO₂). Hydrogen chloride.

SECTION 11: Toxicological information

Acute toxicity (oral) : No data available. (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : No data available. (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Harmful if inhaled.

Reaction mass of ethylbenzene and xylene (no CAS number)	
ATE AU (dermal)	1100 mg/kg bodyweight
ATE AU (gases)	4500 ppmv/4h
ATE AU (vapours)	11 mg/l/4h
ATE AU (dust,mist)	1.5 mg/l/4h
Butanone (78-93-3)	
LD50 oral rat	> 2193 mg/kg (OECD 423 method)
LD50 dermal rabbit	> 5000 mg/kg (OECD 402 method)
LC50 Inhalation - Rat	34 mg/l (4 h)
4-methylpentan-2-one (108-10-1)	
LD50 oral rat	≈ 4570 mg/kg bodyweight rat, (OECD 401 method)
ATE AU (vapours)	11 mg/l/4h
Titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 425 method)

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : No data available. (Based on available data, the classification criteria are not met)
Germ cell mutagenicity : No data available. (Based on available data, the classification criteria are not met)
Carcinogenicity : Suspected of causing cancer.
Reproductive toxicity : No data available. (Based on available data, the classification criteria are not met)
STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard : Not classified (Based on available data, the classification criteria are not met).
Potential adverse human health effects and symptoms : High concentration of vapours may induce: headache, nausea, dizziness. Inhalation may cause irritation, cough, shortness of breath. Repeated exposure may cause skin dryness or cracking. Possible risk of resorption through skin

SECTION 12: Ecological information

12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.
Other information : Do not flush into surface water or sewer system.

Reaction mass of ethylbenzene and xylene (no CAS number)	
LC50 fish 1	2.6 mg/l Oncorhynchus mykiss (Rainbow trout), (OECD 203 method)
EC50 Daphnia 1	> 3.4 mg/l Ceriodaphnia dubia

TIP TOP PRIMER PR 805

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0546

Reaction mass of ethylbenzene and xylene (no CAS number)	
EC50 - Crustacea [2]	1 mg/l Daphnia magna (Water flea), (OECD 202 method)
ErC50 algae	4.9 mg/l Pseudokirchneriella subcapitata, 72 h, (OECD 201 method)
NOEC chronic fish	> 1.3 mg/l 56 d, Oncorhynchus mykiss (Rainbow trout)

Butanone (78-93-3)	
LC50 fish 1	2973 mg/l Pimephales promelas
EC50 Daphnia 1	308 mg/l Daphnia magna (Water flea)
Partition coefficient n-octanol/water (Log Kow)	0.3 (40 °C)
LD50 dermal rabbit	> 5000 mg/kg (OECD 402 method)
LD50 oral rat	> 2193 mg/kg (OECD 423 method)

4-methylpentan-2-one (108-10-1)	
LC50 fish 1	> 179 mg/l Brachydanio rerio (zebra-fish)
EC50 Daphnia 1	> 200 mg/l Daphnia magna (Water flea)
LD50 oral rat	≈ 4570 mg/kg bodyweight rat, (OECD 401 method)

Titanium dioxide (13463-67-7)	
EC50 - Other aquatic organisms [1]	> 100 mg/l
LOEC (chronic)	5 mg/l 21 d - Daphnia magna (Water flea)
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 425 method)

12.2. Persistence and degradability

No additional information available.

12.3. Bioaccumulative potential

Reaction mass of ethylbenzene and xylene (no CAS number)	
Bioaccumulative potential	Low bioaccumulation potential.

Butanone (78-93-3)	
Partition coefficient n-octanol/water (Log Kow)	0.3 (40 °C)
Bioaccumulative potential	Not potentially bioaccumulable.

12.4. Mobility in soil

TIP TOP PRIMER PR 805	
Ecology - soil	No data available.

Butanone (78-93-3)	
Partition coefficient n-octanol/water (Log Kow)	0.3 (40 °C)

12.5. Other adverse effects

Ozone : No data available. (Based on available data, the classification criteria are not met)
Other adverse effects : Significantly hazardous to water.

TIP TOP PRIMER PR 805

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0546

SECTION 13: Disposal considerations

- Waste treatment methods : Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Product/Packaging disposal recommendations : Packaging that cannot be cleaned should be disposed of like the product. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Empty containers should be taken for local recycling, recovery or waste disposal.

SECTION 14: Transport information

In accordance with ADG / IMDG / IATA

ADG	IMDG	IATA
14.1. UN number		
1263	1263	1263
14.2. UN Proper Shipping Name		
PAINT	PAINT	Paint
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		
II - Substances presenting medium danger	II	II
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

14.6. Special precautions for user

- Specific storage requirement : No data available.
- Shock sensitivity : No data available.

14.7. Additional information

- Other information : No supplementary information available

Transport by road and rail

- UN-No. (ADG) : 1263
- Special provision (ADG) : 163, 367
- Limited quantities (ADG) : 5l
- Packing instructions (ADG) : P001, IBC02
- Special packing provisions (ADG) : PP1
- Portable tank and bulk container instructions (ADG) : T4
- Portable tank and bulk container special provisions (ADG) : TP1, TP8, TP28

Transport by sea

- UN-No. (IMDG) : 1263
- Special provisions (IMDG) : 163, 367
- Limited quantities (IMDG) : 5 L
- Excepted quantities (IMDG) : E2

TIP TOP PRIMER PR 805

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0546

Packing instructions (IMDG) : P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP8, TP28
Stowage category (IMDG) : B

Air transport

UN-No. (IATA) : 1263
PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3, A72, A192
ERG code (IATA) : 3L

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 3YE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : Contains substance(s) listed on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

Australian Pesticides and Veterinary Medicines Authority (APVMA)

Not applicable.

15.2. International agreements

No additional information available.

SECTION 16: Other information

Revision date : 25/03/2026

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
DOT	Department of Transport
TDG	Transportation of Dangerous Goods
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

TIP TOP PRIMER PR 805

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0546

Abbreviations and acronyms:	
GHS	Globally Harmonized System of Classification, Labelling and Packaging of Chemicals
IARC	International Agency for Research on Cancer
vPvB	Very Persistent and Very Bioaccumulative
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
CAS	CAS (Chemical Abstracts Service) number
IBC-Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
BCF	Bioconcentration factor
MARPOL 73/78	MARPOL 73/78: International Convention for the Prevention of Pollution From Ships
ADG	Transport of Australian Dangerous Goods

Classification	
Flam. Liq. 1	H224
Acute Tox. 4 (Inhalation)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Carc. 2	H351
STOT SE 3	H336
STOT SE 3	H335
STOT RE 2	H373
Aquatic Acute 3	H402
Aquatic Chronic 3	H412

Full text of H-statements	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Acute 3	Hazardous to the aquatic environment – Acute Hazard, Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

TIP TOP PRIMER PR 805

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0546

Full text of H-statements	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H224	Extremely flammable liquid and vapour
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.