

REMAXX BEAD SEALER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Issue date: 03/12/2003 Revision date: 16/09/2026 Supersedes: 01/09/2022 Version: 2.5

SDS No: 00156-0032



SECTION 1: Identification

1.1. GHS Product identifier

Product form : Mixture
Product name : REMAXX BEAD SEALER
Product code : 593 0807, 593 0814, 593 1394, 593 1395

1.2. Other means of identification

No additional information available.

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Sealant

1.4. Details of manufacturer or importer

Manufacturer

REMA TIP TOP AG
Gruber Strasse 65
Poing 85586
T +49 (0) 8121 / 707 - 100
info@tip-top.de

Importer

REMA TIP TOP Australia Pty Ltd.
3/20 Worth Street
Chullora NSW 2190
Australia
T +61 2 8755 8400
www.rema-tip-top.com.au

E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2	H225
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame



Exclamation mark

Signal word (GHS AU) :

Danger

Contains :

Propan-2-ol (< 25 %); Ethanol (< 25 %)

Hazard statements (GHS AU) :

H225 - Highly flammable liquid and vapour
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS AU) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P261 - Avoid breathing vapours.

REMAXX BEAD SEALER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0032

P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, face protection, protective gloves, protective clothing.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER, a doctor if you feel unwell.
P337+P313 - If eye irritation persists: Get medical attention, medical advice.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and container to in accordance with local and national regulations.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Vapours may form explosive mixture with air.

SECTION 3: Composition and information on ingredients

Comments : Mixture of the substances listed below with nonhazardous additives.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Propan-2-ol	67-63-0	< 25	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Ethanol	64-17-5	< 25	Flam. Liq. 2, H225 Eye Irrit. 2A, H319
Other substances (not contributing to the classification of this product)	-	Up to 100%	-

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
Ethanol	CAS-No.: 64-17-5	(50 ≤ C ≤ 100) Eye Irrit. 2; H319

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Take off immediately all contaminated clothing. Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Move to fresh air in case of accidental inhalation of vapours or decomposition products. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash off immediately with soap and plenty of water. Get medical advice if skin irritation persists.

First-aid measures after eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a physician immediately. Rinse mouth. Drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice.

4.2. Symptoms caused by exposure

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

REMAXX BEAD SEALER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0032

Symptoms/effects after eye contact : Causes serious eye irritation.

4.3. Medical attention and special treatment

Treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Water spray. Dry powder. Carbon dioxide.
Unsuitable extinguishing media : high volume water jet.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour.
Explosion hazard : Vapours may form explosive mixture with air.
General measures : In case of vapour formation use adequate respirator. Ensure adequate air ventilation. Avoid contact with skin, eyes and clothing. Remove ignition sources.
Hazardous decomposition products in case of fire : Carbon oxides (CO, CO₂). Nitrogen oxides.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Hazchem Code : * 3YE
Other information : The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Vapours are heavier than air and may spread along floors. Remove all sources of ignition. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : In case of vapour formation use adequate respirator. Ensure adequate air ventilation. Avoid contact with skin, eyes and clothing. Remove ignition sources.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and materials for containment and cleaning up

For containment : Dam up the liquid spill. Collect spillage.
Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Explosion free apparatus have to be used. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

REMAXX BEAD SEALER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0032

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Take precautionary measures against static discharge. Handle uncleaned empty containers as full ones. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Apply emollient cream. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Pay attention to explosion protection guidelines. Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Incompatible materials : oxidizing materials.
- Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Ethanol (64-17-5)	
Australia - Occupational Exposure Limits	
Local name	Ethyl alcohol (Ethanol)
OES TWA	1880 mg/m ³
	1000 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2025)

8.2. Monitoring methods

- Monitoring methods : A specific exposure sampling method is not available.

8.3. Engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

- Hand protection : This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Butyl rubber	3 (> 60 minutes)	≥0.7		EN ISO 374

- Eye protection : Eyewash bottle with clean water (EN 15154)

Type	Field of application	Characteristics	Standard
Protective goggles (EN 166)	Liquid splashes may occur		EN 166

Type	Standard
Long sleeved protective clothing	EN ISO 6530

- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

REMAXX BEAD SEALER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0032

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A - High-boiling (>65 °C) organic compounds	In case of inadequate ventilation wear	EN 14387

Environmental exposure controls : Avoid release to the environment.
Other information : Do not inhale vapour. Avoid contact with skin and eyes. Wash hands before breaks and at the end of workday. Wash hands immediately after handling the product. Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Colour : dark grey
Odour : alcoholic
Odour threshold : No data available.
pH : No data available.
pH solution : No data available.
Relative evaporation rate (butylacetate=1) : No data available.
Melting point / Freezing point : Melting point: < 0 °C
Boiling point : > 78 °C
Flash point : 12 °C
Auto-ignition temperature : ≈ 425 °C
Flammability : No data available.
Vapour pressure : Vapour pressure: ≈ 57 hPa @ 20 °C
Relative density : No data available.
Density : Density: < 1 g/cm³ @ 20 °C
Solubility : Miscible. at 20 °C.
Log Pow : No data available.
Explosive properties : Product is not explosive. Explosive vapour/air mixtures may be formed.
Oxidising properties : Not oxidising
Explosive limits : 2 Vol-%
Minimum ignition energy : No data available.
VOC content : < 50 %
Fat solubility : No data available.
Additional information : Solvent content < 50%. Solvent separation test (%) 0 %

SECTION 10: Stability and reactivity

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Reacts with oxidants.
Conditions to avoid : Heating can release vapours which can be ignited. Vapour/air-mixtures are explosive at intense warming.
Incompatible materials : Oxidizing agent.
Hazardous decomposition products : No hazardous decomposition products known. Thermal decomposition generates : Carbon oxides (CO, CO2). Nitrogen oxides.

SECTION 11: Toxicological information

Acute toxicity (oral) : No data available. (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : No data available. (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : No data available. (Based on available data, the classification criteria are not met)

Propan-2-ol (67-63-0)	
LD50 oral rat	5840 mg/kg
LD50 dermal rabbit	13900 mg/kg

REMAXX BEAD SEALER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0032

Propan-2-ol (67-63-0)	
LC50 Inhalation - Rat	> 25 mg/l 4 h
LC50 Inhalation - Rat (Vapours)	27908 ppmv
Ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg
LD50 oral	6200 mg/kg
LD50 dermal rabbit	15800 mg/kg
LD50 dermal	20000 mg/kg
LC50 Inhalation - Rat (Vapours)	30 mg/l/4h
Skin corrosion/irritation	: No data available. (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: No data available. (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: No data available. (Based on available data, the classification criteria are not met)
Carcinogenicity	: No data available. (Based on available data, the classification criteria are not met)
Reproductive toxicity	: No data available. (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: No data available. (Based on available data, the classification criteria are not met)
Aspiration hazard	: No data available. (Based on available data, the classification criteria are not met)
Potential adverse human health effects and symptoms	: High concentration of vapours may induce: headache, nausea, dizziness. Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product. May have a narcotic effect at high concentrations

SECTION 12: Ecological information

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: No data available. (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: No data available. (Based on available data, the classification criteria are not met)
Other information	: Do not flush into surface water or sewer system. Ecological injuries are not known or expected under normal use.

Propan-2-ol (67-63-0)	
LC50 fish 1	9640 mg/l Pimephales promelas, 96 h
EC50 Daphnia 1	10000 mg/l Daphnia magna, 48 h
ErC50 algae	1000 mg/l
NOEC chronic crustacea	100 mg/l
Log Pow	0.05
LD50 dermal rabbit	13900 mg/kg
LD50 oral rat	5840 mg/kg
Ethanol (64-17-5)	
LC50 fish 1	11200 mg/l 96 h
EC50 Daphnia 1	5012 mg/l 48 h, Daphnia magna
ErC50 algae	275 mg/l
Bioconcentration factor (BCF REACH)	0.06

REMAXX BEAD SEALER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0032

Ethanol (64-17-5)	
Log Pow	-0.3
LD50 dermal rabbit	15800 mg/kg
LD50 oral rat	10470 mg/kg

12.2. Persistence and degradability

REMAXX BEAD SEALER	
Persistence and degradability	Readily biodegradable

12.3. Bioaccumulative potential

Propan-2-ol (67-63-0)	
Log Pow	0.05
Ethanol (64-17-5)	
Bioconcentration factor (BCF REACH)	0.06
Log Pow	-0.3

12.4. Mobility in soil

Propan-2-ol (67-63-0)	
Log Pow	0.05
Ethanol (64-17-5)	
Log Pow	-0.3

12.5. Other adverse effects

Ozone	: No data available. (Based on available data, the classification criteria are not met)
Other adverse effects	: No additional information available.

SECTION 13: Disposal considerations

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions. Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations.
Product/Packaging disposal recommendations	: Empty containers should be taken for local recycling, recovery or waste disposal. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

In accordance with ADG / IMDG / IATA

ADG	IMDG	IATA
14.1. UN number		
1987	1987	1987
14.2. UN Proper Shipping Name		
ALCOHOLS, N.O.S. (Ethanol ; Isopropanol)	ALCOHOLS, N.O.S. (Ethanol ; Isopropanol)	Alcohols, n.o.s. (Ethanol ; Isopropanol)

REMAXX BEAD SEALER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0032

ADG	IMDG	IATA
14.3. Transport hazard class(es)		
3	3	3
		
14.4. Packing group		
II - Substances presenting medium danger	II	II
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

Other information
No supplementary information available.

14.6. Special precautions for user

Specific storage requirement : No data available.
Shock sensitivity : No data available.

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1987
Special provision (ADG) : 274
Limited quantities (ADG) : 1I
Packing instructions (ADG) : P001, IBC02
Portable tank and bulk container instructions (ADG) : T7
Portable tank and bulk container special provisions (ADG) : TP1, TP8, TP28

Transport by sea

UN-No. (IMDG) : 1987
Special provisions (IMDG) : 274
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T7
Tank special provisions (IMDG) : TP1, TP8, TP28
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG) : B

Air transport

UN-No. (IATA) : 1987
PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364

REMAXX BEAD SEALER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0032

CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3, A180
ERG code (IATA) : 3L

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 3YE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS) : All the chemicals contained in this product are listed introductions
Inventory) status

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

Australian Pesticides and Veterinary Medicines Authority (APVMA)

Not applicable.

15.2. International agreements

No additional information available.

SECTION 16: Other information

Revision date : 16/09/2026
Other information : Data of sections 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge. The delivery specifications are contained in the corresponding product sheet. This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

Abbreviations and acronyms:

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
DOT	Department of Transport
TDG	Transportation of Dangerous Goods
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
GHS	Globally Harmonized System of Classification, Labelling and Packaging of Chemicals
IARC	International Agency for Research on Cancer
vPvB	Very Persistent and Very Bioaccumulative
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration

REMAXX BEAD SEALER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
SDS No: 00156-0032

Abbreviations and acronyms:	
CAS	CAS (Chemical Abstracts Service) number
IBC-Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
BCF	Bioconcentration factor
MARPOL 73/78	MARPOL 73/78: International Convention for the Prevention of Pollution From Ships
ADG	Transport of Australian Dangerous Goods

Classification	
Flam. Liq. 2	H225
Eye Irrit. 2A	H319
STOT SE 3	H336

Full text of H-statements	
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.