

TIP TOP REMA WEAR REPAIR COMPOUND B

Safety Data Sheet

according to the WHS Regulations
Issue date: 25/01/2023 Version: 1.0
SDS No: 00156-0514



SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Product name : TIP TOP REMA WEAR REPAIR COMPOUND B
Product code : 525 1400

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Repair Material

1.4. Details of manufacturer or importer

Manufacturer

REMA TIP TOP AG
65 Gruber Strasse
Poing 85586
Germany
T +49 (0) 8121 / 707 - 100
info@tiptop.de

Importer

REMA TIP TOP Australia Pty Ltd.
3/20 Worth Street
Chullora NSW 2190
Australia
T +61 2 8755 8400
www.rema-tiptop.com.au

E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Corrosive to metals, Category 1	H290
Acute toxicity (oral), Category 4	H302
Skin corrosion/irritation, Category 1B	H314
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Corrosion

Exclamation
mark

Signal word (GHS AU) :

Danger

Contains :

m-phenylenebis(methylamine) (0,25 - 2 %); 3-aminomethyl-3,5,5-trimethylcyclohexylamine (4 - 10 %)

Hazard statements (GHS AU) :

H290 - May be corrosive to metals
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction

Precautionary statements (GHS AU) :

P234 - Keep only in original container
P260 - Do not breathe vapours.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.

TIP TOP REMA WEAR REPAIR COMPOUND B

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0514

P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P301+P312 - IF SWALLOWED: Call a POISON CENTER, a doctor if you feel unwell.
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.
Rinse skin with water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER, a doctor.
P330 - Rinse mouth.
P333+P313 - If skin irritation or rash occurs: Get medical attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P363 - Wash contaminated clothing before reuse.
P390 - Absorb spillage to prevent material damage.
P405 - Store locked up.
P501 - Dispose of contents and container to a hazardous or special waste collection point.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Comments : Mixture of the substances listed below with nonhazardous additives.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Other substances (not contributing to the classification of this product)	-	≥ 60 – < 95	Not classified
Benzyl alcohol	100-51-6	7 - 12	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319
3-aminomethyl-3,5,5-trimethylcyclohexylamine (4 - 10 %)	2855-13-2	4 - 10	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317
m-phenylenebis(methylamine) (0,25 - 2 %)	1477-55-0	0,25 - 2	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Specific concentration limits:			
Name	Product identifier	Specific concentration limits (%)	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (4 - 10 %)	CAS-No.: 2855-13-2	(0.001 ≤ C ≤ 100) Skin Sens. 1A, H317	

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Take off immediately all contaminated clothing. In the event of persistent symptoms receive medical treatment.

TIP TOP REMA WEAR REPAIR COMPOUND B

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0514

First-aid measures after inhalation	: Move to fresh air in case of accidental inhalation of vapours or decomposition products. In the event of symptoms refer for medical treatment.
First-aid measures after skin contact	: Wash off immediately with soap and plenty of water. Get medical advice if skin irritation persists.
First-aid measures after eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist.
First-aid measures after ingestion	: Give a slurry of activated charcoal in water to drink. Drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician immediately. Do not induce vomiting without medical advice.

4.2. Symptoms caused by exposure

Symptoms/effects after skin contact	: Causes severe burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Harmful if swallowed.

4.3. Medical attention and special treatment

Treatment	: Treat symptomatically.
-----------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Alcohol-resistant foam. Carbon dioxide.
Unsuitable extinguishing media	: high volume water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Could burn but do not ignite readily.
Explosion hazard	: Product is not explosive.
General measures	: Avoid contact with skin, eyes and clothing. Ensure adequate air ventilation. Use personal protective clothing. Do not breathe vapour.
Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO ₂). Nitrous gasses.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Hazchem Code	: 2X
Other information	: Collect contaminated firefighting water separately, must not be discharged into the drains. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid contact with skin, eyes and clothing. Ensure adequate air ventilation. Use personal protective clothing. Do not breathe vapour.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: In case of vapour formation use adequate respirator. Wear personal protective equipment.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Do not discharge into the subsoil/soil. Do not discharge into the drains/surface waters/groundwater.

TIP TOP REMA WEAR REPAIR COMPOUND B

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0514

6.3. Methods and materials for containment and cleaning up

For containment : Dike and contain spill.
Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Shovel or sweep up and put in a closed container for disposal. Clean contaminated surface thoroughly.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not smoke. Avoid contact with skin, eyes and clothing. Use only outdoors or in a well-ventilated area. Keep container tightly closed.
Hygiene measures : Do not inhale vapour. Always wash hands after handling the product. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of direct sunlight. Keep container tightly closed in a dry, cool and well-ventilated place.
Incompatible materials : oxidizing materials. Acids. Bases.
Storage temperature : 10 – 30 °C
Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

m-phenylenebis(methylamine) (0,25 - 2 %) (1477-55-0)	
Australia - Occupational Exposure Limits	
Local name	m-Xylene-alpha,alpha'-diamine (m-Xylylendiamine; 1,3-Benzenedimethanamine)
OES C	0.1 mg/m ³
Remark (AU)	Sk - Absorption through the skin may be a significant source of exposure.
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

8.2. Biological Monitoring

Monitoring methods : A specific exposure sampling method is not available.

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Viton	2 (> 30 minutes)	0,7		EN ISO 374
Chemically resistant protective gloves	Nitrile rubber (NBR)	1 (> 10 minutes)	0,4		EN ISO 374

Eye protection : Eyewash bottle with clean water (EN 15154)

TIP TOP REMA WEAR REPAIR COMPOUND B

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0514

Type	Field of application	Characteristics	Standard
Protective goggles (EN 166)	Liquid splashes may occur		EN 166

Skin and body protection :

Type	Standard
Long sleeved protective clothing	EN ISO 6530

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A - High-boiling (>65 °C) organic compounds	In case of inadequate ventilation wear	EN 14387

Environmental exposure controls :

Avoid release to the environment.

Other information :

Do not inhale vapour. Wash hands before breaks and at the end of workday. Wash hands immediately after handling the product. Do not eat, drink or smoke during use. Remove and wash contaminated clothing before re-use.

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous.
Colour	: Black
Odour	: ammonia
Odour threshold	: No data available
pH	: > 8 (20°C)
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: No data available
Boiling point	: > 200
Flash point	: > 100 °C
Auto-ignition temperature	: No data available
Flammability	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density: 1.74 g/cm ³ (21 °C)
Solubility	: Water: Not miscible
Log Pow	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s (40°C)
Explosive properties	: Product is not explosive.
Oxidising properties	: Not oxidising
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 0 %
Fat solubility	: No data available

SECTION 10: Stability and reactivity

Reactivity	: No decomposition if stored normally.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Reactions with acids, alkalis and oxidizing agents.
Conditions to avoid	: To avoid thermal decomposition, do not overheat. Keep out of direct sunlight. Polymerisation occurs when exposed to heat.
Incompatible materials	: Oxidizing agent. acids and bases.
Hazardous decomposition products	: No hazardous decomposition products known. Thermal decomposition generates : Carbon oxides (CO, CO ₂). Nitrous fumes.

TIP TOP REMA WEAR REPAIR COMPOUND B

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0514

SECTION 11: Toxicological information

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

TIP TOP REMA WEAR REPAIR COMPOUND B

ATE AU (oral)	500 mg/kg bodyweight
---------------	----------------------

m-phenylenebis(methylamine) (0,25 - 2 %) (1477-55-0)

LD50 oral rat	930 mg/kg
LD50 dermal rabbit	3100 mg/kg
LC50 Inhalation - Rat	1.16 mg/l
LC50 Inhalation - Rat (Dust/Mist)	1.16 mg/l/4h
LC50 Inhalation - Rat (Vapours)	1.16 mg/l/4h
ATE AU (oral)	500 mg/kg bodyweight
ATE AU (gases)	4500 ppmv/4h
ATE AU (vapours)	11 mg/l/4h
ATE AU (dust,mist)	1.5 mg/l/4h

3-aminomethyl-3,5,5-trimethylcyclohexylamine (4 - 10 %) (2855-13-2)

ATE AU (oral)	500 mg/kg bodyweight
---------------	----------------------

Benzyl alcohol (100-51-6)

LD50 oral rat	1620 mg/kg bw/day (Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Inconclusive, insufficient data)
ATE AU (oral)	500 mg/kg bodyweight
ATE AU (gases)	4500 ppmv/4h
ATE AU (vapours)	11 mg/l/4h
ATE AU (dust,mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Causes severe skin burns. pH: > 8 (20°C)
Serious eye damage/irritation	: Causes serious eye damage. pH: > 8 (20°C)
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

SECTION 12: Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met).
Other information	: Do not flush into surface water or sewer system.

TIP TOP REMA WEAR REPAIR COMPOUND B

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0514

Benzyl alcohol (100-51-6)	
LC50 fish 1	460 mg/l (LC50; EPA OPP 72-1; 96 h; Pimephales promelas; Static system; Fresh water; Experimental value)
Log Pow	1.05

12.2. Persistence and degradability

TIP TOP REMA WEAR REPAIR COMPOUND B	
Persistence and degradability	No data available

12.3. Bioaccumulative potential

TIP TOP REMA WEAR REPAIR COMPOUND B	
Bioaccumulative potential	No data available.

Benzyl alcohol (100-51-6)	
Log Pow	1.05
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

12.4. Mobility in soil

TIP TOP REMA WEAR REPAIR COMPOUND B	
Ecology - soil	No data available.

Benzyl alcohol (100-51-6)	
Surface tension	0.04 N/m (20 °C)
Log Pow	1.05

12.5. Other adverse effects

Ozone : Not classified (Based on available data, the classification criteria are not met)
Other adverse effects : Significantly hazardous to water.

SECTION 13: Disposal considerations

Waste treatment methods : Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Empty containers should be taken for local recycling, recovery or waste disposal. Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information




In accordance with ADG / IMDG / IATA

ADG	IMDG	IATA
14.1. UN number		
2735	2735	2735
14.2. UN Proper Shipping Name		
AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine)	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine)	Amines, liquid, corrosive, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine)

TIP TOP REMA WEAR REPAIR COMPOUND B

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0514

ADG	IMDG	IATA
14.3. Transport hazard class(es)		
8	8	8
		
14.4. Packing group		
II - Substances presenting medium danger	II	II
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 2735
Special provision (ADG) : 274
Limited quantities (ADG) : 1I
Excepted quantities (ADG) : E2
Packing instructions (ADG) : P001, IBC02
Portable tank and bulk container instructions (ADG) : T11
Portable tank and bulk container special provisions (ADG) : TP1, TP27

Transport by sea

UN-No. (IMDG) : 2735
Special provisions (IMDG) : 274
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T11
Tank special provisions (IMDG) : TP1, TP27
EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage) : S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG) : A
Segregation (IMDG) : SGG18, SG35

Air transport

UN-No. (IATA) : 2735
PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y840
PCA limited quantity max net quantity (IATA) : 0.5L
PCA packing instructions (IATA) : 851
PCA max net quantity (IATA) : 1L
CAO packing instructions (IATA) : 855
CAO max net quantity (IATA) : 30L
Special provisions (IATA) : A3, A803
ERG code (IATA) : 8L

TIP TOP REMA WEAR REPAIR COMPOUND B

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0514

14.8. Hazchem or Emergency Action Code

Hazchem Code : 2X

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

15.2. International agreements

No additional information available

SECTION 16: Other information

Classification	
Met. Corr. 1	H290
Acute Tox. 4 (Oral)	H302
Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317

Full text of H-statements	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.