

TIP TOP SOLVENT CF-CE

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Issue date: Revision date: 26/08/2021 Version: 2.2

SDS No: 00156-0233



SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Product name : TIP TOP SOLVENT CF-CE
Product code : 595 9163, 595 9175, 356 1811

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Cleaning agent

1.4. Details of manufacturer or importer

Supplier

REMA TIP TOP AG
65 Gruber Strasse
Poing 85586
Germany
T +49 (0) 8121 / 707 - 100

info@tiptop.de

E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

Importer

REMA TIP TOP Australia Pty Ltd.
3/20 Worth Street
Chullora NSW 2190
Australia
T +61 2 8755 8400

www.rema-tiptop.com.au

1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment — Acute Hazard, Category 1	H400
Hazardous to the aquatic environment — Chronic Hazard, Category 1	H410

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation
mark

Health hazard

Environment

Signal word (GHS AU) :

Danger

Contains :

Ethylacetate (< 55 %); Cyclohexane (< 55 %)

Hazard statements (GHS AU) :

H225 - Highly flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H410 - Very toxic to aquatic life with long lasting effects

TIP TOP SOLVENT CF-CE

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0233



Precautionary statements (GHS AU) :

- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P240 - Ground and bond container and receiving equipment.
- P261 - Avoid breathing vapours.
- P264 - Wash hands, forearms and face thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.
- P273 - Avoid release to the environment.
- P280 - Wear eye protection, face protection, protective gloves, protective clothing.
- P301+P310 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER.
- P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
- P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 - Call a doctor, a POISON CENTER if you feel unwell.
- P331 - Do NOT induce vomiting.
- P332+P313 - If skin irritation occurs: Get medical attention.
- P337+P313 - If eye irritation persists: Get medical attention.
- P391 - Collect spillage.
- P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 - Store in a well-ventilated place. Keep cool.
- P405 - Store locked up.
- P501 - Dispose of contents and container to an approved waste disposal plant.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Vapours may form explosive mixture with air.

SECTION 3: Composition and information on ingredients

Comments : Solvent mixture.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Ethylacetate	141-78-6	< 55	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Cyclohexane	110-82-7	< 55	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Take off immediately all contaminated clothing. In the event of persistent symptoms receive medical treatment. Move the affected person away from the contaminated area.

First-aid measures after inhalation : Move to fresh air in case of accidental inhalation of vapours or decomposition products. Call a physician immediately.

First-aid measures after skin contact : Wash off immediately with soap and plenty of water. Get medical advice if skin irritation persists.

First-aid measures after eye contact : Wash immediately with plenty water (during 20 minutes), also under eyelids. Consult an eye specialist.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. Do not induce vomiting without medical advice.

TIP TOP SOLVENT CF-CE

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0233



4.2. Symptoms caused by exposure

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.

4.3. Medical attention and special treatment

Treatment	: Treat symptomatically.
-----------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: high volume water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour.
General measures	: In case of vapour formation use adequate respirator. Explosion free apparatus have to be used. Ensure adequate air ventilation. Evacuate personnel to a safe area. Remove ignition sources.
Hazardous decomposition products in case of fire	: Carbon monoxide. Carbon dioxide.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Hazchem Code	: * 3YE
Other information	: The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Cool containers / tanks with spray water if possible. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: In case of vapour formation use adequate respirator. Explosion free apparatus have to be used. Ensure adequate air ventilation. Evacuate personnel to a safe area. Remove ignition sources.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours. Avoid contact with skin and eyes.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Do not discharge into drains or the environment. Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and materials for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Shovel or sweep up and put in a closed container for disposal.

TIP TOP SOLVENT CF-CE

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0233



SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep container tightly closed. Vapours are heavier than air and may spread along floors. Ensure good ventilation of the work station. Avoid contact with skin, eyes and clothing. Do not smoke. Keep away from heat and sources of ignition. Take precautionary measures against static discharge. Use explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Pay attention to explosion protection guidelines. Ground/bond container and receiving equipment.
Storage conditions : Keep container tightly closed in a dry, cool and well-ventilated place.
Incompatible materials : oxidizing materials.
Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Ethylacetate (141-78-6)	
Australia - Occupational Exposure Limits	
Local name	Ethyl acetate (Acetic acid ethyl ester; Acetic ester)
OES TWA [1]	720 mg/m ³
OES TWA [2]	200 ppm
OES STEL	1440 mg/m ³
OES STEL [ppm]	400 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
Cyclohexane (110-82-7)	
Australia - Occupational Exposure Limits	
Local name	Cyclohexane
OES TWA [1]	350 mg/m ³
OES TWA [2]	100 ppm
OES STEL	1050 mg/m ³
OES STEL [ppm]	300 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Splash protection. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

TIP TOP SOLVENT CF-CE

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0233



Type	Material	Permeation	Thickness (mm)	Penetration	Standard
protective gloves, Splash protection	Butyl rubber	2 (> 30 minutes)	≥ 0.7		EN ISO 374

Eye protection : Eyewash bottle with clean water (EN 15154). Tightly fitting goggles (EN 166)

Skin and body protection : Solvent-resistant apron. EN 467

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A		EN 14387

Environmental exposure controls : Avoid release to the environment.

Other information : Do not inhale vapour. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes and clothing. Wash hands before breaks and at the end of workday. Wash hands immediately after handling the product. Treat subsequently with skin cream. Remove and wash contaminated clothing before re-use.

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: Colourless
Odour	: Fruity
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Melting point: < -30 °C
Boiling point	: > 76 °C
Flash point	: -11 °C
Auto-ignition temperature	: 260 °C
Flammability (solid, gas)	: No data available
Vapour pressure	: Vapour pressure: 104 hPa @ 20 °C
Relative density	: No data available
Density	: Density: ≈ 0.83 g/cm ³ @ 20 °C
Solubility	: Not miscible. at 20 °C.
Log Pow	: No data available
Viscosity, kinematic	: < 20.5 mm ² /s @ 40 °C
Explosive properties	: Product is not explosive. May form flammable/explosive vapour-air mixture.
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 100 % VOC Directive 2004/42/EC - Decorative paints and varnishes
Fat solubility	: No data available
Solvent content	: 100 %

SECTION 10: Stability and reactivity

Reactivity	: No decomposition if stored normally.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Reactions with oxidizing agents.
Conditions to avoid	: To avoid thermal decomposition, do not overheat. Vapour/air-mixtures are explosive at intense warming. Heating can release vapours which can be ignited.
Incompatible materials	: Strong oxidizing agent.
Hazardous decomposition products	: Thermal decomposition generates : Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

TIP TOP SOLVENT CF-CE

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0233



Cyclohexane (110-82-7)	
LD50 oral rat	> 12705 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

Ethylacetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.

Cyclohexane (110-82-7)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential adverse human health effects and symptoms	: Irritation of mucous membranes. High concentration of vapours may induce: headache, nausea, dizziness

SECTION 12: Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	: Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Very toxic to aquatic life with long lasting effects.
Other information	: Do not flush into surface water or sewer system.

Cyclohexane (110-82-7)	
LC50 fish 1	> 4 mg/l 72h, Selenastrum capricornutum
EC50 Daphnia 1	0.9 mg/l
NOEC chronic algae	0.94 mg/l
BCF - Fish [2]	31 – 129 Cyprinus carpio (Common carp)

12.2. Persistence and degradability

TIP TOP SOLVENT CF-CE	
Persistence and degradability	No data available.

12.3. Bioaccumulative potential

TIP TOP SOLVENT CF-CE	
Bioaccumulative potential	No data available.

Cyclohexane (110-82-7)	
BCF - Fish [2]	31 – 129 Cyprinus carpio (Common carp)

12.4. Mobility in soil

TIP TOP SOLVENT CF-CE	
Ecology - soil	No data available.

TIP TOP SOLVENT CF-CE

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0233



12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : Significantly hazardous to water.

TIP TOP SOLVENT CF-CE

Fluorinated greenhouse gases False

Ethylacetate (141-78-6)

Fluorinated greenhouse gases False

Cyclohexane (110-82-7)

Fluorinated greenhouse gases False

SECTION 13: Disposal considerations

Waste treatment methods : Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Empty containers should be taken for local recycling, recovery or waste disposal. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

ADG	IMDG	IATA
14.1. UN number		
1993	1993	1993
14.2. UN Proper Shipping Name		
FLAMMABLE LIQUID, N.O.S. (Ethylacetate ; Cyclohexane)	FLAMMABLE LIQUID, N.O.S. (Ethylacetate ; Cyclohexane)	Flammable liquid, n.o.s. (Ethylacetate ; Cyclohexane)
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		
II - substances presenting medium danger	II	II
14.5. Environmental hazards		
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

TIP TOP SOLVENT CF-CE

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0233



Transport by road and rail

UN-No. (ADG) : 1993
Special provision (ADG) : 274
Limited quantities (ADG) : 1I
Excepted quantities (ADG) : E2
Packing instructions (ADG) : P001, IBC02
Portable tank and bulk container instructions (ADG) : T7
Portable tank and bulk container special provisions (ADG) : TP1, TP8, TP28

Transport by sea

UN-No. (IMDG) : 1993
Special provisions (IMDG) : 274
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T7
Tank special provisions (IMDG) : TP1, TP28, TP8
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG) : B

Air transport

UN-No. (IATA) : 1993
PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3
ERG code (IATA) : 3H

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 3YE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : All components of this mixture are listed on or exempted from AICIS

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 26/08/2021

TIP TOP SOLVENT CF-CE

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SDS No: 00156-0233



Classification	
Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Full text of H-statements	
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.