



Safety Data Sheet

According to the Model WHS Regulations and the ADG code

TIP TOP SOLVENT CF-R4 SPRAY

Revision date: 27.11.2018

Product code: 00156-0107AUS

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP SOLVENT CF-R4 SPRAY

Art.-No.

595 9149

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent

1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP Australia Pty Ltd.
Street: 3 - 7 Ironbark Close
Place: Warabrook
NSW 2304 / Australia
Telephone: +61-2-4935-0200
Internet: www.rema-tiptop.com.au
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de
1.4. Emergency telephone number: +61-280735031, Infotrac/GBK GmbH-ID: 93591

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS CHEMICAL ACCORDING TO SAFE WORK AUSTRALIA AND WHS CRITERIA
CLASSIFIED AS DANGEROUS GOODS ACCORDING TO THE ADG CODE
POISON SCHEDULE: none allocated (pressurised spray pack)

Classification according to WHS

Hazard categories:
Aerosol: Aerosol 1
Skin corrosion/irritation: Skin Irrit. 2
Serious eye damage/eye irritation: Eye Irrit. 2A
Specific target organ toxicity - single exposure: STOT SE 3
Hazardous to the aquatic environment: Aquatic Chronic 2
Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.

2.2. Label elements

Component(s) to be indicated on the label

Ethyl acetate 30 - 50 %
Aliphatic hydrocarbons > 60 %

Signal word: Danger

Pictograms:



flame



exclamation mark



environment



Safety Data Sheet

According to the Model WHS Regulations and the ADG code

TIP TOP SOLVENT CF-R4 SPRAY

Revision date: 27.11.2018

Product code: 00156-0107AUS

Page 2 of 12

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to approved disposal company or local collection.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.
Heating will cause pressure rise with risk of bursting.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation with aliphatic hydrocarbons (free of aromatic hydrocarbons)



Safety Data Sheet

According to the Model WHS Regulations and the ADG code

TIP TOP SOLVENT CF-R4 SPRAY

Revision date: 27.11.2018

Product code: 00156-0107AUS

Page 3 of 12

Hazardous components

CAS No	Chemical name	Quantity
EC No	Classification according to WHS criteria	
141-78-6	Ethyl acetate	30 - 50 %
205-500-4	Flam. Liq. 2, Eye Irrit. 2A, STOT SE 3; H225 H319 H336 AUH066	
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes	10 - 25 %
927-510-4	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	
106-97-8	Butane	10 - 25 %
203-448-7	Flam. Gas 1, Compressed gas; H220 H280	
74-98-6	Propane	10 - 25 %
200-827-9	Flam. Gas 1, Compressed gas; H220 H280	
64742-49-0	Hydrocarbons, C6, isoalkanes, < 3% n-hexane	10 - 25 %
931-254-9	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	
75-28-5	Isobutane	2.5 - 10 %
200-857-2	Flam. Gas 1, Compressed gas; H220 H280	
110-82-7	Cyclohexane	< 1 %
203-806-2	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410	
110-54-3	n-Hexane	< 1 %
203-777-6	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361f H315 H336 H373 H304 H411	

Full text of H and AUH phrases: see section 16.

Further Information

According to note P to labelling (Australian Hazardous Chemical Information System (HCIS)), "Solvent naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off with soap and plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Rinse mouth.
Never give anything by mouth to an unconscious person.
Summon a doctor immediately.



Safety Data Sheet

According to the Model WHS Regulations and the ADG code

TIP TOP SOLVENT CF-R4 SPRAY

Revision date: 27.11.2018

Product code: 00156-0107AUS

Page 4 of 12

Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.
Causes skin irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.
Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.
HAZCHEM: none allocated

Additional information

Heating will cause pressure rise with risk of bursting.
Cool containers at risk with water spray jet.
Vapours can form an explosive mixture with air.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.
Use only explosion-proof equipment.
Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.
Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid contact with the skin and the eyes.



Safety Data Sheet

According to the Model WHS Regulations and the ADG code

TIP TOP SOLVENT CF-R4 SPRAY

Revision date: 27.11.2018

Product code: 00156-0107AUS

Page 5 of 12

Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

- Do not smoke - volatile.
- Keep away from open flames, hot surfaces and sources of ignition.
- Pay attention to anti-explosion rules.
- Do not spray on a naked flame or any other incandescent material.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Protect against direct sun radiation.
- Keep container tightly closed.
- Use only in well-ventilated areas.
- Avoid temperatures above 50°C.

Hints on joint storage

- Incompatible with oxidizing agents.

Further information on storage conditions

- Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

- Cleaning agent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits (OEL) - Australia

CAS No	Substance	ppm	mg/m ³	Category
141-78-6	Ethyl acetate	200	720	TWA
141-78-6	Ethyl acetate	400	1440	STEL
110-82-7	Cyclohexane	100	350	TWA
110-82-7	Cyclohexane	300	1050	STEL
106-97-8	Butane	800	1900	TWA
106-97-8	Butane	-	-	STEL
110-54-3	n-Hexane	20	72	TWA
110-54-3	n-Hexane	-	-	STEL

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
110-82-7	Cyclohexane	100	350		TWA (8 h)	WEL
		300	1050		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL
110-54-3	n-Hexane	20	72		TWA (8 h)	WEL

8.2. Exposure controls

Protective and hygiene measures

- Avoid contact with eyes and skin.
- Wash hands before breaks and immediately after handling the product.
- When using do not eat, drink or smoke.



Safety Data Sheet

According to the Model WHS Regulations and the ADG code

TIP TOP SOLVENT CF-R4 SPRAY

Revision date: 27.11.2018

Product code: 00156-0107AUS

Page 6 of 12

Remove and wash contaminated clothes before re-use.
Do not breath vapours or spray mist.

Eye/face protection

Safety goggles with side protection.
Eye wash bottle with pure water.

Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.
This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	Colourless
Odour:	Fruity

Test method

pH-Value:	Not determined
-----------	----------------

Changes in the physical state

Melting point:	No information available. @9940nb.... °C
Initial boiling point and boiling range:	Not determined
Sublimation point:	Not determined
Softening point:	Not determined
Pour point:	Not determined
Flash point:	< 0 °C

Flammability

Solid:	Not applicable
Gas:	Not determined

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	Not determined.
Upper explosion limits:	Not determined.
Ignition temperature:	Not determined.

Auto-ignition temperature

Solid:	Not applicable
Gas:	Not determined.
Decomposition temperature:	Not determined.

Oxidizing properties

Not fire-promoting.



Safety Data Sheet

According to the Model WHS Regulations and the ADG code

TIP TOP SOLVENT CF-R4 SPRAY

Revision date: 27.11.2018

Product code: 00156-0107AUS

Page 7 of 12

Vapour pressure: (at 20 °C)	3000 hPa
Vapour pressure: (at 50 °C)	< 10000 hPa
Density (at 20 °C):	0.658 g/cm ³
Bulk density:	Not applicable
Water solubility: (at 20 °C)	Immiscible

Solubility in other solvents

Not determined.

Partition coefficient: Not determined.

Viscosity / dynamic: Not determined.

Viscosity / kinematic: Not determined.

Flow time: Not determined.

Vapour density: Not determined.

Evaporation rate: Not determined.

Solvent separation test: Not determined.

Solvent content: Not determined.

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

Vapours may form explosive mixture with air.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Heating will cause pressure rise with risk of bursting.

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity



Safety Data Sheet

According to the Model WHS Regulations and the ADG code

TIP TOP SOLVENT CF-R4 SPRAY

Revision date: 27.11.2018

Product code: 00156-0107AUS

Page 8 of 12

Based on available data, the classification criteria are not met.
No toxicological data available.

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes
LD50/oral/rat: > 5840 mg/kg (OECD 401)
LD50/dermal/rat: > 2920 mg/kg (OECD 402)
LC50/inhalation/rat: > 23.3 mg/l/4 h

Hydrocarbons, C6, isoalkanes, < 3% n-hexane
LD50/oral/rat: 16570 mg/kg (OECD 401)
LD50/dermal/rat: 3350 mg/kg (OECD 402)
LC50/inhalation/rat: 259354 mg/m³/4 h

Ethyl acetate
LD50/oral/rat: 4935 mg/kg
LD50/dermal/rat: > 5000 mg/kg
LC50/inhalation/rat: 30 mg/l/4 h

Irritation and corrosivity

Causes skin irritation.
Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Ethyl acetate; Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes ; Hydrocarbons, C6, isoalkanes, < 3% n-hexane)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

Other observations

High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.
Toxic to aquatic life with long lasting effects.

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes
LC50/Oncorhynchus mykiss/96 h = 13.4 mg/kg
NOEC/Oncorhynchus mykiss/28 d = 1.534 mg/l
EC50/Daphnia magna/48 h = 3.0 mg/l
NOEC/Daphnia magna/21 h = 0.17 mg/l
ErC50/Pseudokirchneriella subcapitata/48 h = 20 mg/l

Hydrocarbons, C6, isoalkanes, < 3% n-hexane
LC50/Oncorhynchus mykiss/96 h = 18.27 mg/l
NOEC/Oncorhynchus mykiss/28 d = 4.089 mg/l



Safety Data Sheet

According to the Model WHS Regulations and the ADG code

TIP TOP SOLVENT CF-R4 SPRAY

Revision date: 27.11.2018

Product code: 00156-0107AUS

Page 9 of 12

EC50/Daphnia magna/48 h = 31.9 mg/l
NOEC/Daphnia magna/21 h = 7.138 mg/l
ErC50/Pseudokirchneriella subcapitata/48 h = 3.034 mg/l

Ethyl acetate
LC50/EC50/EC50 : > 100 mg/l

Cyclohexane
EC50/Daphnia magna/48 h = 0.9 mg/l
IC50/Selenastrum capricornutum/72 h > 4 mg/l

n-Hexane
LC50/Fish/96 h = 1 - 10 mg/kg
EC50/Daphnia magna/48 h = 1 - 10 mg/kg

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be incinerated, when in compliance with local regulations.
Where possible recycling is preferred to disposal.

Contaminated packaging

Offer empty spray cans to an established disposal company.

SECTION 14: Transport information



Land transport (ADG)

<u>14.1. UN number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
<u>14.4. Packing group:</u>	-
Hazard label:	2.1
Special Provisions:	63 190 277 327 344
Limited quantity:	1 L

**Safety Data Sheet**

According to the Model WHS Regulations and the ADG code

TIP TOP SOLVENT CF-R4 SPRAY

Revision date: 27.11.2018

Product code: 00156-0107AUS

Page 10 of 12

Other applicable information (land transport)

HAZCHEM: none allocated

Marine transport (IMDG)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Special Provisions:	63, 190, 277, 327, 344, 381,959
Limited quantity:	1000 mL
Excepted quantity:	E0
EmS:	F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS, flammable
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes
Hydrocarbons, C6, isoalkanes, < 3% n-hexane

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 57: Cyclohexane

2004/42/EC (VOC): 658 g/l

National regulatory information

Water contaminating class (D): 2 - clearly water contaminating

Additional information

Poison Schedule: none allocated (pressurised spray pack)



Safety Data Sheet

According to the Model WHS Regulations and the ADG code

TIP TOP SOLVENT CF-R4 SPRAY

Revision date: 27.11.2018

Product code: 00156-0107AUS

Page 11 of 12

Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

All components of this mixture are listed on or exempted from AICS.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Changes in chapter: 1, 3, 9, 12, 15.

Abbreviations and acronyms

ADG = Australian Code for the Transport of Dangerous Goods by Road & Rail

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

HAZCHEM = HAZardous CHEMicals

WHS = Work Health and Safety

NOHSC = National Occupational Health and Safety Commission (Australia)

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and AUH phrases (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
AUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present



Safety Data Sheet

According to the Model WHS Regulations and the ADG code

TIP TOP SOLVENT CF-R4 SPRAY

Revision date: 27.11.2018

Product code: 00156-0107AUS

Page 12 of 12

level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)