

TIP TOP CEMENT SC 4000 White

Safety Data Sheet

according to the WHS Regulations
Issue date: 25/06/2024 Version: 1.0
SDS No: 00156-0538



SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Product name : TIP TOP CEMENT SC 4000 White
Product code : 525 2695, 525 2704, 5252705, 525 2712, 525 2729

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesive

1.4. Details of manufacturer or importer

Manufacturer

REMA TIP TOP AG
65 Gruber Strasse
Poing 85586
Germany
T +49 (0) 8121 / 707 - 100
info@tiptop.de

Importer

REMA TIP TOP Australia Pty Ltd.
3/20 Worth Street
Chullora NSW 2190
Australia
T +61 2 8755 8400
www.rema-tiptop.com.au

E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

1.5. Emergency phone number

Emergency number : +61-280735031, Infotrac/GBK GmbH-ID: 93591

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 1	H410

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation
mark

Environment

Signal word (GHS AU) :

Danger

Contains :

Cyclohexane (< 40 %); Other substances (not contributing to the classification of this product) (≥ 10 – < 30 %); Ethylacetate (< 40 %)

Hazard statements (GHS AU) :

H225 - Highly flammable liquid and vapour

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS AU) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

TIP TOP CEMENT SC 4000 White

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0538

P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER, a doctor if you feel unwell.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Vapours may form explosive mixture with air.

SECTION 3: Composition and information on ingredients

Comments : Preparation in organic solvents.

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
Ethylacetate (< 40 %)	141-78-6	< 40	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Cyclohexane	110-82-7	< 40	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Other substances (not contributing to the classification of this product) ($\geq 10 - < 30$ %)	-	$\geq 10 - < 30$	Not classified
Zinc oxide	1314-13-2	< 5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
silicon dioxide crystalline-free	112926-00-8	< 5	Not classified
Colophony	8050-09-7	< 1	Skin Sens. 1, H317
Titanium dioxide	13463-67-7	< 1	Carc. 2, H351

Specific concentration limits:

Comments : Note 10 : The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Take off immediately all contaminated clothing. In the event of persistent symptoms receive medical treatment. Move the affected person away from the contaminated area.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a physician immediately.

TIP TOP CEMENT SC 4000 White

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0538

First-aid measures after skin contact	: Wash off immediately with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician immediately.

4.2. Symptoms caused by exposure

Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: Aspiration hazard.

4.3. Medical attention and special treatment

Treatment	: Treat symptomatically. Delayed fatal pulmonary oedema possible. Keep under medical supervision for at least 48 hours.
-----------	---

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Alcohol resistant foam. Water spray. Dry powder. Carbon dioxide.
Unsuitable extinguishing media	: high volume water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: Product is not explosive. Vapours may form explosive mixture with air.
General measures	: In case of vapour formation use adequate respirator. Evacuate personnel to a safe area. Use explosion-proof equipment.
Hazardous decomposition products in case of fire	: In case of fire: dangerous decomposition products are formed. Carbon oxides (CO, CO ₂). Hydrogen chloride gas.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Hazchem Code	: * 3Y
Other information	: The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: In case of vapour formation use adequate respirator. Evacuate personnel to a safe area. Use explosion-proof equipment.
------------------	--

6.1.1. For non-emergency personnel

Emergency procedures	: Ensure adequate air ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

TIP TOP CEMENT SC 4000 White

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0538

6.3. Methods and materials for containment and cleaning up

- For containment : Dam up the liquid spill.
Methods for cleaning up : Shovel or sweep up and put in a closed container for disposal. Take up liquid spill into absorbent material, e.g.: sand, earth, vermiculite.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep the container tightly closed. Vapours are heavier than air and may spread along floors. Ensure good ventilation of the work station. Avoid contact with skin, eyes and clothing. Do not smoke. Keep away from heat and sources of ignition. Take precautionary measures against static discharge. Use explosion-proof equipment.
Hygiene measures : Do not inhale vapour. Treat subsequently with skin cream. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Pay attention to explosion protection guidelines.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Incompatible materials : oxidizing materials.
Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

Zinc oxide (1314-13-2)	
Australia - Occupational Exposure Limits	
Local name	Zinc oxide
OES TWA	10 mg/m ³ dust 5 mg/m ³ fume
OES STEL	10 mg/m ³ fume
Remark (AU)	Dust: (a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)
Cyclohexane (110-82-7)	
Australia - Occupational Exposure Limits	
Local name	Cyclohexane
OES TWA	350 mg/m ³ 100 ppm
OES STEL	1050 mg/m ³ 300 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)
Ethylacetate (< 40 %) (141-78-6)	
Australia - Occupational Exposure Limits	
Local name	Ethyl acetate (Acetic acid ethyl ester; Acetic ester)
OES TWA	720 mg/m ³

TIP TOP CEMENT SC 4000 White

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0538

Ethylacetate (< 40 %) (141-78-6)	
	200 ppm
OES STEL	1440 mg/m ³ 400 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

Titanium dioxide (13463-67-7)	
Australia - Occupational Exposure Limits	
Local name	Titanium dioxide
OES TWA	10 mg/m ³
Remark (AU)	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Regulatory reference	Workplace exposure standards for airborne contaminants (2022)

8.2. Biological Monitoring

Monitoring methods : A specific exposure sampling method is not available.

8.3. Engineering controls

Appropriate engineering controls : Pay attention to explosion protection guidelines. Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Splash protection. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Nitrile rubber (NBR)	1 (> 10 minutes)	≥0.4		
Chemically resistant protective gloves	Butyl rubber	2 (> 30 minutes)	≥ 0.7		

Eye protection : Eyewash bottle with clean water (EN 15154)

Type	Field of application	Characteristics	Standard
Protective goggles (EN 166)	Liquid splashes may occur		EN 166

Skin and body protection :

Type	Standard
Long sleeved protective clothing	EN ISO 6530

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A - High-boiling (>65 °C) organic compounds		EN 14387

Environmental exposure controls : Avoid release to the environment.

Other information : Do not inhale vapour. Wash hands before breaks and at the end of workday. Wash hands immediately after handling the product. Do not eat, drink or smoke during use. Treat subsequently with skin cream.

SECTION 9: Physical and chemical properties

Physical state : Liquid

TIP TOP CEMENT SC 4000 White

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0538

Appearance	: Liquid. Viscous.
Colour	: Mixture contains one or more component(s) which have the following colour(s): White to light yellow Clear Colourless White
Odour	: Fruity
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: No data available
Boiling point	: 77 – 81 °C
Flash point	: -19 °C
Auto-ignition temperature	: > 250 °C
Flammability	: No data available
Vapour pressure	: Vapour pressure: ≈ 100 hPa @ 20 °C
Relative density	: No data available
Density	: Density: 0.9 g/cm ³ @ 20 °C
Solubility	: immiscible. at 20 °C.
Log Pow	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s @ 40 °C
Viscosity, dynamic	: ≈ 2000 mPa·s
Explosive properties	: Product is not explosive. May form flammable/explosive vapour-air mixture.
Oxidising properties	: Not oxidising
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 75 – 80 %
Fat solubility	: No data available
Additional information	: Efflux time 116 s @23°C, 6 DIN EN ISO 2431. Solvent separation test (%) 0. Solvent content < 80%

SECTION 10: Stability and reactivity

Reactivity	: No decomposition if stored normally. Highly flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: oxidizing materials.
Conditions to avoid	: Vapour/air-mixtures are explosive at intense warming. Heating can release vapours which can be ignited. To avoid thermal decomposition, do not overheat.
Incompatible materials	: Oxidizing agent.
Hazardous decomposition products	: Carbon monoxide. Carbon dioxide. Hydrogen chloride gas.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

Zinc oxide (1314-13-2)

LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402 method)
LC50 Inhalation - Rat	> 5.7 mg/l/4h

Cyclohexane (110-82-7)

LD50 oral rat	> 12705 mg/kg
---------------	---------------

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)

TIP TOP CEMENT SC 4000 White

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0538

STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Potential adverse human health effects and symptoms	: Irritation of mucous membranes. High concentration of vapours may induce: headache, nausea, dizziness. Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product

SECTION 12: Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Very toxic to aquatic life with long lasting effects.
Other information	: Do not flush into surface water or sewer system.

Cyclohexane (110-82-7)	
LC50 fish 1	4 mg/l 72h, Selenastrum capricornutum
EC50 Daphnia 1	0.9 mg/l
BCF - Fish [2]	31 – 129 Cyprinus carpio (Common carp)

silicon dioxide crystalline-free (112926-00-8)	
LC50 fish 1	10000 mg/l

12.2. Persistence and degradability

TIP TOP CEMENT SC 4000 White	
Persistence and degradability	No data available

12.3. Bioaccumulative potential

TIP TOP CEMENT SC 4000 White	
Bioaccumulative potential	No data available.

Cyclohexane (110-82-7)	
BCF - Fish [2]	31 – 129 Cyprinus carpio (Common carp)

12.4. Mobility in soil

TIP TOP CEMENT SC 4000 White	
Ecology - soil	No data available.

12.5. Other adverse effects

Ozone	: Not classified (Based on available data, the classification criteria are not met)
Other adverse effects	: No additional information available

SECTION 13: Disposal considerations

Waste treatment methods	: Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.
-------------------------	--

TIP TOP CEMENT SC 4000 White

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0538

Product/Packaging disposal recommendations : Packaging that cannot be cleaned should be disposed of like the product. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Empty containers should be taken for local recycling, recovery or waste disposal.

SECTION 14: Transport information

In accordance with ADG / IMDG / IATA

ADG	IMDG	IATA
14.1. UN number		
1133	1133	1133
14.2. UN Proper Shipping Name		
ADHESIVES	ADHESIVES	Adhesives
14.3. Transport hazard class(es)		
3	3	3
14.4. Packing group		
III - Substances presenting low danger	III	III
14.5. Environmental hazards		
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : (Packing group III, if content of packaging <= 450l, according 2.3.2.2 IMDG). (Packing group III, if content of packaging <= 30l, according 3.3.3.1.1 IATA)

Transport by road and rail

UN-No. (ADG) : 1133
Special provision (ADG) : 223
Limited quantities (ADG) : 5l
Packing instructions (ADG) : P001, IBC03, LP01
Special packing provisions (ADG) : PP1
Portable tank and bulk container instructions (ADG) : T2
Portable tank and bulk container special provisions (ADG) : TP1

Transport by sea

UN-No. (IMDG) : 1133
Transport regulations (IMDG) : Transport in accordance with section 2.3.2.5 of the IMDG (viscous substance) may be applied
Special provisions (IMDG) : 223, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1

TIP TOP CEMENT SC 4000 White

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0538

IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG) : A
MFAF-No : 127

Air transport

UN-No. (IATA) : 1133
PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 30L (IATA 3.3.3.1.)
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 100L (IATA 3.3.3.1)
Special provisions (IATA) : A3
ERG code (IATA) : 3L
Other applicable information : (Packing group III, if content of packaging \leq 450l, according 2.2.3.1.4 ADR, RID, ADN);
(Packing group III, if content of packaging \leq 450l, according 2.3.2.2 IMDG)

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 3Y

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS : All components of this mixture are listed on or exempted from AICIS Inventory) status

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number : Labelling requirements for SUSMP do not apply to a poison that is packed and sold solely for industrial, laboratory or manufacturing use. However, this product is labelled in accordance with the Safe Work Australia "Code of Practice" for workplace substances.

15.2. International agreements

No additional information available

SECTION 16: Other information

Other information : Data of sections 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge. The delivery specifications are contained in the corresponding product sheet. This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

Abbreviations and acronyms:

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods

TIP TOP CEMENT SC 4000 White

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0538

Abbreviations and acronyms:	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
DOT	Department of Transport
TDG	Transportation of Dangerous Goods
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
GHS	Globally Harmonized System of Classification, Labelling and Packaging of Chemicals
IARC	International Agency for Research on Cancer
vPvB	Very Persistent and Very Bioaccumulative
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
CAS	CAS (Chemical Abstracts Service) number
IBC-Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
BCF	Bioconcentration factor
MARPOL 73/78	MARPOL 73/78: International Convention for the Prevention of Pollution From Ships
ADG	Transport of Australian Dangerous Goods

Classification	
Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336
Aquatic Chronic 1	H410

Full text of H-statements	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation

TIP TOP CEMENT SC 4000 White

Safety Data Sheet

according to the WHS Regulations
SDS No: 00156-0538

Full text of H-statements	
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.