

TIP TOP ADHESIVE TC 5500

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
Issue date: 27/05/2026 Version: 1.0
SDS No: 00359-1396



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : TIP TOP ADHESIVE TC 5500
Product code : 525 2210

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Adhesive

1.2.2. Uses advised against

No additional information available.

1.3. Details of the supplier of the safety data sheet

Manufacturer

TIP TOP Oberflächenschutz Elbe GmbH
Heuweg, 4
6886 Wittenberg
T +49(0)3491/635-50 - F +49(0)3491/635-552

Importer

REMA TIP TOP INDUSTRY UK LTD
Westland Square
DN11 8EW West Yorkshire LEEDS
United Kingdom
T +44 (0)1302 711233
www.rema-tiptop.co.uk

E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

1.4. Emergency telephone number

Emergency number : INTERNATIONAL: +49 (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to GB CLP (SI 2019:720 as amended)

Flammable liquids, Category 3	H226
Acute toxicity (dermal), Category 4	H312
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity – Repeated exposure, Category 2	H373
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

TIP TOP ADHESIVE TC 5500

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
SDS No: 00359-1396

2.2. Label elements

Labelling according to GB CLP (SI 2019:720 as amended)

Hazard pictograms (GB CLP)



GHS02

GHS07

GHS08

Signal word (GB CLP)

: Warning

Contains

: Reaction mass of ethylbenzene and xylene; Formaldehyde, polymer with 4-(1,1,3,3-tetramethylbutyl)phenol, hydrobromic acid-terminated; 2,2'-dithio di(ethylammonium)-bis(dibenzylidithiocarbamate)

Hazard statements (GB CLP)

: H226 - Flammable liquid and vapour.
H312+H332 - Harmful in contact with skin or if inhaled.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (GB CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a POISON CENTER, doctor if you feel unwell.

2.3. Other hazards

Other hazards not contributing to the classification : Vapours may form explosive mixture with air.

Results of PBT and vPvB assessment

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with UK REACH Annex XIII.

Results of Endocrine Disruptor assessment

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of UK REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in GB BPR and GB PPP at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

Mixtures

Comments : Mixture of the substances listed below with nonhazardous additives

Name	Product identifier	%	Classification according to GB CLP (SI 2019:720 as amended)
Reaction mass of ethylbenzene and xylene	CAS-No.: no CAS number EC-No.: 905-588-0	< 80	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304

TIP TOP ADHESIVE TC 5500

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
SDS No: 00359-1396

Name	Product identifier	%	Classification according to GB CLP (SI 2019:720 as amended)
Carbon black	CAS-No.: 1333-86-4 EC-No.: 215-609-9	< 10	Not classified
Formaldehyde, polymer with 4-(1,1,3,3-tetramethylbutyl)phenol, hydrobromic acid-terminated	CAS-No.: 112484-41-0	< 3	Skin Sens. 1B, H317
Zinc oxide	CAS-No.: 1314-13-2 EC-No.: 215-222-5 UK Index-No.: 030-013-00-7	< 1	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
2,2'-dithio di(ethylammonium)-bis(dibenzyl)dithiocarbamate)	CAS-No.: 239446-62-9 EC-No.: 427-180-7	< 1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
4-tert-octylphenol substance listed on UK REACH candidate (4-(1,1,3,3-tetramethylbutyl)phenol)	CAS-No.: 140-66-9 EC-No.: 205-426-2	< 0.05	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Take off immediately all contaminated clothing. In the event of persistent symptoms receive medical treatment. Move the affected person away from the contaminated area.
First-aid measures after inhalation	: Move to fresh air in case of accidental inhalation of vapours or decomposition products. In the event of symptoms refer for medical treatment.
First-aid measures after skin contact	: Wash off immediately with soap and plenty of water. Get medical advice if skin irritation persists.
First-aid measures after eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist.
First-aid measures after ingestion	: Do not induce vomiting. Rinse mouth out with water. Drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician immediately. Do not induce vomiting without medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Harmful if inhaled. May cause respiratory irritation.
Symptoms/effects after skin contact	: Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Chronic symptoms	: May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: high volume water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: Product is not explosive. Explosive vapour/air mixtures may be formed.

TIP TOP ADHESIVE TC 5500

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
SDS No: 00359-1396

Hazardous decomposition products in case of fire : Carbon oxides (CO, CO₂). Sulphur oxides. Bromine compounds.

5.3. Advice for firefighters

Precautionary measures fire : Cool endangered containers with water spray jet.
Firefighting instructions : Fight fire from safe distance and protected location.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : Vapours are heavier than air and may spread along floors. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : In case of vapour formation use adequate respirator. Ensure adequate air ventilation. Evacuate personnel to a safe area. Concerning personal protective equipment to use, see section 8. Remove ignition sources.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill.
Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Shovel or sweep up and put in a closed container for disposal. Clean contaminated surface thoroughly.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

Refer to protective measures listed in sections 7 and 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep container tightly closed. Provide sufficient air exchange and/or exhaust in work rooms. Keep away from heat and sources of ignition. Handle uncleaned empty containers as full ones. Do not smoke. Take precautionary measures against static discharge.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Pay attention to explosion protection guidelines. Ground/bond container and receiving equipment.
Storage conditions : Keep away from heat and sources of ignition. Keep container tightly closed in a dry, cool and well-ventilated place.
Incompatible materials : oxidizing materials.
Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Adhesive.

TIP TOP ADHESIVE TC 5500

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
SDS No: 00359-1396

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

TIP TOP ADHESIVE TC 5500	
United Kingdom - Occupational Exposure Limits	
Local name	Ethylbenzene
WEL TWA (OEL TWA)	441 mg/m ³
	100 ppm
WEL STEL (OEL STEL)	552 mg/m ³
	125 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Carbon black (1333-86-4)	
United Kingdom - Occupational Exposure Limits	
Local name	Carbon black
WEL TWA (OEL TWA)	3.5 mg/m ³
WEL STEL (OEL STEL)	7 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Reaction mass of ethylbenzene and xylene (no CAS number)	
United Kingdom - Occupational Exposure Limits	
Local name	Xylene
WEL TWA (OEL TWA)	220 mg/m ³ o-,m-,p- or mixed isomers
	50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m ³ o-,m-,p- or mixed isomers
	100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	A specific exposure sampling method is not available.
Biological monitoring methods	A specific exposure sampling method is not available

8.1.3. Air contaminants formed

No additional information available.

TIP TOP ADHESIVE TC 5500

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
SDS No: 00359-1396

8.1.4. DNEL and PNEC

No additional information available.

8.1.5. Control banding

No additional information available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Pay attention to explosion protection guidelines. Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Eyewash bottle with clean water (EN 15154)

Eye protection			
Type	Field of application	Characteristics	Standard
Protective goggles (EN 166)	Liquid splashes may occur		EN 166

8.2.2.2. Skin protection

Skin and body protection:

EN 368

Skin and body protection	
Type	Standard
Long sleeved protective clothing	EN 368

Hand protection:

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Viton	6 (> 480 minutes)	≥ 0.7		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment.

Respiratory protection			
Device	Filter type	Condition	Standard
Respiratory protective device with a gas filter	Type A - High-boiling (>65 °C) organic compounds	In the event of insufficient ventilation:	EN 14387

8.2.2.4. Thermal hazards

No additional information available.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

TIP TOP ADHESIVE TC 5500

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
SDS No: 00359-1396

Other information:

Do not inhale vapour. Avoid contact with skin and eyes. Wash hands before breaks and at the end of workday. Wash hands immediately after handling the product. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous.
Odour	: Hydrocarbon-like.
Odour threshold	: Not available
pH	: Not available
Melting point	: < -25 °C
Freezing point	: Not available
Boiling point	: 136 – 145 °C Reaction mass of ethylbenzene and xylene
Flash point	: 24 °C Reaction mass of ethylbenzene and xylene
Flammability	: Not applicable.
Lower explosive limit (LEL)	: 1 Vol-% Reaction mass of ethylbenzene and xylene
Upper explosive limit (UEL)	: 8 Vol-% Reaction mass of ethylbenzene and xylene
Vapour pressure	: 8 hPa Reaction mass of ethylbenzene and xylene
Vapour pressure at 50°C	: 45 hPa Reaction mass of ethylbenzene and xylene
Relative vapour density at 20°C	: Not available
Relative density	: Not available
Density	: 0.91 g/cm ³ @ 20 °C
Solubility	: Water: Not miscible
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: ≈ 460 °C
Decomposition temperature	: Not available
Viscosity, kinematic	: > 20.5 mm ² /s @ 40 °C
Viscosity, dynamic	: 1400 mPa·s
Explosive properties	: Product is not explosive, May form flammable/explosive vapour-air mixture
Oxidising properties	: Non oxidizing.

9.2. Other information

VOC content	: < 80 %
Particle characteristics	: Not applicable.
Additional information	: Solvent content < 80%

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts with oxidants.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat. Vapour/air mixtures are explosive.

10.5. Incompatible materials

Strong oxidizing agent.

TIP TOP ADHESIVE TC 5500

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
SDS No: 00359-1396

10.6. Hazardous decomposition products

No hazardous decomposition products known. Thermal decomposition generates : Carbon oxides (CO, CO₂). Sulphur oxides. Bromine compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Harmful in contact with skin.
Acute toxicity (inhalation) : Inhalation:dust,mist: Harmful if inhaled.

TIP TOP ADHESIVE TC 5500

ATE UK (Dermal)	1455.026 mg/kg bodyweight
-----------------	---------------------------

ATE UK (dust, mist)	1.984 mg/l/4h
---------------------	---------------

Carbon black (1333-86-4)

LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: other:, Guideline: other:, Guideline: other:, Guideline: other:
--------------------	--

Reaction mass of ethylbenzene and xylene (no CAS number)

ATE UK (Dermal)	1100 mg/kg bodyweight
-----------------	-----------------------

ATE UK (Gases)	4500 ppmv/4h
----------------	--------------

ATE UK (vapours)	11 mg/l/4h
------------------	------------

ATE UK (dust, mist)	1.5 mg/l/4h
---------------------	-------------

Zinc oxide (1314-13-2)

LD50 oral rat	> 5000 mg/kg (OECD 401 method)
---------------	--------------------------------

LD50 dermal rat	> 2000 mg/kg bodyweight rat, (OECD 402 method)
-----------------	--

LC50 Inhalation - Rat	> 5.7 mg/l/4h
-----------------------	---------------

2,2'-dithio di(ethylammonium)-bis(dibenzylidithiocarbamate) (239446-62-9)

ATE UK (oral)	500 mg/kg bodyweight
---------------	----------------------

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Carbon black (1333-86-4)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure : May cause respiratory irritation.
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

Other information

Endocrine disrupting properties

No additional information available.

TIP TOP ADHESIVE TC 5500

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
SDS No: 00359-1396

Other information

Potential adverse human health effects and symptoms : May have a narcotic effect at high concentrations, High concentration of vapours may induce: headache, nausea, dizziness, Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

TIP TOP ADHESIVE TC 5500	
EC50 96h - Algae [1]	> 10000 mg/l
Carbon black (1333-86-4)	
EC50 Daphnia 1	> 1000 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 10000 mg/l Desmodesmus subspicatus
EC50 72h - Algae [2]	> 10000 mg/l
Reaction mass of ethylbenzene and xylene (no CAS number)	
LC50 fish 1	2.6 mg/l Oncorhynchus mykiss (Rainbow trout), (OECD 203 method)
EC50 Daphnia 1	> 3.4 mg/l Ceriodaphnia dubia
EC50 - Crustacea [2]	1 mg/l Daphnia magna (Water flea), (OECD 202 method)
ErC50 algae	4.9 mg/l Pseudokirchneriella subcapitata, 72 h, (OECD 201 method)
NOEC chronic fish	> 1.3 mg/l 56 d, Oncorhynchus mykiss (Rainbow trout)

12.2. Persistence and degradability

TIP TOP ADHESIVE TC 5500	
Persistence and degradability	No data available.

12.3. Bioaccumulative potential

TIP TOP ADHESIVE TC 5500	
Bioaccumulative potential	No data available.
Reaction mass of ethylbenzene and xylene (no CAS number)	
Bioaccumulative potential	Low bioaccumulation potential.

12.4. Mobility in soil

TIP TOP ADHESIVE TC 5500	
Ecology - soil	No data available.

12.5. Results of PBT and vPvB assessment

Component	
Carbon black (1333-86-4)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII

TIP TOP ADHESIVE TC 5500

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
SDS No: 00359-1396

Component	
Reaction mass of ethylbenzene and xylene (no CAS number)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII
Zinc oxide (1314-13-2)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII
Formaldehyde, polymer with 4-(1,1,3,3-tetramethylbutyl)phenol, hydrobromic acid-terminated (112484-41-0)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII
4-tert-octylphenol (140-66-9)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII
2,2'-dithio di(ethylammonium)-bis(dibenzylidithiocarbamate) (239446-62-9)	This substance does not meet the PBT criteria of UK REACH regulation, annex XIII This substance does not meet the vPvB criteria of UK REACH regulation, annex XIII

12.6. Other adverse effects

Ozone : Not classified (Based on available data, the classification criteria are not met)

TIP TOP ADHESIVE TC 5500	
Other information	Do not flush into surface water or sewer system

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Recycling is preferred to disposal or incineration. Can be incinerated according to local regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Do not allow into drains or water courses.






Product/Packaging disposal recommendations : Packaging that cannot be cleaned should be disposed of like the product. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Empty containers should be taken for local recycling, recovery or waste disposal.

Additional information : Flammable vapours may accumulate in the container.

European List of Waste (LoW, EC 2000/532) : 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1133	UN 1133	UN 1133	UN 1133	UN 1133
14.2. UN proper shipping name				
ADHESIVES	ADHESIVES	Adhesives	ADHESIVES	ADHESIVES
14.3. Transport hazard class(es)				
3	3	3	3	3
				

TIP TOP ADHESIVE TC 5500


Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
SDS No: 00359-1396

ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	: 
Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

Transport by sea

Special provisions (IMDG)	: 223, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: A

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

TIP TOP ADHESIVE TC 5500

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
SDS No: 00359-1396

Inland waterway transport

Classification code (ADN) : F1
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T2
Portable tank and bulk container special provisions (RID) : TP1
Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. National regulations

UK REACH Annex XVII (Restriction List)

UK REACH Annex XIV (Authorisation List)

This product contains no substance(s) listed on UK REACH Annex XIV (Authorisation List) equal to or above the 0.1% level of disclosure

UK REACH Candidate List (SVHC)

This product contains substance(s) listed on the UK REACH Candidate list (SVHC) at or above the 0.1% level of disclosure: 4-(1,1,3,3-tetramethylbutyl)phenol - Endocrine disrupting properties (Article 57(f) - environment).

Seveso Directive (Disaster Risk Reduction)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5c FLAMMABLE LIQUIDS Flammable liquids, Categories 2 or 3 not covered by P5a and P5b	5000	50000

GB PIC Regulation (Prior Informed Consent)

This product contains no substance(s) listed on the GB PIC List equal to or above the level of SDS disclosure

POP Regulation (Persistent Organic Pollutants)

This product contains no substance(s) listed on the GB POP List equal to or above the level of SDS disclosure

Ozone Regulation (S.I. No. 168 of 2015)

This product contains no substance(s) listed on the GB Ozone Depletion List equal to or above the level of SDS disclosure

Control of Poisons and Explosives Precursors Act

This product contains substance(s) listed on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

TIP TOP ADHESIVE TC 5500

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
SDS No: 00359-1396

This product contains no substance(s) listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains substance(s) listed on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This substance is not listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations

Drug Precursors Regulation (EC 273/2004)

This product contains no substance(s) listed on the GB Drug Precursors List equal to or above the level of SDS disclosure

15.1.2. Other Information

VOC content : < 80 %

15.2. Chemical safety assessment

No additional information available.

SECTION 16: Other information

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
DOT	Department of Transport
TDG	Transportation of Dangerous Goods
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
GHS	Globally Harmonized System of Classification, Labelling and Packaging of Chemicals
IARC	International Agency for Research on Cancer
vPvB	Very Persistent and Very Bioaccumulative
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
CAS	CAS (Chemical Abstracts Service) number
IBC-Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
BCF	Bioconcentration factor
MARPOL 73/78	MARPOL 73/78: International Convention for the Prevention of Pollution From Ships
ADG	Transport of Australian Dangerous Goods

Other information : Data of sections 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge. The delivery specifications are contained in the corresponding product sheet. This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

TIP TOP ADHESIVE TC 5500

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
SDS No: 00359-1396

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 3	H226	On basis of test data
Acute Tox. 4 (Dermal)	H312	Calculation method
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method

TIP TOP ADHESIVE TC 5500

Safety Data Sheet

According REACH Regulation 1907/2006 as retained in UK law by UK REACH SI 2019 No. 758 as amended
SDS No: 00359-1396

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 3	H412	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.