

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Asplit® Acid Solution

Revision date: 31.03.2021

Product code: 00359-1330

Page 1 of 11

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Asplit® Acid Solution

##### Art.-No.

592 1040

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Post-treatment agent

#### 1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Contact person: Laborleiter

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

#### 1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Substance or mixture corrosive to metals: Met. Corr. 1

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Corr. 1A

Serious eye damage/eye irritation: Eye Dam. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

May be corrosive to metals.

Highly flammable liquid and vapour.

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause drowsiness or dizziness.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

Propan-2-ol

Sulphuric acid

Signal word:

Danger

Pictograms:



##### Hazard statements

H225 Highly flammable liquid and vapour.

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H336 May cause drowsiness or dizziness.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Asplit® Acid Solution

Revision date: 31.03.2021

Product code: 00359-1330

Page 2 of 11

### Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe vapour.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P406 Store in a corrosion-resistant container with a resistant inner liner.

### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

Vapours may form explosive mixture with air.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Mixture containing following substances with additives

#### Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
67-63-0	Propan-2-ol			< 65 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
7664-93-9	Sulphuric acid			< 25 %
	231-639-5	016-020-00-8	01-2119458838-20	
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
67-63-0	200-661-7	Propan-2-ol	< 65 %	
	dermal: LD50 = 12800 mg/kg; oral: LD50 = 5050 mg/kg			
7664-93-9	231-639-5	Sulphuric acid	< 25 %	
	Skin Corr. 1A; H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15			

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

- Remove contaminated soaked clothing immediately.
- In the event of persistent symptoms receive medical treatment.
- Take away from danger area and lay down affected person.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Asplit® Acid Solution

Revision date: 31.03.2021

Product code: 00359-1330

Page 3 of 11

### After inhalation

Move to fresh air in case of accidental inhalation of vapours.  
In the event of symptoms refer for medical treatment.

### After contact with skin

Wash off immediately with soap and plenty of water.  
Seek medical treatment immediately.

### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Consult (eye) doctor immediately.

### After ingestion

Do not induce vomiting.  
Summon a doctor immediately.  
Rinse out mouth and give plenty of water to drink.  
Never give anything by mouth to an unconscious person.  
Induce vomiting only upon the advice of a physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eye damage.  
May cause drowsiness or dizziness.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Fire may produce:  
Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and sulphur oxides (SO<sub>x</sub>)

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

### Additional information

Cool containers at risk with water spray jet.  
Collect contaminated firefighting water separately, must not be discharged into the drains.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General measures

Ensure adequate ventilation.  
Keep away noninvolved persons.

#### For non-emergency personnel

Avoid contact with skin, eyes and clothing.  
Do not breathe vapours.

#### For emergency responders

In case of vapour formation use respirator.  
Use personal protective clothing.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Asplit® Acid Solution

Revision date: 31.03.2021

Product code: 00359-1330

Page 4 of 11

### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.  
Do not discharge into the subsoil/soil.

### 6.3. Methods and material for containment and cleaning up

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

#### For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).  
Shovel into suitable container for disposal.  
Do not use metal containers.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).  
Information for disposal see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed.  
Provide appropriate ventilation and exhaust ventilation at the workplaces.  
Avoid contact with skin, eyes and clothing.

#### Advice on protection against fire and explosion

Keep away from heat and sources of ignition.  
Do not smoke.  
Take precautionary measures against static discharges.  
Use only explosion-proof equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep only in original container.  
Do not use metal containers.  
Keep container tightly closed in a dry, cool and well-ventilated place.  
Pay attention to anti-explosion rules.

#### Hints on joint storage

Incompatible with bases.

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Post-treatment agent

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL
7664-93-9	Sulphuric acid (mist)	-	0.05		TWA (8 h)	WEL

### 8.2. Exposure controls

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Asplit® Acid Solution**

Revision date: 31.03.2021

Product code: 00359-1330

Page 5 of 11

**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

**Protective and hygiene measures**

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

**Eye/face protection**

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

**Hand protection**

Protective gloves resistant to chemicals made off viton, Minimum coat thickness 0.7 mm, Permeation resistance (wear duration) approx. 60 minutes, i.e. protective glove &lt;Vitoject 890&gt; made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Skin protection**

Long sleeved clothing (DIN EN ISO 6530)

Solvent-resistant apron (EN 467).

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

**Environmental exposure controls**

Do not flush into surface water or sanitary sewer system.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Colourless
Odour:	Alcoholic

	<b>Test method</b>
pH-Value:	0,3

**Changes in the physical state**

Melting point:	n.d.
Boiling point or initial boiling point and boiling range:	82 °C *)
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	12 °C *)
Sustaining combustion:	Sustaining combustion

**Flammability**

Solid/liquid:	n.a.
Gas:	n.a.

**Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	2,3 vol. % *)
Upper explosion limits:	12,7 vol. % *)
Auto-ignition temperature:	425 °C *)

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Asplit® Acid Solution**

Revision date: 31.03.2021

Product code: 00359-1330

Page 6 of 11

**Self-ignition temperature**Solid: n.a.  
Gas: n.a.

Decomposition temperature: n.d.

**Oxidizing properties**

Not oxidising.

Vapour pressure: 43 hPa \*)  
(at 20 °C)Density: 0,997 g/cm<sup>3</sup>

Bulk density: n.a.

Water solubility: Miscible  
(at 20 °C)**Solubility in other solvents**

n.d.

Partition coefficient n-octanol/water: n.d.

Viscosity / dynamic: n.d.

Viscosity / kinematic: n.d.

Flow time: n.d.

Relative vapour density: n.d.

Evaporation rate: n.d.

Solvent separation test: n.d.

Solvent content: &lt; 65 %

**9.2. Other information**

Solid content: 0 %

\*) Propan-2-ol

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with alkalies.

**10.4. Conditions to avoid**

Heating can release vapours which can be ignited.

Vapours may form explosive mixture with air.

Gives off hydrogen by reaction with metals.

**10.5. Incompatible materials**

Bases.

**10.6. Hazardous decomposition products**

Hydrogen, by reaction with metals.

Fire may produce:

Carbon monoxide, carbon dioxide, sulphur oxides.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® Acid Solution

Revision date: 31.03.2021

Product code: 00359-1330

Page 7 of 11

#### Acute toxicity

Based on available data, the classification criteria are not met.  
No toxicological data available.

#### Irritation and corrosivity

Causes severe skin burns and eye damage.  
Causes serious eye damage.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (Propan-2-ol)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

No data available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecological data are not available.

### 12.2. Persistence and degradability

No data available

### 12.3. Bioaccumulative potential

No data available

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

### 12.6. Endocrine disrupting properties

No data available

### 12.7. Other adverse effects

Low hazard to waters.

#### Further information

Do not flush into surface water or sanitary sewer system.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Can be incinerated, when in compliance with local regulations.  
Where possible recycling is preferred to disposal.

#### List of Wastes Code - residues/unused products

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® Acid Solution

Revision date: 31.03.2021

Product code: 00359-1330

Page 8 of 11

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

**14.1. UN number:** UN 2924  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propan-2-ol, Sulphuric acid)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3+8



Classification code: FC  
Limited quantity: 1 L / 30 kg  
Excepted quantity: E2  
Transport category: 2  
Hazard No: 338  
Tunnel restriction code: D/E

#### Inland waterways transport (ADN)

**14.1. UN number:** UN 2924  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propan-2-ol, Sulphuric acid)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3+8



Classification code: FC  
Limited quantity: 1 L / 30 kg  
Excepted quantity: E2

#### Marine transport (IMDG)

**14.1. UN number:** UN 2924  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propan-2-ol, Sulphuric acid)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3+8



Marine pollutant: No



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® Acid Solution

Revision date: 31.03.2021

Product code: 00359-1330

Page 9 of 11

Limited quantity: 1 L / 30 kg  
Excepted quantity: E2  
EmS: F-E, S-C

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 2924  
**14.2. UN proper shipping name:** FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propan-2-ol, Sulphuric acid, mixture)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3+8



Limited quantity Passenger: 0.5 L  
Passenger LQ: Y340  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 352  
IATA-max. quantity - Passenger: 1 L  
IATA-packing instructions - Cargo: 363  
IATA-max. quantity - Cargo: 5 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

#### 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC): &lt; 65 %

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

#### Additional information

This product is regulated by Annex II of Regulation (EU) 2019/1148 on the marketing and use of explosives precursors. All suspicious transactions and significant disappearances and thefts have to be reported to the responsible national contact point. Sales personnel at all trading levels has to be instructed.

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Asplit® Acid Solution**

Revision date: 31.03.2021

Product code: 00359-1330

Page 10 of 11

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,2,3,5,6,7,8,9,10,11,12,14,15.

**Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H336	Calculation method

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® Acid Solution

Revision date: 31.03.2021

Product code: 00359-1330

Page 11 of 11

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*