

Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Solution

Revision date: 28.07.2023 Product code: 00359-1207 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Asplit® LC Solution

Art.-No.

592 0820

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Mortar

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-552 Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

Company name: REMA TIP TOP INDUSTRY UK LTD
Street: Plumtree Industrial Estate, Harworth
Place: Doncaster, DN11 8EW, South Yorkshire

Telephone: +44 (0)1302 711233 Internet: www.rema-tiptop.co.uk

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories:

Acute toxicity: Acute Tox. 3 Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1A

Germ cell mutagenicity: Muta. 2 Carcinogenicity: Carc. 1B

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements: Toxic if swallowed.

Harmful in contact with skin or if inhaled.

May cause respiratory irritation.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction. Suspected of causing genetic defects.

May cause cancer.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

GB CLP Regulation



Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Solution

Revision date: 28.07.2023 Product code: 00359-1207 Page 2 of 12

Hazard components for labelling

2-Furaldehyde

Phenol

formaldehyde

N-(3-(trimethoxysilyl)propyl)ethylenediamine

Signal word: Danger

Pictograms:







Hazard statements

H301 Toxic if swallowed.

H312+H332 Harmful in contact with skin or if inhaled.

H335 May cause respiratory irritation.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.H341 Suspected of causing genetic defects.

H350 May cause cancer.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P273 Avoid release to the environment.

Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture containing following substances with additives



Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Solution

Revision date: 28.07.2023 Product code: 00359-1207 Page 3 of 12

Hazardous components

CAS No	Chemical name			
	EC No	Index No	REACH No	
	GHS Classification			
98-01-1	2-Furaldehyde		< 30 %	
	202-627-7	605-010-00-4 01-2119486861-27		
	Carc. 2, Acute Tox. 3, Acute Tox. 3 H331 H301 H312 H315 H319 H33	2, STOT SE 3; H351		
108-95-2	Phenol		< 10 %	
	203-632-7	604-001-00-2	01-2119471329-32	
	Muta. 2, Acute Tox. 3, Acute Tox. 1 H341 H331 H311 H301 H314 H37	RE 2, Aquatic Chronic 2;		
50-00-0	formaldehyde		< 1 %	
	200-001-8	605-001-00-5	01-2119488953-20	
	Carc. 1B, Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Skin Sens. 1A; H350 H341 H331 H311 H301 H314 H317			
1760-24-3	N-(3-(trimethoxysilyl)propyl)ethyler		< 1 %	
	217-164-6		01-2119970215-39	
	Eye Dam. 1, Skin Sens. 1; H318 H		_	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
98-01-1	202-627-7	2-Furaldehyde	< 30 %
	I	E = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = al: LD50 = 65 mg/kg	
108-95-2	203-632-7	Phenol	< 10 %
	inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg Skin Corr. 1B; H314: >= 3 - 100 Skin Irrit. 2; H315: >= 1 - < 3 Eye Irrit. 2; H319: >= 1 - < 3		
50-00-0	200-001-8	formaldehyde	< 1 %
	inhalation: ATE = 3 mg/l (vapours); inhalation: LC50 = 0,578 mg/l (dusts or mists); dermal: LD50 = 270 mg/kg; oral: LD50 = 600 - 800 mg/kg Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 5 - < 25 Eye Irrit. 2; H319: >= 5 - < 25 Skin Sens. 1; H317: >= 0,2 - 100 STOT SE 3; H335: >= 5 - 100		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

Seek medical treatment immediately.

After contact with skin

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.



Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Solution

Revision date: 28.07.2023 Product code: 00359-1207 Page 4 of 12

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Consult (eye) doctor immediately.

After ingestion

Do not induce vomiting.

Summon a doctor immediately.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

May cause cancer.

Suspected of causing genetic defects.

Toxic if swallowed.

Harmful in contact with skin or if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May cause respiratory irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

Attention. Phenols in high amounts cause local anesthetic effects so that pain due to burns may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide and carbon dioxide

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.

Remove persons to safety.

Keep away sources of ignition.

For non-emergency personnel

Do not breathe vapours.

Avoid contact with skin, eyes and clothing.



Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Solution

Revision date: 28.07.2023 Product code: 00359-1207 Page 5 of 12

For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Use only in thoroughly ventilated areas.

Provide suitable extraction at the processing machines.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Take measures against electrostatically charging.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Hints on joint storage

Incompatible with acids.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Mortar

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
98-01-1	2-Furaldehyde (furfural)	2	8		TWA (8 h)	WEL
		5	20		STEL (15 min)	WEL
50-00-0	Formaldehyde	2	2.5		TWA (8 h)	WEL
		2	2.5		STEL (15 min)	WEL
108-95-2	Phenol	2	7.8		TWA (8 h)	WEL
		4	16		STEL (15 min)	WEL



Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Solution

Revision date: 28.07.2023 Product code: 00359-1207 Page 6 of 12

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Pay attention to explosion protection guidelines.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance approx. 480 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Dark brown
Odour: Like phenoles

Test method

pH-Value: n.d.

Changes in the physical state

Melting point/freezing point:

n.d.

Boiling point or initial boiling point and

100 - 200 °C

boiling range:

Sublimation point: n.a. Softening point: n.d.

Flash point: 78 °C DIN EN ISO 2719

Flammability

Solid/liquid: n.a.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: 2,1 (*)
Upper explosion limits: 19,3 (*)
Auto-ignition temperature: 315 $^{\circ}$ C (*)



Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Solution

Revision date: 28.07.2023 Product code: 00359-1207 Page 7 of 12

Self-ignition temperature

Solid: n.a.
Gas: n.a.

Decomposition temperature: > 110 °C

Oxidizing properties

Not oxidising.

Vapour pressure: ~ 1,4 hPa (*)

Density: 1,221 g/cm³

Bulk density: n.a.

Water solubility: Partially soluble

(at 20 °C)

Solubility in other solvents

n.d.

Partition coefficient n-octanol/water: n.d.

Viscosity / dynamic: 125 - 165 mPa·s ISO 3219

(at 23 °C)

Viscosity / kinematic: n.d.
Flow time: n.d.
Relative vapour density: n.d.
Evaporation rate: n.d.
Solvent separation test: n.d.
Solvent content: n.d.

9.2. Other information

(*) Solvent

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with strong acids.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

Avoid temperatures above 25°C.

10.5. Incompatible materials

Strong acids

10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information



Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Solution

Revision date: 28.07.2023 Product code: 00359-1207 Page 8 of 12

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Toxic if swallowed.

Harmful in contact with skin or if inhaled.

No toxicological data available.

ATEmix calculated

ATE (oral) 224,2 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 9,400 mg/l; ATE (inhalation dust/mist) 1,418 mg/l

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

May cause an allergic skin reaction. (formaldehyde; N-(3-(trimethoxysilyl)propyl)ethylenediamine)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (Phenol; formaldehyde)

May cause cancer. (formaldehyde)

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (2-Furaldehyde)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.



Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Solution

Revision date: 28.07.2023 Product code: 00359-1207 Page 9 of 12

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 2927

14.2. UN proper shipping name: TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. (2-Furaldehyde,

Phenol)

14.3. Transport hazard class(es):6.114.4. Packing group:IIHazard label:6.1+8



Classification code: TC1

Limited quantity: 100 mL / 30 kg

Excepted quantity: E4
Transport category: 2
Hazard No: 68
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 2927

14.2. UN proper shipping name: TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. (2-Furaldehyde,

Phenol)

14.3. Transport hazard class(es):6.114.4. Packing group:IIHazard label:6.1+8



Classification code: TC1

Limited quantity: 100 mL / 30 kg

Excepted quantity:

Marine transport (IMDG)



Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Solution

Revision date: 28.07.2023 Product code: 00359-1207 Page 10 of 12

14.1. UN number: UN 2927

14.2. UN proper shipping name: TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. (2-Furaldehyde, phenol)

14.3. Transport hazard class(es):6.114.4. Packing group:IIHazard label:6.1+8



Marine pollutant:

Limited quantity: 100 mL / 30 kg

Excepted quantity: E4
EmS: F-A, S-B


Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 2927

14.2. UN proper shipping name: TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. (2-Furaldehyde, phenol,

solution)

14.3. Transport hazard class(es):6.114.4. Packing group:IIHazard label:6.1+8



Limited quantity Passenger: 0.5 L
Passenger LQ: Y640
Excepted quantity: E4

IATA-packing instructions - Passenger: 653
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 660
IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 75

2004/42/EC (VOC): < 30 %

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

National regulatory information



Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Solution

Revision date: 28.07.2023 Product code: 00359-1207 Page 11 of 12

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Consider Chemical prohibition regulation.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,6,7,8,10,11,12,14.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.				
H311	Toxic in contact with skin.				
H312	Harmful in contact with skin.				
11040 11000					

H312+H332 Harmful in contact with skin or if inhaled.
H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.H341 Suspected of causing genetic defects.

H350 May cause cancer.

H351 Suspected of causing cancer.



Safety Data Sheet

according to UK REACH Regulation

Asplit® LC Solution

Revision date: 28.07.2023 Product code: 00359-1207 Page 12 of 12

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)