



Safety Data Sheet

according to UK REACH Regulation

Asplit® LF Hardener

Revision date: 07.09.2023

Product code: 00359-1191

Page 2 of 10

Hazard statements

H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.

Precautionary statements

P260	Do not breathe gas/vapour/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

This substance does not have endocrine disrupting properties with respect to non-target organisms.

SECTION 3: Composition/information on ingredients

3.1. Substances

Sum formula:	C8 H4 Cl2 O2
Molecular weight:	203,01

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
88-95-9	Phthaloyl dichloride			> 99 %
	201-869-0		01-2119958967-12-0000	
	Acute Tox. 4, Skin Corr. 1B, Resp. Sens. 1, Skin Sens. 1, STOT SE 3; H312 H314 H334 H317 H335			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
88-95-9	201-869-0	Phthaloyl dichloride	> 99 %
	dermal: ATE = 1100 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
Call a physician immediately.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
If patient is not breathing, apply artificial respiration.



Safety Data Sheet

according to UK REACH Regulation

Asplit® LF Hardener

Revision date: 07.09.2023

Product code: 00359-1191

Page 3 of 10

Call a physician immediately.

After contact with skin

In case of contact with skin wash off immediately with plenty of water.
Seek medical treatment immediately.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Harmful in contact with skin.
Causes severe skin burns and eye damage.
May cause respiratory irritation.
May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide and carbon dioxide
Hydrochloric acid
Chlorine compounds

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.
Collect contaminated firefighting water separately, must not be discharged into the drains.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.
Keep away noninvolved persons.

For non-emergency personnel

Do not breathe vapours.
Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.



Safety Data Sheet

according to UK REACH Regulation

Asplit® LF Hardener

Revision date: 07.09.2023

Product code: 00359-1191

Page 4 of 10

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.
Clean contaminated surface thoroughly.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.
Do not use metal containers.

Other information

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.
Do not use metal containers.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary suck off at workplace.
Keep container tightly closed.
Handle and open container with care.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.
Protect from atmospheric moisture and water.
Protect against direct sun radiation.
Do not use metal containers.
Recommended storage temperature: > 10°C

Hints on joint storage

Incompatible with:
Bases
Oxidizing agents
Alcohols

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Hardener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

This product does not contain any substances for which a Workplace Exposure Limit has been set in concentrations above the limits.



Safety Data Sheet

according to UK REACH Regulation

Asplit® LF Hardener

Revision date: 07.09.2023

Product code: 00359-1191

Page 5 of 10

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale gases/vapours/aerosols.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance approx. 480 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

Protective gloves resistant to chemicals made off viton, minimum coat thickness 0.7 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

Skin protection

Acid-resistant protective clothing, rubber boots.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type E) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Colourless
Odour:	Pungent

	Test method
pH-Value:	n.d.

Changes in the physical state

Melting point/freezing point: approx. 16 °C

Boiling point or initial boiling point and boiling range: approx. 281 °C

Sublimation point: n.a.

Softening point: n.d.

Flash point: 113 °C Closed cup

Sustaining combustion: Sustaining combustion

Flammability

Solid/liquid: n.a.

Explosive properties

The product is not explosive.

Lower explosion limits: n.d.

Upper explosion limits: n.d.

**Safety Data Sheet**

according to UK REACH Regulation

Asplit® LF Hardener

Revision date: 07.09.2023

Product code: 00359-1191

Page 6 of 10

Auto-ignition temperature:	n.d.
Self-ignition temperature	
Solid:	n.a.
Gas:	n.a.
Decomposition temperature:	n.d.
Oxidizing properties	
Not oxidising.	
Vapour pressure: (at 47 °C)	39,997 hPa
Density (at 20 °C):	1,41 g/cm ³
Bulk density:	n.a.
Water solubility:	Reacts with water.
Solubility in other solvents	
n.d.	
Partition coefficient n-octanol/water:	Log Pow: 0,88
Viscosity / dynamic: (at 20 °C)	n.d.
Viscosity / kinematic:	n.d.
Flow time: (at 23 °C)	n.d.
Relative vapour density:	n.d.
Evaporation rate:	n.d.
Solvent separation test:	0 %
Solvent content:	0 %

9.2. Other information

Refractive index: 1,5684 (20°C)

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.
Reactions with alcohols.
Reactions with alkalies.
Reacts violently with water.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

10.5. Incompatible materials

oxidizing agents
Bases.
alcohols

10.6. Hazardous decomposition products

No hazardous decomposition products known.
Fire may produce:
Carbon monoxide and carbon dioxide

**Safety Data Sheet**

according to UK REACH Regulation

Asplit® LF Hardener

Revision date: 07.09.2023

Product code: 00359-1191

Page 7 of 10

Hydrochloric acid
Phosgene

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Harmful in contact with skin.
No toxicological data available.

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

May cause an allergic skin reaction. (Phthaloyl dichloride)
May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Phthaloyl dichloride)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Phthaloyl dichloride)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards**Endocrine disrupting properties**

No data available

Other information

Ingestion can cause gastrointestinal irritation, headache, nausea, vomiting, vertigo, intoxication, unconsciousness and death.
Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

SECTION 12: Ecological information**12.1. Toxicity**

Ecological data are not available.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of UK REACH.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Severe hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

Safety Data Sheet

according to UK REACH Regulation

Asplit® LF Hardener

Revision date: 07.09.2023

Product code: 00359-1191

Page 8 of 10

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal.
Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.
Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 3265
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Phthaloyl dichloride)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8



Classification code:	C3
Limited quantity:	1 L / 30 kg
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number:	UN 3265
14.2. UN proper shipping name:	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Phthaloyl dichloride)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8



Classification code:	C3
Limited quantity:	1 L / 30 kg
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number:	UN 3265
-------------------------	---------

Safety Data Sheet

according to UK REACH Regulation

Asplit® LF Hardener

Revision date: 07.09.2023

Product code: 00359-1191

Page 9 of 10

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Phthaloyl dichloride)

14.3. Transport hazard class(es): 8

14.4. Packing group: II

Hazard label: 8



Marine pollutant: No

Limited quantity: 1 L / 30 kg

Excepted quantity: E2

EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3265

14.2. UN proper shipping name: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Phthaloyl dichloride)

14.3. Transport hazard class(es): 8

14.4. Packing group: II

Hazard label: 8



Limited quantity Passenger: 0.5 L

Passenger LQ: Y840

Excepted quantity: E2

IATA-packing instructions - Passenger: 851

IATA-max. quantity - Passenger: 1 L

IATA-packing instructions - Cargo: 855

IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC): 0 %

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.



Safety Data Sheet

according to UK REACH Regulation

Asplit® LF Hardener

Revision date: 07.09.2023

Product code: 00359-1191

Page 10 of 10

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,6,7,8,9,10,11,12,14,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.