

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® LP 922 Hardener

Revision date: 31.03.2021

Product code: 00359-1213

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Asplit® LP 922 Hardener

Art.-No.

105 8186

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hardener

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Contact person: Laborleiter

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Substance or mixture corrosive to metals: Met. Corr. 1

Skin corrosion/irritation: Skin Corr. 1B

Germ cell mutagenicity: Muta. 2

Hazard Statements:

May be corrosive to metals.

Causes severe skin burns and eye damage.

Suspected of causing genetic defects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

4-Hydroxybenzenesulphonic acid

Phenol

p-toluenesulphonic acid monohydrate

Signal word: Danger

Pictograms:



Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

H341 Suspected of causing genetic defects.

Precautionary statements

P201 Obtain special instructions before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® LP 922 Hardener

Revision date: 31.03.2021

Product code: 00359-1213

Page 2 of 11

P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P390	Absorb spillage to prevent material damage.
P406	Store in a corrosion-resistant container with a resistant inner liner.

2.3. Other hazards

Not known.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Mixture containing following substances with additives

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
98-67-9	4-Hydroxybenzenesulphonic acid			< 50 %
	202-691-6		01-2119538813-35	
	Met. Corr. 1, Skin Corr. 1B; H290 H314			
6192-52-5	p-toluenesulphonic acid monohydrate			< 20 %
	203-180-0	016-030-00-2	01-2119538811-39	
	Skin Corr. 1C, Eye Dam. 1, STOT SE 3; H314 H318 H335			
7664-38-2	Phosphoric acid			< 10 %
	231-633-2	015-011-00-6	01-2119485924-24	
	Met. Corr. 1, Skin Corr. 1B; H290 H314			
7664-93-9	Sulphuric acid			< 5 %
	231-639-5	016-020-00-8	01-2119458838-20	
	Skin Corr. 1A; H314			
108-95-2	Phenol			< 2 %
	203-632-7	604-001-00-2	01-2119471329-32	
	Muta. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, STOT RE 2; H341 H331 H311 H301 H314 H373			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® LP 922 Hardener

Revision date: 31.03.2021

Product code: 00359-1213

Page 3 of 11

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
6192-52-5	203-180-0	p-toluenesulphonic acid monohydrate	< 20 %
		oral: LD50 = 2480 mg/kg STOT SE 3; H335: >= 20 - 100	
7664-38-2	231-633-2	Phosphoric acid	< 10 %
		Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25	
7664-93-9	231-639-5	Sulphuric acid	< 5 %
		Skin Corr. 1A; H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15	
108-95-2	203-632-7	Phenol	< 2 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg Skin Corr. 1B; H314: >= 3 - 100 Skin Irrit. 2; H315: >= 1 - < 3 Eye Irrit. 2; H319: >= 1 - < 3	

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.
Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.
Seek medical treatment immediately.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Consult (eye) doctor immediately.

After ingestion

Do not induce vomiting.
Summon a doctor immediately.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eye damage.
Suspected of causing genetic defects.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® LP 922 Hardener

Revision date: 31.03.2021

Product code: 00359-1213

Page 4 of 11

Carbon monoxide (CO), carbon dioxide (CO₂), sulphur oxides (SO_x) and phosphorus oxides (PO_x).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Ensure adequate ventilation.

Keep away noninvolved persons.

For non-emergency personnel

Avoid contact with skin, eyes and clothing.

Do not breathe vapours.

For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Do not use metal containers.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Provide appropriate ventilation and exhaust ventilation at the workplaces.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in original container.

Keep container tightly closed in a dry, cool and well-ventilated place.

Hints on joint storage

Incompatible with bases.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® LP 922 Hardener

Revision date: 31.03.2021

Product code: 00359-1213

Page 5 of 11

7.3. Specific end use(s)

Hardener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
7664-38-2	Orthophosphoric acid	-	1		TWA (8 h)	WEL
		-	2		STEL (15 min)	WEL
108-95-2	Phenol	2	7.8		TWA (8 h)	WEL
		4	16		STEL (15 min)	WEL
7664-93-9	Sulphuric acid (mist)	-	0.05		TWA (8 h)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made of viton, minimum coat thickness 0.7 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Acid-resistant protective clothing.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

Environmental exposure controls

Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	green brown
Odour:	Characteristic

pH-Value:

Test method
1,5 10 g/l

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® LP 922 Hardener

Revision date: 31.03.2021

Product code: 00359-1213

Page 6 of 11

Changes in the physical state

Melting point:	n.d.
Boiling point or initial boiling point and boiling range:	100 °C
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	n.a.

Flammability

Solid/liquid:	n.a.
Gas:	n.a.

Explosive properties

The product is not explosive.

Lower explosion limits:	n.a.
Upper explosion limits:	n.a.
Auto-ignition temperature:	n.d.

Self-ignition temperature

Solid:	n.a.
Gas:	n.a.

Decomposition temperature: n.d.

Oxidizing properties

Not oxidising.

Vapour pressure: 23 hPa
(at 20 °C)Density: 1,36 g/cm³ DIN 51757

Bulk density: n.a.

Water solubility: Completely miscible
(at 20 °C)**Solubility in other solvents**

n.d.

Partition coefficient n-octanol/water: n.d.

Viscosity / dynamic: n.d.

Viscosity / kinematic: n.d.
(at 40 °C)

Flow time: n.d.

Relative vapour density: n.d.

Evaporation rate: n.d.

Solvent separation test: 0 %

Solvent content: 0 %

9.2. Other information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.

10.2. Chemical stability



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® LP 922 Hardener

Revision date: 31.03.2021

Product code: 00359-1213

Page 7 of 11

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with alkalies.

Reactions with metals, with evolution of hydrogen.

10.4. Conditions to avoid

Gives off hydrogen by reaction with metals.

10.5. Incompatible materials

Bases.

Metals

10.6. Hazardous decomposition products

Hydrogen, by reaction with metals.

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO₂), sulphur oxides (SO_x) and phosphorus oxides (PO_x).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.

Irritation and corrosivity

Causes severe skin burns and eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (Phenol)

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® LP 922 Hardener

Revision date: 31.03.2021

Product code: 00359-1213

Page 8 of 11

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

Low hazard to waters.

A pH-change becomes possible in water.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN 1760

14.2. UN proper shipping name:

CORROSIVE LIQUID, N.O.S. (4-Hydroxybenzenesulphonic acid, Sulphuric acid)

14.3. Transport hazard class(es):

8

14.4. Packing group:

II

Hazard label:

8



Classification code:

C9

Limited quantity:

1 L / 30 kg

Excepted quantity:

E2

Transport category:

2

Hazard No:

80

Tunnel restriction code:

E

Inland waterways transport (ADN)

14.1. UN number:

UN 1760

14.2. UN proper shipping name:

CORROSIVE LIQUID, N.O.S. (4-Hydroxybenzenesulphonic acid, Sulphuric acid)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® LP 922 Hardener

Revision date: 31.03.2021

Product code: 00359-1213

Page 9 of 11

14.3. Transport hazard class(es): 8**14.4. Packing group:** II

Hazard label: 8



Classification code: C9

Limited quantity: 1 L / 30 kg

Excepted quantity: E2

Marine transport (IMDG)**14.1. UN number:** UN 1760**14.2. UN proper shipping name:** CORROSIVE LIQUID, N.O.S. CORROSIVE LIQUID, N.O.S.
(4-Hydroxybenzenesulphonic acid, sulphuric acid)**14.3. Transport hazard class(es):** 8**14.4. Packing group:** II

Hazard label: 8



Marine pollutant: No

Limited quantity: 1 L / 30 kg

Excepted quantity: E2

EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number:** UN 1760**14.2. UN proper shipping name:** CORROSIVE LIQUID, N.O.S. (4-Hydroxybenzenesulphonic acid,
sulphuric acid, mixture)**14.3. Transport hazard class(es):** 8**14.4. Packing group:** II

Hazard label: 8



Limited quantity Passenger: 0.5 L

Passenger LQ: Y840

Excepted quantity: E2

IATA-packing instructions - Passenger: 851

IATA-max. quantity - Passenger: 1 L

IATA-packing instructions - Cargo: 855

IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® LP 922 Hardener

Revision date: 31.03.2021

Product code: 00359-1213

Page 10 of 11

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC): 0 %

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Additional information

This product is regulated by Annex II of Regulation (EU) 2019/1148 on the marketing and use of explosives precursors. All suspicious transactions and significant disappearances and thefts have to be reported to the responsible national contact point. Sales personnel at all trading levels has to be instructed.

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,3,6,7,10,11,12,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	Expert judgement and weight of evidence determination
Skin Corr. 1B; H314	Calculation method
Muta. 2; H341	Calculation method

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® LP 922 Hardener

Revision date: 31.03.2021

Product code: 00359-1213

Page 11 of 11

Relevant H and EUH statements (number and full text)

H290	May be corrosive to metals.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H373	May cause damage to organs through prolonged or repeated exposure.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)