

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP CEMENT INNERLINER SEALER

Revision date: 02.07.2020

Product code: 00156-0074

Page 1 of 10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

TIP TOP CEMENT INNERLINER SEALER

##### Art.-No.

511 1190, 514 3240, 514 3250, 514 9301, 514 9302, 515 9004, 515 9005, 515 9011, 515 9012, 515 9027, 515 9028, 515 9029, 515 9035, 515 9042, 515 9058, 515 9059, 599 2200

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

adhesive

#### 1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG

Street: Gruber Strasse 65

Place: D-85586 Poing

Telephone: +49 (0) 8121 / 707 - 100

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

#### 1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

Naphtha (petroleum)

Signal word: Danger

##### Pictograms:



##### Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

##### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP CEMENT INNERLINER SEALER

Revision date: 02.07.2020

Product code: 00156-0074

Page 2 of 10

P312 Call a POISON CENTER/doctor if you feel unwell.  
P273 Avoid release to the environment.

### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.  
Vapours may form explosive mixture with air.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Preparation solved in petroleum spirit

#### Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
64742-49-0	Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane]	< 50 %		
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Naphtha (petroleum) [Hydrocarbons, C6, isoalkanes, < 3% n-hexane]	< 20 %		
	931-254-9		01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
1314-13-2	Zinc oxide	< 1 %		
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			

Full text of H and EUH statements: see section 16.

#### Further Information

According to note P to the regulation (EC) no. 1272/2008, "Naphtha (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately.  
In the event of persistent symptoms receive medical treatment.  
Take away from danger area and lay down affected person.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours.  
Seek medical treatment immediately.

#### After contact with skin

Wash off with soap and plenty of water.  
Treat subsequently with skin cream.  
Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP CEMENT INNERLINER SEALER

Revision date: 02.07.2020

Product code: 00156-0074

Page 3 of 10

Summon a doctor immediately.

#### **After ingestion**

Do not induce vomiting.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

Attention. Beware, danger of aspiration.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Causes skin irritation.

May cause drowsiness or dizziness.

Attention. Beware, danger of aspiration.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

### SECTION 5: Firefighting measures

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

##### **Unsuitable extinguishing media**

Full water jet

#### **5.2. Special hazards arising from the substance or mixture**

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and sulphur oxides (SO<sub>x</sub>)

#### **5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.

Protective suit.

#### **Additional information**

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### SECTION 6: Accidental release measures

#### **6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.

Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

#### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

#### **6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

#### **6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

### SECTION 7: Handling and storage

#### **7.1. Precautions for safe handling**



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP CEMENT INNERLINER SEALER

Revision date: 02.07.2020

Product code: 00156-0074

Page 4 of 10

### Advice on safe handling

Keep container tightly closed.  
Vapours are heavier than air and spread along ground.  
Use only in thoroughly ventilated areas.

### Advice on protection against fire and explosion

Keep away from heat and sources of ignition.  
Do not smoke.  
Take precautionary measures against static discharges.  
Use only explosion-proof equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.  
Pay attention to anti-explosion rules.

#### Hints on joint storage

Incompatible with oxidizing agents.

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

adhesive

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL

### 8.2. Exposure controls

#### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

#### Protective and hygiene measures

Do not inhale vapours.  
Wash hands before breaks and immediately after handling the product.  
When using do not eat, drink or smoke.  
Treat subsequently with skin cream.  
Avoid contact with skin, eyes and clothing.  
Remove and wash contaminated clothes before re-use.

#### Eye/face protection

Tightly fitting goggles (EN 166).

#### Hand protection

Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril 735> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

#### Skin protection

Solvent-resistant apron (EN 467).

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP CEMENT INNERLINER SEALER

Revision date: 02.07.2020

Product code: 00156-0074

Page 5 of 10

### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Black
Odour:	Hydrocarbon-like

#### Test method

pH-Value:	n.d.
-----------	------

### Changes in the physical state

Melting point:	n.d.
Initial boiling point and boiling range:	60 - 95 °C
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	- 24 °C DIN EN ISO 3679

### Flammability

Solid:	n.a.
Gas:	n.a.

### Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	1,0 vol. % *)
Upper explosion limits:	7,3 vol. % *)
Ignition temperature:	413 °C

### Auto-ignition temperature

Solid:	n.a.
Gas:	n.a.

Decomposition temperature:	n.d.
----------------------------	------

### Oxidizing properties

Not oxidising.

Vapour pressure: (at 20 °C)	150 hPa *)
--------------------------------	------------

Density:	0,83 g/cm <sup>3</sup>
----------	------------------------

Bulk density:	n.a.
---------------	------

Water solubility: (at 20 °C)	Immiscible
---------------------------------	------------

### Solubility in other solvents

n.d.

Partition coefficient:	n.d.
------------------------	------

Viscosity / dynamic:	6000 mPa·s
----------------------	------------

Viscosity / kinematic: (at 40 °C)	> 20,5 mm <sup>2</sup> /s
--------------------------------------	---------------------------

Flow time: (at 23 °C)	454 s 6 DIN EN ISO 2431
--------------------------	-------------------------

Vapour density:	n.d.
-----------------	------



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP CEMENT INNERLINER SEALER

Revision date: 02.07.2020

Product code: 00156-0074

Page 6 of 10

Evaporation rate:	7,6 *)
Solvent separation test:	0 %
Solvent content:	60 - 70 %

### 9.2. Other information

\*) Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane, Hydrocarbons, C6, isoalkanes, < 3% n-hexane

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No decomposition if stored and applied as directed.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.  
Vapour/air mixtures are explosive at intensive warming.  
Heating can release vapours which can be ignited.

### 10.5. Incompatible materials

oxidizing agents

### 10.6. Hazardous decomposition products

No hazardous decomposition products known.  
Fire may produce:  
Carbon monoxide, carbon dioxide, sulphur oxides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.  
No toxicological data available.  
Naphtha (petroleum)  
LD50/oral/rat: > 2000 mg/kg  
LD50/dermal/rabbit: > 2000 mg/kg  
LC50/inhalation/rat: > 20 mg/l

#### Irritation and corrosivity

Causes skin irritation.  
Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane])

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP CEMENT INNERLINER SEALER

Revision date: 02.07.2020

Product code: 00156-0074

Page 7 of 10

#### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### **Practical experience**

#### **Other observations**

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Contact with eyes may cause irritation.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

### SECTION 12: Ecological information

#### **12.1. Toxicity**

Ecological data are not available.

Naphtha (petroleum)

EC50/Daphnia: 1 - 10 mg/l

EC50/Algae: 10 - 100 mg/l

Zinc oxide

EC50/Ceriodaphnia dubia/48 h = 0,01 - 0,1 mg/l

EC50/Selenastrum capricornutum/72 h = 0,01 - 0,1 mg/l

Toxic to aquatic life with long lasting effects.

#### **12.2. Persistence and degradability**

No data available

#### **12.3. Bioaccumulative potential**

No data available

#### **12.4. Mobility in soil**

No data available

#### **12.5. Results of PBT and vPvB assessment**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

#### **12.6. Other adverse effects**

Low hazard to waters.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### **13.1. Waste treatment methods**

##### **Disposal recommendations**

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

##### **List of Wastes Code - residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

##### **Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP CEMENT INNERLINER SEALER

Revision date: 02.07.2020

Product code: 00156-0074

Page 8 of 10

Packaging that cannot be cleaned should be disposed of like the product.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	ADHESIVES
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Transport category:	3
Tunnel restriction code:	E

#### Other applicable information (land transport)

Receptacle max. 450 L, ADR subsection 2.2.3.1.4  
HAZCHEM: 3YE

#### Inland waterways transport (ADN)

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	Adhesives
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1

#### Marine transport (IMDG)

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	ADHESIVES
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Marine pollutant:	Yes
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
EmS:	F-E, S-D

#### Other applicable information (marine transport)

Receptacle max. 450 L, IMDG Code subsection 2.3.2.2

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP CEMENT INNERLINER SEALER

Revision date: 02.07.2020

Product code: 00156-0074

Page 9 of 10

### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	ADHESIVES
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Limited quantity Passenger:	10 L
Passenger LQ:	Y344
Excepted quantity:	E1
IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	30 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	100 L

### Other applicable information (air transport)

\*) [3.3.3.1 IATA DGR]

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

2004/42/EC (VOC):	< 70 %
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS
Additional information:	E2

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

## SECTION 16: Other information



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP CEMENT INNERLINER SEALER

Revision date: 02.07.2020

Product code: 00156-0074

Page 10 of 10

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses  
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation int er  
IMDG = International Maritime Code for Dangerous Goods  
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization  
MARPOL = International Convention for the Prevention of Pollution from Ships  
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals  
CAS = Chemical Abstract Service  
EN = European norm  
ISO = International Organization for Standardization  
DIN = Deutsche Industrie Norm  
PBT = Persistent Bioaccumulative and Toxic  
vPvB = Very Persistent and very Bio-accumulative  
LD = Lethal dose  
LC = Lethal concentration  
EC = Effect concentration  
IC = Median immobilisation concentration or median inhibitory concentration

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

#### Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*