

according to UK REACH Regulation

TIP TOP COROPUR AKTIVATOR A-1949

Revision date: 02.12.2021

Product code: 00359-1228

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP COROPUR AKTIVATOR A-1949

Art.-No.

580 0676, 580 0700, 580 0717, 580 0730, 580 0740, 580 0760, 580 1510 (Coropur Non Abrassiv) 580 0690, 580 0724, 580 1527, 580 1730, 580 1740, 580 1750 (Coropur Non Abrassiv LS)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Activator

1.3. Details of the supplier of the safety data sheet

Manufacturer Company name: Street: Place:	TIP TOP Oberflaechenschutz Elbe Gmbl Heuweg 4 D-06886 Wittenberg	
Telephone:	+49(0)3491/635-50	Telefax:+49(0)3491/635-552
Responsible Department:	Responsible for the safety data sheet: so	is@gbk-ingeineim.de
Supplier Company name: Street: Place:	REMA TIP TOP INDUSTRY UK LTD Plumtree Industrial Estate, Harworth Doncaster, DN11 8EW, South Yorkshire	e
Telephone: Internet:	+44 (0)1302 711233 www.rema-tiptop.co.uk	
<u>1.4. Emergency telephone</u> number:	INTERNATIONAL: +49 - (0) 6132 - 8446 In England and Wales: NHS 111 In Scotl	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories: Flammable liquid: Flam. Liq. 3 Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1 Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Flammable liquid and vapour. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexan-1,2-diylbiscarbamate n-Butyl acetate Signal word: Warning



according to UK REACH Regulation

TIP TOP COROPUR AKTIVATOR A-1949

Revision date: 02.12.2021

Product code: 00359-1228

Page 2 of 11

Pictograms:



Hazard statements

H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P391	Collect spillage.
P370+P378	In case of fire: Use extinguishing powder or sand to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures EUH066 Repeated expo

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Polyoxazolidine

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
59719-67-4	Bis[2-[2-(1-methylethyl)-3-oxazo	lidinyl]ethyl] hexan-1,2-diylbiscar	bamate	50 - 100 %
	261-879-6		01-2119983487-19	
	Eye Irrit. 2, Skin Sens. 1, Aquati	c Chronic 2; H319 H317 H411		
123-86-4	n-Butyl acetate			25 - 50 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226	H336 EUH066		

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures



according to UK REACH Regulation

TIP TOP COROPUR AKTIVATOR A-1949

Revision date: 02.12.2021

Product code: 00359-1228

Page 3 of 11

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately. If you feel unwell, seek medical advice. Take away from danger area and lay down affected person. Never give anything by mouth to an unconscious person.

In case of the person being unconscious put him/her in a stable side position.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products. Refer for medical treatment.

If patient is not breathing, apply artificial respiration.

After contact with skin

Wash off with soap and plenty of water. Consult a doctor if skin irritation persists. Do not use solvents or thinners.

After contact with eyes

Remove contact lens.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Summon a doctor immediately. Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

5.3. Advice for firefighters

Use breathing apparatus with independent air supply. Protective suit.

Additional information

Cool containers at risk with water spray jet. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Vapours are heavier than air and spread along ground. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.



according to UK REACH Regulation

TIP TOP COROPUR AKTIVATOR A-1949

Revision date: 02.12.2021

Product code: 00359-1228

Page 4 of 11

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use only explosion-proof equipment. Ensure adequate ventilation. Keep away sources of ignition. Keep away noninvolved persons.

For non-emergency personnel

Do not breathe vapours. Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator. Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water. Inform competent authority about release into the sewage, ground or into waters.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Keep a good ventilation and air-exhaust at the place of work. Vapours are heavier than air and spread along ground. Avoid contact with the skin and the eyes.

When using do not eat, drink or smoke.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition. Do not smoke. Take precautionary measures against static discharges. Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place. Pay attention to anti-explosion protection rules. Protect from heat and direct solar radiation. Storage temperature between 15°C to 30°C Do not empty container under pressure. No pressure tank! Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Hints on joint storage

Incompatible with: Oxidizing agents



according to UK REACH Regulation

TIP TOP COROPUR AKTIVATOR A-1949

Revision date: 02.12.2021

Product code: 00359-1228

Page 5 of 11

Acids and bases.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Activator

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothing before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour:	Liquid Various Characteristic		
		Test method	
pH-Value:		n.a.	
Changes in the physical state Melting point/freezing point:		n.d.	



according to UK REACH Regulation

TIP TOP	COROPUR AKTIVATOR A-1949	
Revision date: 02.12.2021	Product code: 00359-1228	Page 6 of 11
Boiling point or initial boiling point and boiling range: Sublimation point:	126 °C n.a.	*)
Softening point:	n.d.	
Flash point:	27 °C	DIN 53213
Sustaining combustion:	Sustaining combustion	
Flammability Solid/liquid: Gas:	n.a. n.a.	
	11.a.	
Explosive properties The product is considered non-explosi	ve; nevertheless explosive vapour/air mixtu	ire can be generated
Lower explosion limits:	1,9 vol. %	-
Upper explosion limits:	6,1 vol. %	*)
Auto-ignition temperature:	370 °C	*)
Self-ignition temperature		
Solid: Gas:	n.a. n.a.	
Decomposition temperature:	n.d.	
Oxidizing properties Not oxidising.		
Vapour pressure: (at 20 °C)	5,27 hPa	
Density (at 20 °C): Bulk density:	0,99 g/cm³ n.a.	
Water solubility: (at 20 °C)	Immiscible	
Solubility in other solvents n.d.		
Partition coefficient n-octanol/water:	n.d.	
Viscosity / dynamic:	n.d.	
Viscosity / kinematic: (at 40 °C)	< 20,5 mm²/s	
Flow time: (at 20 °C)	14 s	4 DIN 53211
Relative vapour density:	n.d.	
Solvent separation test:	n.d.	
Solvent content:	40 %	
9.2. Other information		
Solid content:	60 %	
*) n-Butyl acetate		

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.



according to UK REACH Regulation

TIP TOP COROPUR AKTIVATOR A-1949

Revision date: 02.12.2021

Product code: 00359-1228

Page 7 of 11

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat. Heating can release vapours which can be ignited. Vapour/air-mixtures are explosive at intense warming.

10.5. Incompatible materials

Strong oxidizing agents Strong acids and strong bases

10.6. Hazardous decomposition products

No hazardous decomposition products known. Fire may produce: Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met. No toxicological data available.

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexan-1,2-diylbiscarbamate)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (n-Butyl acetate)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea anc vomiting.

Inhalation of high concentrations may cause injuries to liver, kidneys and central nervous system.

A longer or repeated contact my lead to irritation of eyes and mucous membranes.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available. **12.2. Persistence and degradability**



according to UK REACH Regulation

TIP TOP COROPUR AKTIVATOR A-1949

Revision date: 02.12.2021

Product code: 00359-1228

Page 8 of 11

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations. Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1263
14.2. UN proper shipping name:	Paint related material
<u>14.3. Transport hazard class(es):</u>	3
14.4. Packing group:	III
Hazard label:	3
Classification code: Limited quantity: Excepted quantity:	F1 5 L / 30 kg E1
Transport category: Hazard No:	3
Tunnel restriction code:	30 D/F
Inland waterways transport (ADN)	



according to UK REACH Regulation

TIP TO Revision date: 02.12.2021	DP COROPUR AKTIVATOR A-1949 Product code: 00359-1228	Page 9 of 11
<u>14.1. UN number:</u>	UN 1263	
14.2. UN proper shipping name:	Paint related material	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	III	
Hazard label:	3	
Classification code:	F1	
Limited quantity:	5 L / 30 kg	
Excepted quantity:	E1	
Marine transport (IMDG)		
14.1. UN number:	UN 1263	
<u>14.2. UN proper shipping name:</u>	Paint related material (Bis[2-[2-(1-methylethyl) -3-oxazolidinyl]ethyl]hexane-1,2-diylbiscarbamate)	
<u>14.3. Transport hazard class(es):</u>	3	
14.4. Packing group:	III	
Hazard label:	3	
Marine pollutant: Limited quantity:	Yes 5 L / 30 kg	
Excepted quantity:	E1	
EmS:	F-E, S-E	
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number:</u>	UN 1263	
14.2. UN proper shipping name:	Paint related material	
14.3. Transport hazard class(es):	3	
<u>14.4. Packing group:</u> Hazard label:	III 3	
Limited quantity Passenger:	10 L	
Passenger LQ:	Y344	
Excepted quantity: IATA-packing instructions - Passenger:	E1 : 355	
IATA-max. quantity - Passenger:	60 L	
IATA-packing instructions - Cargo:	366	
IATA-max. quantity - Cargo:	220 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	Yes	



according to UK REACH Regulation

TIP TOP COROPUR AKTIVATOR A-1949

Revision date: 02.12.2021

Product code: 00359-1228

Page 10 of 11

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practices.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information	
Restrictions on use (REACH, annex X	VII):
Entry 3, Entry 40	
2010/75/EU (VOC):	396 g/l
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS
Additional information:	E2
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water hazard class (D):	2 - obviously hazardous to water
45.0 Chamical asfaty assaurant	

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,4,6,7,8,9,10,11,12,13,14,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

- RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
- ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
- IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

- CAS = Chemical Abstract Service
- EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

- LD = Lethal dose
- LC = Lethal concentration
- EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration



according to UK REACH Regulation

TIP TOP COROPUR AKTIVATOR A-1949

Revision date: 02.12.2021

Product code: 00359-1228

Page 11 of 11

Relevant H and EUH statements (number and full text)

- H226 Flammable liquid and vapour.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

'The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)