



Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ACTIVATOR A-873 FOR COROPUR TAR 21 (MR 15:1)

Revision date: 22.05.2023

Product code: 00359-1267

Page 2 of 12

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P370+P378	In case of fire: Use Dry chemical, Sand to extinguish.
P391	Collect spillage.
P403+P235	Store in a well-ventilated place. Keep cool.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Polyoxazolidine

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
59719-67-4	Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexan-1,2-diylbiscarbamate			50 - 100 %
	261-879-6		01-2119983487-19	
	Eye Irrit. 2, Skin Sens. 1B, Aquatic Chronic 2; H319 H317 H411			
1330-20-7	Xylene (mixed isomers)			15 - 25 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
100-41-4	Ethyl benzene			2,5 - 5 %
	202-849-4	601-023-00-4	01-2119489370-35	
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

TIP TOP COROPUR ACTIVATOR A-873 FOR COROPUR TAR 21 (MR 15:1)

Revision date: 22.05.2023

Product code: 00359-1267

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1330-20-7	215-535-7	Xylene (mixed isomers)	15 - 25 %
		inhalation: ATE = 11 mg/l (vapours); dermal: ATE = 1100 mg/kg	
100-41-4	202-849-4	Ethyl benzene	2,5 - 5 %
		inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg	

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.
Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.
Keep warm and calm injured person.
If patient is not breathing, apply artificial respiration.
Seek medical treatment immediately.

After contact with skin

In case of contact with skin wash off immediately with soap and water.
Do not use solvents or thinners.

After contact with eyes

Remove contact lens.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Rinse mouth.
Never give anything by mouth to an unconscious person.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause damage to organs through prolonged or repeated exposure.
Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)



Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ACTIVATOR A-873 FOR COROPUR TAR 21 (MR 15:1)

Revision date: 22.05.2023

Product code: 00359-1267

Page 4 of 12

High smoke development

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away sources of ignition.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Remove persons to safety.

For non-emergency personnel

Do not breathe vapours.

Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Clean contaminated surface thoroughly.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not wear contact lenses when handling the product.

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Keep a good ventilation and air-exhaust at the place of work.

Do not empty container under pressure. No pressure tank!

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ACTIVATOR A-873 FOR COROPUR TAR 21 (MR 15:1)

Revision date: 22.05.2023

Product code: 00359-1267

Page 5 of 12

Requirements for storage rooms and vessels

- Keep container tightly closed in a dry, cool and well-ventilated place.
- Pay attention to anti-explosion rules.
- Take precautionary measures against static discharges.
- Storage temperature between 15°C to 30°C

Hints on joint storage

- Incompatible with:
strong oxidizing agents, strong acids and strong bases

Further information on storage conditions

- Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

- Protection against corrosion

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls

Appropriate engineering controls

- Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

- Do not inhale vapours.
- Wash hands before breaks and immediately after handling the product.
- When using do not eat, drink or smoke.
- Avoid contact with skin, eyes and clothing.
- Remove and wash contaminated clothes before re-use.

Eye/face protection

- Tightly fitting goggles (EN 166).
- Eye wash bottle with pure water (EN 15154).

Hand protection

- Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Safety Data Sheet**

according to UK REACH Regulation

TIP TOP COROPUR ACTIVATOR A-873 FOR COROPUR TAR 21 (MR 15:1)

Revision date: 22.05.2023

Product code: 00359-1267

Page 6 of 12

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Various
Odour:	Characteristic

Test method

pH-Value:	n.d.
-----------	------

Changes in the physical state

Melting point/freezing point:	n.d.
Boiling point or initial boiling point and boiling range:	139 °C *)
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	24 °C DIN 53213
Sustaining combustion:	Sustaining combustion

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	0,83 vol. % **)
Upper explosion limits:	8,0 vol. % **)
Auto-ignition temperature:	430 °C **)

Self-ignition temperature

Solid:	n.a.
Gas:	n.a.

Decomposition temperature:	n.d.
----------------------------	------

Oxidizing properties

Not oxidising.

Vapour pressure: (at 20 °C)	1,342 hPa
--------------------------------	-----------

Density (at 20 °C):	1,03 g/cm ³
---------------------	------------------------

Bulk density:	n.a.
---------------	------

Water solubility:	Immiscible
-------------------	------------

Solubility in other solvents

n.d.

Partition coefficient n-octanol/water:	n.d.
--	------

Viscosity / dynamic:	n.d.
----------------------	------

Viscosity / kinematic: (at 40 °C)	< 300 mm ² /s
--------------------------------------	--------------------------

Flow time: (at 20 °C)	65 s 4 DIN 53211
--------------------------	------------------

Evaporation rate:	n.d.
-------------------	------

Solvent separation test:	n.d.
--------------------------	------



Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ACTIVATOR A-873 FOR COROPUR TAR 21 (MR 15:1)

Revision date: 22.05.2023

Product code: 00359-1267

Page 7 of 12

Solvent content: 21 %

9.2. Other information

Solid content: 79 %

*) Xylene (mixed isomers)

**) Ethyl benzene

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.
Vapour/air mixtures are explosive at intensive warming.
Heating can release vapours which can be ignited.

10.5. Incompatible materials

Strong oxidizing agents
Strong acids and strong bases

10.6. Hazardous decomposition products

No hazardous decomposition products known.
Fire may produce:
Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.
No toxicological data available.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) 5790 mg/kg; ATE (inhalation vapour) 49,70 mg/l; ATE (inhalation dust/mist) 30,61 mg/l

Irritation and corrosivity

Causes skin irritation.
Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexan-1,2-diylbiscarbamate)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Xylene (mixed isomers))

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.



Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ACTIVATOR A-873 FOR COROPUR TAR 21 (MR 15:1)

Revision date: 22.05.2023

Product code: 00359-1267

Page 8 of 12

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Components of the product may be absorbed into the body through the skin.

Contact with eyes may cause irritation.

Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

Attention. Beware, danger of aspiration!

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

Empty containers should be taken for local recycling, recovery or waste disposal.

Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ACTIVATOR A-873 FOR COROPUR TAR 21 (MR 15:1)

Revision date: 22.05.2023

Product code: 00359-1267

Page 9 of 12

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint (Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl]hexan-1,2-diylbiscarbamate)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Marine pollutant: Yes
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3

Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ACTIVATOR A-873 FOR COROPUR TAR 21 (MR 15:1)

Revision date: 22.05.2023

Product code: 00359-1267

Page 10 of 12

14.4. Packing group:

Hazard label:

III

3



Limited quantity Passenger:

10 L

Passenger LQ:

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger:

355

IATA-max. quantity - Passenger:

60 L

IATA-packing instructions - Cargo:

366

IATA-max. quantity - Cargo:

220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

Yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practices.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC):

212 g/l

Information according to 2012/18/EU
(SEVESO III):

P5c FLAMMABLE LIQUIDS

Additional information:

E2

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,4,6,7,8,9,10,11,12,14,15.



Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ACTIVATOR A-873 FOR COROPUR TAR 21 (MR 15:1)

Revision date: 22.05.2023

Product code: 00359-1267

Page 11 of 12

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.



Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ACTIVATOR A-873 FOR COROPUR TAR 21 (MR 15:1)

Revision date: 22.05.2023

Product code: 00359-1267

Page 12 of 12

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)