



Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ZINC M

Revision date: 12.05.2022 Product code: 00359-1176 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP COROPUR ZINC M

Art.-No.

580 0016, 580 0023, 580 0030

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coating component

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50 Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

Company name: REMA TIP TOP INDUSTRY UK LTD
Street: Plumtree Industrial Estate, Harworth
Place: Doncaster, DN11 8EW, South Yorkshire

Telephone: +44 (0)1302 711233 Internet: www.rema-tiptop.co.uk

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 3; H226 Resp. Sens. 1; H334 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Aromatic polyisocyanate

Aromatic polyisocyanate prepolymer

4-isocyanatosulphonyltoluene

Fatty acids, C18-unsaturated, dimers, reaction products with N, N-dimethyl-1,3-propanediamine and

1,3-propanediamine

Signal word: Danger

Pictograms:







Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ZINC M

Revision date: 12.05.2022 Product code: 00359-1176 Page 2 of 12

Hazard statements

H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Ke	ep away from	heat, hot surfa	aces, sparks,	open flames an	d other ignition sourc	es. No
---------	--------------	-----------------	---------------	----------------	------------------------	--------

smoking.

P261 Avoid breathing vapour.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 Wear respiratory protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use Dry chemical. Sand to extinguish.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Aromatic polyisocyanate



Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ZINC M

Revision date: 12.05.2022 Product code: 00359-1176 Page 3 of 12

Hazardous components

Chemical name				
EC No	Index No	REACH No		
GHS Classification				
Zinc powder - zinc dust (pyroph	oric)		50 - 100 %	
231-175-3	030-001-00-1			
Pyr. Sol. 1, Water-react. 1, Aquatic Acute 1, Aquatic Chronic 1; H250 H260 H400 H410				
Solvent naphta (petroleum)			5 - 10 %	
918-668-5	649-356-00-4	01-2119455851-35		
Flam. Liq. 3, STOT SE 3, STOT H411 EUH066	SE 3, Asp. Tox. 1, Aquatic Chro	onic 2; H226 H335 H336 H304		
n-Butyl acetate			5 - 10 %	
204-658-1	607-025-00-1	01-2119485493-29		
Flam. Liq. 3, STOT SE 3; H226	H336 EUH066			
Aromatic polyisocyanate				
500-120-8				
Eye Irrit. 2, Skin Sens. 1; H319	H317			
Aromatic polyisocyanate				
Skin Sens. 1; H317	•			
Aromatic polyisocyanate prepolymer				
Acute Tox. 4, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1; H332 H319 H334 H317				
4-isocyanatosulphonyltoluene				
223-810-8	615-012-00-7	01-2119980050-47		
Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, STOT SE 3; H315 H319 H334 H335 EUH014				
Fatty acids, C18-unsaturated, dimers, reaction products with N, N-dimethyl-1,3-propanediamine and 1,3-propanediamine				
605-296-0		01-2119970640-38		
Skin Sens. 1A; H317				
	EC No GHS Classification Zinc powder - zinc dust (pyrophical 231-175-3 Pyr. Sol. 1, Water-react. 1, Aqual Solvent naphta (petroleum) 918-668-5 Flam. Liq. 3, STOT SE 3, STOT H411 EUH066 n-Butyl acetate 204-658-1 Flam. Liq. 3, STOT SE 3; H226 Aromatic polyisocyanate 500-120-8 Eye Irrit. 2, Skin Sens. 1; H319 Aromatic polyisocyanate Skin Sens. 1; H317 Aromatic polyisocyanate prepolyisocyanate prepolyisocyana	EC No GHS Classification Zinc powder - zinc dust (pyrophoric) 231-175-3	EC No Index No REACH No GHS Classification Zinc powder - zinc dust (pyrophoric) 231-175-3 030-001-00-1 Pyr. Sol. 1, Water-react. 1, Aquatic Acute 1, Aquatic Chronic 1; H250 H260 H400 H410 Solvent naphta (petroleum) 918-668-5 649-356-00-4 01-2119455851-35 Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066 n-Butyl acetate 204-658-1 607-025-00-1 01-2119485493-29 Flam. Liq. 3, STOT SE 3; H226 H336 EUH066 Aromatic polyisocyanate 500-120-8 Eye Irrit. 2, Skin Sens. 1; H319 H317 Aromatic polyisocyanate prepolymer Skin Sens. 1; H317 Aromatic polyisocyanate prepolymer Acute Tox. 4, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1; H332 H319 H334 H317 4-isocyanatosulphonyltoluene 223-810-8 615-012-00-7 01-2119980050-47 Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, STOT SE 3; H315 H319 H334 H335 EUH014 Fatty acids, C18-unsaturated, dimers, reaction products with N, N-dimethyl-1,3-propanediamine and 1,3-propanediamine 605-296-0 01-2119970640-38	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Specific Conc. Limits, M-factors and ATE	
127821-00-5		Aromatic polyisocyanate prepolymer	1 - 2,5 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists)		
4083-64-1	223-810-8	4-isocyanatosulphonyltoluene	0,5 - 1 %
	Skin Irrit. 2; H315: >= 5 - 100		

Further Information

According to note P to the regulation (EC) no. 1272/2008, "Solvent naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

SECTION 4: First aid measures

4.1. Description of first aid measures





Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ZINC M

Revision date: 12.05.2022 Product code: 00359-1176 Page 4 of 12

General information

Remove contaminated soaked clothing immediately.

If you feel unwell, seek medical advice.

Take away from danger area and lay down affected person.

In case of the person being unconscious put him/her in a stable side position.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

Refer for medical treatment.

If patient is not breathing, apply artificial respiration.

After contact with skin

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

Do not use solvents or thinners.

After contact with eyes

Remove contact lens.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Vapours are heavier than air and spread along ground.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures





Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ZINC M

Revision date: 12.05.2022 Product code: 00359-1176 Page 5 of 12

General advice

Ensure adequate ventilation.

Keep away sources of ignition.

Keep away noninvolved persons.

For non-emergency personnel

Avoid contact with skin, eyes and clothing.

Do not breathe vapours.

For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

Use only explosion-proof equipment.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Inform competent authority about release into the sewage, ground or into waters.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

Container should not be gas-tight closed.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Keep a good ventilation and air-exhaust at the place of work.

Vapours are heavier than air and spread along ground.

Avoid contact with the skin and the eyes.

When using do not eat, drink or smoke.

Do not empty container under pressure. No pressure tank!

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion protection rules.

Protect from heat and direct solar radiation.

Storage temperature between 15°C to 30°C

Hints on joint storage

Incompatible with:

Oxidizing agents

Acids and bases.



TIP TOP Oberflaechenschutz Elbe GmbH

Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ZINC M

Revision date: 12.05.2022 Product code: 00359-1176 Page 6 of 12

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Coating component

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
-	Isocyanates, all (as -NCO) Except methyl isocyanate	-	0.02		TWA (8 h)	WEL
		-	0.07		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothing before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Various
Odour: Characteristic

Test method

Print date: 12.05.2022

pH-Value: n.d.



Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ZINC M

Revision date: 12.05.2022 Product code: 00359-1176 Page 7 of 12

Changes in the physical state

Melting point/freezing point:

n.d.

Boiling point or initial boiling point and

126 °C (*)

boiling range:

Sublimation point: n.a. Softening point: n.d.

Flash point: 39 °C DIN 53213

Sustaining combustion: Sustaining combustion

Flammability

Solid/liquid: n.a. Gas: n.a.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:

Upper explosion limits:

7,0 vol. % (**)

Auto-ignition temperature:

180 °C

Self-ignition temperature

Solid: n.a. Gas: n.a. Decomposition temperature: n.d.

Vapour pressure: 0,9842 hPa

(at 20 °C)

Density (at 20 °C):

Bulk density:

n.a.

Water solubility:

2,57 g/cm³

n.a.

Immiscible

(at 20 °C)

Solubility in other solvents

n.d.

Partition coefficient n-octanol/water:

Viscosity / dynamic:

Viscosity / kinematic:

> 20,5 mm²/s

(at 40 °C)

Flow time:

Relative vapour density:

Evaporation rate:

Solvent separation test:

Solvent content:

n.d.

n.d.

16 %

9.2. Other information

Solid content: 84 %

(*) n-Butyl acetate

(**) Solvent naphta (petroleum)

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.





Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ZINC M

Revision date: 12.05.2022 Product code: 00359-1176 Page 8 of 12

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Heating can release vapours which can be ignited.

Vapour/air-mixtures are explosive at intense warming.

10.5. Incompatible materials

Strong oxidizing agents

Strong acids and strong bases

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains isocyanates. May produce an allergic reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Aromatic polyisocyanate prepolymer; 4-isocyanatosulphonyltoluene)

May cause an allergic skin reaction. (Aromatic polyisocyanate; Aromatic polyisocyanate; Aromatic polyisocyanate prepolymer; Fatty acids, C18-unsaturated, dimers, reaction products with N,

N-dimethyl-1,3-propanediamine and 1,3-propanediamine)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available


Other information

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Inhalation of high concentrations may cause injuries to liver, kidneys and central nervous system.

A longer or repeated contact my lead to irritation of eyes and mucous membranes.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.





Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ZINC M

Revision date: 12.05.2022 Product code: 00359-1176 Page 9 of 12

With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocyanates; therefore keep room aerated and ventilated.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Very toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:UN 126314.2. UN proper shipping name:Paint14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ZINC M

Revision date: 12.05.2022 Product code: 00359-1176 Page 10 of 12



Classification code: F1

Limited quantity: 5 L / 30 kg

Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number:UN 126314.2. UN proper shipping name:Paint14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1

Limited quantity: 5 L / 30 kg

Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1263

14.2. UN proper shipping name: Paint (Solvent naphtha (petroleum))

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Marine pollutant:

Limited quantity:

Excepted quantity:

EmS:

Yes

5 L / 30 kg

E1

EnS:

F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:UN 126314.2. UN proper shipping name:Paint14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1

IATA-packing instructions - Passenger: 355 IATA-max. quantity - Passenger: 60 L



TIP TOP Oberflaechenschutz Elbe GmbH

Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ZINC M

Revision date: 12.05.2022 Product code: 00359-1176 Page 11 of 12

IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Print date: 12.05.2022

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

2010/75/EU (VOC): 403 g/l 2004/42/EC (VOC): 403 g/l

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS

(SEVESO III):

Additional information: E1

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Consider Chemical prohibition regulation.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,4,6,7,8,9,10,11,12,13,14,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk



Safety Data Sheet

according to UK REACH Regulation

TIP TOP COROPUR ZINC M

Revision date: 12.05.2022 Product code: 00359-1176 Page 12 of 12

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Resp. Sens. 1; H334	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

Relevant H and EUH statements (number and full text)

Зe	levant H and EUH s	statements (number and full text)
	H226	Flammable liquid and vapour.
	H250	Catches fire spontaneously if exposed to air.
	H260	In contact with water releases flammable gases which may ignite spontaneously.
	H304	May be fatal if swallowed and enters airways.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H332	Harmful if inhaled.
	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	H335	May cause respiratory irritation.
	H336	May cause drowsiness or dizziness.
	H400	Very toxic to aquatic life.
	H410	Very toxic to aquatic life with long lasting effects.
	H411	Toxic to aquatic life with long lasting effects.
	EUH014	Reacts violently with water.
	EUH066	Repeated exposure may cause skin dryness or cracking.
	EUH204	Contains isocyanates. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

'The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)