



## ESKANOL ACCELERATOR NL 23

Revision date: 25.11.2022

Product code: 00359-1291

Page 2 of 11

### Hazard statements

H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H360Fd	May damage fertility. Suspected of damaging the unborn child.
H412	Harmful to aquatic life with long lasting effects.

### Precautionary statements

P261	Avoid breathing vapour.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/container to in accordance with local and national regulations.

### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Mixture containing following substances with additives

## ESKANOL ACCELERATOR NL 23

Revision date: 25.11.2022

Product code: 00359-1291

Page 3 of 11

### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
6846-50-0	1-isopropyl-2,2-dimethyltrimethylene diisobutyrate			60 - 70 %
	229-934-9		01-2119451093-47	
	Repr. 2, Aquatic Chronic 3; H361d H412			
136-52-7	Cobalt bis (2-ethylhexanoate)			10 - 20 %
	205-250-6		01-2119524678-29	
	Repr. 1B, Eye Irrit. 2, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 3; H360Fd H319 H317 H400 H412			
121-69-7	N,N-Dimethylaniline			5 - 10 %
	204-493-5	612-016-00-0	01-2119935241-47	
	Carc. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Aquatic Chronic 2; H351 H331 H311 H301 H411			
1330-20-7	Xylene (mixed isomers)			5 - 10 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
128-37-0	2,6-bis(1,1-dimethylethyl)-4-methylphenol			0,1 - 1,0 %
	204-881-4		01-2119555270-46	
	Aquatic Chronic 1; H410			
1338-02-9	naphthenic acids, copper salts; copper naphthenate			0,1 - 1,0 %
	215-657-0	029-003-00-5	01-2120784744-41	
	Flam. Liq. 3, Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1; H226 H302 H400 H410			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
121-69-7	204-493-5	N,N-Dimethylaniline	5 - 10 %
	inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg		
1330-20-7	215-535-7	Xylene (mixed isomers)	5 - 10 %
	inhalation: ATE = 11 mg/l (vapours); dermal: ATE = 1100 mg/kg		
128-37-0	204-881-4	2,6-bis(1,1-dimethylethyl)-4-methylphenol	0,1 - 1,0 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 6000 mg/kg Aquatic Chronic 1; H410: M=1		
1338-02-9	215-657-0	naphthenic acids, copper salts; copper naphthenate	0,1 - 1,0 %
	oral: ATE = 500 mg/kg Aquatic Acute 1; H400: M=10		

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Symptoms of poisoning may not occur for hours, therefore medical supervision for at least 48 hours necessary.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

## ESKANOL ACCELERATOR NL 23

Revision date: 25.11.2022

Product code: 00359-1291

Page 4 of 11

In the event of symptoms refer for medical treatment.

### **After contact with skin**

Wash off immediately with soap and plenty of water.  
Consult a doctor if skin irritation persists.

### **After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical treatment by eye specialist.

### **After ingestion**

Do not induce vomiting.  
Drink plenty of water or milk.  
Never give anything by mouth to an unconscious person.  
Summon a doctor immediately.  
Induce vomiting only upon the advice of a physician.

### **4.2. Most important symptoms and effects, both acute and delayed**

Suspected of causing cancer.  
May damage fertility. Suspected of damaging the unborn child.  
Causes serious eye irritation.  
May cause an allergic skin reaction.

### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

## SECTION 5: Firefighting measures

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

#### **Unsuitable extinguishing media**

Full water jet

### **5.2. Special hazards arising from the substance or mixture**

Fire may produce:  
carbon monoxide and carbon dioxide

### **5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective suit.

### **Additional information**

Cool containers at risk with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## SECTION 6: Accidental release measures

### **6.1. Personal precautions, protective equipment and emergency procedures**

#### **General advice**

Ensure adequate ventilation.  
Keep away noninvolved persons.

#### **For non-emergency personnel**

Do not breathe vapours.  
Avoid contact with skin, eyes and clothing.

#### **For emergency responders**

In case of vapour formation use respirator.  
Use personal protective clothing.

### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.  
Clean contaminated surface thoroughly.

## ESKANOL ACCELERATOR NL 23

Revision date: 25.11.2022

Product code: 00359-1291

Page 5 of 11

### 6.3. Methods and material for containment and cleaning up

#### **For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

#### **For cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### **Advice on safe handling**

Keep container tightly closed.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

When using do not eat, drink or smoke.

#### **Advice on protection against fire and explosion**

No special protective measures against fire required.

### 7.2. Conditions for safe storage, including any incompatibilities

#### **Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.

Protect against direct sun radiation.

Recommended storage temperature: +5°C - +30°C

#### **Hints on joint storage**

Incompatible with oxidizing agents.

#### **Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Accelerator

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL
121-69-7	N,N-Dimethylaniline	5	25		TWA (8 h)	WEL
		10	50		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

## ESKANOL ACCELERATOR NL 23

Revision date: 25.11.2022

Product code: 00359-1291

Page 6 of 11

### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

### DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
128-37-0	2,6-bis(1,1-dimethylethyl)-4-methylphenol			
Worker DNEL,		inhalation		3,5 mg/m <sup>3</sup>
Worker DNEL,		dermal		0,5 mg/kg bw/day

### 8.2. Exposure controls

#### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

#### Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

#### Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

#### Hand protection

Butyl rubber, Fluoro rubber, Nitrile rubber

Glove material must be impermeable and resistant against product / substance / preparation. Gloves material should comply with breakthrough times, permeation rates, and degradation.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

#### Skin protection

Long sleeved clothing (DIN EN ISO 6530)

#### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	purple	
Odour:	Characteristic	
pH-Value:		n.d.

#### Changes in the physical state

Melting point/freezing point:		n.d.
Boiling point or initial boiling point and boiling range:		n.d.
Sublimation point:		n.a.
Softening point:		n.d.

## ESKANOL ACCELERATOR NL 23

Revision date: 25.11.2022

Product code: 00359-1291

Page 7 of 11

Flash point: 67 °C

**Flammability**

Solid/liquid: n.a.

Gas: n.a.

**Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: n.d.

Upper explosion limits: n.d.

Auto-ignition temperature: n.d.

**Self-ignition temperature**

Solid: n.a.

Gas: n.a.

Decomposition temperature: n.d.

**Oxidizing properties**

Not oxidising.

Vapour pressure: n.d.

Density (at 20 °C): 0,956 g/cm<sup>3</sup>

Bulk density: n.a.

Water solubility:  
(at 20 °C) Immiscible**Solubility in other solvents**

n.d.

Partition coefficient n-octanol/water: n.d.

Viscosity / dynamic:  
(at 20 °C) 6 mPa·s

Viscosity / kinematic: n.d.

Flow time: n.d.

Relative vapour density: n.d.

Evaporation rate: n.d.

Solvent separation test: 0 %

Solvent content: &lt; 10 %

**9.2. Other information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with oxidizing agents.

**10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat.

Protect against direct sun radiation.

## ESKANOL ACCELERATOR NL 23

Revision date: 25.11.2022

Product code: 00359-1291

Page 8 of 11

### 10.5. Incompatible materials

Strong oxidizing agents

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### **Acute toxicity**

Based on available data, the classification criteria are not met.  
No toxicological data available.

#### **Irritation and corrosivity**

Causes serious eye irritation.  
Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### **Sensitising effects**

May cause an allergic skin reaction. (Cobalt bis (2-ethylhexanoate))

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of causing cancer. (N,N-Dimethylaniline)  
May damage fertility. (Cobalt bis (2-ethylhexanoate))  
Suspected of damaging the unborn child. (1-isopropyl-2,2-dimethyltrimethylene diisobutyrate)  
Germ cell mutagenicity: Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

Based on available data, the classification criteria are not met.

#### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

### 11.2. Information on other hazards

#### **Endocrine disrupting properties**

No data available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecological data are not available.  
Harmful to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

No data available

### 12.3. Bioaccumulative potential

No data available

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.



## ESKANOL ACCELERATOR NL 23

Revision date: 25.11.2022

Product code: 00359-1291

Page 9 of 11

### 12.7. Other adverse effects

Hazardous water pollutant.

### **Further information**

Do not flush into surface water or sanitary sewer system.

Risk of drinking water contamination even when low quantities are released into the ground.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

#### **List of Wastes Code - residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### **Contaminated packaging**

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

## SECTION 14: Transport information

### **Land transport (ADR/RID)**

#### 14.1. UN number:

No dangerous good in sense of this transport regulation.

#### 14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

#### 14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

#### 14.4. Packing group:

No dangerous good in sense of this transport regulation.

### **Inland waterways transport (ADN)**

#### 14.1. UN number:

No dangerous good in sense of this transport regulation.

#### 14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

#### 14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

#### 14.4. Packing group:

No dangerous good in sense of this transport regulation.

### **Marine transport (IMDG)**

#### 14.1. UN number:

No dangerous good in sense of this transport regulation.

#### 14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

#### 14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

#### 14.4. Packing group:

No dangerous good in sense of this transport regulation.

### **Air transport (ICAO-TI/IATA-DGR)**

#### 14.1. UN number:

No dangerous good in sense of this transport regulation.

#### 14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

#### 14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

#### 14.4. Packing group:

No dangerous good in sense of this transport regulation.

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

## ESKANOL ACCELERATOR NL 23

Revision date: 25.11.2022

Product code: 00359-1291

Page 10 of 11

### 14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

### 14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC): < 10 %

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

#### National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

#### Additional information

Consider Chemical prohibition regulation.

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 2,4,6,7,8,11,12,15.

### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

## ESKANOL ACCELERATOR NL 23

Revision date: 25.11.2022

Product code: 00359-1291

Page 11 of 11

LD = Lethal dose  
 LC = Lethal concentration  
 EC = Effect concentration  
 IC = Median immobilisation concentration or median inhibitory concentration

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1A; H317	Calculation method
Carc. 2; H351	Calculation method
Repr. 1B; H360F	Calculation method
Repr. 2; H361d	
Aquatic Chronic 3; H412	

### Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H360F	May damage fertility.
H360Fd	May damage fertility. Suspected of damaging the unborn child.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

*The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*