

ESKANOL LPT-IN

Revision date: 23.08.2022

Product code: 00359-1311

Page 2 of 11

Hazard statements

H242	Heating may cause a fire.
H302+H332	Harmful if swallowed or if inhaled.
H314	Causes severe skin burns and eye damage.
H361d	Suspected of damaging the unborn child.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P234	Keep only in original packaging.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P410	Protect from sunlight.
P411+P235	Store at temperatures not exceeding 30 °C/86 °F. Keep cool.
P420	Store separately.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture containing following substances with additives

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
6846-50-0	1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	55 - 65 %
	229-934-9	
	01-2119451093-47	
	Repr. 2, Aquatic Chronic 3; H361d H412	
1338-23-4	Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide	30 - 35 %
	700-954-4	
	01-2119514691-43	
	Self-react. D, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1; H242 H332 H302 H314 H318	

Full text of H and EUH statements: see section 16.

ESKANOL LPT-IN

Revision date: 23.08.2022

Product code: 00359-1311

Page 3 of 11

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1338-23-4	700-954-4	Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide	30 - 35 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: ATE = 500 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
Adhere to personal protective measures when giving first aid.
Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours.

After inhalation

Supply fresh air, if required oxygen, consult a physician.
If patient is not breathing, apply artificial respiration.
Remove the casualty into fresh air and keep him immobile.
In case of the person being unconscious put him/her in a stable side position.

After contact with skin

Wash off immediately with soap and plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Summon a doctor immediately.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed or if inhaled.
Causes severe skin burns and eye damage.
Suspected of damaging the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide and carbon dioxide
Hydrocarbons

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

ESKANOL LPT-IN

Revision date: 23.08.2022

Product code: 00359-1311

Page 4 of 11

Additional information

- Cool containers at risk with water spray jet.
- Collect contaminated firefighting water separately, must not be discharged into the drains.
- Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

- Ensure adequate ventilation.
- Keep away sources of ignition.
- Keep away noninvolved persons.

For non-emergency personnel

- Avoid contact with skin, eyes and clothing.
- Do not breathe vapours.

For emergency responders

- In case of vapour formation use respirator.
- Use personal protective clothing.

6.2. Environmental precautions

- Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

For containment

- Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

- Shovel into suitable container for disposal.
- Soak up with inert absorbent material (e.g. vermiculite, clean sand).
- Dilute larger quantities of desensitization agent (e.g. fuel oil) to < 10% before disposal.
- Do not keep container sealed.

6.4. Reference to other sections

- Observe protective instructions (see Sections 7 and 8).
- Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Do not breathe vapours.
- Wash hands before breaks and at the end of workday.
- Keep away from acids, bases, heavy metal salts and reducing agents.

Advice on protection against fire and explosion

- Keep away from sources of ignition - No smoking.
- Keep away from open flames, hot surfaces and sources of ignition.
- Use explosion-proof equipment / fittings and non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep only in original container.
- Keep container tightly closed in a dry, cool and well-ventilated place.
- Protect against direct sun radiation.
- Recommended storage temperature: 0°C - 30°C

Hints on joint storage

- Incompatible with:
Reducing agents., Heavy metal salts, Acids and bases.

ESKANOL LPT-IN

Revision date: 23.08.2022

Product code: 00359-1311

Page 5 of 11

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Hardener

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
1338-23-4	Methyl ethyl ketone peroxides (MEKP)	0.2	1.5		STEL (15 min)	WEL

Additional advice on limit values

This product does not contain any substances for which a Workplace Exposure Limit has been set in concentrations above the limits.

8.2. Exposure controls**Appropriate engineering controls**Pay attention to anti-explosion protection rules.
Ensure adequate ventilation, especially in confined areas.**Protective and hygiene measures**Do not inhale vapours.
Avoid contact with eyes and skin.
Wash hands before breaks and immediately after handling the product.
When using do not eat, drink or smoke.
Remove and wash contaminated clothing before re-use.**Eye/face protection**Tightly fitting goggles (EN 166).
Eye wash bottle with pure water (EN 15154).**Hand protection**Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance approx. 480 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.
This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.
Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>**Skin protection**Long sleeved clothing (DIN EN ISO 6530)
Apron (EN 467).**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Colourless
Odour:	Characteristic

Test method

ESKANOL LPT-IN

Revision date: 23.08.2022

Product code: 00359-1311

Page 6 of 11

pH-Value:	n.d.
Changes in the physical state	
Melting point/freezing point:	< - 25 °C
Boiling point or initial boiling point and boiling range:	Decomposition
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	84 °C ISO 3679
Flammability	
Solid/liquid:	n.a.
Gas:	n.a.
Explosive properties	
The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.	
Lower explosion limits:	n.d.
Upper explosion limits:	n.d.
Auto-ignition temperature:	n.a.
Self-ignition temperature	
Solid:	n.a.
Gas:	n.a.
Decomposition temperature:	> 60 °C
Oxidizing properties	
May cause fire.	
Vapour pressure:	n.d.
Density (at 20 °C):	1,01 g/cm ³
Bulk density:	n.a.
Water solubility: (at 20 °C)	n.d.
Solubility in other solvents	
Phthalates: Miscible	
Partition coefficient n-octanol/water:	n.d.
Viscosity / dynamic:	n.d.
Viscosity / kinematic: (at 20 °C)	13 mm ² /s
Flow time:	n.d.
Relative vapour density:	n.d.
Evaporation rate:	n.d.
Solvent separation test:	0 %
Solvent content:	0 %

9.2. Other information

Refractive index: 1,438
SADT approx. + 60°C

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored normally.

ESKANOL LPT-IN

Revision date: 23.08.2022

Product code: 00359-1311

Page 7 of 11

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts with:

Soil, rust, chemicals, strong acids and bases and accelerators (heavy metal salts, amines).

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Self-Accelerating decomposition temperature (SADT) from 60°C (SADT).

Vapours may form explosive mixture with air.

10.5. Incompatible materials

Soil, rust, chemicals, strong acids and bases and accelerators (heavy metal salts, amines).

10.6. Hazardous decomposition products

No decomposition if stored normally.

Fire may produce:

Carbon monoxide and carbon dioxide

Hydrocarbons

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Harmful if swallowed.

Harmful if inhaled.

No toxicological data available.

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (1-isopropyl-2,2-dimethyltrimethylene diisobutyrate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

ESKANOL LPT-IN

Revision date: 23.08.2022

Product code: 00359-1311

Page 8 of 11

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Low hazard to waters.

Further information

Do not release undiluted into wastewater or drainage ditch.

Do not release undiluted or in higher quantities into the groundwater, sewerage or waters.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN 3105

14.2. UN proper shipping name:

ORGANIC PEROXIDE TYPE D, LIQUID (Butanone peroxide)

14.3. Transport hazard class(es):

5.2

14.4. Packing group:

-

Hazard label:

5.2



Classification code:

P1

Limited quantity:

125 mL / 30 kg

Excepted quantity:

E0

Transport category:

2

Tunnel restriction code:

D

Inland waterways transport (ADN)

ESKANOL LPT-IN

Revision date: 23.08.2022

Product code: 00359-1311

Page 9 of 11

14.1. UN number: UN 3105
14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE D, LIQUID (Butanone peroxide)
14.3. Transport hazard class(es): 5.2
14.4. Packing group: -
Hazard label: 5.2



Classification code: P1
Limited quantity: 125 mL / 30 kg
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 3105
14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE D, LIQUID (Methyl ethyl ketone peroxide)
14.3. Transport hazard class(es): 5.2
14.4. Packing group: -
Hazard label: 5.2



Marine pollutant: No
Limited quantity: 125 mL / 30 kg
Excepted quantity: E0
EmS: F-J, S-R

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3105
14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE D, LIQUID (Methyl ethyl ketone peroxide)
14.3. Transport hazard class(es): 5.2
14.4. Packing group: -
Hazard label: 5.2



Limited quantity Passenger: Forbidden
Passenger LQ: Forbidden
Excepted quantity: E0
IATA-packing instructions - Passenger: 570
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 570
IATA-max. quantity - Cargo: 10 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

ESKANOL LPT-IN

Revision date: 23.08.2022

Product code: 00359-1311

Page 10 of 11

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC):

0 %

Information according to 2012/18/EU (SEVESO III):

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,12,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

ESKANOL LPT-IN

Revision date: 23.08.2022

Product code: 00359-1311

Page 11 of 11

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Org. Perox. D; H242	On basis of test data
Acute Tox. 4; H302	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Repr. 2; H361d	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H242	Heating may cause a fire.
H302	Harmful if swallowed.
H302+H332	Harmful if swallowed or if inhaled.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)