

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ESKANOL PU 23 COMP. B**

Revision date: 27.04.2021

Product code: 00359-1310

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

ESKANOL PU 23 COMP. B

**Art.-No.**

10626

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Hardener

**1.3. Details of the supplier of the safety data sheet**

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Contact person: Laborleiter

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

**1.4. Emergency telephone number:**INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 3

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements:

Flammable liquid and vapour.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**

Hexamethylene-1,6-diisocyanate, homopolymer

Xylene (mixed isomers)

Hexamethylene diisocyanate

**Signal word:** Warning**Pictograms:**

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## ESKANOL PU 23 COMP. B

Revision date: 27.04.2021

Product code: 00359-1310

Page 2 of 13

### Hazard statements

|      |  |
|------|--|
| H226 | Flammable liquid and vapour.                                       |
| H315 | Causes skin irritation.  |
| H317 | May cause an allergic skin reaction.                               |
| H319 | Causes serious eye irritation.                                     |
| H332 | Harmful if inhaled.  |
| H335 | May cause respiratory irritation.                                  |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

### Precautionary statements

|                |  |
|----------------|--|
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                   |
| P260           | Do not breathe vapour.   |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.   |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.                           |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P314           | Get medical advice/attention if you feel unwell.   |

### Special labelling of certain mixtures

|        |   |
|--------|---|
| EUH204 | Contains isocyanates. May produce an allergic reaction. |
|--------|---|

### Labelling of packages where the contents do not exceed 125 ml

Signal word: Warning

Pictograms:



### Hazard statements

H317

### Precautionary statements

P280

### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

Vapours may form explosive mixture with air.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Aliphatic polyisocyanate

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## ESKANOL PU 23 COMP. B

Revision date: 27.04.2021

Product code: 00359-1310

Page 3 of 13

### Hazardous components

| CAS No     | Chemical name   |              |                  | Quantity |
|------------|---|--------------|------------------|----------|
|            | EC No   | Index No     | REACH No         |          |
|            | GHS Classification  |              |                  |          |
| 28182-81-2 | Hexamethylene-1,6-diisocyanate, homopolymer   |              |                  | < 75 %   |
|            | 500-060-2   |              | 01-2119488934-20 |          |
|            | Acute Tox. 4, Skin Sens. 1, STOT SE 3; H332 H317 H335   |              |                  |          |
| 108-65-6   | 2-Methoxy-1-methylethyl acetate   |              |                  | < 15 %   |
|            | 203-603-9   | 607-195-00-7 | 01-2119475791-29 |          |
|            | Flam. Liq. 3, STOT SE 3; H226 H336  |              |                  |          |
| 1330-20-7  | Xylene (mixed isomers)  |              |                  | < 15 %   |
|            | 215-535-7   | 601-022-00-9 | 01-2119488216-32 |          |
|            | Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412 |              |                  |          |

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

| CAS No     | EC No     | Chemical name  | Quantity |
|------------|-----------|--|----------|
|            |           | Specific Conc. Limits, M-factors and ATE   |          |
| 28182-81-2 | 500-060-2 | Hexamethylene-1,6-diisocyanate, homopolymer  | < 75 %   |
|            |           | inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists)                           |          |
| 108-65-6   | 203-603-9 | 2-Methoxy-1-methylethyl acetate  | < 15 %   |
|            |           | dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5155 mg/kg   |          |
| 1330-20-7  | 215-535-7 | Xylene (mixed isomers)   | < 15 %   |
|            |           | inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg |          |

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

- Remove contaminated soaked clothing immediately.
- If you feel unwell, seek medical advice.
- Take away from danger area and lay down affected person.
- In case of the person being unconscious put him/her in a stable side position.

#### After inhalation

- Move to fresh air in case of accidental inhalation of vapours or decomposition products.
- Refer for medical treatment.
- If patient is not breathing, apply artificial respiration.

#### After contact with skin

- Wash off with soap and plenty of water.
- Consult a doctor if skin irritation persists.
- Do not use solvents or thinners.

#### After contact with eyes

- Remove contact lens.
- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- Seek medical treatment by eye specialist.

#### After ingestion

- Do not induce vomiting.
- Rinse out mouth and give plenty of water to drink.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ESKANOL PU 23 COMP. B**

Revision date: 27.04.2021

Product code: 00359-1310

Page 4 of 13

Never give anything by mouth to an unconscious person.  
Summon a doctor immediately.  
Induce vomiting only upon the advice of a physician.

**4.2. Most important symptoms and effects, both acute and delayed**

Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Harmful if inhaled.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Fire may produce:  
carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)  
Hydrogen cyanide (HCN)  
Isocyanates (NCO).

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective suit.

**Additional information**

Cool containers at risk with water spray jet.  
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.  
Vapours are heavier than air and spread along ground.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General measures**

Ensure adequate ventilation.  
Remove persons to safety.  
Keep away sources of ignition.

**For non-emergency personnel**

Avoid contact with skin, eyes and clothing.  
Do not breathe vapours.

**For emergency responders**

In case of vapour formation use respirator.  
Use personal protective clothing.

**6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.  
Do not discharge into the subsoil/soil.  
Inform competent authority about release into the sewage, ground or into waters.

**6.3. Methods and material for containment and cleaning up**



# Safety Data Sheet

according to Regulation (EC) No 1907/2006



## ESKANOL PU 23 COMP. B

Revision date: 27.04.2021

Product code: 00359-1310

Page 5 of 13

### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

### For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

Container should not be gas-tight closed.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed.

Keep a good ventilation and air-exhaust at the place of work.

Vapours are heavier than air and spread along ground.

Avoid contact with the skin and the eyes.

When using do not eat, drink or smoke.

Do not empty container under pressure. No pressure tank!

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion protection rules.

Protect from heat and direct solar radiation.

Recommended storage temperature: 10°C - 30°C

#### Hints on joint storage

Incompatible with:

Oxidizing agents

Acids and bases.

Water, amines, alcohols

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Hardener

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## ESKANOL PU 23 COMP. B

Revision date: 27.04.2021

Product code: 00359-1310

Page 6 of 13

### Exposure limits (EH40)

| CAS No    | Substance               | ppm | mg/m <sup>3</sup> | fibres/ml | Category      | Origin |
|-----------|-------------------------|-----|-------------------|-----------|---------------|--------|
| 108-65-6  | 1-Methoxypropyl acetate | 50  | 274               |           | TWA (8 h)     | WEL    |
|           |                         | 100 | 548               |           | STEL (15 min) | WEL    |
| 1330-20-7 | Xylene: mixed isomers   | 50  | 220               |           | TWA (8 h)     | WEL    |
|           |                         | 100 | 441               |           | STEL (15 min) | WEL    |

### Biological Monitoring Guidance Values (EH40)

| CAS No    | Substance                           | Parameter                         | Value        | Test material | Sampling time |
|-----------|-------------------------------------|-----------------------------------|--------------|---------------|---------------|
| 1330-20-7 | Xylene, o-, m-, p- or mixed isomers | methyl hippuric acid (creatinine) | 650 mmol/mol | urine         | Post shift    |

### DNEL/DMEL values

| CAS No   | Substance                       | DNEL type                | Exposure route | Effect   | Value                 |
|----------|---------------------------------|--------------------------|----------------|----------|-----------------------|
| 108-65-6 | 2-Methoxy-1-methylethyl acetate |                          |                |          |                       |
|          |                                 | Consumer DNEL, long-term | oral           | systemic | 36 mg/kg bw/day       |
|          |                                 | Consumer DNEL, long-term | dermal         | systemic | 320 mg/kg bw/day      |
|          |                                 | Worker DNEL, long-term   | dermal         | systemic | 796 mg/kg bw/day      |
|          |                                 | Consumer DNEL, long-term | inhalation     | systemic | 33 mg/m <sup>3</sup>  |
|          |                                 | Worker DNEL, long-term   | inhalation     | systemic | 275 mg/m <sup>3</sup> |

### PNEC values

| CAS No   | Substance                       | Environmental compartment                        | Value       |
|----------|---------------------------------|--|-------------|
| 108-65-6 | 2-Methoxy-1-methylethyl acetate |  |             |
|          |                                 | Freshwater                                       | 0,635 mg/l  |
|          |                                 | Freshwater (intermittent releases)               | 635 mg/l    |
|          |                                 | Marine water                                     | 0,064 mg/l  |
|          |                                 | Freshwater sediment                              | 3,29 mg/kg  |
|          |                                 | Marine sediment                                  | 0,329 mg/kg |
|          |                                 | Micro-organisms in sewage treatment plants (STP) | 100 mg/l    |
|          |                                 | Soil   | 0,29 mg/kg  |

### 8.2. Exposure controls

#### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

#### Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothing before re-use.

#### Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ESKANOL PU 23 COMP. B**

Revision date: 27.04.2021

Product code: 00359-1310

Page 7 of 13

**Hand protection**

Protective gloves resistant to chemicals made off viton, minimum coat thickness 0.7 mm, permeation resistance (wear duration) approx. 30 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de.  
Splash protection: Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance approx. 480 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.  
This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Skin protection**

Long sleeved clothing (DIN EN ISO 6530)

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state: Liquid  
Colour: Colourless  
Odour: Characteristic

**Test method**

pH-Value: n.d.

**Changes in the physical state**

Melting point: n.d.

Boiling point or initial boiling point and boiling range: n.d.

Sublimation point: n.a.

Softening point: n.d.

Flash point: 27 °C Calculated

Sustaining combustion: Sustaining combustion

**Flammability**

Solid/liquid: n.a.

Gas: n.a.

**Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: n.d.

Upper explosion limits: n.d.

Auto-ignition temperature: n.d.

**Self-ignition temperature**

Solid: n.a.

Gas: n.a.

Decomposition temperature: n.d.

**Oxidizing properties**

Not oxidising.

Vapour pressure:  
(at 20 °C) n.d.

Density (at 20 °C): approx. 1,08 g/cm<sup>3</sup> ISO 2811-2

Bulk density: n.a.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ESKANOL PU 23 COMP. B**

Revision date: 27.04.2021

Product code: 00359-1310

Page 8 of 13

|   |                          |
|---|--------------------------|
| Water solubility:<br>(at 20 °C)             | Immiscible               |
| <b>Solubility in other solvents</b><br>n.d. |                          |
| Partition coefficient n-octanol/water:      | n.d.                     |
| Viscosity / dynamic:<br>(at 20 °C)          | 45 - 65 mPa·s ISO 2884-1 |
| Viscosity / kinematic:<br>(at 40 °C)        | 39 mm <sup>2</sup> /s    |
| Flow time:<br>(at 23 °C)                    | 8 s 6 DIN 53211          |
| Relative vapour density:                    | n.d.                     |
| Evaporation rate:                           | n.d.                     |
| Solvent separation test:                    | n.d.                     |
| Solvent content:                            | < 30 %                   |

**9.2. Other information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**Reactions with acids, alkalies and oxidizing agents  
Reacts with: Water, amines, alcohols**10.4. Conditions to avoid**To avoid thermal decomposition, do not overheat.  
Heating can release vapours which can be ignited.  
Vapour/air-mixtures are explosive at intense warming.**10.5. Incompatible materials**Strong oxidizing agents  
Strong acids and strong bases  
Water, amines, alcohols**10.6. Hazardous decomposition products**No known hazardous decomposition products.  
Fire may produce:  
Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)  
Hydrogen cyanide gas, Isocyanates**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**Harmful if inhaled.  
No toxicological data available.  
ATEmix/inhalation: ~ 12 mg/l/4 h [vapour]**Irritation and corrosivity**



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ESKANOL PU 23 COMP. B**

Revision date: 27.04.2021

Product code: 00359-1310

Page 9 of 13

Causes skin irritation.

Causes serious eye irritation.

**Sensitising effects**Contains isocyanates. May produce an allergic reaction. May cause an allergic skin reaction.  
(Hexamethylene-1,6-diisocyanate, homopolymer)**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (Hexamethylene-1,6-diisocyanate, homopolymer)

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (Xylene (mixed isomers))

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

**11.2. Information on other hazards****Endocrine disrupting properties**

No data available

**Other information**

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Inhalation of high concentrations may cause injuries to liver, kidneys and central nervous system.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocyanates; therefore keep room aerated and ventilated.

**SECTION 12: Ecological information****12.1. Toxicity**

Ecological data are not available.

**12.2. Persistence and degradability**

No data available

| CAS No   | Chemical name                   | Method     | Value | d  | Source |
|----------|---------------------------------|------------|-------|----|--------|
|          |                                 | Evaluation |       |    |        |
| 108-65-6 | 2-Methoxy-1-methylethyl acetate |            |       |    |        |
|          | OECD 301F                       |            | 90%   | 28 | ECHA   |
|          | Formation of carbon dioxide     |            |       |    |        |
|          | OECD 301F                       |            | 83%   | 28 | ECHA   |
|          | Oxygen consumption              |            |       |    |        |
|          | OECD 301F                       |            | 99%   | 28 | ECHA   |
|          | DOC decrease                    |            |       |    |        |

**12.3. Bioaccumulative potential**

No data available

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## ESKANOL PU 23 COMP. B

Revision date: 27.04.2021

Product code: 00359-1310

Page 10 of 13

### 12.6. Endocrine disrupting properties

No data available

### 12.7. Other adverse effects

Hazardous water pollutant.

### **Further information**

Do not flush into surface water or sanitary sewer system.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Can be incinerated, when in compliance with local regulations.  
Where possible recycling is preferred to disposal.

#### **List of Wastes Code - residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

#### **Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.  
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.  
Packaging that cannot be cleaned should be disposed of like the product.

## SECTION 14: Transport information

### **Land transport (ADR/RID)**

|   |         |
|---|---------|
| <b><u>14.1. UN number:</u></b>                  | UN 1263 |
| <b><u>14.2. UN proper shipping name:</u></b>    | PAINT   |
| <b><u>14.3. Transport hazard class(es):</u></b> | 3       |
| <b><u>14.4. Packing group:</u></b>              | III     |
| Hazard label:                                   | 3       |



|                          |             |
|--------------------------|-------------|
| Classification code:     | F1          |
| Special Provisions:      | 163 367 650 |
| Limited quantity:        | 5 L / 30 kg |
| Excepted quantity:       | E1          |
| Transport category:      | 3           |
| Hazard No:               | 30          |
| Tunnel restriction code: | D/E         |

### **Inland waterways transport (ADN)**

|   |         |
|---|---------|
| <b><u>14.1. UN number:</u></b>                  | UN 1263 |
| <b><u>14.2. UN proper shipping name:</u></b>    | Paint   |
| <b><u>14.3. Transport hazard class(es):</u></b> | 3       |
| <b><u>14.4. Packing group:</u></b>              | III     |
| Hazard label:                                   | 3       |

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## ESKANOL PU 23 COMP. B

Revision date: 27.04.2021

Product code: 00359-1310

Page 11 of 13



Classification code: F1  
Special Provisions: 163 367 650  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1

### Marine transport (IMDG)

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** PAINT  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Marine pollutant: No  
Special Provisions: 163, 223, 367, 955  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1  
EmS: F-E, S-E

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** PAINT  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: A3 A72 A192  
Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

### 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ESKANOL PU 23 COMP. B**

Revision date: 27.04.2021

Product code: 00359-1310

Page 12 of 13

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC): &lt; 500 g/l

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,4,6,7,8,9,10,11,12,14,15.

**Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ESKANOL PU 23 COMP. B**

Revision date: 27.04.2021

Product code: 00359-1310

Page 13 of 13

**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

| Classification      | Classification procedure |
|---------------------|--------------------------|
| Flam. Liq. 3; H226  | On basis of test data    |
| Acute Tox. 4; H332  | Calculation method       |
| Skin Irrit. 2; H315 | Calculation method       |
| Eye Irrit. 2; H319  | Calculation method       |
| Skin Sens. 1; H317  | Calculation method       |
| STOT SE 3; H335     | Calculation method       |
| STOT RE 2; H373     | Calculation method       |

**Relevant H and EUH statements (number and full text)**

|        |  |
|--------|--|
| H226   | Flammable liquid and vapour.                                       |
| H304   | May be fatal if swallowed and enters airways.                      |
| H312   | Harmful in contact with skin.                                      |
| H315   | Causes skin irritation.  |
| H317   | May cause an allergic skin reaction.                               |
| H319   | Causes serious eye irritation.                                     |
| H332   | Harmful if inhaled.  |
| H335   | May cause respiratory irritation.                                  |
| H336   | May cause drowsiness or dizziness.                                 |
| H373   | May cause damage to organs through prolonged or repeated exposure. |
| H412   | Harmful to aquatic life with long lasting effects.                 |
| EUH204 | Contains isocyanates. May produce an allergic reaction.            |

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

*The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*