

according to UK REACH Regulation

TIP TOP FIXPASTE REMAREP SPRAY PART A

Revision date: 14.04.2025

Product code: 00156-0540

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP FIXPASTE REMAREP SPRAY PART A

Art.-No.

525 3314

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Repair material

1.3. Details of the supplier of the safety data sheet

Manufacturer

Wanulacturer	
Company name:	REMA TIP TOP AG
Street:	Gruber Strasse 65
Place:	D-85586 Poing
Telephone:	+49 (0) 8121 / 707 - 100
Responsible Department:	Responsible for the safety data sheet: sds@gbk-ingelheim.de
Supplier	
Company name:	REMA TIP TOP INDUSTRY UK LTD
Street:	Plumtree Industrial Estate, Harworth
Place:	Doncaster, DN11 8EW, South Yorkshire
Telephone:	+44 (0)1302 711233
Internet:	www.rema-tiptop.co.uk
1.4. Emergency telephone	INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
number:	In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Carc. 2; H351 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Polypropylene glycol, diphenylmethane diisocyanate polymer Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate Diphenylmethane-4,4'-diisocyanate o-(p-isocyanatobenzyl)phenyl isocyanate Danger

Signal word:



according to UK REACH Regulation

TIP TOP FIXPASTE REMAREP SPRAY PART A

Revision date: 14.04.2025

Product code: 00156-0540

Page 2 of 12





Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P201	Obtain special instructions before use.
P260	Do not breathe vapour.
P264	Wash skin thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P308+P313	IF exposed or concerned: Get medical advice/attention.

Special labelling of certain mixtures

EUH204

Contains isocyanates. May produce an allergic reaction. As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation with isocyanates



according to UK REACH Regulation

TIP TOP FIXPASTE REMAREP SPRAY PART A

Revision date: 14.04.2025

Product code: 00156-0540

Page 3 of 12

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)		
39420-98-9	Polypropylene glycol, diphenylmet		< 90 %	
	Resp. Sens. 1, Skin Sens. 1; H334	H317		
26447-40-5	Reaction mass of 4,4'-methylenedi isocyanate	phenyl diisocyanate and o-(p-isocyar	natobenzyl) phenyl	< 25 %
	247-714-0	615-005-00-9	01-2120770510-62	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
101-68-8	Diphenylmethane-4,4'-diisocyanate			< 15 %
	202-966-0	615-005-00-9	01-2119457014-47	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, 2; H351 H332 H315 H319 H334 H	Eye Irrit. 2, Resp. Sens. 1, Skin Sens 317 H335 H373	. 1, STOT SE 3, STOT RE	
5873-54-1	o-(p-isocyanatobenzyl)phenyl isocy	/anate		< 15 %
	227-534-9	615-005-00-9	01-2119480143-45	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
2536-05-2 Diphenylmethane-2,2'-diisocyanate			< 1 %	
	219-799-4	615-005-00-9	01-2119927323-43	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, 2; H351 H332 H315 H319 H334 H	- Eye Irrit. 2, Resp. Sens. 1, Skin Sens 317 H335 H373	. 1, STOT SE 3, STOT RE	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
26447-40-5	247-714-0	Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate	< 25 %
	9200 mg/kg S	E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: STOT SE 3; H335: >= 5 - 100	
101-68-8	202-966-0	Diphenylmethane-4,4'-diisocyanate	< 15 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 0,368 mg/l (dusts or mists); dermal: LD50 = > 9400 mg/kg; oral: LD50 = > 2000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100		
5873-54-1	227-534-9	o-(p-isocyanatobenzyl)phenyl isocyanate	< 15 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 0,31 mg/l (dusts or mists); dermal: LD50 = > 9400 mg/kg; oral: LD50 = > 2000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100		
2536-05-2	219-799-4	Diphenylmethane-2,2'-diisocyanate	< 1 %
	> 15000 mg/kg	E = 11 mg/l (vapours); inhalation: LC50 = 0,370 mg/l (dusts or mists); oral: LD50 = g Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; 100 STOT SE 3; H335: >= 5 - 100	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.



according to UK REACH Regulation

TIP TOP FIXPASTE REMAREP SPRAY PART A

Revision date: 14.04.2025

Product code: 00156-0540

Page 4 of 12

Take away from danger area and lay down affected person.

After inhalation

If patient is not breathing, apply artificial respiration. Move to fresh air in case of accidental inhalation of vapours. Refer for medical treatment.

After contact with skin

Remove immediately adhering matter.

Consult a physician.

Wash contaminated skin with plenty of water and soap or with liquid polyethylene glycol.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting. Rinse out mouth thoroughly with water. Never give anything by mouth to an unconscious person. Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause respiratory irritation.

Suspected of causing cancer.

May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Keep under medical supervision for at least 48 hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce: carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) Hydrogen cyanide (HCN) Isocyanates (NCO).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures



according to UK REACH Regulation

TIP TOP FIXPASTE REMAREP SPRAY PART A

Revision date: 14.04.2025

Product code: 00156-0540

Page 5 of 12

General advice

Ensure adequate ventilation. Remove persons to safety.

For non-emergency personnel

Do not breathe vapours. Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator. Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water. Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

Container should not be gas-tight closed.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Vapours are heavier than air and spread along ground. Avoid contact with the skin and the eyes. Do not breathe vapours. Local exhaust. Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Advice on general occupational hygiene

Do not inhale vapours. Avoid contact with eyes and skin. Wash hands before breaks and immediately after handling the product. When using do not eat, drink or smoke. Take off immediately all contaminated clothing.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place. Keep at temperatures between 15°C and 35°C.

Hints on joint storage

Exothermic reaction with: Acids and bases. Water, amines, alcohols



according to UK REACH Regulation

TIP TOP FIXPASTE REMAREP SPRAY PART A

Revision date: 14.04.2025

Product code: 00156-0540

Page 6 of 12

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs. Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

7.3. Specific end use(s)

Repair material

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
-	Isocyanates, all (as -NCO) Except methyl isocyanate	-	0.02		TWA (8 h)	WEL
		-	0.07		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
		isocyanate-derived diamine (creatinine)	1 µmol/mol		At the end of the period of exposure

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
5873-54-1	o-(p-isocyanatobenzyl)phenyl isocyanate			
Worker DNEL,	acute	dermal	systemic	50 mg/kg bw/day
Worker DNEL,	acute	inhalation	systemic	0,1 mg/m³
Worker DNEL,	acute	dermal	local	28,7 mg/cm ²
Worker DNEL,	acute	inhalation	local	0,1 mg/m³
Worker DNEL,	long-term	dermal	systemic	0 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	0,05 mg/m³
Worker DNEL,	long-term	dermal	local	0 mg/cm ²
Consumer DN	EL, acute	dermal	systemic	25 mg/kg bw/day
Consumer DN	EL, acute	inhalation	systemic	0,05 mg/m³
Consumer DN	EL, acute	oral	systemic	20 mg/kg bw/day
Consumer DN	EL, acute	dermal	local	17,2 mg/cm ²
Consumer DN	EL, long-term	dermal	local	0 mg/cm ²
Consumer DN	EL, long-term	dermal	systemic	0 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	0,025 mg/m³
Consumer DN	EL, long-term	oral	systemic	0 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	local	0,025 mg/m³
Worker DNEL,	long-term	inhalation	local	0,05 mg/m³



according to UK REACH Regulation

TIP TOP FIXPASTE REMAREP SPRAY PART A

Revision date: 14.04.2025

Product code: 00156-0540

Page 7 of 12

PNEC values

CAS No	Substance		
Environmenta	Environmental compartment		
5873-54-1 o-(p-isocyanatobenzyl)phenyl isocyanate			
Freshwater		> 1 mg/l	
Marine water		> 0,1 mg/l	
Micro-organisms in sewage treatment plants (STP)		> 1 mg/l	
Soil		> 1 mg/kg	

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face protection

Eye wash bottle with pure water (EN 15154). Tightly fitting goggles (EN 166).

Hand protection

Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance (wear duration) > 240 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	Liquid Yellowish		
Odour:	Characteristic		
Changes in the physical state			
Melting point/freezing point:		n.d.	
Boiling point or initial boiling point and boiling range:		n.d.	
Sublimation point:		n.a.	
Softening point:		n.d.	
Flash point:		> 200 °C	
Flammability Solid/liquid:		n.a.	
Explosive properties The product is not explosive.			
Lower explosion limits:		n.d.	
Upper explosion limits:		n.d.	
Auto-ignition temperature:		n.d.	



according to UK REACH Regulation

TIP TO	P FIXPASTE REMAREP SPRAY PART A	
Revision date: 14.04.2025	Product code: 00156-0540	Page 8 of 12
Self-ignition temperature		
Solid:	n.a.	
Gas:	n.a.	
Decomposition temperature:	n.d.	
pH-Value:	n.a.	
Viscosity / dynamic: (at 25 °C)	2500 - 4500 mPa·s	
Viscosity / kinematic:	n.d.	
Flow time:	n.d.	
Water solubility: (at 20 °C)	Reacts with water.	
Solubility in other solvents n.d.		
Partition coefficient n-octanol/water:	n.d.	
Vapour pressure: (at 25 °C)	< 0,00001 hPa	
Density (at 20 °C):	1,08 - 1,12 g/cm³	
Bulk density:	n.a.	
Relative vapour density:	8,5	
9.2. Other information		
Information with regard to physical hazar	d classes	
Oxidizing properties Not oxidising.		
Other safety characteristics		
Solvent separation test:	0 %	
Solvent content:	0 %	
Evaporation rate:	n.d.	
Further Information		
No data available		

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with strong acids and alkalies. Reacts with: Water, amines, alcohols

10.4. Conditions to avoid

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

10.5. Incompatible materials

Acids and bases.

Water, amines, alcohols

10.6. Hazardous decomposition products

Fire may produce:

Hydrogen cyanide gas



according to UK REACH Regulation

TIP TOP FIXPASTE REMAREP SPRAY PART A

Revision date: 14.04.2025

Product code: 00156-0540

Page 9 of 12

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) Isocyanates

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met. No toxicological data available.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 10,78 mg/l; ATE (inhalation dust/mist) 1,471 mg/l

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Polypropylene glycol, diphenylmethane diisocyanate polymer; Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate; Diphenylmethane-4,4'-diisocyanate; o-(p-isocyanatobenzyl)phenyl isocyanate; Diphenylmethane-2,2'-diisocyanate)

May cause an allergic skin reaction. (Polypropylene glycol, diphenylmethane diisocyanate polymer; Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate;

Diphenylmethane-4,4'-diisocyanate; o-(p-isocyanatobenzyl)phenyl isocyanate;

Diphenylmethane-2,2'-diisocyanate)

Contains isocyanates. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate; Diphenylmethane-4,4'-diisocyanate; o-(p-isocyanatobenzyl)phenyl isocyanate; Diphenylmethane-2,2'-diisocyanate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate; Diphenylmethane-4,4'-diisocyanate; o-(p-isocyanatobenzyl)phenyl isocyanate)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate; Diphenylmethane-4,4'-diisocyanate; o-(p-isocyanatobenzyl)phenyl isocyanate)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

Not readily biodegradable.



according to UK REACH Regulation

TIP TOP FIXPASTE REMAREP SPRAY PART A

Revision date: 14.04.2025

Product code: 00156-0540

Page 10 of 12

12.3. Bioaccumulative potential

A bioaccumulation potential is to be expected.

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Low hazard to waters.

Further information

In aqueous systems, formation of unsoluble and chemically inert (inactive) polyureas. Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal. Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:14.2. UN proper shipping name:14.3. Transport hazard class(es):14.4. Packing group:

Inland waterways transport (ADN) 14.1. UN number or ID number:

14.2. UN proper shipping name: 14.3. Transport hazard class(es):

14.4. Packing group:

Marine transport (IMDG)

14.1. UN number or ID number: 14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Air transport (ICAO-TI/IATA-DGR)

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.



according to UK REACH Regulation

TIP TOP FIXPASTE REMAREP SPRAY PART A				
Revision date: 14.04.2025	Product code: 00156-0540	Page 11 of 12		
<u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.			
14.5. Environmental hazards				
ENVIRONMENTALLY HAZARDOUS:	No			
14.6. Special precautions for user				
No dangerous good in sense of this tra				
14.7. Maritime transport in bulk according to No dangerous good in sense of this tra				
SECTION 15: Regulatory information				
15.1. Safety, health and environmental regul	ations/legislation specific for the substance or mixture			
EU regulatory information				
Restrictions on use (REACH, annex XVII): Entry 3, Entry 56, Entry 74, Entry 75				
Directive 2004/42/EC on VOC in paints and varnishes:	0 %			
Information according to Directive 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)			
National regulatory information				
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juve work protection guideline' (94/33/EC). Observe employment restriction under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.			
Water hazard class (D):	1 - slightly hazardous to water			
15.2. Chemical safety assessment				

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

- RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
- ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
- IMDG = International Maritime Code for Dangerous Goods
- IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
- MARPOL = International Convention for the Prevention of Pollution from Ships
- IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
- CAS = Chemical Abstract Service
- EN = European norm
- ISO = International Organization for Standardization
- DIN = Deutsche Industrie Norm
- PBT = Persistent Bioaccumulative and Toxic
- vPvB = Very Persistent and very Bio-accumulative



according to UK REACH Regulation

TIP TOP FIXPASTE REMAREP SPRAY PART A

Revision date: 14.04.2025

Product code: 00156-0540

Page 12 of 12

LD = Lethal dose

- LC = Lethal concentration
- EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure	
Carc. 2; H351	Calculation method	
Skin Irrit. 2; H315	Calculation method	
Eye Irrit. 2; H319	Calculation method	
Resp. Sens. 1; H334	Calculation method	
Skin Sens. 1; H317	Calculation method	
STOT SE 3; H335	Calculation method	
STOT RE 2; H373	Calculation method	

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH204	Contains isocyanates. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)