



Safety Data Sheet

according to UK REACH Regulation

TIP TOP REMACOAT D-40 POLY

Revision date: 05.01.2023

Product code: 00359-1097

Page 2 of 11

Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statements

P260	Do not breathe vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P273	Avoid release to the environment.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.
The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture containing following substances with additives

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64852-22-8	Glyceryl poly(oxypropylene) triamine			< 50 %
	Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3; H315 H318 H412			
68479-98-1	Diethylmethylbenzenediamine			< 25 %
	270-877-4	612-130-00-0	01-2119486805-25	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1; H312 H302 H319 H373 H400 H410			
5285-60-9	4,4'-methylenebis[N-sec-butylaniline]			< 10 %
	226-122-6		01-2120807289-49	
	Acute Tox. 4, Skin Sens. 1B, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1; H302 H317 H373 H400 H410			
9046-10-0	Poly(oxy(methyl-1,2-ethanediyl)),alpha-(2-aminomethylethyl)omega-(2-aminomethylethoxy)-			< 5 %
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Aquatic Chronic 3; H302 H314 H318 H412			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

TIP TOP REMACOAT D-40 POLY

Revision date: 05.01.2023

Product code: 00359-1097

Page 3 of 11

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
68479-98-1	270-877-4	Diethylmethylbenzenediamine	< 25 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 598 mg/kg	
5285-60-9	226-122-6	4,4'-methylenebis[N-sec-butylaniline]	< 10 %
		dermal: LD50 = 3090 mg/kg; oral: LD50 = 1380 mg/kg Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	
9046-10-0		Poly(oxy(methyl-1,2-ethanediyl)),alpha-(2-aminomethylethyl)omega-(2-aminomethylethoxy)-	< 5 %
		dermal: LD50 = 2090 mg/kg; oral: LD50 = 475 mg/kg	

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.
Consult a physician.
Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.
In the event of symptoms refer for medical treatment.

After contact with skin

In case of contact with skin wash off immediately with plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Summon a doctor immediately.

After ingestion

Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)



Safety Data Sheet

according to UK REACH Regulation

TIP TOP REMACOAT D-40 POLY

Revision date: 05.01.2023

Product code: 00359-1097

Page 4 of 11

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.
Keep away noninvolved persons.

For non-emergency personnel

Do not breathe vapours.
Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.
Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.
Avoid contact with the skin and the eyes.
Do not breathe vapours.
Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.
No special protective measures against fire required.

Advice on general occupational hygiene

Do not inhale vapours.
Avoid contact with eyes and skin.
Wash hands before breaks and immediately after handling the product.
When using do not eat, drink or smoke.
Remove and wash contaminated clothes before re-use.

7.2. Conditions for safe storage, including any incompatibilities



Safety Data Sheet

according to UK REACH Regulation

TIP TOP REMACOAT D-40 POLY

Revision date: 05.01.2023

Product code: 00359-1097

Page 5 of 11

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Hints on joint storage

Incompatible with acids.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Coating system for protection against wear and corrosion

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
7727-43-7	Barium sulphate, inhalable dust	-	10		TWA (8 h)	WEL

Additional advice on limit values

This product does not contain any substances for which a Workplace Exposure Limit has been set in concentrations above the limits.

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid - viscous
Colour:	Various
Odour:	Amine like

Test method

Changes in the physical state

Melting point/freezing point: n.d.

**Safety Data Sheet**

according to UK REACH Regulation

TIP TOP REMACOAT D-40 POLY

Revision date: 05.01.2023

Product code: 00359-1097

Page 6 of 11

Boiling point or initial boiling point and boiling range: n.d.
Sublimation point: n.a.
Softening point: n.d.
Flash point: > 100 °C

Flammability

Solid/liquid: n.a.
Gas: n.a.

Explosive properties

The product is not explosive.

Lower explosion limits: n.d.
Upper explosion limits: n.d.
Auto-ignition temperature: n.d.

Self-ignition temperature

Solid: n.a.
Gas: n.a.

Decomposition temperature: n.d.

pH-Value: n.d.

Viscosity / dynamic: 1500 - 2000 mPa·s
(at 25 °C)

Viscosity / kinematic: n.d.

Flow time: > 40 s 6 DIN/ISO 2431
(at 25 °C)

Water solubility: Immiscible

Solubility in other solvents

n.d.

Partition coefficient n-octanol/water: n.d.

Vapour pressure: n.d.

Density (at 25 °C): 1,17 - 1,21 g/cm³

Bulk density: n.a.

Relative vapour density: n.d.

9.2. Other information**Information with regard to physical hazard classes**

Oxidizing properties
Not oxidising.

Other safety characteristics

Solvent separation test: 0 %

Solvent content: 0 %

Evaporation rate: n.d.

Further Information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.



Safety Data Sheet

according to UK REACH Regulation

TIP TOP REMACOAT D-40 POLY

Revision date: 05.01.2023

Product code: 00359-1097

Page 7 of 11

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

10.5. Incompatible materials

Acids.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.

ATEmix/oral: > 2000 mg/kg

ATEmix/dermal: > 2000 mg/kg

ATEmix calculated

ATE (oral) 2207,2 mg/kg; ATE (dermal) 5365,9 mg/kg

Irritation and corrosivity

Causes skin irritation.

Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (4,4'-methylenebis[N-sec-butylaniline])

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Diethylmethylbenzenediamine)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Inhalation of vapours in high concentration may cause irritation of respiratory system.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Very toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to UK REACH Regulation

TIP TOP REMACOAT D-40 POLY

Revision date: 05.01.2023

Product code: 00359-1097

Page 8 of 11

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazardous water pollutant.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Diethylmethylenediamine)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Limited quantity:

5 L / 30 kg

Excepted quantity:

E1



Safety Data Sheet

according to UK REACH Regulation

TIP TOP REMACOAT D-40 POLY

Revision date: 05.01.2023

Product code: 00359-1097

Page 9 of 11

Transport category: 3
Hazard No: 90
Tunnel restriction code: -

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diethylmethylbenzenediamine)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Classification code: M6
Limited quantity: 5 L / 30 kg
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diethylmethylbenzenediamine)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Marine pollutant: Yes
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diethylmethylbenzenediamine)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Limited quantity Passenger: 30 kg G
Passenger LQ: Y964
Excepted quantity: E1
IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

**Safety Data Sheet**

according to UK REACH Regulation

TIP TOP REMACOAT D-40 POLY

Revision date: 05.01.2023

Product code: 00359-1097

Page 10 of 11

ENVIRONMENTALLY HAZARDOUS: Yes

**14.6. Special precautions for user**

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC): 0 %

Information according to 2012/18/EU (SEVESO III): E1 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,4,6,7,8,9,10,11,12,14,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

**Safety Data Sheet**

according to UK REACH Regulation

TIP TOP REMACOAT D-40 POLY

Revision date: 05.01.2023

Product code: 00359-1097

Page 11 of 11

LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)