

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP REMAFIX S H3**

Revision date: 21.02.2022

Product code: 00359-1085

Page 1 of 11

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

TIP TOP REMAFIX S H3

**Art.-No.**

525 2891

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Hardener

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

**Supplier**

Company name: REMA TIP TOP INDUSTRY UK LTD

Street: Plumtree Industrial Estate, Harworth

Place: Doncaster, DN11 8EW, South Yorkshire

Telephone: +44 (0)1302 711233

Internet: www.rema-tiptop.co.uk

**1.4. Emergency telephone number:**INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard Statements:

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

Diphenylmethanediisocyanate, isomers and homologues

Diphenylmethane-4,4'-diisocyanate

Diphenylmethane-2,4'-diisocyanate

Diphenylmethane-2,2'-diisocyanate

**Signal word:** Danger

# Safety Data Sheet

according to UK REACH Regulation


## TIP TOP REMAFIX S H3

Revision date: 21.02.2022

Product code: 00359-1085

Page 2 of 11

### Pictograms:



### Hazard statements

H332	Harmful if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

### Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.

### Special labelling of certain mixtures

EUH204	Contains isocyanates. May produce an allergic reaction. As from 24 August 2023 adequate training is required before industrial or professional use.
--------	--

### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Preparation with isocyanates

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP REMAFIX S H3**

Revision date: 21.02.2022

Product code: 00359-1085

Page 3 of 11

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
9016-87-9	Diphenylmethanediisocyanate, isomers and homologues			75 - < 100 %
			01-2119457024-46	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
101-68-8	Diphenylmethane-4,4'-diisocyanate			10 - < 20 %
	202-966-0	615-005-00-9	01-2119457014-47	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
5873-54-1	Diphenylmethane-2,4'-diisocyanate			5 - < 15 %
	227-534-9	615-005-00-9	01-2119480143-45	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
2536-05-2	Diphenylmethane-2,2'-diisocyanate			0,3 - < 1 %
	219-799-4	615-005-00-9	01-2119927323-43	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
9016-87-9		Diphenylmethanediisocyanate, isomers and homologues	75 - < 100 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = > 9400 mg/kg; oral: LD50 = > 10000 mg/kg mg/kg		
101-68-8	202-966-0	Diphenylmethane-4,4'-diisocyanate	10 - < 20 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 0,368 mg/l (dusts or mists); dermal: LD50 = > 9400 mg/kg; oral: LD50 = > 2000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100		
5873-54-1	227-534-9	Diphenylmethane-2,4'-diisocyanate	5 - < 15 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 0,387 mg/l (dusts or mists); dermal: LD50 = > 9400 mg/kg; oral: LD50 = > 2000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100		
2536-05-2	219-799-4	Diphenylmethane-2,2'-diisocyanate	0,3 - < 1 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 0,370 mg/l (dusts or mists); oral: LD50 = > 15000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100		

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

- Remove contaminated soaked clothing immediately.
- In the event of persistent symptoms receive medical treatment.
- Take away from danger area and lay down affected person.

**After inhalation**

- Move to fresh air in case of accidental inhalation of vapours.
- If patient is not breathing, apply artificial respiration.
- Refer for medical treatment.



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP REMAFIX S H3

Revision date: 21.02.2022

Product code: 00359-1085

Page 4 of 11

#### After contact with skin

Wash contaminated skin with plenty of water and soap or with liquid polyethylene glycol.  
Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical treatment by eye specialist.

#### After ingestion

Do not induce vomiting.  
Rinse out mouth thoroughly with water.  
Never give anything by mouth to an unconscious person.  
Summon a doctor immediately.  
Induce vomiting only upon the advice of a physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
Harmful if inhaled.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause respiratory irritation.  
May cause damage to organs through prolonged or repeated exposure.  
Suspected of causing cancer.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Keep under medical supervision for at least 48 hours.  
Treat symptoms.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Fire may produce:  
carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)  
Hydrogen cyanide (HCN)

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

#### Additional information

Cool containers at risk with water spray jet.  
Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Ensure adequate ventilation.  
Remove persons to safety.

#### For non-emergency personnel

Do not breathe vapours.



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP REMAFIX S H3

Revision date: 21.02.2022

Product code: 00359-1085

Page 5 of 11

Avoid contact with skin, eyes and clothing.

#### For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

#### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

##### For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Container should not be gas-tight closed.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

#### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Avoid contact with the skin and the eyes.

Do not breathe vapours.

Local exhaust.

Use only in thoroughly ventilated areas.

#### Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

#### Hints on joint storage

Exothermic reaction with:

Acids and bases.

Water, amines, alcohols

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

### 7.3. Specific end use(s)

Hardener

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters



# Safety Data Sheet

according to UK REACH Regulation

**TIP TOP REMAFIX S H3**

Revision date: 21.02.2022

Product code: 00359-1085

Page 6 of 11

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
-	Isocyanates, all (as -NCO) Except methyl isocyanate	-	0.02		TWA (8 h)	WEL
		-	0.07		STEL (15 min)	WEL

**8.2. Exposure controls****Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

**Protective and hygiene measures**

Do not inhale vapours.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Take off immediately all contaminated clothing.

**Eye/face protection**

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

**Hand protection**

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

**Skin protection**

Long sleeved clothing (DIN EN ISO 6530)

Single-use coverall

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Brown
Odour:	Musty

pH-Value: n.a.

**Changes in the physical state**

Melting point/freezing point: n.d.

Boiling point or initial boiling point and boiling range: > 300 °C DIN 53171

Sublimation point: n.a.

Pour point: approx. - 30 °C ISO 3016

Flash point: approx. 229 °C DIN EN ISO 2719

**Flammability**

Solid/liquid: n.a.

**Test method**

**Safety Data Sheet**

according to UK REACH Regulation

**TIP TOP REMAFIX S H3**

Revision date: 21.02.2022

Product code: 00359-1085

Page 7 of 11

Gas: n.a.

**Explosive properties**

The product is not explosive.

Lower explosion limits: n.d.

Upper explosion limits: n.d.

Auto-ignition temperature: &gt; 500 °C DIN 51794

**Self-ignition temperature**

Solid: n.a.

Gas: n.a.

Decomposition temperature: 090202031022 °C

**Oxidizing properties**

Not oxidising.

Vapour pressure: approx. 11 hPa EC A 4

(at 20 °C)

Vapour pressure: approx. 20 hPa EC A 4

(at 50 °C)

Density (at 25 °C): approx. 1,23 g/cm<sup>3</sup> DIN 51757

Bulk density: n.a.

Water solubility: Reacts with water.

(at 20 °C)

**Solubility in other solvents**

n.d.

Partition coefficient n-octanol/water: n.d.

Viscosity / dynamic: approx. 145 mPa·s DIN 53019

(at 20 °C)

Viscosity / kinematic: n.d.

Flow time: n.d.

Relative vapour density: n.d.

Evaporation rate: n.d.

Solvent separation test: 0 %

Solvent content: 0 %

**9.2. Other information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with strong acids and alkalies.

Reacts with: Water, amines, alcohols

**10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat. [Decomposition temperature ~ 200°C]

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.



# Safety Data Sheet

according to UK REACH Regulation

## TIP TOP REMAFIX S H3

Revision date: 21.02.2022

Product code: 00359-1085

Page 8 of 11

### 10.5. Incompatible materials

Acids and bases.  
Water, amines, alcohols

### 10.6. Hazardous decomposition products

No hazardous decomposition products known.  
Fire may produce:  
Hydrogen cyanide gas, Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### Acute toxicity

Harmful if inhaled.  
No toxicological data available.  
Diphenylmethanediisocyanate, isomers and homologues  
LD50/oral/rat: > 10000 mg/kg [OECD 401]  
LD50/dermal/rabbit: > 9400 mg/kg [OECD 402]

#### Irritation and corrosivity

Causes skin irritation.  
Causes serious eye irritation.

#### Sensitising effects

Contains isocyanates. May produce an allergic reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Diphenylmethanediisocyanate, isomers and homologues;  
Diphenylmethane-4,4'-diisocyanate; Diphenylmethane-2,4'-diisocyanate; Diphenylmethane-2,2'-diisocyanate)  
May cause an allergic skin reaction. (Diphenylmethanediisocyanate, isomers and homologues;  
Diphenylmethane-4,4'-diisocyanate; Diphenylmethane-2,4'-diisocyanate; Diphenylmethane-2,2'-diisocyanate)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Diphenylmethanediisocyanate, isomers and homologues;  
Diphenylmethane-4,4'-diisocyanate; Diphenylmethane-2,4'-diisocyanate; Diphenylmethane-2,2'-diisocyanate)  
Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause respiratory irritation. (Diphenylmethanediisocyanate, isomers and homologues;  
Diphenylmethane-4,4'-diisocyanate; Diphenylmethane-2,4'-diisocyanate; Diphenylmethane-2,2'-diisocyanate)

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Diphenylmethanediisocyanate, isomers and homologues; Diphenylmethane-4,4'-diisocyanate; Diphenylmethane-2,4'-diisocyanate)

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

No data available

#### Other information

With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocyanates; therefore keep room aerated and ventilated.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecological data are not available.  
Diphenylmethanediisocyanate, isomers and homologues





## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP REMAFIX S H3

Revision date: 21.02.2022

Product code: 00359-1085

Page 9 of 11

LC50/Danio rerio/96h > 1000 mg/l [OECD 203]  
EC50/Daphnia magna/48h > 1000 mg/l [OECD 202]  
EC50/Scenedesmus subspicatus/72h > 1640 mg/l [OECD 201]  
EC50/Activated sludge/3h > 100 mg/l [OECD 209]

#### **12.2. Persistence and degradability**

Biodegradable (OECD): 0% [28 d; OECD 302 C]  
Not readily biodegradable.

#### **12.3. Bioaccumulative potential**

No data available

#### **12.4. Mobility in soil**

No data available

#### **12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### **12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### **12.7. Other adverse effects**

Low hazard to waters.

#### **Further information**

In aqueous systems, formation of insoluble and chemically inert (inactive) polyureas.  
Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### **13.1. Waste treatment methods**

##### **Disposal recommendations**

Where possible recycling is preferred to disposal.  
Can be incinerated, when in compliance with local regulations.

##### **List of Wastes Code - residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

##### **Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.  
Contaminated packagings are to be treated like the product itself.  
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

<b><u>14.1. UN number:</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.2. UN proper shipping name:</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.3. Transport hazard class(es):</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.4. Packing group:</u></b>	No dangerous good in sense of this transport regulation.

#### **Inland waterways transport (ADN)**

<b><u>14.1. UN number:</u></b>	No dangerous good in sense of this transport regulation.
<b><u>14.2. UN proper shipping name:</u></b>	No dangerous good in sense of this transport regulation.



# Safety Data Sheet

according to UK REACH Regulation

**TIP TOP REMAFIX S H3**

Revision date: 21.02.2022

Product code: 00359-1085

Page 10 of 11

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Marine transport (IMDG)**

**14.1. UN number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

No dangerous good in sense of this transport regulation.

**14.7. Maritime transport in bulk according to IMO instruments**

No dangerous good in sense of this transport regulation.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 56, Entry 75

2004/42/EC (VOC): 0 %

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,4,6,7,9,10,11,12,13,15.



# Safety Data Sheet

according to UK REACH Regulation

**TIP TOP REMAFIX S H3**

Revision date: 21.02.2022

Product code: 00359-1085

Page 11 of 11

**Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses  
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure  
IMDG = International Maritime Code for Dangerous Goods  
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization  
MARPOL = International Convention for the Prevention of Pollution from Ships  
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals  
CAS = Chemical Abstract Service  
EN = European norm  
ISO = International Organization for Standardization  
DIN = Deutsche Industrie Norm  
PBT = Persistent Bioaccumulative and Toxic  
vPvB = Very Persistent and very Bio-accumulative  
LD = Lethal dose  
LC = Lethal concentration  
EC = Effect concentration  
IC = Median immobilisation concentration or median inhibitory concentration

**Relevant H and EUH statements (number and full text)**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH204	Contains isocyanates. May produce an allergic reaction.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

*'The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.'*