

according to UK REACH Regulation

# **TIP TOP REMAPUR 75 COMP B**

Revision date: 03.01.2024

Product code: 00156-0534

Page 1 of 11

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

TIP TOP REMAPUR 75 COMP B

#### Art.-No.

7691001

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Repair material

# 1.3. Details of the supplier of the safety data sheet

## Manufacturer

Wanulacturer	
Company name:	REMA TIP TOP AG
Street:	Gruber Strasse 65
Place:	D-85586 Poing
Telephone:	+49 (0) 8121 / 707 - 100
Responsible Department:	Responsible for the safety data sheet: sds@gbk-ingelheim.de
Supplier	
Company name:	REMA TIP TOP INDUSTRY UK LTD
Street:	Plumtree Industrial Estate, Harworth
Place:	Doncaster, DN11 8EW, South Yorkshire
Telephone:	+44 (0)1302 711233
Internet:	www.rema-tiptop.co.uk
<u>1.4. Emergency telephone</u>	INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
<u>number:</u>	In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

### GB CLP Regulation

Eye Irrit. 2; H319 STOT RE 2; H373 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

# GB CLP Regulation

Hazard components for labelling Diethylmethylbenzenediamine

Signal word:

**Pictograms:** 



#### Hazard statements

H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P260 Do not breathe vapour.



Page 2 of 11

# Safety Data Sheet

according to UK REACH Regulation

### **TIP TOP REMAPUR 75 COMP B**

Revision date: 03.01.2024	Product code: 00156-0534
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P314	Get medical advice/attention if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.

#### Special labelling of certain mixtures

Contains Dibutyltin dilaurate. May produce an allergic reaction.

#### 2.3. Other hazards

EUH208

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

### **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

### Chemical characterization

Mixture containing following substances with additives

#### Hazardous components

CAS No	Chemical name		Quantity	
	EC No	Index No	REACH No	
	GHS Classification			
68479-98-1	Diethylmethylbenzenediamine			< 15 %
	270-877-4	612-130-00-0	01-2119486805-25	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1; H312 H302 H319 H373 H400 H410		quatic Chronic 1; H312	
77-58-7	Dibutyltin dilaurate			< 0,25 %
	201-039-8	050-030-00-3	01-2119496068-27	
	Muta. 2, Repr. 1B, Eye Irrit. 2, Skin Sens. 1, STOT SE 1, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H341 H360FD H319 H317 H370 H372 H400 H410		quatic Acute 1, Aquatic	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE			
CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
68479-98-1	270-877-4	Diethylmethylbenzenediamine	< 15 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 598 mg/kg		
77-58-7	201-039-8	Dibutyltin dilaurate	< 0,25 %
Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1			

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

# General information

Remove contaminated soaked clothing immediately. Consult a physician.

Take away from danger area and lay down affected person.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.



according to UK REACH Regulation

**TIP TOP REMAPUR 75 COMP B** 

Revision date: 03.01.2024

Product code: 00156-0534

Page 3 of 11

In the event of symptoms refer for medical treatment.

#### After contact with skin

In case of contact with skin wash off immediately with plenty of water. Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Summon a doctor immediately.

# After ingestion

Do not induce vomiting. Rinse out mouth and give plenty of water to drink. Never give anything by mouth to an unconscious person. Summon a doctor immediately. Induce vomiting only upon the advice of a physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

### Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

#### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

#### 5.3. Advice for firefighters

Use breathing apparatus with independent air supply. Protective suit.

#### Additional information

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

# **SECTION 6:** Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

#### **General advice**

Ensure adequate ventilation. Remove persons to safety.

#### For non-emergency personnel

#### Do not breathe vapours.

Avoid contact with skin, eyes and clothing.

#### For emergency responders

In case of vapour formation use respirator. Use personal protective clothing.

#### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.



## according to UK REACH Regulation

## **TIP TOP REMAPUR 75 COMP B**

Revision date: 03.01.2024

Product code: 00156-0534

Page 4 of 11

# 6.3. Methods and material for containment and cleaning up

# For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

### For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

#### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed. Avoid contact with the skin and the eyes. Do not breathe vapours. Use only in thoroughly ventilated areas.

#### Advice on protection against fire and explosion

Keep away from heat and sources of ignition. No special protective measures against fire required.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place. Recommended storage temperature:  $15^{\circ}C - 25^{\circ}C$ 

# Hints on joint storage

Incompatible with:

Oxidizing agents, Acids and bases.

# Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

# 7.3. Specific end use(s)

Repair material

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Additional advice on limit values

To date, no national critical limit values exist.

### 8.2. Exposure controls

#### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

### Protective and hygiene measures

Do not inhale vapours. Avoid contact with eyes and skin. Wash hands before breaks and immediately after handling the product. When using do not eat, drink or smoke. Remove and wash contaminated clothes before re-use.

### Eye/face protection

Tightly fitting goggles (EN 166). Eye wash bottle with pure water (EN 15154).



# according to UK REACH Regulation

## **TIP TOP REMAPUR 75 COMP B**

Revision date: 03.01.2024

Product code: 00156-0534

Page 5 of 11

# Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

#### Skin protection

Long sleeved clothing (DIN EN ISO 6530)

# **Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

### **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Colour:	Liquid Yellowish-brown	
Odour:	Soft	
pH-Value:		n.d.
Changes in the physical state		
Melting point/freezing point:		n.d.
Boiling point or initial boiling point and boiling range:		> 200 °C
Sublimation point: Softening point:		n.a. n.d.
Flash point:		> 200 °C
Flammability Solid/liquid:		n.a.
Explosive properties The product is not explosive.		
Lower explosion limits:		n.d.
Upper explosion limits:		n.d.
Auto-ignition temperature:		n.d.
Self-ignition temperature		
Solid: Gas:		n.a. n.a.
Decomposition temperature:		n.d.
Oxidizing properties		n.d.
Not oxidising.		
Vapour pressure:		n.d.
Density (at 23 °C): Bulk density:		1,07 - 1,1 g/cm³ n.a.
Water solubility:		Immiscible
Solubility in other solvents n.d.		
Partition coefficient n-octanol/water:		n.d.
Viscosity / dynamic: (at 25 °C)		1000 - 2000 mPa·s



### according to UK REACH Regulation

TIP TOP REMAPUR 75 COMP B		
Revision date: 03.01.2024	Product code: 00156-0534	Page 6 of 11
Viscosity / kinematic:	n.d.	
Flow time: (at 25 °C)	n.d.	
Relative vapour density:	n.d.	
Evaporation rate:	n.d.	
Solvent separation test:	0 %	
Solvent content:	0 %	
9.2. Other information		

### 9.2. Other information

#### No data available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No decomposition if stored and applied as directed.

### 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

# 10.5. Incompatible materials

Oxidizing agents, Acids and bases.

# 10.6. Hazardous decomposition products

No known hazardous decomposition products. Fire may produce: Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

## **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation

## Acute toxicity

Based on available data, the classification criteria are not met. No toxicological data available. ATEmix/oral: > 2000 mg/kg ATEmix/dermal: > 2000 mg/kg

# ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

# Irritation and corrosivity

Causes serious eye irritation. Skin corrosion/irritation: Based on available data, the classification criteria are not met.

# Sensitising effects

Based on available data, the classification criteria are not met. Contains Dibutyltin dilaurate. May produce an allergic reaction.

# Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

# STOT-single exposure

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

# **TIP TOP REMAPUR 75 COMP B**

Revision date: 03.01.2024

Product code: 00156-0534

Page 7 of 11

# STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Diethylmethylbenzenediamine)

### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

### 11.2. Information on other hazards

## **Endocrine disrupting properties**

No data available

#### Other information

Inhalation of vapours in high concentration may cause irritation of respiratory system. Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

#### **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

# 12.2. Persistence and degradability

No data available

# 12.3. Bioaccumulative potential

No data available

#### 12.4. Mobility in soil

No data available

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

Hazardous water pollutant.

### Further information

Do not flush into surface water or sanitary sewer system.

#### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Where possible recycling is preferred to disposal. Can be incinerated, when in compliance with local regulations.

# List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken



according to UK REACH Regulation

# TIP TOP REMAPUR 75 COMP B

Revision date: 03.01.2024

Product code: 00156-0534

Page 8 of 11

for reuse.

# **SECTION 14: Transport information**

Land transport (ADR/RID)	
<u>14.1. UN number:</u>	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3. Transport hazard class(es):	(Diethylmethylbenzenediamine) 9
14.4. Packing group:	III
Hazard label:	9
	<b>~ 办</b>
	AID
	9
Classification code:	M6
Special Provisions:	274 335 375 601
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Transport category:	3
Hazard No:	90
Tunnel restriction code:	-
Inland waterways transport (ADN)	
<u>14.1. UN number:</u>	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diethylmethylbenzenediamine)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
	9
Classification code:	M6
Special Provisions:	274 335 375 601
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Marine transport (IMDG)	
<u>14.1. UN number:</u>	UN 3082
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diethylmethylbenzenediamine)
14.3. Transport hazard class(es):	9
14.4. Packing group:	III
Hazard label:	9
	9
Special Provisions:	274 335 969
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
EmS:	F-A, S-F

REMA	RI	EMA TIP TOP AG
	Safety Data Sheet	
ΤΟΡ	according to UK REACH Regulation	
	TIP TOP REMAPUR 75 COMP B	
Revision date: 03.01.2024	Product code: 00156-0534	Page 9 of 11
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number:</u>	UN 3082	
14.2. UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.C (Diethylmethylbenzenediamine)	).S.
14.3. Transport hazard class(es):	9	
14.4. Packing group:	III	
Hazard label:	° •	
Special Provisions:	A97 A158 A197 A215	
Limited quantity Passenger:	30 kg G	
Passenger LQ:	Y964 E1	
Excepted quantity: IATA-packing instructions - Passenger:	E1 964	
IATA-packing institucions - Passenger: IATA-max. quantity - Passenger:	450 L	
IATA-packing instructions - Cargo:	964	
IATA-max. quantity - Cargo:	450 L	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	Yes	

## 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

## 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

# SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information Restrictions on use (REACH, annex XVII):	
Entry 3, Entry 30, Entry 75 Directive 2004/42/EC on VOC in paints and varnishes:	0 %
Information according to Directive 2012/18/EU (SEVESO III):	E2 Hazardous to the Aquatic Environment
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water hazard class (D):	2 - obviously hazardous to water

## 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

# **SECTION 16: Other information**

-2-



according to UK REACH Regulation

**TIP TOP REMAPUR 75 COMP B** 

Revision date: 03.01.2024

Product code: 00156-0534

Page 10 of 11

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

- ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation
  - intérieure

IMDG = International Maritime Code for Dangerous Goods

- IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
- MARPOL = International Convention for the Prevention of Pollution from Ships
- IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

## Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	Calculation method

### Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H341	Suspected of causing genetic defects.
H360FD	May damage fertility. May damage the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains Dibutyltin dilaurate. May produce an allergic reaction.

## **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)



according to UK REACH Regulation

# **TIP TOP REMAPUR 75 COMP B**

Revision date: 03.01.2024

Product code: 00156-0534

Page 11 of 11

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)