

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP SOLUTION STL-NL4

Revision date: 27.04.2023

Product code: 00156-0445

Page 1 of 13

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

TIP TOP SOLUTION STL-NL4

##### Art.-No.

538 0755, 538 0762, 538 0773, 538 0787

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

adhesive

##### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Company name: REMA TIP TOP AG  
Street: Gruber Strasse 65  
Place: D-85586 Poing  
Telephone: +49 (0) 8121 / 707 - 100  
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

##### Supplier

Company name: REMA TIP TOP INDUSTRY UK LTD  
Street: Plumtree Industrial Estate, Harworth  
Place: Doncaster, DN11 8EW, South Yorkshire  
Telephone: +44 (0)1302 711233  
Internet: www.rema-tiptop.co.uk

##### 1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

Flam. Liq. 2; H225  
Skin Irrit. 2; H315  
STOT SE 3; H336  
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

##### GB CLP Regulation

##### Hazard components for labelling

Naphtha (petroleum)

Signal word: Danger

##### Pictograms:



##### Hazard statements

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP SOLUTION STL-NL4

Revision date: 27.04.2023

Product code: 00156-0445

Page 2 of 13

#### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P262	Do not get in eyes, on skin, or on clothing.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P273	Avoid release to the environment.

#### Special labelling of certain mixtures

EUH208	Contains Colophonium, 1,3-Dihydroxybenzene, Methenamine, N-phenyl-1-naphthylamine, N-(1,3-Dimethylbutyl)-N'-phenyl-p-phenylenediamine. May produce an allergic reaction.
--------	--

#### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Preparation solved in petroleum spirit

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP SOLUTION STL-NL4

Revision date: 27.04.2023

Product code: 00156-0445

Page 3 of 13

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-49-0	Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane]			< 60 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Naphtha (petroleum) [Hydrocarbons, C6, isoalkanes, < 3% n-hexane]			< 20 %
	931-254-9		01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
1314-13-2	Zinc oxide			< 2,5 %
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
8050-09-7	Colophonium			< 1 %
	232-475-7	650-015-00-7	01-2119480418-32	
	Skin Sens. 1; H317			
108-46-3	1,3-Dihydroxybenzene			< 1 %
	203-585-2	604-010-00-1	01-2119480136-40	
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, STOT SE 1, STOT SE 2, Aquatic Acute 1, Aquatic Chronic 3; H302 H315 H318 H317 H370 H371 H400 H412			
100-97-0	Methenamine			< 1 %
	202-905-8	612-101-00-2	01-2119474895-20	
	Flam. Sol. 2, Skin Sens. 1; H228 H317			
90-30-2	N-phenyl-1-naphthylamine			< 1 %
	201-983-0		01-2119488704-27	
	Acute Tox. 4, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H317 H400 H410			
793-24-8	N-(1,3-Dimethylbutyl)-N'-phenyl-p-phenylenediamine			< 0,3 %
	212-344-0		01-2119485839-15	
	Repr. 1B, Acute Tox. 4, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H360FD H302 H317 H400 H410			

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP SOLUTION STL-NL4

Revision date: 27.04.2023

Product code: 00156-0445

Page 4 of 13

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1314-13-2	215-222-5	Zinc oxide	< 2,5 %
		Aquatic Acute 1; H400: M=1 Aquatic Chronic 1; H410: M=1	
108-46-3	203-585-2	1,3-Dihydroxybenzene	< 1 %
		dermal: LD50 = 3360 mg/kg; oral: LD50 = 301 mg/kg	
100-97-0	202-905-8	Methenamine	< 1 %
		dermal: LD50 = 2001 mg/kg; oral: LD50 = 9200 mg/kg	
90-30-2	201-983-0	N-phenyl-1-naphthylamine	< 1 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = 1625 mg/kg	
793-24-8	212-344-0	N-(1,3-Dimethylbutyl)-N'-phenyl-p-phenylenediamine	< 0,3 %
		dermal: LD50 = > 7940 mg/kg; oral: LD50 = 893 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10	

#### Further Information

According to note P to the regulation (EC) no. 1272/2008, "Naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately.  
In the event of persistent symptoms receive medical treatment.  
Take away from danger area and lay down affected person.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours.  
Seek medical treatment immediately.

#### After contact with skin

Wash off with soap and plenty of water.  
Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Summon a doctor immediately.

#### After ingestion

Do not induce vomiting.  
Rinse out mouth and give plenty of water to drink.  
Never give anything by mouth to an unconscious person.  
Summon a doctor immediately.  
The decision whether to induce vomiting or not is to be taken by a physician.

### 4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness.  
Causes skin irritation.  
Attention. Beware, danger of aspiration.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP SOLUTION STL-NL4

Revision date: 27.04.2023

Product code: 00156-0445

Page 5 of 13

#### **Suitable extinguishing media**

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

#### **Unsuitable extinguishing media**

Full water jet

#### **5.2. Special hazards arising from the substance or mixture**

Fire may produce:

carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)

#### **5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.

Protective suit.

#### **Additional information**

Cool containers at risk with water spray jet.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Vapours are heavier than air and spread along ground.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **General advice**

Ensure adequate ventilation.

Remove persons to safety.

Keep away sources of ignition.

##### **For non-emergency personnel**

Do not breathe vapours.

Avoid contact with skin, eyes and clothing.

##### **For emergency responders**

In case of vapour formation use respirator.

Use personal protective clothing.

#### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

##### **For cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

#### **6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Keep container tightly closed.

Use only in thoroughly ventilated areas.

Vapours are heavier than air and spread along ground.

##### **Advice on protection against fire and explosion**

Keep away from heat and sources of ignition.

Do not smoke.

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP SOLUTION STL-NL4

Revision date: 27.04.2023

Product code: 00156-0445

Page 6 of 13

Take precautionary measures against static discharges.  
Use only explosion-proof equipment.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.  
Pay attention to anti-explosion protection rules.

##### Hints on joint storage

Incompatible with oxidizing agents.

##### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

#### 7.3. Specific end use(s)

adhesive

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL
108-46-3	Resorcinol	10	46		TWA (8 h)	WEL
		20	92		STEL (15 min)	WEL
8050-09-7	Rosin-based solder flux fume	-	0.05		TWA (8 h)	WEL
		-	0.15		STEL (15 min)	WEL

#### 8.2. Exposure controls

##### Appropriate engineering controls

Pay attention to anti-explosion protection rules.  
Ensure adequate ventilation, especially in confined areas.

##### Protective and hygiene measures

Wash hands before breaks and immediately after handling the product.  
When using do not eat, drink or smoke.  
Treat subsequently with skin cream.  
Remove and wash contaminated clothing before re-use.

##### Eye/face protection

Tightly fitting goggles (EN 166).

##### Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by [www.kcl.de](http://www.kcl.de).

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

##### Skin protection

Solvent-resistant apron (EN 467).

##### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP SOLUTION STL-NL4

Revision date: 27.04.2023

Product code: 00156-0445

Page 7 of 13

#### SECTION 9: Physical and chemical properties

##### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Black
Odour:	Hydrocarbon-like

##### Test method

pH-Value: n.d.

##### Changes in the physical state

Melting point/freezing point:	< - 50 °C
Boiling point or initial boiling point and boiling range:	60 - 95 °C *)
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	- 25 °C *)
Sustaining combustion:	Sustaining combustion

##### Flammability

Solid/liquid: n.a.

##### Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	0,6 vol. % *)
Upper explosion limits:	8,3 vol. % *)
Auto-ignition temperature:	n.d.

##### Self-ignition temperature

Solid: n.a.  
Gas: n.a.

Decomposition temperature: n.d.

##### Oxidizing properties

Not oxidising.

Vapour pressure: 100 - 200 hPa \*)  
(at 20 °C)Density: < 1 g/cm<sup>3</sup>

Bulk density: n.a.

Water solubility: Immiscible  
(at 20 °C)

##### Solubility in other solvents

n.d.

Partition coefficient n-octanol/water: n.d.

Viscosity / dynamic: &lt; 1200 mPa·s

Viscosity / kinematic: > 20,5 mm<sup>2</sup>/s  
(at 40 °C)

Flow time: n.d.

Relative vapour density: n.d.

Evaporation rate: n.d.

Solvent separation test: n.d.

Solvent content: &lt; 80 %

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP SOLUTION STL-NL4

Revision date: 27.04.2023

Product code: 00156-0445

Page 8 of 13

#### **9.2. Other information**

\*) Naphtha (petroleum)

### **SECTION 10: Stability and reactivity**

#### **10.1. Reactivity**

No decomposition if stored and applied as directed.

#### **10.2. Chemical stability**

Stable under normal conditions.

#### **10.3. Possibility of hazardous reactions**

Reactions with oxidizing agents.

#### **10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat.  
Heating can release vapours which can be ignited.  
Vapour/air-mixtures are explosive at intense warming.

#### **10.5. Incompatible materials**

oxidizing agents

#### **10.6. Hazardous decomposition products**

No hazardous decomposition products known.  
Fire may produce:  
Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>)

### **SECTION 11: Toxicological information**

#### **11.1. Information on hazard classes as defined in GB CLP Regulation**

##### **Acute toxicity**

Based on available data, the classification criteria are not met.  
No toxicological data available.  
Naphtha (petroleum)  
LD50/oral/rat: > 2000 mg/kg  
LD50/dermal/rabbit: > 2000 mg/kg  
LC50/inhalation: > 20 mg/l/4h

##### **Irritation and corrosivity**

Causes skin irritation.  
Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

##### **Sensitising effects**

Contains Colophonium, 1,3-Dihydroxybenzene, Methenamine, N-phenyl-1-naphthylamine, N-(1,3-Dimethylbutyl)-N'-phenyl-p-phenylenediamine. May produce an allergic reaction.

##### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

##### **STOT-single exposure**

May cause drowsiness or dizziness. (Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane])

##### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

##### **Aspiration hazard**

Based on available data, the classification criteria are not met.

##### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### **11.2. Information on other hazards**



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP SOLUTION STL-NL4

Revision date: 27.04.2023

Product code: 00156-0445

Page 9 of 13

#### Endocrine disrupting properties

No data available

#### Other information

Contact with eyes may cause irritation.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

A longer or repeated contact may lead to irritation of eyes and mucous membranes.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Lead has cumulative properties, wherefore lead compounds can be health-damaging in the event of long-term or frequent exposure. Following symptoms are resulting from chronic lead uptake: fatigue, headaches, constipation and colic.

May cause sensitization of susceptible persons by skin contact.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecological data are not available.

Naphtha (petroleum)

LC50/fish: 1 - 10 mg/l

EC50/Daphnia: 1 - 10 mg/l

EC50/Algae: 10 - 100 mg/l

NOEC/Fish: 1 - 10 mg/l

NOEC/Daphnia: 1 - 10 mg/l

Toxic to aquatic life with long lasting effects.

#### 12.2. Persistence and degradability

Naphtha (petroleum)

Readily biodegradable.

#### 12.3. Bioaccumulative potential

Naphtha (petroleum)

A bioaccumulation potential is to be expected.

#### 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meet the criteria.

#### 12.7. Other adverse effects

Low hazard to waters.

#### Further information

Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

##### List of Wastes Code - residues/unused products

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP SOLUTION STL-NL4

Revision date: 27.04.2023

Product code: 00156-0445

Page 10 of 13

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

#### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Classification code: F1  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E2  
Transport category: 2  
Hazard No: 33  
Tunnel restriction code: D/E

#### Inland waterways transport (ADN)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Classification code: F1  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E2

#### Marine transport (IMDG)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives (Naphtha (petroleum))  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP SOLUTION STL-NL4

Revision date: 27.04.2023

Product code: 00156-0445

Page 11 of 13

Marine pollutant: Yes  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E2  
EmS: F-E, S-D

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3



Limited quantity Passenger: 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

#### 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC): &lt; 80 %

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information: E2

##### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D): 1 - slightly hazardous to water

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP SOLUTION STL-NL4

Revision date: 27.04.2023

Product code: 00156-0445

Page 12 of 13

#### SECTION 16: Other information

##### Changes

This data sheet contains changes from the previous version in section(s): 1,3,4,9,12,15.

##### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
 RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses  
 ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure  
 IMDG = International Maritime Code for Dangerous Goods  
 IATA/ICAO = International Air Transport Association / International Civil Aviation Organization  
 MARPOL = International Convention for the Prevention of Pollution from Ships  
 IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 REACH = Registration, Evaluation, Authorization and Restriction of Chemicals  
 CAS = Chemical Abstract Service  
 EN = European norm  
 ISO = International Organization for Standardization  
 DIN = Deutsche Industrie Norm  
 PBT = Persistent Bioaccumulative and Toxic  
 vPvB = Very Persistent and very Bio-accumulative  
 LD = Lethal dose  
 LC = Lethal concentration  
 EC = Effect concentration  
 IC = Median immobilisation concentration or median inhibitory concentration

##### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 2; H411	Calculation method

##### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H228	Flammable solid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H360FD	May damage fertility. May damage the unborn child.
H370	Causes damage to organs (CNS, Blood) if swallowed.
H371	May cause damage to organs (the respiratory system) if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Colophonium, 1,3-Dihydroxybenzene, Methenamine, N-phenyl-1-naphthylamine, N-(1,3-Dimethylbutyl)-N'-phenyl-p-phenylenediamine. May produce an allergic reaction.



## Safety Data Sheet

according to UK REACH Regulation

### TIP TOP SOLUTION STL-NL4

Revision date: 27.04.2023

Product code: 00156-0445

Page 13 of 13

#### Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*