

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP SOLVENT CF-R4

Revision date: 01.02.2021

Product code: 00156-0009

Page 1 of 10

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

TIP TOP SOLVENT CF-R4

##### Art.-No.

525 3254, 595 9118, 595 9125, 595 9132, 595 9156

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Cleaning agent

#### 1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG

Street: Gruber Strasse 65

Place: D-85586 Poing

Telephone: +49 (0) 8121 / 707 - 100

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

#### 1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Aspiration hazard: Asp. Tox. 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

Ethyl acetate

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, &lt; 3% n-hexane

Signal word: Danger

##### Pictograms:



##### Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP SOLVENT CF-R4

Revision date: 01.02.2021

Product code: 00156-0009

Page 2 of 10

### Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing vapour.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P331 Do NOT induce vomiting.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P273 Avoid release to the environment.

### Special labelling of certain mixtures

- EUH066 Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.  
Vapours may form explosive mixture with air.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Preparation solved in petroleum spirit

#### Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
141-78-6	Ethyl acetate			< 75 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
92062-15-2	Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane [Solvent naphta (petroleum)]			< 35 %
	926-605-8		01-2119486291-36	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			

Full text of H and EUH statements: see section 16.

#### Further Information

According to note P to the regulation (EC) no. 1272/2008, "Solvent naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately.  
In the event of persistent symptoms receive medical treatment.  
Take away from danger area and lay down affected person.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP SOLVENT CF-R4

Revision date: 01.02.2021

Product code: 00156-0009

Page 3 of 10

If you feel unwell, seek medical advice.

#### **After contact with skin**

Wash off with soap and plenty of water.  
Consult a doctor if skin irritation persists.

#### **After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Consult a physician.

#### **After ingestion**

Do not induce vomiting.  
Never give anything by mouth to an unconscious person.  
Summon a doctor immediately.  
Induce vomiting only upon the advice of a physician.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Causes serious eye irritation.  
May be fatal if swallowed and enters airways.  
May cause drowsiness or dizziness.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

##### **Unsuitable extinguishing media**

Full water jet

#### **5.2. Special hazards arising from the substance or mixture**

Fire may produce:  
carbon monoxide and carbon dioxide

#### **5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.  
Protective suit.

#### **Additional information**

Vapours are heavier than air and spread along ground.  
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.  
Cool containers at risk with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.  
Use only explosion-proof equipment.  
Avoid contact with skin, eyes and clothing.  
Ensure adequate ventilation.  
Remove persons to safety.  
Keep away sources of ignition.

#### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

#### **6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).  
Shovel into suitable container for disposal.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP SOLVENT CF-R4

Revision date: 01.02.2021

Product code: 00156-0009

Page 4 of 10

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).  
Information for disposal see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed.  
Vapours are heavier than air and spread along ground.  
Use only in thoroughly ventilated areas.  
Avoid contact with skin, eyes and clothing.

#### Advice on protection against fire and explosion

Do not smoke - volatile.  
Keep away from heat and sources of ignition.  
Take precautionary measures against static discharges.  
Use only explosion-proof equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.  
Pay attention to anti-explosion rules.

#### Hints on joint storage

Incompatible with strong acids and oxidizing agents.

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Cleaning agent

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL

### 8.2. Exposure controls

#### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

#### Protective and hygiene measures

Do not inhale vapours.  
Wash hands before breaks and immediately after handling the product.  
When using do not eat, drink or smoke.  
Treat subsequently with skin cream.  
Remove and wash contaminated clothes before re-use.

#### Eye/face protection

Tightly fitting goggles (EN 166).  
Eye wash bottle with pure water (EN 15154).



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP SOLVENT CF-R4

Revision date: 01.02.2021

Product code: 00156-0009

Page 5 of 10

### Hand protection

Splash protection:

Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance (wear duration) approx. 120 minutes, i.e. protective glove &lt;Butoject 898&gt; made by www.kcl.de.

Protective gloves resistant to chemicals made off nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 30 minutes, i.e. protective glove &lt;Camatril Velours 730&gt; made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

### Skin protection

Solvent-resistant apron (EN 467).

### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Colourless
Odour:	Solvent-like

#### Test method

pH-Value: n.d.

### Changes in the physical state

Melting point: n.d.

Initial boiling point and boiling range: n.d.

Sublimation point: n.a.

Softening point: n.d.

Flash point: - 17 °C DIN EN ISO 13736

### Flammability

Solid: n.a.

Gas: n.a.

### Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: 2,1 vol. %

Upper explosion limits: 11,5 vol. %

Ignition temperature: 460 °C

### Auto-ignition temperature

Solid: n.a.

Gas: n.a.

Decomposition temperature: n.d.

### Oxidizing properties

Not oxidising.

Vapour pressure:  
(at 20 °C) 100 hPaDensity (at 20 °C): approx. 0,85 g/cm<sup>3</sup>

Bulk density: n.a.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP SOLVENT CF-R4

Revision date: 01.02.2021

Product code: 00156-0009

Page 6 of 10

Water solubility: (at 20 °C)	Immiscible
<b>Solubility in other solvents</b> n.d.	
Partition coefficient:	n.d.
Viscosity / dynamic:	n.d.
Viscosity / kinematic: (at 40 °C)	< 20,5 mm <sup>2</sup> /s
Flow time:	< 30 s 3 DIN/ISO 2431
Vapour density:	n.d.
Evaporation rate:	n.d.
Solvent separation test:	0 %
Solvent content:	100 %

### 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No decomposition if stored and applied as directed.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reactions with acids.  
Reactions with oxidizing agents.

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.  
Vapour/air mixtures are explosive at intensive warming.  
Heating can release vapours which can be ignited.

### 10.5. Incompatible materials

Acids and oxidizing agents.

### 10.6. Hazardous decomposition products

No hazardous decomposition products known.  
Fire may produce:  
Carbon monoxide and carbon dioxide

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### **Acute toxicity**

Based on available data, the classification criteria are not met.  
No toxicological data available.  
Ethyl acetate  
LD50/oral/rat: 5620 mg/kg  
LD50/dermal/rabbit: > 18000 mg/kg  
LC50/inhalation/rat: 56 mg/l/4 h

#### **Irritation and corrosivity**

Causes serious eye irritation.  
Skin corrosion/irritation: Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP SOLVENT CF-R4

Revision date: 01.02.2021

Product code: 00156-0009

Page 7 of 10

#### **Sensitising effects**

Based on available data, the classification criteria are not met.

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

May cause drowsiness or dizziness. (Ethyl acetate ; Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane [Solvent naphta (petroleum)])

#### **STOT-repeated exposure**

Repeated exposure may cause skin dryness or cracking.

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

#### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### **Practical experience**

#### **Other observations**

Inhalation of high vapour concentration may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

Ecological data are not available.

Toxic to aquatic life with long lasting effects.

Ethyl acetate

LC50/Pimephales promelas/96 h = 230 mg/l

EC50/Daphnia magna/48 h = 610 mg/l

EC50/Scenedesmus subspicatus /72 h = 5600 mg/l

NOEC/Daphnia magna/21 d = 2,4 mg/l

NOEC/Desmodesmus subspicatus/72 h > 100 mg/l

Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane

LC50/Oncorhynchus mykiss/96 h = 12 mg/l

EC50/Daphnia magna/48 h = 3 mg/l

EC50/Pseudokirchneriella subcapitata/72 h = 55 mg/l

### **12.2. Persistence and degradability**

No data available

### **12.3. Bioaccumulative potential**

No data available

### **12.4. Mobility in soil**

No data available

### **12.5. Results of PBT and vPvB assessment**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

### **12.6. Other adverse effects**

Hazardous water pollutant.

### **Further information**

Do not flush into surface water or sanitary sewer system.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP SOLVENT CF-R4

Revision date: 01.02.2021

Product code: 00156-0009

Page 8 of 10

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Where possible recycling is preferred to disposal.  
Can be incinerated, when in compliance with local regulations.

#### List of Wastes Code - residues/unused products

080117 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; wastes from paint or varnish removal containing organic solvents or other hazardous substances; hazardous waste

#### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.  
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.  
Packaging that cannot be cleaned should be disposed of like the product.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	Paint related material
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

### Inland waterways transport (ADN)

<b>14.1. UN number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	Paint related material
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E2

### Marine transport (IMDG)

<b>14.1. UN number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	Paint related material (Solvent naphtha (petroleum))



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP SOLVENT CF-R4

Revision date: 01.02.2021

Product code: 00156-0009

Page 9 of 10

**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3



Marine pollutant: Yes  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E2  
EmS: F-E, S-E

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1263**14.2. UN proper shipping name:** Paint related material**14.3. Transport hazard class(es):** 3**14.4. Packing group:** II

Hazard label: 3



Limited quantity Passenger: Y341 / 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

2004/42/EC (VOC): 100 %

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

(SEVESO III):

Additional information: E2

#### National regulatory information



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## TIP TOP SOLVENT CF-R4

Revision date: 01.02.2021

Product code: 00156-0009

Page 10 of 10

**Employment restrictions:**

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 2,7,9,10,12.

### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses  
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation inté-  
IMDG = International Maritime Code for Dangerous Goods  
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization  
MARPOL = International Convention for the Prevention of Pollution from Ships  
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals  
CAS = Chemical Abstract Service  
EN = European norm  
ISO = International Organization for Standardization  
DIN = Deutsche Industrie Norm  
PBT = Persistent Bioaccumulative and Toxic  
vPvB = Very Persistent and very Bio-accumulative  
LD = Lethal dose  
LC = Lethal concentration  
EC = Effect concentration  
IC = Median immobilisation concentration or median inhibitory concentration

### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.  
EUH066 Repeated exposure may cause skin dryness or cracking.

### Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

*'The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.'*