



Safety Data Sheet

according to UK REACH Regulation

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 26.08.2021

Product code: 00156-0008

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP SOLVENT LIQUID BUFFER

Art.-No.

505 9685, 505 9702, 505 9719, 505 9740, 507 9706, 511 1190, 514 4870, 599 2200, 356 1810

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: REMA TIP TOP AG
Street: Gruber Strasse 65
Place: D-85586 Poing
Telephone: +49 (0) 8121 / 707 - 100
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

Company name: REMA TIP TOP AUTOMOTIVE UK LTD
Street: Westland Square
Place: LEEDS, West Yorkshire, LS11 5XS
Telephone: +44 (0)113 2770044
e-mail: info@tip-top.co.uk
Internet: www.rema-tiptop.co.uk

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Naphtha (petroleum)

Signal word: Danger

Safety Data Sheet

according to UK REACH Regulation

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 26.08.2021

Product code: 00156-0008

Page 2 of 11

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H304	May be fatal if swallowed and enters airways.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P261	Avoid breathing vapour.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P273	Avoid release to the environment.
P391	Collect spillage.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation solved in petroleum spirit

Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	GHS Classification	
	Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 5% n-hexane]	> = 75 %
	921-024-6	01-2119475514-35
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	
64742-49-0	Naphtha (petroleum) [Hydrocarbons, C6, isoalkanes, < 5% n-hexane]	<= 25 %
	931-254-9	01-2119484651-34
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411	

Full text of H and EUH statements: see section 16.



Safety Data Sheet

according to UK REACH Regulation

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 26.08.2021

Product code: 00156-0008

Page 3 of 11

Further Information

According to note P to the regulation (EC) no. 1272/2008, "Naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.
Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
If you feel unwell, seek medical advice.

After contact with skin

Wash off with soap and plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways. Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Vapours are heavier than air and spread along ground.
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures



Safety Data Sheet

according to UK REACH Regulation

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 26.08.2021

Product code: 00156-0008

Page 4 of 11

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Ensure adequate ventilation.
Keep away noninvolved persons.

For non-emergency personnel

Do not breathe vapours.
Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.
Use personal protective clothing.
Use only explosion-proof equipment.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.
Vapours are heavier than air and spread along ground.
Use only in thoroughly ventilated areas.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Do not smoke - volatile.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.
Pay attention to anti-explosion rules.

Hints on joint storage

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Cleaning agent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to UK REACH Regulation

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 26.08.2021

Product code: 00156-0008

Page 5 of 11

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Colourless
Odour:	Hydrocarbon-like

	Test method
pH-Value:	n.a.

Changes in the physical state

Melting point/freezing point:	n.d.
Boiling point or initial boiling point and boiling range:	60 - 95 °C ASTM D1078
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	- 25 °C

Flammability

Solid/liquid:	n.a.
Gas:	n.a.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	1,0 vol. %
Upper explosion limits:	7,3 vol. %



Safety Data Sheet

according to UK REACH Regulation

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 26.08.2021

Product code: 00156-0008

Page 6 of 11

Auto-ignition temperature:	413 °C
Self-ignition temperature	
Solid:	n.a.
Gas:	n.a.
Decomposition temperature:	n.d.
Oxidizing properties	
Not oxidising.	
Vapour pressure: (at 20 °C)	150 hPa
Density (at 15 °C):	0,693 g/cm ³ DIN 51757
Bulk density:	n.a.
Water solubility: (at 20 °C)	0,02 g/L
Solubility in other solvents	
n.d.	
Partition coefficient n-octanol/water:	(n-octanol/water) Log Pow: 4 - 5,1
Viscosity / dynamic:	0,45 mPa·s
Viscosity / kinematic: (at 40 °C)	< 20,5 mm ² /s
Flow time:	n.d.
Relative vapour density:	n.d.
Evaporation rate:	7,6 ASTM D 3539
Solvent separation test:	0 %
Solvent content:	100 %

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.
Vapour/air mixtures are explosive at intensive warming.
Heating can release vapours which can be ignited.

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

No hazardous decomposition products known.
Fire may produce:
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

Safety Data Sheet

according to UK REACH Regulation

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 26.08.2021

Product code: 00156-0008

Page 7 of 11

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

LD50/oral/rat: > 2000 mg/kg

LD50/dermal/rabbit: > 2000 mg/kg

LC50/inhalation/rat: > 20 mg/l

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 5% n-hexane]; Naphtha (petroleum) [Hydrocarbons, C6, isoalkanes, < 5% n-hexane])

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Hazard of lung oedema.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Contact with eyes may cause irritation.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Naphtha (petroleum)

EC50/Daphnia: 1 - 10 mg/l

EC50/Algae: 10 - 100 mg/l

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

The product is readily biodegradable to OECD criteria.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

Safety Data Sheet

according to UK REACH Regulation

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 26.08.2021

Product code: 00156-0008

Page 8 of 11

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

Low hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (EXCEPT 07 AND 08);
waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent
mixtures; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1263
<u>14.2. UN proper shipping name:</u>	Paint related material
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

<u>14.1. UN number:</u>	UN 1263
<u>14.2. UN proper shipping name:</u>	Paint related material
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3



Classification code:	F1
----------------------	----

Safety Data Sheet

according to UK REACH Regulation

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 26.08.2021

Product code: 00156-0008

Page 9 of 11

Limited quantity: 5 L / 30 kg
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint related material (Naphtha (petroleum))
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Marine pollutant: Yes
Limited quantity: 5 L / 30 kg
Excepted quantity: E2
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint related material
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

2004/42/EC (VOC): 95 - 100 %

Safety Data Sheet

according to UK REACH Regulation

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 26.08.2021

Product code: 00156-0008

Page 10 of 11

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,6,7,9,10,11,12,14,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.



Safety Data Sheet

according to UK REACH Regulation

TIP TOP SOLVENT LIQUID BUFFER

Revision date: 26.08.2021

Product code: 00156-0008

Page 11 of 11

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)