



Safety Data Sheet

according to UK REACH Regulation

TIP TOP TOPCOAT LSE

Revision date: 22.02.2022

Product code: 00359-0001

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP TOPCOAT LSE

Art.-No.

590 3490, 590 3500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-stick coating

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: TIP TOP Oberflächenschutz Elbe GmbH
Street: Heuweg 4
Place: D-06886 Wittenberg
Telephone: +49(0)3491/635-50
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de
Telefax: +49(0)3491/635-552

Supplier

Company name: REMA TIP TOP INDUSTRY UK LTD
Street: Plumtree Industrial Estate, Harworth
Place: Doncaster, DN11 8EW, South Yorkshire
Telephone: +44 (0)1302 711233
Internet: www.rema-tiptop.co.uk

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225
Acute Tox. 4; H332
Skin Irrit. 2; H315
Eye Irrit. 2; H319
Resp. Sens. 1; H334
Skin Sens. 1; H317
Carc. 2; H351
STOT SE 3; H335
STOT SE 3; H336
STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation**Hazard components for labelling**

Aromatic polyisocyanate
Diphenylmethanediisocyanate, isomers and homologues
Diphenylmethane-4,4'-diisocyanate
Diphenylmethane-2,4'-diisocyanate
Diphenylmethane-2,2'-diisocyanate

Signal word: Danger

Safety Data Sheet

according to UK REACH Regulation

TIP TOP TOPCOAT LSE

Revision date: 22.02.2022

Product code: 00359-0001

Page 2 of 13

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.

Special labelling of certain mixtures

EUH204	Contains isocyanates. May produce an allergic reaction. As from 24 August 2023 adequate training is required before industrial or professional use.
--------	--

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation with isocyanates

**Safety Data Sheet**

according to UK REACH Regulation

TIP TOP TOPCOAT LSE

Revision date: 22.02.2022

Product code: 00359-0001

Page 3 of 13

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
67815-87-6	Aromatic polyisocyanate			< 40 %
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT RE 2; H332 H315 H319 H334 H317 H373			
141-78-6	Ethyl acetate			< 35 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
9016-87-9	Diphenylmethanediisocyanate, isomers and homologues			< 25 %
			01-2119457024-46	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
101-68-8	Diphenylmethane-4,4'-diisocyanate			< 5 %
	202-966-0	615-005-00-9	01-2119457014-47	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
5873-54-1	Diphenylmethane-2,4'-diisocyanate			< 5 %
	227-534-9	615-005-00-9	01-2119480143-45	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
2536-05-2	Diphenylmethane-2,2'-diisocyanate			< 1 %
	219-799-4	615-005-00-9	01-2119927323-43	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
67815-87-6		Aromatic polyisocyanate	< 40 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists)		
141-78-6	205-500-4	Ethyl acetate	< 35 %
	dermal: LD50 = > 18000 mg/kg; oral: LD50 = 5620 mg/kg		
9016-87-9		Diphenylmethanediisocyanate, isomers and homologues	< 25 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = > 9400 mg/kg; oral: LD50 = > 10000 mg/kg mg/kg		
101-68-8	202-966-0	Diphenylmethane-4,4'-diisocyanate	< 5 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 0,368 mg/l (dusts or mists); dermal: LD50 = > 9400 mg/kg; oral: LD50 = > 2000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100		
5873-54-1	227-534-9	Diphenylmethane-2,4'-diisocyanate	< 5 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 0,387 mg/l (dusts or mists); dermal: LD50 = > 9400 mg/kg; oral: LD50 = > 2000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100		
2536-05-2	219-799-4	Diphenylmethane-2,2'-diisocyanate	< 1 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 0,370 mg/l (dusts or mists); oral: LD50 = > 15000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100		



Safety Data Sheet

according to UK REACH Regulation

TIP TOP TOPCOAT LSE

Revision date: 22.02.2022

Product code: 00359-0001

Page 4 of 13

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.
Take away from danger area and lay down affected person.
Keep under medical supervision for at least 48 hours.

After inhalation

If patient is not breathing, apply artificial respiration.
Move to fresh air in case of accidental inhalation of vapours.
Refer for medical treatment.

After contact with skin

Remove immediately adhering matter.
Wash off immediately with soap and plenty of water.
Treat subsequently with skin cream.
Consult a physician.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Summon a doctor immediately.
Rinse out mouth thoroughly with water.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Harmful if inhaled.
Suspected of causing cancer.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.
May cause drowsiness or dizziness.
With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocyanates; therefore keep room aerated and ventilated.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)
Hydrogen cyanide (HCN)
Isocyanates (NCO).



Safety Data Sheet

according to UK REACH Regulation

TIP TOP TOPCOAT LSE

Revision date: 22.02.2022

Product code: 00359-0001

Page 5 of 13

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.

Remove persons to safety.

Keep away sources of ignition.

For non-emergency personnel

Do not breathe vapours.

Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Container should not be gas-tight closed.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Vapours are heavier than air and spread along ground.

Avoid contact with the skin and the eyes.

Do not breathe vapours.

Local exhaust.

Use only in well-ventilated areas.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Vapours can form an explosive mixture with air.

7.2. Conditions for safe storage, including any incompatibilities

**Safety Data Sheet**

according to UK REACH Regulation

TIP TOP TOPCOAT LSE

Revision date: 22.02.2022

Product code: 00359-0001

Page 6 of 13

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.
Pay attention to anti-explosion rules.

Hints on joint storage

Exothermic reaction with:
Water, amines, alcohols
Acids and bases.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.
Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

7.3. Specific end use(s)

Anti-stick coating

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL
-	Isocyanates, all (as -NCO) Except methyl isocyanate	-	0.02		TWA (8 h)	WEL
		-	0.07		STEL (15 min)	WEL

8.2. Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.
Avoid contact with eyes and skin.
Wash hands before breaks and immediately after handling the product.
When using do not eat, drink or smoke.
Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).
Eye wash bottle with pure water (EN 15154).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

Skin protection

Light protective clothing

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

**Safety Data Sheet**

according to UK REACH Regulation

TIP TOP TOPCOAT LSE

Revision date: 22.02.2022

Product code: 00359-0001

Page 7 of 13

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: Liquid
Colour: Greenish
Odour: Fruity

Test method

pH-Value: n.d.

Changes in the physical state

Melting point/freezing point: n.d.
Boiling point or initial boiling point and boiling range: approx. 77 °C
Sublimation point: n.a.
Softening point: n.d.
Flash point: - 4 °C

Flammability

Solid/liquid: n.a.
Gas: n.a.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: 2,1 vol. %
Upper explosion limits: n.d.
Auto-ignition temperature: > 460 °C

Self-ignition temperature

Solid: n.a.
Gas: n.a.

Decomposition temperature: n.d.

Oxidizing properties

Not oxidising.

Vapour pressure: n.d.

Density (at 20 °C): 1,08 g/cm³

Bulk density: n.a.

Water solubility: Reacts with water.
(at 20 °C)

Solubility in other solvents

Acetone, dichloromethane: Miscible

Partition coefficient n-octanol/water: n.d.

Viscosity / dynamic: n.d.

Viscosity / kinematic: n.d.

Flow time: < 30 s 4 DIN EN ISO 2431
(at 23 °C)

Relative vapour density: n.d.

Evaporation rate: n.d.

Solvent separation test: n.d.

Solvent content: < 70 %



Safety Data Sheet

according to UK REACH Regulation

TIP TOP TOPCOAT LSE

Revision date: 22.02.2022

Product code: 00359-0001

Page 8 of 13

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts with:
Water, amines, alcohols
Acids and bases.

10.4. Conditions to avoid

Vapours may form explosive mixture with air.
Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.
Container should not be gas-tight closed. Risk of bursting.

10.5. Incompatible materials

Water, amines, alcohols
Acids and bases.

10.6. Hazardous decomposition products

No hazardous decomposition products known.
Fire may produce:
Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)
Hydrogen cyanide gas, Isocyanates

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Harmful if inhaled.
No toxicological data available.

ATE_{mix} calculated

ATE (inhalation vapour) 16,53 mg/l; ATE (inhalation dust/mist) 2,255 mg/l

Irritation and corrosivity

Causes skin irritation.
Causes serious eye irritation.

Sensitising effects

Contains isocyanates. May produce an allergic reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Aromatic polyisocyanate; Diphenylmethanediisocyanate, isomers and homologues; Diphenylmethane-4,4'-diisocyanate; Diphenylmethane-2,4'-diisocyanate; Diphenylmethane-2,2'-diisocyanate) May cause an allergic skin reaction. (Aromatic polyisocyanate; Diphenylmethanediisocyanate, isomers and homologues; Diphenylmethane-4,4'-diisocyanate; Diphenylmethane-2,4'-diisocyanate; Diphenylmethane-2,2'-diisocyanate)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Diphenylmethanediisocyanate, isomers and homologues; Diphenylmethane-4,4'-diisocyanate; Diphenylmethane-2,4'-diisocyanate; Diphenylmethane-2,2'-diisocyanate)
Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.



Safety Data Sheet

according to UK REACH Regulation

TIP TOP TOPCOAT LSE

Revision date: 22.02.2022

Product code: 00359-0001

Page 9 of 13

STOT-single exposure

May cause respiratory irritation. (Diphenylmethanediisocyanate, isomers and homologues)
May cause drowsiness or dizziness. (Ethyl acetate)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Aromatic polyisocyanate; Diphenylmethanediisocyanate, isomers and homologues)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocyanates; therefore keep room aerated and ventilated.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Low hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

In aqueous systems, formation of insoluble and chemically inert (inactive) polyureas.

The transformation with water into CO₂ and polyureas is strongly stimulated by so-called liquid crushers (ammonia, soda or alcohols, combined with liquid soap).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Safety Data Sheet

according to UK REACH Regulation

TIP TOP TOPCOAT LSE

Revision date: 22.02.2022

Product code: 00359-0001

Page 10 of 13

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1263

14.2. UN proper shipping name: Paint

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Classification code: F1

Limited quantity: 5 L / 30 kg

Excepted quantity: E2

Transport category: 2

Hazard No: 33

Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1263

14.2. UN proper shipping name: Paint

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Classification code: F1

Limited quantity: 5 L / 30 kg

Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1263

14.2. UN proper shipping name: Paint

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Marine pollutant: No

Limited quantity: 5 L / 30 kg

Excepted quantity: E2

EmS: F-E, S-E

Safety Data Sheet

according to UK REACH Regulation

TIP TOP TOPCOAT LSE

Revision date: 22.02.2022

Product code: 00359-0001

Page 11 of 13

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	PAINT
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 56, Entry 75

2004/42/EC (VOC): < 35%

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,6,7,10,11,12,14.



Safety Data Sheet

according to UK REACH Regulation

TIP TOP TOPCOAT LSE

Revision date: 22.02.2022

Product code: 00359-0001

Page 12 of 13

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Resp. Sens. 1; H334	Calculation method
Skin Sens. 1; H317	Calculation method
Carc. 2; H351	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH204 Contains isocyanates. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of



Safety Data Sheet

according to UK REACH Regulation

TIP TOP TOPCOAT LSE

Revision date: 22.02.2022

Product code: 00359-0001

Page 13 of 13

accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)