

according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE PARA SOLUTION

Revision date: 29.09.2022

Product code: 00359-1332

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP ADHESIVE PARA SOLUTION

Art.-No.

538 1460, 538 1504

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesive

1.3. Details of the supplier of the safety data sheet

| Company name: | TIP TOP Oberflaechenschutz E | Elbe GmbH |
|--------------------------|---------------------------------|--|
| Street: | Heuweg 4 | |
| Place: | D-06886 Wittenberg | |
| Telephone: | +49(0)3491/635-50 | Telefax:+49(0)3491/635-552 |
| Responsible Department: | Responsible for the safety data | i sheet: sds@gbk-ingelheim.de |
| 1.4. Emergency telephone | INTERNATIONAL: +49 - (0) 61 | 32 - 84463, GBK GmbH (24h - 7d/w - 365d/a) |
| <u>number:</u> | Public Poisons Information Line | e: +353 (0) 1 809 2166 (8am-10pm 7 days a |
| | week) | |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Hazard categories: Flammable liquid: Flam. Liq. 2 Skin corrosion/irritation: Skin Irrit. 2 Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Naphtha (petroleum) Danger

Signal word:

Pictograms:

P210



Hazard statements

| H225 | Highly flammable liquid and vapour. |
|------|--|
| H315 | Causes skin irritation. |
| H336 | May cause drowsiness or dizziness. |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE PARA SOLUTION

| Revision date: 29.09.2022 | Product code: 00359-1332 | Page 2 of 11 |
|---------------------------|--|--------------|
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. | |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse ski water or shower. | in with |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. | |
| P312 | Call a POISON CENTER/doctor if you feel unwell. | |
| P273 | Avoid release to the environment. | |

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation solved in petroleum spirit

Hazardous components

| CAS No | Chemical name | | | Quantity |
|------------|---|----------------------------------|-----------------------------|----------|
| | EC No | Index No | REACH No | |
| | GHS Classification | | | |
| 64742-49-0 | Naphtha (petroleum) (Hydrocarl n-hexane) | oons, C6-C7, n-alkanes, iso-alka | nes, cyclic compounds, < 3% | < 70 % |
| | 921-024-6 | | 01-2119475514-35 | |
| | Flam. Liq. 2, Skin Irrit. 2, STOT H411 | SE 3, Asp. Tox. 1, Aquatic Chror | nic 2; H225 H315 H336 H304 | |
| 64742-49-0 | Naphtha (petroleum) (Hydrocarbons, C6, isoalkanes, < 3% n-hexane) | | | |
| | 931-254-9 | | 01-2119484651-34 | |
| | Flam. Liq. 2, Skin Irrit. 2, STOT H411 | SE 3, Asp. Tox. 1, Aquatic Chror | nic 2; H225 H315 H336 H304 | |
| 1314-13-2 | Zinc oxide | | | < 1 % |
| | 215-222-5 | 030-013-00-7 | 01-2119463881-32 | |
| | Aquatic Acute 1, Aquatic Chronic 1; H400 H410 | | | |

Full text of H and EUH statements: see section 16.

Further Information

According to note P to the directive 67/548/EEC, "Naphta (petroleum)" is not to be classified as "carcinogenic" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately. In the event of persistent symptoms receive medical treatment. Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE PARA SOLUTION

Revision date: 29.09.2022

Product code: 00359-1332

Page 3 of 11

Seek medical treatment immediately.

After contact with skin

Wash off with soap and plenty of water. Treat subsequently with skin cream. Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Summon a doctor immediately.

After ingestion

Do not induce vomiting. Rinse out mouth and give plenty of water to drink. Never give anything by mouth to an unconscious person. Summon a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause drowsiness or dizziness. Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water iet.

5.2. Special hazards arising from the substance or mixture

Fire may produce: Carbon monoxide, carbon dioxide and sulphur oxides.

5.3. Advice for firefighters

Use breathing apparatus with independent air supply. Protective suit

Additional information

The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Cool containers at risk with water spray jet. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation. Remove persons to safety. Keep away sources of ignition.

For non-emergency personnel

Do not breathe vapours. Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator. Use personal protective clothing.



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE PARA SOLUTION

Revision date: 29.09.2022

Product code: 00359-1332

Page 4 of 11

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Informations for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Vapours are heavier than air and spread along ground. Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition. Do not smoke. Take precautionary measures against static discharges.

Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place. Pay attention to anti-explosion rules.

Hints on joint storage

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

| CAS No | Substance | ppm | mg/m³ | fib/cm³ | Category | Origin |
|-----------|---|-----|--------|---------|---------------|--------|
| 9006-04-6 | Natural Rubber Latex (as inhalable allergenic proteins) | - | 0.0001 | | TWA (8 h) | |
| 1314-13-2 | Zinc oxide, fume (Respirable Fraction) | - | 2 | | TWA (8 h) | |
| | | - | 10 | | STEL (15 min) | |

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Pay attention to explosion protection rules.



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE PARA SOLUTION

Revision date: 29.09.2022

Product code: 00359-1332

Page 5 of 11

Protective and hygiene measures

Wash hands before breaks and immediately after handling the product. When using do not eat, drink or smoke. Treat subsequently with skin cream. Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Hand protection

Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state: | Liquid | |
|---|---|-----------------------|
| Colour: | Beige | |
| Odour: | Hydrocarbon-like | |
| | | Test method |
| pH-Value: | n.d. | |
| Changes in the physical state | | |
| Melting point/freezing point: | < - 20 °C | |
| Boiling point or initial boiling point and boiling range: | 60 - 95 °C | *) |
| Sublimation point: | n.a. | |
| Softening point: | n.d. | |
| Flash point: | - 25 °C | *) |
| Sustaining combustion: | Sustaining combustion | |
| Flammability | | |
| Solid/liquid: | n.a. | |
| Gas: | n.a. | |
| Explosive properties The product is considered non-exp | olosive; nethertheless explosive vapour/air mixtu | ure can be generated. |
| Lower explosion limits: | 1,0 vol. % | *) |
| Upper explosion limits: | 7,3 vol. % | *) |
| Auto-ignition temperature: | 413 °C | *) |
| Self-ignition temperature Solid: | n.a. | |
| Gas: | n.a. | |
| Decomposition temperature: | n.d. | |
| | | |



according to Regulation (EC) No 1907/2006

| TIP Revision date: 29.09.2022 | TOP ADHESIVE PARA SOLUTION Product code: 00359-1332 | Page 6 of 1 |
|---|--|-------------|
| Oxidizing properties Not oxidising. | | |
| Vapour pressure: (at 20 °C) | 150 hPa 3 | *) |
| Density (at 20 °C): Bulk density: | 0,72 g/cm³ n.a. | |
| Water solubility: (at 20 °C) | Immiscible | |
| Solubility in other solvents n.d. | | |
| Partition coefficient n-octanol/water: | n.d. | |
| Viscosity / dynamic: (at 40 °C) | > 20,5 mPa·s | |
| Viscosity / kinematic: | n.d. | |
| Flow time: | n.d. | |
| Relative vapour density: | n.d. | |
| Evaporation rate: | n.d. | |
| Solvent separation test: | n.d. | |
| Solvent content: | < 90 % | |
| 9.2. Other information | | |
| *) Naphtha (petroleum) | | |
| SECTION 10: Stability and reactivit | ty | |
| 10.1. Reactivity No decomposition if stored and ap | nlied as directed | |
| 10.2. Chemical stability | pied as directed. | |
| Stable under normal conditions. | | |
| 10.3. Possibility of hazardous reaction | IS | |
| Reactions with oxidising agents. | | |
| 10.4. Conditions to avoid | | |
| To avoid thermal decomposition, d Vapour/air mixtures are explosive Heating can release vapours which | at intensive warming. | |
| 10.5. Incompatible materials Oxidizing agents | 5 | |
| 10.6. Hazardous decomposition produ | icts | |
| No hazardous decomposition prod Fire may produce: | lucts known. | |
| Carbon monoxide, carbon dioxide | and sulphur oxides. | |
| SECTION 11: Toxicological inform | ation | |
| 11.1. Information on hazard classes as Acute toxicity | s defined in Regulation (EC) No 1272/2008 | |

Revision No: 1,2 - Replaces version: 1,1



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE PARA SOLUTION

Revision date: 29.09.2022

Product code: 00359-1332

Page 7 of 11

Based on available data, the classification criteria are not met. No toxical dates available.

Naphtha (petroleum)

LD50/oral/rat: > 2000 mg/kg (Estimated)

LD50/dermal/rabbit: > 2000 mg/kg (Estimated)

LC50/inhalativ/rat: > 20 mg/l (Estimated)

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Naphtha (petroleum) (Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane); Naphtha (petroleum) (Hydrocarbons, C6, isoalkanes, < 3% n-hexane))

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Contact with eyes may cause irritation.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological dates are not available. Naphtha (petroleum) EC50/Daphnia: 1 - 10 mg/l LC50/algae: 10 - 100 mg/l Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Naphtha (petroleum) Liable to easy biological disintegration.

12.3. Bioaccumulative potential

Naphtha (petroleum)

A bioaccumulation potential is to be expected.

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE PARA SOLUTION

Revision date: 29.09.2022

Product code: 00359-1332

Page 8 of 11

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazard to waters.

Further information

080409

Ecological injuries are not known or expected under normal use. Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations. Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

| 14.1. UN number:14.2. UN proper shipping name:14.3. Transport hazard class(es):14.4. Packing group:Hazard label: | UN 1133 ADHESIVES 3 II 3 |
|---|---|
| Classification code: Special Provisions: Limited quantity: Excepted quantity: Transport category: Hazard No: Tunnel restriction code: | F1 640D 5 L / 30 kg E2 2 33 D/E |
| Inland waterways transport (ADN) <u>14.1. UN number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> | UN 1133 Adhesives 3 II |

I



according to Regulation (EC) No 1907/2006

| TIP T Revision date: 29.09.2022 | | PARA SOLUTION : 00359-1332 | | Page 9 of 11 |
|---|---------------------|--------------------------------------|-----|--------------|
| Hazard label: | 3 | | | |
| | | | | |
| Classification code: | F1 | | | |
| Special Provisions: Limited quantity: | 640D 5 L / 30 kg | | | |
| Excepted quantity: | E2 | | | |
| Marine transport (IMDG) | | | | |
| 14.1. UN number: | UN 1133 | | | |
| 14.2. UN proper shipping name: | ADHESIVES | | | |
| <u>14.3. Transport hazard class(es):</u> 14.4. Packing group: | 3 | | | |
| Hazard label: | 3 | | | |
| | | | | |
| Marine pollutant: | Yes | | | |
| Special Provisions: Limited quantity: | - 5 L / 30 kg | | | |
| Excepted quantity: | E2 | | | |
| EmS: | F-E, S-D | | | |
| Air transport (ICAO-TI/IATA-DGR) | | | | |
| <u>14.1. UN number:</u> | UN 1133 | | | |
| 14.2. UN proper shipping name: | ADHESIVES 3 | | | |
| <u>14.3. Transport hazard class(es):</u> 14.4. Packing group: | 3 | | | |
| Hazard label: | 3 | | | |
| | | | | |
| Special Provisions: | A3 | | | |
| Limited quantity Passenger: | 1 L | | | |
| Passenger LQ: Excepted quantity: | Y341 E2 | | | |
| IATA-packing instructions - Passenger: | | 353 | | |
| IATA-max. quantity - Passenger: | | 5 L | | |
| IATA-packing instructions - Cargo: IATA-max. quantity - Cargo: | | 364 60 L | | |
| 14.5. Environmental hazards | | | | |
| ENVIRONMENTALLY HAZARDOUS: | Yes | | 3LL | |

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice. **14.7. Maritime transport in bulk according to IMO instruments**



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE PARA SOLUTION

Revision date: 29.09.2022

Product code: 00359-1332

Page 10 of 11

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

| Restrictions on use (REACH, annex X | VII): |
|---|---|
| Entry 3, Entry 40, Entry 75 | |
| 2004/42/EC (VOC): | < 90 % |
| Information according to 2012/18/EU (SEVESO III): | P5c FLAMMABLE LIQUIDS |
| Additional information: | E2 |
| National regulatory information | |
| Employment restrictions: | Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. |
| Water hazard class (D): | 2 - obviously hazardous to water |
| <u>15.2. Chemical safety assessment</u> | |

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,6,7,9,10,11,12,14,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure IMDG = International Maritime Code for Dangerous Goods IATA/ICAO = International Air Transport Association / International Civil Aviation Organization MARPOL = International Convention for the Prevention of Pollution from Ships IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk GHS = Globally Harmonized System of Classification and Labelling of Chemicals REACH = Registration, Evaluation, Authorization and Restriction of Chemicals CAS = Chemical Abstract Service EN = European norm ISO = International Organization for Standardization DIN = Deutsche Industrie Norm PBT = Persistent Bioaccumulative and Toxic vPvB = Very Persistent and very Bio-accumulative LD = Lethal dose LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE PARA SOLUTION

Revision date: 29.09.2022

Product code: 00359-1332

Page 11 of 11

| H315 | Causes skin irritation. |
|------|---|
| H336 | May cause drowsiness or dizziness. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| | Toxic to aquatic life with long lasting offects |

H411 Toxic to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

'The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)