

according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE SH-3E SOLUTION

Revision date: 11.01.2023

Product code: 00359-1236

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP ADHESIVE SH-3E SOLUTION

Art.-No.

538 1402, 538 1431, 538 1513

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use	of the	substance/mixture	

Adhesive

1.3. Details of the supplier of the safety data sheet

Company name:	TIP TOP Oberflaechenschutz El	be GmbH
Street:	Heuweg 4	
Place:	D-06886 Wittenberg	
Telephone:	+49(0)3491/635-50	Telefax: +49(0)3491/635-552
Responsible Department:	Responsible for the safety data s	sheet: sds@gbk-ingelheim.de
<u>1.4. Emergency telephone</u> number:		2 - 84463, GBK GmbH (24h - 7d/w - 365d/a) +353 (0) 1 809 2166 (8am-10pm 7 days a

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Hazard categories: Flammable liquid: Flam. Liq. 3 Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2 Hazard Statements: Flammable liquid and vapour. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

Warning

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Signal word:

Pictograms:

Hazard statements

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE SH-3E SOLUTION

Revision date: 11.01.2023

Product code: 00359-1236

Page 2 of 11

P304+P340	water or shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P273	Avoid release to the environment.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking. EUH208

Contains Di(benzothiazol-2-yl) disulphide. May produce an allergic reaction.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation in aliphatic hydrocarbons

Sum formula:

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification	·		
	Hydrocarbons, C9-C10, n	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3,	Asp. Tox. 1, Aquatic Chronic 3; H2	26 H336 H304 H412 EUH066	
1314-13-2	Zinc oxide	< 20 %		
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic	Chronic 1; H400 H410		
7704-34-9	Sulphur			< 5 %
	231-722-6	016-094-00-1	01-2119520616-43	
	Skin Irrit. 2; H315			
120-78-5	Di(benzothiazol-2-yl) disu	< 1 %		
	204-424-9	613-135-00-0	01-2119489366-24	
	Skin Sens. 1, Aquatic Acu	te 1, Aquatic Chronic 1; H317 H40	0 H410 EUH031	

Full text of H and EUH statements: see section 16.



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE SH-3E SOLUTION

Revision date: 11.01.2023

Product code: 00359-1236

Page 3 of 11

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Cond	. Limits, M-factors and ATE	
1314-13-2	215-222-5	Zinc oxide	< 20 %
		1; H400: M=1 nic 1; H410: M=1	
7704-34-9	231-722-6	Sulphur	< 5 %
	oral: LD50 =	> 5000 mg/kg	
120-78-5	204-424-9	Di(benzothiazol-2-yl) disulphide	< 1 %
		1; H400: M=1 nic 1; H410: M=1	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately. In the event of persistent symptoms receive medical treatment. Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours. Seek medical treatment immediately.

After contact with skin

Wash off with soap and plenty of water. Treat subsequently with skin cream. Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Summon a doctor immediately.

After ingestion

Do not induce vomiting. Summon a doctor immediately. Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking. Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide, carbon dioxide and sulphur oxides.

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE SH-3E SOLUTION

Revision date: 11.01.2023

Product code: 00359-1236

Page 4 of 11

Protective suit.

Additional information

The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Cool containers at risk with water spray jet. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use only explosion-proof equipment.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Vapours are heavier than air and spread along ground. Remove persons to safety.

For non-emergency personnel

Do not breathe vapours. Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator. Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Informations for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Vapours are heavier than air and spread along ground. Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition. Do not smoke. Take precautionary measures against static discharges. Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place. Pay attention to anti-explosion rules.

Hints on joint storage

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE SH-3E SOLUTION

Revision date: 11.01.2023

Product code: 00359-1236

Page 5 of 11

7.3. Specific end use(s)

Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
1317-65-3	Marble, respirable dust	-	4		TWA (8 h)	
9006-04-6	Natural Rubber Latex (as inhalable allergenic proteins)	-	0.0001		TWA (8 h)	
1314-13-2	Zinc oxide, fume (Respirable Fraction)	-	2		TWA (8 h)	
		-	10		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
1317-65-3	Calcium carbonate			
Worker DNEL,	long-term	inhalation	systemic	10 mg/m³
Consumer DNEL, long-term		inhalation	systemic	10 mg/m ³
Consumer DNEL, acute		dermal	systemic	6,1 mg/kg bw/day
Consumer DN	Consumer DNEL, long-term		systemic	6,1 mg/kg bw/day
DNEO				

PNEC values

CAS No	Substance		
Environmental compartment Value		Value	
1317-65-3	1317-65-3 Calcium carbonate		
Micro-organism	Micro-organisms in sewage treatment plants (STP) 100 mg/l		

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

- Treat subsequently with skin cream.
- Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Hand protection

Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE SH-3E SOLUTION

Revision date: 11.01.2023

Product code: 00359-1236

Page 6 of 11

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

Physical state:	Liquid	
Colour:	Pink	
Odour:	Hydrocarbon-like	
		Test method
pH-Value:	n.d.	
Changes in the physical state		
Melting point/freezing point:	n. d.	
Boiling point or initial boiling point an	d 130 - 190 °C	*)
boiling range:		
Sublimation point:	n.a.	
Softening point:	n.d.	
Flash point:	> 23 °C	*)
Sustaining combustion:	Sustaining combustion	
Flammability		
Solid/liquid:	n.a.	
Gas:	n.a.	
Explosive properties The product is considered non-ex	xplosive; nethertheless explosive vapour/air mixture can b	e generated.
Lower explosion limits:	0,6 vol. %	*)
Upper explosion limits:	7,0 vol. %	,
Auto-ignition temperature:	> 200 °C	*)
Self-ignition temperature		1
Solid:	n.a.	
Gas:	n.a.	
Decomposition temperature:	n.d.	
Oxidizing properties Not oxidising.		
Vapour pressure: (at 20 °C)	8 hPa	*)
Density (at 20 °C):	0,85 g/cm³	
Bulk density:	n.a.	
Water solubility:	Immiscible	
(at 20 °C)		
Solubility in other solvents n.d.		
Partition coefficient n-octanol/water:	n.d.	
Viscosity / dynamic:	n.d.	
Viscosity / kinematic: (at 40 °C)	> 20,5 mm²/s	



according to Regulation (EC) No 1907/2006

evision date: 11.01.2023	Product code: 00359-1236	Page 7 of 1
Flow time: (at 23 °C)	> 30 sec 3 DIN/ISO 24	31
Relative vapour density:	n.d.	
Evaporation rate:	n.d.	
Solvent separation test:	n.d.	
Solvent content:	< 70 %	

*) Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidising agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat. Heating can release vapours which can be ignited. Vapour/air-mixtures are explosive at intense warming.

10.5. Incompatible materials

Oxidizing agents

10.6. Hazardous decomposition products

No hazardous decomposition products known. Fire may produce: Carbon monoxide, carbon dioxide, sulphur oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

No toxical dates available.

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Di(benzothiazol-2-yl) disulphide. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE SH-3E SOLUTION

Revision date: 11.01.2023

Product code: 00359-1236

Page 8 of 11

Endocrine disrupting properties

No data available

Other information

Repeated exposure may cause skin dryness or cracking.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Contact with eyes may cause irritation.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological dates are not available. Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazard to waters.

Further information

080409

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations. Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information



according to Regulation (EC) No 1907/2006

Revision date: 11.01.2023	TIP TOP ADHESIVE SH-3E SOLUTION Product code: 00359-1236	Page 9 of 1
Land transport (ADR/RID)		
14.1. UN number:	UN1133	
14.2. UN proper shipping name:	Adhesives	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	III	
Hazard label:	3	
Classification code:	F1	
Limited quantity:	5 L / 30 kg	
Transport category: Hazard No:	3	
Tunnel restriction code:	30 D/E	
Inland waterways transport (ADN)		
<u>14.1. UN number:</u>	UN1133	
<u>14.2. UN proper shipping name:</u>	Adhesives	
14.3. Transport hazard class(es):	3	
14.4. Packing group:		
Hazard label:	3	
Classification code: Limited quantity:	F1 5 L / 30 kg	
Marine transport (IMDG)	3 L / 30 kg	
<u>14.1. UN number:</u>	UN1133	
14.1. UN proper shipping name:	Adhesives (Naphtha (petroleum))	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	а Ш	
Hazard label:	3	
Marine pollutant:	Yes	
Limited quantity:	5 L / 30 kg	
EmS:	F-E, S-D	
Air transport (ICAO-TI/IATA-DGR)		
<u>14.1. UN number:</u>	UN1133	
14.2. UN proper shipping name:	Adhesives	
14.3. Transport hazard class(es):	3	
14.4. Packing group:	III	
Hazard label:	3	



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE SH-3E SOLUTION						
Revision date: 11.01.2023	Product	code: 00359-1236		Page 10 of 11		
Special Provisions: Limited quantity Passenger:	A3 Y344 / 10 L					
IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:		355 60 L 366 220 L				
14.5. Environmental hazards						
ENVIRONMENTALLY HAZARDOUS:	Yes		¥_2			

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 40, Entry 75	
2004/42/EC (VOC):	< 70 %
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS
Additional information:	E2
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water hazard class (D):	2 - obviously hazardous to water
15.2. Chemical safety assessment	

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,6,7,8,9,10,11,12,13,14,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

- RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
- ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk



according to Regulation (EC) No 1907/2006

TIP TOP ADHESIVE SH-3E SOLUTION

Revision date: 11.01.2023

Product code: 00359-1236

Page 11 of 11

GHS = Globally Harmonized System of Classification and Labelling of Chemicals REACH = Registration, Evaluation, Authorization and Restriction of Chemicals CAS = Chemical Abstract Service EN = European norm ISO = International Organization for Standardization DIN = Deutsche Industrie Norm PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH031	Contact with acids liberates toxic gas.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Di(benzothiazol-2-yl) disulphide. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal

warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)