



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® 876 Solution

Revision date: 30.11.2023

Product code: 00359-1209

Page 2 of 11

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P273	Avoid release to the environment.
P405	Store locked up.

### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Epoxy resin formulation, contains solvents

#### Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
		REACH No
	Classification (Regulation (EC) No 1272/2008)	
25068-38-6	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	< 90 %
	500-033-5	603-074-00-8
		01-2119456619-26
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411	
110-88-3	1,3,5-trioxan, trioxymethylene	< 15 %
	203-812-5	605-002-00-0
		01-2119487944-20
	Flam. Sol. 1, Repr. 2, STOT SE 3; H228 H361d H335	
	Reaction mass of ethylbenzene and xylene	
	905-588-0	01-2119488216-32
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304	

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
25068-38-6	500-033-5	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	< 90 %
		dermal: LD50 = 11400 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100	
	905-588-0	Reaction mass of ethylbenzene and xylene	< 10 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg STOT RE 2; H373: >= 10 - 100	

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Asplit® 876 Solution**

Revision date: 30.11.2023

Product code: 00359-1209

Page 3 of 11

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.  
In the event of persistent symptoms receive medical treatment.

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours or decomposition products.  
In the event of symptoms refer for medical treatment.

**After contact with skin**

Wash off immediately with soap and plenty of water.  
Consult a doctor if skin irritation persists.

**After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical treatment by eye specialist.

**After ingestion**

Summon a doctor immediately.  
Never give anything by mouth to an unconscious person.  
Induce vomiting only upon the advice of a physician.

**4.2. Most important symptoms and effects, both acute and delayed**

Causes serious eye irritation.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Suspected of damaging the unborn child.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

**Unsuitable extinguishing media**

Full water jet.

**5.2. Special hazards arising from the substance or mixture**

Fire may produce:  
carbon monoxide and carbon dioxide

**5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.  
Protective suit.

**Additional information**

Cool containers at risk with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Ensure adequate ventilation.  
Keep away noninvolved persons.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® 876 Solution

Revision date: 30.11.2023

Product code: 00359-1209

Page 4 of 11

#### For non-emergency personnel

Do not breathe vapours.  
Avoid contact with skin, eyes and clothing.

#### For emergency responders

In case of vapour formation use respirator.  
Use personal protective clothing.

#### 6.2. Environmental precautions

Clean contaminated surface thoroughly.  
Do not discharge into the drains/surface waters/groundwater.

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

##### For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).  
Shovel into suitable container for disposal.

#### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).  
Informations for disposal look up chapter 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed.  
Use only in thoroughly ventilated areas.  
Avoid contact with skin, eyes and clothing.

#### Advice on protection against fire and explosion

Keep product and empty container away from heat and sources of ignition.  
Do not smoke.  
Take precautionary measures against static discharges.

#### Advice on general occupational hygiene

Do not inhale vapours.  
Wash hands before breaks and immediately after handling the product.  
When using do not eat, drink or smoke.  
Avoid contact with skin, eyes and clothing.  
Remove and wash contaminated clothes before re-use.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.  
Protect against direct sun radiation.

#### Hints on joint storage

Incompatible with:  
Oxidizing agents  
Amines  
Acids and bases.

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Mortar

## SECTION 8: Exposure controls/personal protection

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Asplit® 876 Solution**

Revision date: 30.11.2023

Product code: 00359-1209

Page 5 of 11

**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
100-41-4	Ethylbenzene	100	442		TWA (8 h)	
		200	884		STEL (15 min)	
1330-20-7	Xylene, mixed isomers	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

**Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
100-41-4	Ethyl benzene	Mandelic acid and phenylglyoxylic acid	0.7 g/g	Creatinine	End of shift at end of workweek

**8.2. Exposure controls****Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

**Hand protection**

Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril 735> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

**Skin protection**

Long sleeved clothing (DIN EN ISO 6530)

**Respiratory protection**

No personal respiratory protective equipment normally required.

In case of insufficient ventilation or long-term effect wear suitable respiratory equipment. Filter type A-P2 (EN 141)

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Colourless
Odour:	Characteristic

**Test method****Changes in the physical state**

Melting point/freezing point:	n. d.
Boiling point or initial boiling point and boiling range:	> 110 °C
Sublimation point:	n.a.
Softening point:	n. d.
Flash point:	approx. 33 °C ISO 2719

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Asplit® 876 Solution**

Revision date: 30.11.2023

Product code: 00359-1209

Page 6 of 11

**Flammability**

Solid/liquid: n.a.

**Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: 1,0 vol. % \*)

Upper explosion limits: 8,0 vol. % \*)

Auto-ignition temperature: &gt; 300 °C

**Self-ignition temperature**

Solid: n.a.

Gas: n.a.

Decomposition temperature: n. d.

pH-Value: 4,5 (200 g/l)

Viscosity / dynamic:  
(at 25 °C) 350 - 450 mPa·s DIN 53015

Viscosity / kinematic: n. d.

Flow time: n. d.

Water solubility:  
(at 20 °C) Miscible**Solubility in other solvents**

n. d.

Partition coefficient n-octanol/water: n. d.

Vapour pressure:  
(at 20 °C) 0,8 hPa \*)Density (at 20 °C): approx. 1,12 g/cm<sup>3</sup> ISO 2811

Bulk density: n.a.

Relative vapour density: n. d.

**9.2. Other information****Information with regard to physical hazard classes**

Oxidizing properties

Not oxidising.

**Other safety characteristics**

Solvent separation test: n. d.

Solvent content: &lt; 10%

Evaporation rate: n. d.

**Further Information**

\*) Reaction mass of ethylbenzene and xylene

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with acids, alkalies and oxidising agents.

Reactions with amines.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Asplit® 876 Solution**

Revision date: 30.11.2023

Product code: 00359-1209

Page 7 of 11

**10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat.  
Protect against direct sun radiation.

**10.5. Incompatible materials**

Strong oxidizing agents  
Acids and bases  
Amines

**10.6. Hazardous decomposition products**

No known hazardous decomposition products.  
Fire may produce:  
Carbon monoxide and carbon dioxide

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.  
No toxicological data available.  
Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)  
LD50/oral/rat: 11400 mg/kg  
LD50/dermal/rabbit:  $>$  2000 mg/kg

**ATEmix calculated**

ATE (oral)  $>$  2000 mg/kg; ATE (dermal)  $>$  2000 mg/kg; ATE (inhalation vapour)  $>$  20 mg/l; ATE (inhalation dust/mist)  $>$  5 mg/l

**Irritation and corrosivity**

Causes skin irritation.  
Causes serious eye irritation.

**Sensitising effects**

May cause an allergic skin reaction. (Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700))

**Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of damaging the unborn child. (1,3,5-trioxan, trioxymethylene)  
Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

**11.2. Information on other hazards****Endocrine disrupting properties**

No data available

**SECTION 12: Ecological information****12.1. Toxicity**

Ecological data are not available.  
Toxic to aquatic life with long lasting effects.  
Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® 876 Solution

Revision date: 30.11.2023

Product code: 00359-1209

Page 8 of 11

LC50/Oncorhynchus mykiss/96 h = 2 mg/l  
EC50/Daphnia magna/48 h = 1,8 mg/l  
ErC50/Scenedesmus capricornutum/72 h = 11 mg/l

#### **12.2. Persistence and degradability**

Not readily biodegradable.

#### **12.3. Bioaccumulative potential**

No data available

#### **12.4. Mobility in soil**

No data available

#### **12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### **12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### **12.7. Other adverse effects**

Hazard to waters.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### **13.1. Waste treatment methods**

##### **Disposal recommendations**

Can be incinerated, when in compliance with local regulations.  
Where possible recycling is preferred to disposal.

##### **List of Wastes Code - residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

##### **Contaminated packaging**

Contaminated packagings are to be treated like the product itself.  
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.  
Packaging that cannot be cleaned should be disposed of like the product.

### SECTION 14: Transport information

#### **Land transport (ADR/RID)**

<b><u>14.1. UN number or ID number:</u></b>	UN 1866
<b><u>14.2. UN proper shipping name:</u></b>	Resin solution
<b><u>14.3. Transport hazard class(es):</u></b>	3
<b><u>14.4. Packing group:</u></b>	III
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® 876 Solution

Revision date: 30.11.2023

Product code: 00359-1209

Page 9 of 11

Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

#### Inland waterways transport (ADN)

<b>14.1. UN number or ID number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1

#### Marine transport (IMDG)

<b>14.1. UN number or ID number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution (Epoxy resin)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Marine pollutant:	Yes
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
EmS:	F-E, S-E

#### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number or ID number:</b>	UN 1866
<b>14.2. UN proper shipping name:</b>	Resin solution
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Limited quantity Passenger:	10 L	
Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:		355
IATA-max. quantity - Passenger:		60 L
IATA-packing instructions - Cargo:		366
IATA-max. quantity - Cargo:		220 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	Yes
----------------------------	-----





## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Asplit® 876 Solution

Revision date: 30.11.2023

Product code: 00359-1209

Page 10 of 11

#### **14.6. Special precautions for user**

Handle in accordance with good industrial hygiene and safety practice.

#### **14.7. Maritime transport in bulk according to IMO instruments**

The transport takes place only in approved and appropriate packaging.

### SECTION 15: Regulatory information

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in  
paints and varnishes: < 10 %Information according to Directive  
2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information: E2

##### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

##### **Additional information**

Consider Chemical prohibition regulation.

#### **15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

### SECTION 16: Other information

#### **Changes**

This data sheet contains changes from the previous version in section(s): 2,6,7,10,11,12,14,15.

#### **Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation  
intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals  
in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Asplit® 876 Solution**

Revision date: 30.11.2023

Product code: 00359-1209

Page 11 of 11

LD = Lethal dose  
LC = Lethal concentration  
EC = Effect concentration  
IC = Median immobilisation concentration or median inhibitory concentration

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Repr. 2; H361d	Calculation method
Aquatic Chronic 2; H411	Calculation method

**Relevant H and EUH statements (number and full text)**

H226 Flammable liquid and vapour.  
H228 Flammable solid.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*