



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## **Asplit® Acid Solution**

Revision date: 15.01.2024 Product code: 00359-1330 Page 1 of 11

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Asplit® Acid Solution

Art.-No.

592 1040

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Post-treatment agent

## 1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg
Telephone: +49(0)3491/635-50

Telephone: +49(0)3491/635-50 Telefax:

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

<u>1.4. Emergency telephone</u> INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a) <u>number:</u> Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a

week)

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

# Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Flam. Liq. 2; H225 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

### Regulation (EC) No 1272/2008

# Hazard components for labelling

Propan-2-ol Sulphuric acid

Signal word: Danger

Pictograms:







### **Hazard statements**

H225 Highly flammable liquid and vapour.

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.
H336 May cause drowsiness or dizziness.

## **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Asplit® Acid Solution** 

Revision date: 15.01.2024 Product code: 00359-1330 Page 2 of 11

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P406 Store in a corrosion-resistant container with a resistant inner liner.

#### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### **Chemical characterization**

Mixture containing following substances with additives:

### **Hazardous components**

CAS No	Chemical name			
	EC No	Index No	REACH No	
	GHS Classification			
67-63-0	Propan-2-ol			
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
7664-93-9	Sulphuric acid			
	231-639-5	016-020-00-8	01-2119458838-20	
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318			

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. L	Limits, M-factors and ATE	
7664-93-9	231-639-5	Sulphuric acid	< 25 %
	Skin Corr. 1A; F	H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15	

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours.

In the event of symptoms refer for medical treatment.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## **Asplit® Acid Solution**

Revision date: 15.01.2024 Product code: 00359-1330 Page 3 of 11

### After contact with skin

Wash off immediately with soap and plenty of water.

Seek medical treatment immediately.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Consult (eye) doctor immediately.

### After ingestion

Do not induce vomiting.

Summon a doctor immediately.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Induce vomiting only upon the advice of a physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eye damage.

May cause drowsiness or dizziness.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

### Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide, carbon dioxide and sulphur oxides.

## 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

## Additional information

Cool containers at risk with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Ensure adequate ventilation.

Keep away noninvolved persons.

#### For non-emergency personnel

Avoid contact with skin, eyes and clothing.

Do not breathe vapours.

### For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

### 6.3. Methods and material for containment and cleaning up



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## **Asplit® Acid Solution**

Revision date: 15.01.2024 Product code: 00359-1330 Page 4 of 11

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

### For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Do not use metal containers.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Informations for disposal look up chapter 13.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

## Advice on safe handling

Keep container tightly closed.

Provide appropriate ventilation and exhaust ventilation at the workplaces.

Avoid contact with skin, eyes and clothing.

# Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

# 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep only in original container.

Do not use metal containers.

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

# Hints on joint storage

Incompatible with bases.

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

## 7.3. Specific end use(s)

Post-treatment agent

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-63-0	Isopropyl alcohol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	
7664-93-9	Sulphuric acid	-	0.05		TWA (8 h)	



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## **Asplit® Acid Solution**

Revision date: 15.01.2024 Product code: 00359-1330 Page 5 of 11

#### **Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	_	End of shift at end of workweek

#### 8.2. Exposure controls

#### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

### Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

### Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

# Hand protection

Protective gloves resistant to chemicals made off viton, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) approx. 60 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

### Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Solvent-resistant apron (EN 467).

### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

# **Environmental exposure controls**

Do not flush into surface water or sanitary sewer system.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Colourless
Odour: Alcoholic

Print date: 15.01.2024

pH-Value: 0,3

Changes in the physical state

Melting point/freezing point: n. d. Boiling point or initial boiling point and 82  $^{\circ}$ C \*)

boiling range:

Sublimation point: n.a. Softening point: n. d. Flash point: 12  $^{\circ}$ C \*)

Sustaining combustion: Sustaining combustion

**Flammability** 



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## **Asplit® Acid Solution**

Revision date: 15.01.2024 Product code: 00359-1330 Page 6 of 11

Solid/liquid: n.a.

## **Explosive properties**

The product is considered non-explosive; nethertheless explosive vapour/air mixture can be generated.

Lower explosion limits: 2,3 vol. % \*) Upper explosion limits: 12,7 vol. % \*) Auto-ignition temperature: 425  $^{\circ}$ C \*)

Self-ignition temperature

Solid: n.a. Gas: n.a. Decomposition temperature: n. d.

### **Oxidizing properties**

Not oxidising.

Vapour pressure: 43 hPa \*)

(at 20 °C)

Density: 0,997 g/cm³
Bulk density: n.a.
Water solubility: Miscible (at 20 °C)

# Solubility in other solvents

n. d.

Partition coefficient n-octanol/water: n. d. Viscosity / dynamic: n. d. Viscosity / kinematic: n. d. Flow time: n. d. Relative vapour density: n. d. Evaporation rate: n. d. Solvent separation test: n. d. < 65 % Solvent content:

9.2. Other information

Solid content: 0 %

\*) Propan-2-ol

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No decomposition if stored and applied as directed.

## 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reactions with alkalies.

### 10.4. Conditions to avoid

Heating can release vapours which can be ignited.

Vapours may form explosive mixture with air.

Gives off hydrogen by reaction with metals.

### 10.5. Incompatible materials

Bases.



## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# **Asplit® Acid Solution**

Revision date: 15.01.2024 Product code: 00359-1330 Page 7 of 11

## 10.6. Hazardous decomposition products

Hydrogen, by reaction with metals.

Fire may produce:

Carbon monoxide, carbon dioxide, sulphur oxides.

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxical dates available.

#### **ATEmix** calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

#### Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

#### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause drowsiness or dizziness. (Propan-2-ol)

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

# 11.2. Information on other hazards

### **Endocrine disrupting properties**

No data available

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Ecological dates are not available.

### 12.2. Persistence and degradability

No data available

### 12.3. Bioaccumulative potential

No data available

#### 12.4. Mobility in soil

No data available

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

Slightly water hazardous.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## **Asplit® Acid Solution**

Revision date: 15.01.2024 Product code: 00359-1330 Page 8 of 11

#### **Further information**

Do not flush into surface water or sanitary sewer system.

### **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

### **Disposal recommendations**

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

#### List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

#### Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse

Packaging that cannot be cleaned should be disposed of like the product.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

**14.1. UN number:** UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propan-2-ol, Sulphuric acid)

14.3. Transport hazard class(es): 3
14.4. Packing group: ||

Hazard label: 3+8



Classification code: FC

Limited quantity: 1 L / 30 kg

Excepted quantity: E2
Transport category: 2
Hazard No: 338
Tunnel restriction code: D/E

### Inland waterways transport (ADN)

**14.1. UN number:** UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propan-2-ol, Sulphuric acid)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+8



Classification code: FC
Limited quantity: 1 L / 30 kg
Excepted quantity: E2

# Marine transport (IMDG)



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## **Asplit® Acid Solution**

Revision date: 15.01.2024 Product code: 00359-1330 Page 9 of 11

**14.1. UN number:** UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propan-2-ol, Sulphuric acid)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+8



Marine pollutant:

Limited quantity:

Excepted quantity:

E2

EmS:

F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 2924

14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Propan-2-ol, Sulphuric acid,

mixture)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3+8



Limited quantity Passenger: 0.5 L
Passenger LQ: Y340
Excepted quantity: E2

IATA-packing instructions - Passenger:352IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:363IATA-max. quantity - Cargo:5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in < 65 %

paints and varnishes:

Information according to Directive P5c FLAMMABLE LIQUIDS

2012/18/EU (SEVESO III):

Additional information

This product is regulated by Annex II of Regulation (EU) 2019/1148 on the marketing and use of explosives



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# **Asplit® Acid Solution**

Revision date: 15.01.2024 Product code: 00359-1330 Page 10 of 11

precursors. All suspicious transactions and significant disappearances and thefts have to be reported to the responsible national contact point. Sales personnel at all trading levels has to be instructed.

### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 2,12.

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 3; H336	Calculation method

### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# **Asplit® Acid Solution**

Revision date: 15.01.2024 Product code: 00359-1330 Page 11 of 11

H336

May cause drowsiness or dizziness.

### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)