

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® OC Hardener

Revision date: 30.11.2023

Product code: 00359-1240

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Asplit® OC Hardener

Art.-No.

592 0670

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Hardener

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax:

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a week)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Org. Perox. D; H242

Eye Irrit. 2; H319

Skin Sens. 1; H317

Repr. 1B; H360D

Aquatic Acute 1; H400

Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Dicyclohexyl phthalate

dibenzoyl peroxide

Signal word:

Danger

Pictograms:



Hazard statements

H242

Heating may cause a fire.

H319

Causes serious eye irritation.

H317

May cause an allergic skin reaction.

H360D

May damage the unborn child.

H410

Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® OC Hardener

Revision date: 30.11.2023

Product code: 00359-1240

Page 2 of 11

P220	Keep away from clothing and other combustible materials.
P234	Keep only in original packaging.
P264	Wash thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410	Protect from sunlight.
P411+P235	Store at temperatures not exceeding 30 °C/86 °F. Keep cool.
P420	Store separately.
P501	Dispose of contents/container to in accordance with local and national regulations.

2.3. Other hazards

Endocrine disrupting properties: Dicyclohexyl phthalate.

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Dust may form explosive mixtures with air.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Hardener based on dibenzoyl peroxide

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
94-36-0	dibenzoyl peroxide			40 - 50 %
	202-327-6	617-008-00-0	01-2119511472-50	
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H241 H319 H317 H400 H410			
84-61-7	Dicyclohexyl phthalate			40 - 50 %
	201-545-9	607-719-00-4	01-2119978223-34	
	Repr. 1B, Skin Sens. 1, Aquatic Chronic 2; H360D H317 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
94-36-0	202-327-6	dibenzoyl peroxide	40 - 50 %
	Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10		

Further Information

SVHC substance [Regulation (EC) No 1907/2006, Article 57]

Dicyclohexyl phthalate

SECTION 4: First aid measures**4.1. Description of first aid measures**



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® OC Hardener

Revision date: 30.11.2023

Product code: 00359-1240

Page 3 of 11

General information

Remove contaminated soaked clothing immediately.
Adhere to personal protective measures when giving first aid.
Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours.

After inhalation

Supply fresh air, if required oxygen, consult a physician.
If patient is not breathing, apply artificial respiration.
Remove the casualty into fresh air and keep him immobile.
In case of the person being unconscious put him/her in a stable side position.

After contact with skin

Wash off immediately with soap and plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Summon a doctor immediately.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of damaging fertility.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide and carbon dioxide
Hydrocarbons

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.
Keep away sources of ignition.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® OC Hardener

Revision date: 30.11.2023

Product code: 00359-1240

Page 4 of 11

Keep away noninvolved persons.

For non-emergency personnel

Do not breathe vapours.

Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Shovel into suitable container for disposal.

Soak up with inert absorbent material (e.g. vermiculite, clean sand).

In compliance with regulations by local authorities this can be subjected to a special treatment (e.g. thermal utilization) after dilution with an inert solid to 10% content of peroxides.

Do not keep container sealed.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Informations for disposal look up chapter 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

Avoid the formation of dust. Do not breathe dust.

Wash hands before breaks and at the end of workday.

Keep away from acids, bases, heavy metal salts and reducing agents.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Keep away from open flames, hot surfaces and sources of ignition.

Use explosion-proof equipment / fittings and non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep only in original container.

Keep container tightly closed in a dry, cool and well-ventilated place.

Protect against direct sun radiation.

Recommended storage temperature: +5°C - +30°C

Hints on joint storage

Incompatible with:

Reducing agents, Heavy metal salts, Acids and bases.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Hardener

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® OC Hardener

Revision date: 30.11.2023

Product code: 00359-1240

Page 5 of 11

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	
84-61-7	Dicyclohexyl phthalate	-	5		TWA (8 h)	

8.2. Exposure controls**Appropriate engineering controls**

Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

Protective and hygiene measures

Do not inhale dust.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Remove and wash contaminated clothing before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Apron (EN 467).

Respiratory protection

Breathing apparatus (particle filter) only if dust is formed. (Particle filter P2)

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Powder
Colour:	Whitish
Odour:	Characteristic

Test method

pH-Value: n.a.

Changes in the physical state

Melting point/freezing point: n.a.

Boiling point or initial boiling point and boiling range: n.a.

Sublimation point: n.a.

Softening point: n.a.

Flash point: n.a.

Flammability

Solid/liquid: May cause fire.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® OC Hardener

Revision date: 30.11.2023

Product code: 00359-1240

Page 6 of 11

Explosive properties

The product is considered non-explosive; nevertheless explosive dust/air mixture can be generated

Lower explosion limits: n. d.

Upper explosion limits: n. d.

Auto-ignition temperature: n.a.

Self-ignition temperature

Solid: The product is not self-igniting.

Gas: n.a.

Decomposition temperature: +60 °C SADT

Oxidizing properties

May cause fire.

Vapour pressure: n.a.

Density (at 20 °C): 1,12 g/cm³

Bulk density (at 20 °C): n. d.

Water solubility:
(at 20 °C) n. d.**Solubility in other solvents**

n. d.

Partition coefficient n-octanol/water: n. d.

Viscosity / dynamic: n.a.

Viscosity / kinematic: n.a.

Flow time: n.a.

Relative vapour density: n.a.

Evaporation rate: n.a.

Solvent separation test: n.a.

Solvent content: 0 %

9.2. Other information

SADT (UN-Test H.4): approx. 60°C

Active oxygen: 3,2 - 3,4%

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored normally.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts with:

Soil, rust, chemicals, strong acids and bases and accelerators (heavy metal salts, amines)

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Self-Accelerating decomposition temperature (SADT) from 60°C (SADT).

Dust may form explosive mixtures with air.

10.5. Incompatible materials

Soil, rust, chemicals, strong acids and bases and accelerators (heavy metal salts, amines)

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® OC Hardener

Revision date: 30.11.2023

Product code: 00359-1240

Page 7 of 11

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Fire may produce:

Carbon monoxide and carbon dioxide

Hydrocarbons

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

dibenzoyl peroxide: LD50/oral/rat: > 5000 mg/kg

Dicyclohexyl phthalate: LD50/oral/rat: > 2000 mg/kg

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (dibenzoyl peroxide; Dicyclohexyl phthalate)

Carcinogenic/mutagenic/toxic effects for reproduction

May damage the unborn child. (Dicyclohexyl phthalate)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards**Endocrine disrupting properties**

Endocrine disrupting properties: Dicyclohexyl phthalate.

Other information

No data available

SECTION 12: Ecological information**12.1. Toxicity**

Ecological data are not available.

Very toxic to aquatic life with long lasting effects.

dibenzoyl peroxide

LC50/Oncorhynchus mykiss/96 h = 0,0602 mg/l

EC50/Daphnia magna/48 h = 110 mg/l

EC50/Pseudokirchneriella subcapitata/72 h = 0,0711 mg/l

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® OC Hardener

Revision date: 30.11.2023

Product code: 00359-1240

Page 8 of 11

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

Risk of drinking water contamination even when low quantities are released into the ground.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

In compliance with regulations by local authorities this can be subjected to a special treatment (e.g. thermal utilization) after dilution with an inert solid to 10% content of peroxides.

Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 3106
14.2. UN proper shipping name:	ORGANIC PEROXIDE TYPE D, SOLID (dibenzoyl peroxide)
14.3. Transport hazard class(es):	5.2
14.4. Packing group:	-
Hazard label:	5.2



Classification code:	P1
Limited quantity:	500 g / 30 kg
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

Inland waterways transport (ADN)

14.1. UN number:	UN 3106
-------------------------	---------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® OC Hardener

Revision date: 30.11.2023

Product code: 00359-1240

Page 9 of 11

14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE D, SOLID (dibenzoyl peroxide)

14.3. Transport hazard class(es): 5.2

14.4. Packing group: -

Hazard label: 5.2



Classification code: P1

Limited quantity: 500 g / 30 kg

Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 3106

14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE D, SOLID (Dibenzoyl peroxide)

14.3. Transport hazard class(es): 5.2

14.4. Packing group: -

Hazard label: 5.2



Marine pollutant: No

Limited quantity: 500 g / 30 kg

Excepted quantity: E0

EmS: F-J, S-R

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3106

14.2. UN proper shipping name: ORGANIC PEROXIDE TYPE D, SOLID (Dibenzoyl peroxide)

14.3. Transport hazard class(es): 5.2

14.4. Packing group: -

Hazard label: 5.2



Limited quantity Passenger: Forbidden

Passenger LQ: Forbidden

Excepted quantity: E0

IATA-packing instructions - Passenger: 570

IATA-max. quantity - Passenger: 5 kg

IATA-packing instructions - Cargo: 570

IATA-max. quantity - Cargo: 10 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® OC Hardener

Revision date: 30.11.2023

Product code: 00359-1240

Page 10 of 11

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):
Dicyclohexyl phthalate

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 30, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: 0 %

Information according to Directive 2012/18/EU (SEVESO III): E1 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Consider Chemical prohibition regulation.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,3,6,7,8,9,10,11,12,13,14.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® OC Hardener

Revision date: 30.11.2023

Product code: 00359-1240

Page 11 of 11

LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Org. Perox. D; H242	On basis of test data
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Repr. 1B; H360D	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

Relevant H and EUH statements (number and full text)

H241 Heating may cause a fire or explosion.
H242 Heating may cause a fire.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H360D May damage the unborn child.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)