

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® OC Solution 3

Revision date: 01.07.2022

Product code: 00359-1288

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Asplit® OC Solution 3

Art.-No.

592 0640

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Mortar

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a week)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Irrit. 2; H315

Eye Irrit. 2; H319

Resp. Sens. 1; H334

Skin Sens. 1; H317

Carc. 2; H351

STOT SE 3; H335

STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements


Regulation (EC) No 1272/2008

Hazard components for labelling

Diphenylmethanediisocyanate, isomeres and homologues

Signal word: Danger

Pictograms:



Hazard statements

H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® OC Solution 3

Revision date: 01.07.2022

Product code: 00359-1288

Page 2 of 10

Precautionary statements

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.

Special labelling of certain mixtures

- EUH204 Contains isocyanates. May produce an allergic reaction.
As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.
The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation with isocyanates

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
9016-87-9	Diphenylmethanediisocyanate, isomeres and homologues			90 - 100 %
			01-2119457024-46	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
9016-87-9		Diphenylmethanediisocyanate, isomeres and homologues	90 - 100 %	
	inhalation: ATE = 11 mg/l (vapours); dermal: LD50 = > 9400 mg/kg; oral: LD50 = > 10000 mg/kg mg/kg			

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.

After inhalation

Move to fresh air in case of accidental inhalation of fumes from overheating or combustion.
Keep warm and calm injured person.
Refer for medical treatment.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® OC Solution 3

Revision date: 01.07.2022

Product code: 00359-1288

Page 3 of 10

After contact with skin

Remove immediately adhering matter.
Wash contaminated skin with plenty of water and soap or with liquid polyethylene glycol.
Consult a physician.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Induce vomiting only upon the advice of a physician.
Summon a doctor immediately.
Rinse out mouth thoroughly with water.

4.2. Most important symptoms and effects, both acute and delayed

Harmful if inhaled.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x).
Hydrogen cyanide (HCN)
Isocyanates (NCO).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.
Keep away noninvolved persons.

For non-emergency personnel

Do not breathe vapours.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® OC Solution 3

Revision date: 01.07.2022

Product code: 00359-1288

Page 4 of 10

Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

No not container for disposal.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Informations for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Avoid contact with the skin and the eyes.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours.

When working with spray, exhaustion of air becomes indispensable.

Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Recommended storage temperature: 20°C - 25°C

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

Hints on joint storage

Exothermic reaction with:

Acids and bases.

Water, amines, alcohols

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Mortar

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® OC Solution 3

Revision date: 01.07.2022

Product code: 00359-1288

Page 5 of 10

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Take off immediately all contaminated clothing.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>**Skin protection**

Light protective clothing

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Brown
Odour:	Musty

pH-Value:

n. d.

Test method**Changes in the physical state**

Melting point/freezing point:

n. d.

Boiling point or initial boiling point and boiling range:

n. d.

Sublimation point:

n.a.

Softening point:

n. d.

Stock pint:

Flash point:

> 150 °C

Flammability

Solid/liquid:

n.a.

Gas:

n.a.

Explosive properties

The product is not explosive.

Lower explosion limits:

n. d.

Upper explosion limits:

n. d.

Auto-ignition temperature:

n. d.

Self-ignition temperature

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® OC Solution 3

Revision date: 01.07.2022

Product code: 00359-1288

Page 6 of 10

Solid:	n.a.
Gas:	n.a.
Decomposition temperature:	n. d.
Oxidizing properties	
Not oxidising.	
Vapour pressure: (at 20 °C)	< 0,00001 hPa
Density (at 20 °C):	1,23 g/cm ³
Bulk density:	n.a.
Water solubility:	Reacts with water
Solubility in other solvents	
n. d.	
Partition coefficient n-octanol/water:	n. d.
Viscosity / dynamic: (at 25 °C)	200 mPa·s
Viscosity / kinematic:	n. d.
Flow time:	n. d.
Relative vapour density:	n. d.
Evaporation rate:	n. d.
Solvent separation test:	0 %
Solvent content:	0 %

9.2. Other information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with strong acids and alkalies.

Reacts with: Water, amines, alcohols

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

10.5. Incompatible materials

Acids and bases

Water, amines, alcohols

10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Hydrogen cyanide gas.

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)

Isocyanates

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® OC Solution 3

Revision date: 01.07.2022

Product code: 00359-1288

Page 7 of 10

Acute toxicity

Based on available data, the classification criteria are not met.

LD50/oral/rat: > 10000 mg/kg [OECD 401]

LD50/dermal/rabbit: > 9400 mg/kg [OECD 402]

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Skin irritation (rabbit): Irritant [OECD 404]

Eyes irritation (rabbit): Irritant [OECD 405]

Sensitising effects

Contains isocyanates. May produce an allergic reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Diphenylmethanediisocyanate, isomeres and homologues)

May cause an allergic skin reaction. (Diphenylmethanediisocyanate, isomeres and homologues)

Sensitization skin (guinea pig): Sensitising [OECD 405]

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (Diphenylmethanediisocyanate, isomeres and homologues)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Diphenylmethanediisocyanate, isomeres and homologues)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Diphenylmethanediisocyanate, isomeres and homologues)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocyanates; therefore keep room aerated and ventilated.

SECTION 12: Ecological information

12.1. Toxicity

LC50/Brachydanio rerio/96 h > 1000 mg/l [OECD 203]

EC50/Daphnia magna/48 h > 1000 mg/l [OECD 202]

EC50/Desmodesmus subspicatus/72 h > 1640 mg/l [OECD 201]

EC50/Activated sludge/3 h > 100 mg/l [OECD 209]

NOEC/Daphnia magna/21 d \geq 10 mg/l [OECD 211]

EC50/Eisenia fetida/336 h > 1000 mg/l [OECD 207]

12.2. Persistence and degradability

Not readily biodegradable.

12.3. Bioaccumulative potential

There is no indication of bioaccumulation potential.

Bioconcentration factor (BCF): 200 (Cyprinus carpio)

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® OC Solution 3

Revision date: 01.07.2022

Product code: 00359-1288

Page 8 of 10

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Slightly water hazardous.

Further information

In aqueous systems, formation of insoluble and chemically inert (inactive) polyureas.

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® OC Solution 3

Revision date: 01.07.2022

Product code: 00359-1288

Page 9 of 10

14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

2004/42/EC (VOC): 0 %

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,6,7,9,10,11,12,13,14,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® OC Solution 3

Revision date: 01.07.2022

Product code: 00359-1288

Page 10 of 10

LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Resp. Sens. 1; H334	Calculation method
Skin Sens. 1; H317	Calculation method
Carc. 2; H351	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
EUH204 Contains isocyanates. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

'The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)