

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® VEQ Powder

Revision date: 07.09.2023

Product code: 00359-1203

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Asplit® VEQ Powder

Art.-No.

592 0360

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Filler

1.3. Details of the supplier of the safety data sheet

Company name:	TIP TOP Oberflächenschutz Elbe GmbH		
Street:	Heuweg 4		
Place:	D-06886 Wittenberg		
Telephone:	+49(0)3491/635-50	Telefax:	+49(0)3491/635-552
Responsible Department:	Responsible for the safety data sheet: sds@gbk-ingelheim.de		

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a week)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

STOT RE 2; H373
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Quartz

Signal word: Warning**Pictograms:****Hazard statements**

H373	May cause damage to organs (lung) through prolonged or repeated exposure if inhaled.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P260	Do not breathe dust.
P284	In case of inadequate ventilation wear respiratory protection.
P314	Get medical advice/attention if you feel unwell.
P273	Avoid release to the environment.
P391	Collect spillage.

Special labelling of certain mixtures

EUH208	Contains dibenzoyl peroxide. May produce an allergic reaction.
--------	--

2.3. Other hazards

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® VEQ Powder

Revision date: 07.09.2023

Product code: 00359-1203

Page 2 of 10

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of the following substances with non-hazardous admixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
14808-60-7	Quartz			95 - < 100 %
	231-545-4			
14808-60-7	Quartz			< 5 %
	231-545-4			
	STOT RE 1; H372			
94-36-0	dibenzoyl peroxide			< 1 %
	202-327-6	617-008-00-0	01-2119511472-50	
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H241 H319 H317 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
94-36-0	202-327-6	dibenzoyl peroxide	< 1 %
	Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove and wash contaminated clothing before re-use.

After inhalation

Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.

In the event of symptoms refer for medical treatment.

After contact with skin

No specific precautions required.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

If eye irritation persists, consult a specialist.

After ingestion

In the event of symptoms refer for medical treatment.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® VEQ Powder

Revision date: 07.09.2023

Product code: 00359-1203

Page 3 of 10

4.2. Most important symptoms and effects, both acute and delayed

May cause damage to organs through prolonged or repeated exposure if inhaled. [lung]
When dust is produced, slight irritations of eyes and mucous membranes are possible.
Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough.
May cause sensitization of susceptible persons by skin contact.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Product does not burn, fire-extinguishing activities according to surrounding.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

No data available

5.3. Advice for firefighters

In case of fire, wear suitable respiratory equipment with positive air supply.
Protective suit.

Additional information

Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.
Avoid dust formation.
Keep away noninvolved persons.

For non-emergency personnel

Do not breathe dust.
Avoid contact with skin, eyes and clothing.

For emergency responders

In case of respirable dust, use a self-contained breathing apparatus.
Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For containment

Avoid dust formation.

For cleaning up

Pick up mechanically, avoiding dust, and provide disposal in suitable recipients.
Where possible recycling is preferred to disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Informations for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® VEQ Powder

Revision date: 07.09.2023

Product code: 00359-1203

Page 4 of 10

Advice on safe handling

- Keep container tightly closed.
- Avoid the formation and deposition of dust.
- Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

Advice on protection against fire and explosion

- No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

- Keep container tightly closed in a dry, cool and well-ventilated place.

Hints on joint storage

- No materials to be especially mentioned.

Further information on storage conditions

- Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

- Filler

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
7778-18-9	Calcium sulphate	-	10		TWA (8 h)	
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	
14808-60-7	Quartz, respirable dust (crystalline silica)	-	0.1		TWA (8 h)	

Additional advice on limit values

- Obey TLV for common dust, if applicable.

8.2. Exposure controls**Appropriate engineering controls**

- Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

Protective and hygiene measures

- Do not inhale dust.
- Wash hands before breaks and at the end of workday.
- When using do not eat, drink or smoke.
- Remove and wash contaminated clothing before re-use.

Eye/face protection

- Safety goggles with side protection (EN 166).

Hand protection

- Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.
- This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
- Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.
- Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

Skin protection

- Long sleeved clothing (DIN EN ISO 6530)

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® VEQ Powder

Revision date: 07.09.2023

Product code: 00359-1203

Page 5 of 10

Respiratory protection

Dust mask (EN 149)

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Powder	
Colour:	Grey	
Odour:	Odourless	
pH-Value:		n.d.

Changes in the physical state

Melting point/freezing point:		n.d.
Boiling point or initial boiling point and boiling range:		n.d.
Sublimation point:		n.d.
Softening point:		n.d.
Flash point:		n.a.
Sustaining combustion:	Not sustaining combustion	

Flammability

Solid/liquid:		n.d.
		n.a.

Explosive properties

The product is not explosive.

Lower explosion limits:		n.a.
Upper explosion limits:		n.a.
Auto-ignition temperature:		n.a.

Self-ignition temperature

Solid:		n.d.
Gas:		n.a.
Decomposition temperature:		n.d.

Oxidizing properties

Not oxidising.

Vapour pressure:		n.a.
Density:		n.d.
Bulk density:	1370 kg/m ³	
Water solubility: (at 20 °C)	More or less insoluble	

Solubility in other solvents

n.d.

Partition coefficient n-octanol/water:		n.d.
Viscosity / dynamic:		n.a.
Viscosity / kinematic:		n.a.
Flow time:		n.a.
Relative vapour density:		n.a.
Evaporation rate:		n.a.
Solvent separation test:		0 %

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® VEQ Powder

Revision date: 07.09.2023

Product code: 00359-1203

Page 6 of 10

Solvent content:

0 %

9.2. Other information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

10.4. Conditions to avoid

Not known.

10.5. Incompatible materials

No materials to be especially mentioned.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**Based on available data, the classification criteria are not met.
No toxicological data available.**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains dibenzoyl peroxide. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (Quartz)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards**Endocrine disrupting properties**

No data available

Other informationWhen dust is produced, slight irritations of eyes and mucous membranes are possible.
Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough.
May cause sensitization of susceptible persons by skin contact.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® VEQ Powder

Revision date: 07.09.2023

Product code: 00359-1203

Page 7 of 10

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meet the criteria.

12.7. Other adverse effects

No data available

Further information

Ecological injuries are not known or expected under normal use.
Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.
Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080299 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of other coatings (including ceramic materials); wastes not otherwise specified

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.
Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN 3077

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(dibenzoyl peroxide)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® VEQ Powder

Revision date: 07.09.2023

Product code: 00359-1203

Page 8 of 10

Classification code: M7
Special Provisions: 274 335 375 601
Limited quantity: 5 kg / 30 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 90
Tunnel restriction code: -

Inland waterways transport (ADN)

14.1. UN number: UN 3077
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(dibenzoyl peroxide)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Classification code: M7
Special Provisions: 274 335 375 601
Limited quantity: 5 kg / 30 kg
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 3077
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Dibenzoyl peroxide)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Marine pollutant: Yes
Special Provisions: 274 335 966 967 969
Limited quantity: 5 kg / 30 kg
Excepted quantity: E1
EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3077
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Dibenzoyl peroxide)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Special Provisions: A97 A158 A179 A197 A215
Limited quantity Passenger: 30 kg G
Passenger LQ: Y956

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Asplit® VEQ Powder

Revision date: 07.09.2023

Product code: 00359-1203

Page 9 of 10

Excepted quantity:	E1	
IATA-packing instructions - Passenger:		956
IATA-max. quantity - Passenger:		400 kg
IATA-packing instructions - Cargo:		956
IATA-max. quantity - Cargo:		400 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

2004/42/EC (VOC):	0 %
Information according to 2012/18/EU (SEVESO III):	E2 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
--------------------------	---

Water hazard class (D):	1 - slightly hazardous to water
-------------------------	---------------------------------

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,6,7,8,9,11,12,14,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Asplit® VEQ Powder

Revision date: 07.09.2023

Product code: 00359-1203

Page 10 of 10

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs (lung) through prolonged or repeated exposure if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains dibenzoyl peroxide. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)