

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROFLAKE 27

Revision date: 22.01.2024

Product code: 00359-1126

Page 1 of 13

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

TIP TOP COROFLAKE 27

##### Art.-No.

590 0730, 590 0740

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Coating material

##### 1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax:

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

##### 1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)  
Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a week)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

##### Regulation (EC) No 1272/2008

Flam. Liq. 3; H226

Acute Tox. 4; H332

Skin Irrit. 2; H315

Eye Irrit. 2; H319

Repr. 2; H361d

STOT SE 3; H335

STOT RE 1; H372

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

##### Regulation (EC) No 1272/2008

##### Hazard components for labelling

Styrene

Methanol

N,N-dimethylaniline

##### Signal word:

Danger

##### Pictograms:



##### Hazard statements

H226

Flammable liquid and vapour.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H332

Harmful if inhaled.

H335

May cause respiratory irritation.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROFLAKE 27

Revision date: 22.01.2024

Product code: 00359-1126

Page 2 of 13

H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.

#### Special labelling of certain mixtures

EUH208	Contains Neodecanoic acid, cobalt salt. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Epoxide-vinyl ester-resin in styrene

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**TIP TOP COROFLAKE 27**

Revision date: 22.01.2024

Product code: 00359-1126

Page 3 of 13

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
100-42-5	Styrene			< 35 %
	202-851-5	601-026-00-0	01-2119457861-32	
	Flam. Liq. 3, Repr. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 3; H226 H361d H332 H315 H319 H335 H372 H304 H412			
14808-60-7	Quartz (SiO <sub>2</sub> )			< 1 %
	238-878-4		01-2120770509-45	
13463-67-7	Titanium dioxide			< 5 %
	236-675-5	022-006-00-2	01-2119489379-17	
	Carc. 2; H351			
79-41-4	Methacrylic acid			< 1 %
	201-204-4	607-088-00-5	01-2119463884-26	
	Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1, STOT SE 3; H311 H332 H302 H314 H318 H335			
27253-31-2	Neodecanoic acid, cobalt salt			< 0,3 %
	248-373-0	607-230-00-6	01-2119970733-31	
	Repr. 1B, Acute Tox. 4, Skin Sens. 1, Aquatic Chronic 3; H360D H302 H317 H412			
67-56-1	Methanol			< 0,3 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			
121-69-7	N,N-dimethylaniline			< 0,3 %
	204-493-5	612-016-00-0	01-2119935241-47	
	Carc. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, Aquatic Chronic 2; H351 H331 H311 H301 H411			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
100-42-5	202-851-5	Styrene	< 35 %
	inhalation: LC50 = 11,8 mg/l (vapours); oral: LD50 = 2650 mg/kg		
79-41-4	201-204-4	Methacrylic acid	< 1 %
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 500 -1000 mg/kg; oral: LD50 = 1320 mg/kg STOT SE 3; H335: >= 1 - 100		
27253-31-2	248-373-0	Neodecanoic acid, cobalt salt	< 0,3 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 3000 mg/kg		
67-56-1	200-659-6	Methanol	< 0,3 %
	inhalation: LC50 = 83,9 mg/l (vapours); dermal: LD50 = 15800 mg/kg; oral: LD50 = 5630 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10		
121-69-7	204-493-5	N,N-dimethylaniline	< 0,3 %
	inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: ATE = 100 mg/kg		

**Further Information**

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter <=



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROFLAKE 27

Revision date: 22.01.2024

Product code: 00359-1126

Page 4 of 13

10 µm.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

###### General information

Remove contaminated soaked clothing immediately.  
In the event of persistent symptoms receive medical treatment.  
Take away from danger area and lay down affected person.

###### After inhalation

Move to fresh air in case of accidental inhalation of vapours.  
Seek medical treatment immediately.  
If patient is not breathing, apply artificial respiration. In case of breathing difficulties give oxygen.

###### After contact with skin

Wash off immediately with soap and plenty of water.  
Consult a doctor if skin irritation persists.

###### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Consult (eye) doctor immediately.

###### After ingestion

Do not induce vomiting.  
Summon a doctor immediately.  
Rinse out mouth and give plenty of water to drink.  
Never give anything by mouth to an unconscious person.  
Induce vomiting only upon the advice of a physician.

##### 4.2. Most important symptoms and effects, both acute and delayed

Harmful if inhaled.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
Causes damage to organs through prolonged or repeated exposure. (the ear)  
Suspected of damaging the unborn child.  
Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

##### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

###### Unsuitable extinguishing media

Full water jet.

##### 5.2. Special hazards arising from the substance or mixture

Fire may produce:  
carbon monoxide and carbon dioxide  
Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

##### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

###### Additional information

Vapours are heavier than air and spread along ground.  
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROFLAKE 27

Revision date: 22.01.2024

Product code: 00359-1126

Page 5 of 13

Cool containers at risk with water spray jet.  
Collect contaminated firefighting water separately, must not be discharged into the drains.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

#### SECTION 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

###### General advice

Ensure adequate ventilation.  
Remove persons to safety.  
Keep away sources of ignition.

###### For non-emergency personnel

Avoid contact with skin, eyes and clothing.  
Do not breathe vapours.

###### For emergency responders

In case of vapour formation use respirator.  
Use personal protective clothing.

##### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.  
Do not discharge into the subsoil/soil.

##### 6.3. Methods and material for containment and cleaning up

###### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

###### For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).  
Shovel into suitable container for disposal.

##### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).  
Informations for disposal look up chapter 13.

#### SECTION 7: Handling and storage

##### 7.1. Precautions for safe handling

###### Advice on safe handling

Keep container tightly closed.  
Vapours are heavier than air and spread along ground.  
Use only in thoroughly ventilated areas.  
Provide suitable extraction at the processing machines.

###### Advice on protection against fire and explosion

Keep away from heat and sources of ignition.  
Do not smoke.  
Take precautionary measures against static discharges.  
Use only explosion-proof equipment.

##### 7.2. Conditions for safe storage, including any incompatibilities

###### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.  
Pay attention to anti-explosion rules.  
Storage temperature between 10°C to 30°C (=50°F to 86°F).

###### Hints on joint storage

Incompatible with:  
Oxidizing agents, Metal halogenides, Peroxides

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROFLAKE 27

Revision date: 22.01.2024

Product code: 00359-1126

Page 6 of 13

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

#### 7.3. Specific end use(s)

Coating material

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
149-57-5	Ethyl hexanoic acid	-	5		TWA (8 h)	
1332-58-7	Kaolin, respirable dust	-	2.0		TWA (8 h)	
79-41-4	Methacrylic acid	20	70		TWA (8 h)	
		40	140		STEL (15 min)	
67-56-1	Methyl alcohol	200	260		TWA (8 h)	
12001-26-2	Mica, respirable dust	-	3		TWA (8 h)	
121-69-7	N,N-Dimethylaniline	5	25		TWA (8 h)	
		10	50		STEL (15 min)	
14808-60-7	Quartz, respirable dust (crystalline silica)	-	0.1		TWA (8 h)	
100-42-5	Styrene	20	85		TWA (8 h)	
		40	170		STEL (15 min)	
13463-67-7	Titanium dioxide, total inhalable dust	-	10		TWA (8 h)	

##### Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
100-42-5	Styrene	Mandelic acid plus phenylglyoxylic acid	400 mg/g	Creatinine	End of shift
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift

#### 8.2. Exposure controls

##### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.  
Pay attention to explosion protection rules.

##### Protective and hygiene measures

Do not inhale vapours.  
Wash hands before breaks and immediately after handling the product.  
When using do not eat, drink or smoke.  
Treat subsequently with skin cream.  
Remove and wash contaminated clothes before re-use.

##### Eye/face protection

Tightly fitting goggles (EN 166).  
Eye wash bottle with pure water (EN 15154).

##### Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**TIP TOP COROFLAKE 27**

Revision date: 22.01.2024

Product code: 00359-1126

Page 7 of 13

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

**Skin protection**

Long sleeved clothing (DIN EN ISO 6530)

Solvent-resistant apron (EN 467).

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Viscous liquid
Colour:	Beige
Odour:	Like styrene

**Test method**

pH-Value: n. d.

**Changes in the physical state**

Melting point/freezing point: n. d.

Boiling point or initial boiling point and boiling range: n. d.

Sublimation point: n.a.

Softening point: n. d.

Flash point: 31 °C \*)

Sustaining combustion: Sustaining combustion

**Flammability**

Solid/liquid: n.a.

**Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: 1,1 vol. % \*)

Upper explosion limits: 8,9 vol. % \*)

Auto-ignition temperature: 480 °C \*)

**Self-ignition temperature**

Solid: n.a.

Gas: n.a.

Decomposition temperature: n. d.

**Oxidizing properties**

Not oxidising.

Vapour pressure: 6 hPa \*)  
(at 20 °C)

Density: 1,14 - 1,18 g/cm<sup>3</sup>

Bulk density: n.a.

Water solubility: Immiscible  
(at 20 °C)

**Solubility in other solvents**

n. d.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**TIP TOP COROFLAKE 27**

Revision date: 22.01.2024

Product code: 00359-1126

Page 8 of 13

Partition coefficient n-octanol/water:	n. d.
Viscosity / dynamic: (at 25 °C)	3000 - 3500 mPa·s
Viscosity / kinematic: (at 40 °C)	> 20,5 mm <sup>2</sup> /s
Flow time: (at 25 °C)	> 40 s Ford beaker, no. 6
Relative vapour density:	n. d.
Evaporation rate:	n. d.
Solvent separation test:	< 3 %
Solvent content:	< 5 %

**9.2. Other information**

\*) Styrene

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with oxidising agents.

Reactions with peroxides.

**10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat.  
Vapour/air mixtures are explosive at intensive warming.  
Heating can release vapours which can be ignited.  
Avoid temperatures above 50°C.  
If heating up polymerisation.

**10.5. Incompatible materials**

Metal halogenides, Oxidizing agents, Peroxides

**10.6. Hazardous decomposition products**

No known hazardous decomposition products.  
Fire may produce:  
Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).  
Carbon monoxide and carbon dioxide

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Harmful if inhaled.  
No toxic dates available.  
Styrene  
LD50/oral/rat: 5000 mg/kg  
LD50/dermal/rat: > 2000 mg/kg  
LC50/inhalativ/rat: 11,8 mg/l/4h

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) 4,381 mg/l



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**TIP TOP COROFLAKE 27**

Revision date: 22.01.2024

Product code: 00359-1126

Page 9 of 13

**Irritation and corrosivity**

Causes skin irritation.  
Causes serious eye irritation.

**Sensitising effects**

Based on available data, the classification criteria are not met.  
Contains Neodecanoic acid, cobalt salt. May produce an allergic reaction.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of damaging the unborn child. (Styrene)  
Germ cell mutagenicity: Based on available data, the classification criteria are not met.  
Carcinogenicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause respiratory irritation. (Styrene)

**STOT-repeated exposure**

Causes damage to organs through prolonged or repeated exposure. (Styrene)

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

**11.2. Information on other hazards****Endocrine disrupting properties**

No data available

**Other information**

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.  
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

**SECTION 12: Ecological information****12.1. Toxicity**

Ecological data are not available.  
Harmful to aquatic life with long lasting effects.  
Styrene  
LC50/Pimephales promelas/96 h = 4,02 mg/kg  
EC50/Daphnia magna/48 h = 4,7 mg/kg  
EC50/Pseudokirchneriella subcapitata/72 h > 4,9 mg/kg

**12.2. Persistence and degradability**

No data available

**12.3. Bioaccumulative potential**

No data available

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Hazard to waters.  
Product is toxic to fish and their nutrient animals.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROFLAKE 27

Revision date: 22.01.2024

Product code: 00359-1126

Page 10 of 13

#### Further information

Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Can be incinerated, when in compliance with local regulations.  
Where possible recycling is preferred to disposal.

##### List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

##### Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.  
Packaging that cannot be cleaned should be disposed of like the product.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

**14.1. UN number:** UN 1866  
**14.2. UN proper shipping name:** RESIN SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Special Provisions: 640E  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1  
Transport category: 3  
Hazard No: 30  
Tunnel restriction code: D/E

#### Other applicable information (land transport)

Viscous substance - excepted quantity if in containers with a capacity up to 450 l (subsection 2.2.3.1.5 ADR).

#### Inland waterways transport (ADN)

**14.1. UN number:** UN 1866  
**14.2. UN proper shipping name:** Resin solution  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP COROFLAKE 27

Revision date: 22.01.2024

Product code: 00359-1126

Page 11 of 13

Limited quantity: 5 L / 30 kg  
Excepted quantity: E1

#### Other applicable information (inland waterways transport)

Viscous substance - excepted quantity if in containers with a capacity up to 450 l (subsection 2.2.3.1.5 ADN).

#### Marine transport (IMDG)

**14.1. UN number:** UN 1866  
**14.2. UN proper shipping name:** RESIN SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: 223, 955  
Limited quantity: 5 L / 30 kg  
Excepted quantity: E1  
EmS: F-E, S-E

#### Other applicable information (marine transport)

Viscous substance - excepted quantity if in containers with a capacity up to 30 l (subsection 2.3.2.5 IMDG Code).

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1866  
**14.2. UN proper shipping name:** RESIN SOLUTION  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: A3  
Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

#### 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**TIP TOP COROFLAKE 27**

Revision date: 22.01.2024

Product code: 00359-1126

Page 12 of 13

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in  
paints and varnishes: < 5 %; < 90 g/lInformation according to Directive  
2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

**Additional information**

Consider Chemical prohibition regulation.

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 8,9,12.

**Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses  
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure  
IMDG = International Maritime Code for Dangerous Goods  
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization  
MARPOL = International Convention for the Prevention of Pollution from Ships  
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals  
CAS = Chemical Abstract Service  
EN = European norm  
ISO = International Organization for Standardization  
DIN = Deutsche Industrie Norm  
PBT = Persistent Bioaccumulative and Toxic  
vPvB = Very Persistent and very Bio-accumulative  
LD = Lethal dose  
LC = Lethal concentration  
EC = Effect concentration  
IC = Median immobilisation concentration or median inhibitory concentration

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**TIP TOP COROFLAKE 27**

Revision date: 22.01.2024

Product code: 00359-1126

Page 13 of 13

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 1; H372	Calculation method
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H360D	May damage the unborn child.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Neodecanoic acid, cobalt salt. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*