

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Art.-No.

580 0047, 580 0054, 580 1352

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Coating component

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a week)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 3; H226

Resp. Sens. 1; H334

Skin Sens. 1; H317

Carc. 2; H351

STOT SE 3; H335

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Solvent naphtha (petroleum)

Aromatic polyisocyanate

4,4'-Methylene-diphenyl diisocyanate

Diphenylmethane-2,4'-diisocyanate

Diphenylmethane-2,2'-diisocyanate

Formaldehyde, oligomeric reaction products with aniline and phosgene

Fatty acids, C18-unsaturated, dimers, reaction products with N, N-dimethyl-1,3-propanediamine and 1,3-propanediamine

Signal word: Danger**Pictograms:****Hazard statements**

H226

Flammable liquid and vapour.

H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 2 of 15

H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P370+P378	In case of fire: Use Dry fire-extinguishing substance, Sand to extinguish.
P233	Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

EUH204	Contains isocyanates. May produce an allergic reaction. As from 24 August 2023 adequate training is required before industrial or professional use.
--------	--

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Aromatic polyisocyanate

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 3 of 15

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-95-6	Solvent naphtha (petroleum)			12,5 - 20 %
	918-668-5	649-356-00-4	01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
147993-65-5	Aromatic polyisocyanate			5 - 10 %
	Resp. Sens. 1, Skin Sens. 1; H334 H317			
101-68-8	4,4'-Methylene-diphenyl diisocyanate			2,5 - 5 %
	202-966-0	615-005-00-9	01-2119457014-47	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
1330-20-7	Xylene (mixed isomers)			1 - 2,5 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412			
5873-54-1	Diphenylmethane-2,4'-diisocyanate			1 - 2,5 %
	227-534-9	615-005-00-9	01-2119480143-45	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
2536-05-2	Diphenylmethane-2,2'-diisocyanate			< 0,5 %
	219-799-4	615-005-00-9	01-2119927323-43	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
32055-14-4	Formaldehyde, oligomeric reaction products with aniline and phosgene			< 0,5 %
	500-079-6		01-2119457024-46	
	Carc. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1A, Skin Sens. 1, STOT SE 3, STOT RE 2; H351 H332 H315 H319 H334 H317 H335 H373			
162627-17-0	Fatty acids, C18-unsaturated, dimers, reaction products with N, N-dimethyl-1,3-propanediamine and 1,3-propanediamine			< 0,5 %
	605-296-0		01-2119970640-38	
	Skin Sens. 1A; H317			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 4 of 15

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
101-68-8	202-966-0	4,4'-Methylene-diphenyl diisocyanate	2,5 - 5 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 0,368 mg/l (dusts or mists); dermal: LD50 = > 9400 mg/kg; oral: LD50 = > 2000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100	
1330-20-7	215-535-7	Xylene (mixed isomers)	1 - 2,5 %
		inhalation: ATE = 11 mg/l (vapours); dermal: ATE = 1100 mg/kg	
5873-54-1	227-534-9	Diphenylmethane-2,4'-diisocyanate	1 - 2,5 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 0,31 mg/l (dusts or mists); dermal: LD50 = > 9400 mg/kg; oral: LD50 = > 2000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100	
2536-05-2	219-799-4	Diphenylmethane-2,2'-diisocyanate	< 0,5 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = 0,370 mg/l (dusts or mists); oral: LD50 = > 15000 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 Resp. Sens. 1; H334: >= 0,1 - 100 STOT SE 3; H335: >= 5 - 100	
32055-14-4	500-079-6	Formaldehyde, oligomeric reaction products with aniline and phosgene	< 0,5 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists) Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 STOT SE 3; H335: >= 5 - 100	

Further Information

According to note P to the directive 67/548/EEC, "Solvent naphta (petroleum)" is not to be classified as "carcinogenic" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

- Remove contaminated soaked clothing immediately.
- If you feel unwell, seek medical advice.
- Take away from danger area and lay down affected person.
- In case of the person being unconscious put him/her in a stable side position.

After inhalation

- Move to fresh air in case of accidental inhalation of vapours or decomposition products.
- Refer for medical treatment.
- If patient is not breathing, apply artificial respiration.

After contact with skin

- Wash off with soap and plenty of water.
- Consult a doctor if skin irritation persists.
- Do not use solvents or thinners.

After contact with eyes

- Remove contact lens.
- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- Seek medical treatment by eye specialist.

After ingestion

- Do not induce vomiting.
- Rinse out mouth and give plenty of water to drink.
- Never give anything by mouth to an unconscious person.
- Summon a doctor immediately.
- Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- May cause an allergic skin reaction.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 5 of 15

Suspected of causing cancer.
May cause respiratory irritation.
Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x).

Hydrogen cyanide (HCN)

Isocyanates (NCO).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Vapours are heavier than air and spread along ground.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.

Keep away sources of ignition.

Keep away noninvolved persons.

For non-emergency personnel

Do not breathe vapours.

Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.

Use personal protective clothing.

Use only explosion-proof equipment.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Inform competent authority about release into the sewerage, ground or into waters.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

No not container for disposal.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 6 of 15

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Informations for disposal look up chapter 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Keep container tightly closed.
Keep a good ventilation and air-exhaust at the place of work.
Vapours are heavier than air and spread along ground.
Avoid contact with the skin and the eyes.
When using do not eat, drink or smoke.
Do not empty container under pressure. No pressure tank!
Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.
Do not smoke.
Take precautionary measures against static discharges.
Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.
Pay attention to anti-explosion protection rules.
Protect from heat and direct solar radiation.
Storage temperature between 15°C to 30°C

Hints on joint storage

Incompatible with:
Oxidizing agents
Acids and bases.
Water, amines, alcohols

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Coating component

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
101-68-8	4,4'-Methylene-diphenyl diisocyanate (as -NCO)	0.005	-		TWA (8 h)	
-	Isocyanates (all, as -NCO)	-	0.02		TWA (8 h)	
			0.07		STEL (15 min)	
1330-20-7	Xylene, mixed isomers	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 7 of 15

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
101-68-8	4,4'-Methylene-diphenyl diisocyanate			
Worker DNEL, acute		dermal	systemic	50 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	0,1 mg/m ³
Worker DNEL, acute		dermal	local	28,7 mg/cm ²
Worker DNEL, acute		inhalation	local	0,1 mg/m ³
Worker DNEL, long-term		inhalation	systemic	0,05 mg/m ³
Worker DNEL, long-term		inhalation	local	0,05 mg/m ³
Consumer DNEL, acute		dermal	systemic	25 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	0,05 mg/m ³
Consumer DNEL, acute		oral	systemic	20 mg/kg bw/day
Consumer DNEL, acute		dermal	local	17,2 mg/cm ²
Consumer DNEL, acute		inhalation	local	0,05 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	0,025 mg/m ³
Consumer DNEL, long-term		inhalation	local	0,025 mg/m ³
5873-54-1	Diphenylmethane-2,4'-diisocyanate			
Worker DNEL, acute		dermal	systemic	50 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	0,1 mg/m ³
Worker DNEL, acute		dermal	local	28,7 mg/cm ²
Worker DNEL, acute		inhalation	local	0,1 mg/m ³
Worker DNEL, long-term		dermal	systemic	0 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	0,05 mg/m ³
Worker DNEL, long-term		dermal	local	0 mg/cm ²
Consumer DNEL, acute		dermal	systemic	25 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	0,05 mg/m ³
Consumer DNEL, acute		oral	systemic	20 mg/kg bw/day
Consumer DNEL, acute		dermal	local	17,2 mg/cm ²
Consumer DNEL, long-term		dermal	local	0 mg/cm ²
Consumer DNEL, long-term		dermal	systemic	0 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,025 mg/m ³
Consumer DNEL, long-term		oral	systemic	0 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	0,025 mg/m ³
Worker DNEL, long-term		inhalation	local	0,05 mg/m ³

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 8 of 15

PNEC values

CAS No	Substance	Value
Environmental compartment		
101-68-8	4,4'-Methylene-diphenyl diisocyanate	
Freshwater		1 mg/l
Marine water		0,1 mg/l
Soil		1 mg/kg
Micro-organisms in sewage treatment plants (STP)		1 mg/l
Freshwater (intermittent releases)		10 mg/l
5873-54-1	Diphenylmethane-2,4'-diisocyanate	
Freshwater		> 1 mg/l
Marine water		> 0,1 mg/l
Micro-organisms in sewage treatment plants (STP)		> 1 mg/l
Soil		> 1 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothing before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Various
Odour:	Characteristic

Test method

pH-Value: n. d.

Changes in the physical state

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 9 of 15

Melting point/freezing point:	n. d.
Boiling point or initial boiling point and boiling range:	155 °C *)
Sublimation point:	n.a.
Softening point:	n. d.
Flash point:	30 °C DIN 53213
Sustaining combustion:	Sustaining combustion

Flammability

Solid/liquid:	n.a.
Gas:	n.a.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	0,8 vol. % *)
Upper explosion limits:	7,0 vol. % *)
Auto-ignition temperature:	180 °C

Self-ignition temperature

Solid:	n.a.
Gas:	n.a.

Decomposition temperature: n. d.

Oxidizing properties

Not oxidising.

Vapour pressure: (at 20 °C)	0,459 hPa
Density (at 20 °C):	1,12 g/cm ³
Bulk density:	n.a.
Water solubility: (at 20 °C)	Immiscible

Solubility in other solvents

n. d.

Partition coefficient n-octanol/water:	n. d.
Viscosity / dynamic: (at 20 °C)	750 mPa·s
Viscosity / kinematic:	n. d.
Flow time: (at 20 °C)	45 s 4 DIN 53211
Relative vapour density:	n. d.
Evaporation rate:	n. d.
Solvent separation test:	< 3 %
Solvent content:	20 %

9.2. Other information

Solid content: 80 %

*) Solvent naphtha (petroleum)

SECTION 10: Stability and reactivity**10.1. Reactivity**

No decomposition if stored and applied as directed.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 10 of 15

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidising agents.

Reacts with: Water, amines, alcohols

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Heating can release vapours which can be ignited.

Vapour/air-mixtures are explosive at intense warming.

10.5. Incompatible materials

Strong oxidizing agents

Strong acids and strong bases

Water, amines, alcohols

10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)

Hydrogen cyanide gas., Isocyanates

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

No toxic data available.

ATEmix calculated

ATE (dermal) 44176,7 mg/kg; ATE (inhalation vapour) 111,45 mg/l; ATE (inhalation dust/mist) 20,325 mg/l

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Eye irritation: Not classified.

Sensitising effects

Contains isocyanates. May produce an allergic reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. (Aromatic polyisocyanate; 4,4'-Methylene-diphenyl diisocyanate;

Diphenylmethane-2,4'-diisocyanate; Diphenylmethane-2,2'-diisocyanate; Formaldehyde, oligomeric reaction products with aniline and phosgene)

May cause an allergic skin reaction. (Aromatic polyisocyanate; 4,4'-Methylene-diphenyl diisocyanate; Diphenylmethane-2,4'-diisocyanate; Diphenylmethane-2,2'-diisocyanate; Formaldehyde, oligomeric reaction products with aniline and phosgene; Fatty acids, C18-unsaturated, dimers, reaction products with N, N-dimethyl-1,3-propanediamine and 1,3-propanediamine)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing cancer. (4,4'-Methylene-diphenyl diisocyanate; Diphenylmethane-2,4'-diisocyanate; Diphenylmethane-2,2'-diisocyanate; Formaldehyde, oligomeric reaction products with aniline and phosgene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 11 of 15

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Inhalation of high concentrations may cause injuries to liver, kidneys and central nervous system.

A longer or repeated contact may lead to irritation of eyes and mucous membranes.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocyanates; therefore keep room aerated and ventilated.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meet the criteria.

12.7. Other adverse effects

Slightly water hazardous.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 12 of 15

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Other applicable information (land transport)

Viscous substance - excepted quantity if in containers with a capacity up to 450 l (subsection 2.2.3.1.5 ADR)

Inland waterways transport (ADN)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E1

Other applicable information (inland waterways transport)

Viscous substance - excepted quantity if in containers with a capacity up to 450 l (subsection 2.2.3.1.5 ADN)

Marine transport (IMDG)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Marine pollutant: No
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
EmS: F-E, S-E

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 13 of 15

Other applicable information (marine transport)

Viscous substance - excepted quantity if in containers with a capacity up to 30 l (subsection 2.3.2.5 IMDG Code).

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	Paint
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3



Limited quantity Passenger:	10 L
Passenger LQ:	Y344
Excepted quantity:	E1
IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 56, Entry 75

2010/75/EU (VOC): 227 g/l

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

1 - slightly hazardous to water

Additional information

Consider Chemical prohibition regulation.

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 14 of 15

This data sheet contains changes from the previous version in section(s): 2,3,4,6,7,8,9,10,11,12,13,14,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Resp. Sens. 1; H334	Calculation method
Skin Sens. 1; H317	Calculation method
Carc. 2; H351	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH204	Contains isocyanates. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR BONDING AND INSULATING PRIMER

Revision date: 30.06.2022

Product code: 00359-1259

Page 15 of 15

(in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)