



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR FERRO

Revision date: 27.06.2022

Product code: 00359-1177

Page 2 of 13

H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P370+P378	In case of fire: Use Sand, Dry powder to extinguish.
P233	Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.

Special labelling of certain mixtures

EUH204	Contains isocyanates. May produce an allergic reaction. As from 24 August 2023 adequate training is required before industrial or professional use.
--------	--

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Aromatic polyisocyanate

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR FERRO

Revision date: 27.06.2022

Product code: 00359-1177

Page 3 of 13

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
123-86-4	n-Butyl acetate			10 - 12,5 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
53317-61-6	Aromatic polyisocyanate			10 - 12,5 %
	500-120-8			
	Eye Irrit. 2, Skin Sens. 1; H319 H317			
64742-95-6	Solvent naphta (petroleum)			5 - 10 %
	918-668-5	649-356-00-4	01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
103051-64-5	Aromatic polyisocyanate			5 - 10 %
	Skin Sens. 1; H317			
127821-00-5	Aromatic polyisocyanate prepolymer			2,5 - 5 %
	Eye Irrit. 2, Skin Sens. 1; H319 H317			
4083-64-1	4-isocyanatosulphonyltoluene			2,5 - 5 %
	223-810-8	615-012-00-7	01-2119980050-47	
	Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, STOT SE 3; H315 H319 H334 H335 EUH014			
64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics			1 - 2,5 %
	265-150-3	649-327-00-6		
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304			
162627-17-0	Fatty acids, C18-unsaturated, dimers, reaction products with N, N-dimethyl-1,3-propanediamine and 1,3-propanediamine			< 5 %
	605-296-0		01-2119970640-38	
	Skin Sens. 1A; H317			
26471-62-5	4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate			< 0,5 %
	247-722-4	615-006-00-4	01-2119454791-34	
	Carc. 2, Acute Tox. 2, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3, Aquatic Chronic 3; H351 H330 H315 H319 H334 H317 H335 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
4083-64-1	223-810-8	4-isocyanatosulphonyltoluene	2,5 - 5 %	
	Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100 STOT SE 3; H335: >= 5 - 100			
26471-62-5	247-722-4	4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate	< 0,5 %	
	inhalation: ATE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists) Resp. Sens. 1; H334: >= 0,1 - 100			

Further Information

According to note P to the directive 67/548/EEC, "Solvent naphta (petroleum)" is not to be classified as "carcinogenic" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

According to note P to the directive 67/548/EEC, "Naphta (petroleum)" is not to be classified as "carcinogenic"



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR FERRO

Revision date: 27.06.2022

Product code: 00359-1177

Page 4 of 13

ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.
Keep warm and calm injured person.
If patient is not breathing, apply artificial respiration.
Seek medical treatment immediately.

After contact with skin

In case of contact with skin wash off immediately with soap and water.
Do not use solvents or thinners.

After contact with eyes

Remove contact lens.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x).
Hydrogen cyanide gas., Isocyanates
High smoke development

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Vapours are heavier than air and spread along ground.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR FERRO

Revision date: 27.06.2022

Product code: 00359-1177

Page 5 of 13

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use only explosion-proof equipment.
Ensure adequate ventilation.
Keep away sources of ignition.
Remove persons to safety.

For non-emergency personnel

Do not breathe vapours.
Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator.
Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.
Inform competent authority about release into the sewerage, ground or into waters.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.
Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.
No not container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Informations for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not wear contact lenses when handling the product.
Keep container tightly closed.
Vapours are heavier than air and spread along ground.
Keep a good ventilation and air-exhaust at the place of work.
Do not empty container under pressure. No pressure tank!

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.
Do not smoke.
Take precautionary measures against static discharges.
Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.
Pay attention to anti-explosion rules.
Take precautionary measures against static discharges.
Storage temperature between 15°C to 30°C

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR FERRO

Revision date: 27.06.2022

Product code: 00359-1177

Page 6 of 13

Hints on joint storage

Incompatible with:
strong oxidizing agents, strong acids and strong bases
Water, amines, alcohols

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Protection against corrosion

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
123-86-4	Butyl acetate	150	710		TWA (8 h)	
		200	950		STEL (15 min)	
-	Isocyanates (all, as -NCO)	-	0.02		TWA (8 h)	
		-	0.07		STEL (15 min)	

8.2. Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.
Wash hands before breaks and immediately after handling the product.
When using do not eat, drink or smoke.
Avoid contact with skin, eyes and clothing.
Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Hand protection

Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril 735> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: Liquid
Colour: Various
Odour: Characteristic

Test method

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR FERRO

Revision date: 27.06.2022

Product code: 00359-1177

Page 7 of 13

pH-Value: n. d.

Changes in the physical state

Melting point/freezing point: n. d.

Boiling point or initial boiling point and boiling range: 126 °C (*)

Sublimation point: n.a.

Softening point: n. d.

Flash point: 32 °C DIN 53213

Sustaining combustion: Sustaining combustion

Flammability

Solid/liquid: n.a.

Gas: n.a.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits: 1,23 vol. %

Upper explosion limits: 7,0 vol. %

Auto-ignition temperature: 180 °C

Self-ignition temperature

Solid: n.a.

Gas: n.a.

Decomposition temperature: n. d.

Oxidizing properties

Not oxidising.

Vapour pressure: 1,87 hPa
(at 20 °C)Density (at 20 °C): 1,52 g/cm³

Bulk density: n.a.

Water solubility: Immiscible

Solubility in other solvents

n. d.

Partition coefficient n-octanol/water: n. d.

Viscosity / dynamic: n. d.

Viscosity / kinematic: > 20,5 mm²/s
(at 40 °C)Flow time: 300 s 4 DIN EN ISO 2431
(at 20 °C)

Relative vapour density: n. d.

Evaporation rate: n. d.

Solvent separation test: < 3 %

Solvent content: 23 %

9.2. Other information

Solid content: 77 %

(*) n-Butyl acetate

SECTION 10: Stability and reactivity

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR FERRO

Revision date: 27.06.2022

Product code: 00359-1177

Page 8 of 13

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidising agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

Rapid exothermic polymerisation will occur in the presence of water, amines, alkalis and alcohols.

10.5. Incompatible materials

Strong oxidizing agents

Strong acids and strong bases

Water, amines, alcohols

10.6. Hazardous decomposition products

No hazardous decomposition products known.

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)

Hydrogen cyanide gas., Isocyanates

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

ATE_{mix/oral}: > 2000 mg/kg

ATE_{mix/dermal}: > 2000 mg/kg

ATE_{mix/inhalation}: > 20 mg/l

ATE_{mix} calculated

ATE (inhalation vapour) 104,17 mg/l; ATE (inhalation dust/mist) 10,417 mg/l

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Contains isocyanates. May produce an allergic reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. (4-isocyanatosulphonyltoluene; 4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate)

May cause an allergic skin reaction. (Aromatic polyisocyanate; Aromatic polyisocyanate; Aromatic polyisocyanate prepolymer; Fatty acids, C18-unsaturated, dimers, reaction products with N, N-dimethyl-1,3-propanediamine and 1,3-propanediamine; 4-methyl-m-phenylene diisocyanate, toluene-2,6-di-isocyanate)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR FERRO

Revision date: 27.06.2022

Product code: 00359-1177

Page 9 of 13

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards**Endocrine disrupting properties**

No data available

Other information

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Components of the product may be absorbed into the body through the skin.

Contact with eyes may cause irritation.

With hypersensitive people, reactions as cough or difficulty of breathing may appear even with tiny concentrations of isocyanates; therefore keep room aerated and ventilated.

Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

Attention. Beware, danger of aspiration!

SECTION 12: Ecological information**12.1. Toxicity**

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR FERRO

Revision date: 27.06.2022

Product code: 00359-1177

Page 10 of 13

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

Empty containers should be taken for local recycling, recovery or waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1263

14.2. UN proper shipping name: Paint

14.3. Transport hazard class(es): 3

14.4. Packing group: III

Hazard label: 3



Classification code: F1

Limited quantity: 5 L / 30 kg

Excepted quantity: E1

Transport category: 3

Hazard No: 30

Tunnel restriction code: D/E

Other applicable information (land transport)

Viscous substance - excepted quantity if in containers with a capacity up to 450 l (subsection 2.2.3.1.5 ADR).

Inland waterways transport (ADN)

14.1. UN number: UN 1263

14.2. UN proper shipping name: Paint

14.3. Transport hazard class(es): 3

14.4. Packing group: III

Hazard label: 3



Classification code: F1

Limited quantity: 5 L / 30 kg

Excepted quantity: E1

Other applicable information (inland waterways transport)

Viscous substance - excepted quantity if in containers with a capacity up to 450 l (subsection 2.2.3.1.5 ADN).

Marine transport (IMDG)

14.1. UN number: UN 1263

14.2. UN proper shipping name: Paint

14.3. Transport hazard class(es): 3

14.4. Packing group: III

Hazard label: 3



Safety Data Sheet

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR FERRO

Revision date: 27.06.2022

Product code: 00359-1177

Page 11 of 13

Marine pollutant:	No
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
EmS:	F-E, S-E

Other applicable information (marine transport)

Viscous substance - excepted quantity if in containers with a capacity up to 30 l (subsection 2.3.2.5 IMDG Code).

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	Paint
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3



Limited quantity Passenger:	10 L
Passenger LQ:	Y344
Excepted quantity:	E1
IATA-packing instructions - Passenger:	355
IATA-max. quantity - Passenger:	60 L
IATA-packing instructions - Cargo:	366
IATA-max. quantity - Cargo:	220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
Entry 3, Entry 40, Entry 75

2004/42/EC (VOC):	353 g/l
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR FERRO

Revision date: 27.06.2022

Product code: 00359-1177

Page 12 of 13

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,6,7,8,9,10,11,12,14,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Eye Irrit. 2; H319	Calculation method
Resp. Sens. 1; H334	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH014 Reacts violently with water.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH204 Contains isocyanates. May produce an allergic reaction.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

TIP TOP COROPUR FERRO

Revision date: 27.06.2022

Product code: 00359-1177

Page 13 of 13

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)