

ESKANOL EF SOLUTION

Revision date: 14.02.2022

Product code: 00359-1298

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ESKANOL EF SOLUTION

Art.-No.

10019, 10020

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

bonding material

1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
Public Poisons Information Line: +353 (0) 1 809 2166 (8am-10pm 7 days a week)

Further Information

EC-SDS applicable for following products:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Irrit. 2; H315

Eye Irrit. 2; H319

Skin Sens. 1; H317

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

bis-[4-(2,3-epoxipropoxy)phenyl]propane


Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane

Bisphenol-F epoxy resin

Phenol, methylstyrenated

Signal word: Warning

Pictograms:



Hazard statements

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

H319

Causes serious eye irritation.

H411

Toxic to aquatic life with long lasting effects.

ESKANOL EF SOLUTION

Revision date: 14.02.2022

Product code: 00359-1298

Page 2 of 11

Precautionary statements

- P260 Do not breathe vapour.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P273 Avoid release to the environment.
 P391 Collect spillage.

Special labelling of certain mixtures

- EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture containing following substances with additives :

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
1675-54-3	bis-[4-(2,3-epoxipropoxy)phenyl]propane			< 60 %
	216-823-5	603-073-00-2	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
933999-84-9	Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane			< 25 %
	618-939-5		01-2119463471-41	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H319 H317 H412			
9003-36-5	Bisphenol-F epoxy resin			< 20 %
	500-006-8		01-2119454392-40	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
68512-30-1	Phenol, methylstyrenated			< 10 %
	270-966-8		01-2119555274-38	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 3; H315 H317 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
1675-54-3	216-823-5	bis-[4-(2,3-epoxipropoxy)phenyl]propane	< 60 %
	Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100		
9003-36-5	500-006-8	Bisphenol-F epoxy resin	< 20 %
	dermal: LD50 = > 400 mg/kg; oral: LD50 = > 2000 mg/kg		



Safety Data Sheet

according to Regulation (EC) No 1907/2006



ESKANOL EF SOLUTION

Revision date: 14.02.2022

Product code: 00359-1298

Page 3 of 11

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.
Causes skin irritation.
May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide and carbon dioxide
Phenoles

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.

ESKANOL EF SOLUTION

Revision date: 14.02.2022

Product code: 00359-1298

Page 4 of 11

Remove persons to safety.

For non-emergency personnel

Avoid contact with skin, eyes and clothing.
Do not breathe vapours.

For emergency responders

In case of vapour formation use respirator.
Use personal protective clothing.

6.2. Environmental precautions

Clean contaminated surface thoroughly.
Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Informations for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.
Use only in thoroughly ventilated areas.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

No special protective measures against fire required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.
Protect against direct sun radiation.
Recommended storage temperature: 10°C - 30°C

Hints on joint storage

Incompatible with:
Oxidizing agents
Amines
Acids and bases.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

bonding material

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

This product does not contain any substances for which a Workplace Exposure Limit has been set in concentrations above the limits.

ESKANOL EF SOLUTION

Revision date: 14.02.2022

Product code: 00359-1298

Page 5 of 11

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off viton, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) approx. 30 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de.

Splash protection: Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) > 10 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

No personal respiratory protective equipment normally required.

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Various
Odour:	Soft

	Test method
pH-Value:	n. d.
Changes in the physical state	
Melting point/freezing point:	n. d.
Boiling point or initial boiling point and boiling range:	> 93 °C (Calculated)
Sublimation point:	n.a.
Softening point:	n. d.
Flash point:	> 93 °C
Flammability	
Solid/liquid:	n.a.
Gas:	n.a.
Explosive properties	
The product is not explosive.	
Lower explosion limits:	n. d.

ESKANOL EF SOLUTION

Revision date: 14.02.2022

Product code: 00359-1298

Page 6 of 11

Upper explosion limits:	n. d.
Auto-ignition temperature:	n. d.
Self-ignition temperature	
Solid:	n.a.
Gas:	n.a.
Decomposition temperature:	n. d.
Oxidizing properties	
Not oxidising.	
Vapour pressure:	n. d.
Density (at 20 °C):	approx. 1,14 g/cm ³
Bulk density:	n.a.
Water solubility: (at 20 °C)	Immiscible
Solubility in other solvents	
n. d.	
Partition coefficient n-octanol/water:	n. d.
Viscosity / dynamic:	465 - 700 mPa·s
Viscosity / kinematic:	n. d.
Flow time:	n. d.
Relative vapour density:	n. d.
Evaporation rate:	n. d.
Solvent separation test:	n. d.
Solvent content:	0 %

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidising agents.
Reactions with amines.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.
Protect against direct sun radiation.

10.5. Incompatible materials

Strong oxidizing agents
Amines
Acids and bases

10.6. Hazardous decomposition products

No known hazardous decomposition products.
Fire may produce:
Carbon monoxide and carbon dioxide
Phenol

ESKANOL EF SOLUTION

Revision date: 14.02.2022

Product code: 00359-1298

Page 7 of 11

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.
No toxicological data available.

Irritation and corrosivity

Causes skin irritation.
Causes serious eye irritation.

Sensitising effects

Contains epoxy constituents. May produce an allergic reaction. May cause an allergic skin reaction. (bis-[4-(2,3-epoxypropoxy)phenyl]propane; Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane; Bisphenol-F epoxy resin; Phenol, methylstyrenated)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.
Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Not readily biodegradable.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no component meets the criteria.
No data available

12.7. Other adverse effects

Hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

ESKANOL EF SOLUTION

Revision date: 14.02.2022

Product code: 00359-1298

Page 8 of 11

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.
Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080411 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); adhesive and sealant sludges containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packagings are to be treated like the product itself.
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.
Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Epoxy resin)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

Limited quantity:

5 L / 30 kg

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

-

Inland waterways transport (ADN)

14.1. UN number:

UN 3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Epoxy resin)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Hazard label:

9



Classification code:

M6

Special Provisions:

274 335 375 601

ESKANOL EF SOLUTION

Revision date: 14.02.2022

Product code: 00359-1298

Page 9 of 11

Limited quantity: 5 L / 30 kg
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Marine pollutant: Yes
Special Provisions: 274, 335, 969
Limited quantity: 5 L / 30 kg
Excepted quantity: E1
EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
Hazard label: 9



Special Provisions: A97 A158 A197 A215
Limited quantity Passenger: 30 kg G
Passenger LQ: Y964
Excepted quantity: E1
IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

**14.6. Special precautions for user**

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

ESKANOL EF SOLUTION

Revision date: 14.02.2022

Product code: 00359-1298

Page 10 of 11

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2004/42/EC (VOC): < 5 %

Information according to 2012/18/EU (SEVESO III): E2 Hazardous to the Aquatic Environment

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2.

Changes in chapter:

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method



Safety Data Sheet

according to Regulation (EC) No 1907/2006



ESKANOL EF SOLUTION

Revision date: 14.02.2022

Product code: 00359-1298

Page 11 of 11

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

'The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)