



**ESKANOL PO SOLUTION**

Revision date: 23.08.2022

Product code: 00359-1326

Page 2 of 11

**Precautionary statements**

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.

**2.3. Other hazards**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Mixture containing following substances with additives :

**Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
100-42-5	Styrene			< 45 %
	202-851-5	601-026-00-0	01-2119457861-32	
	Flam. Liq. 3, Repr. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 3; H226 H361d H332 H315 H319 H335 H372 H304 H412			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
100-42-5	202-851-5	Styrene	< 45 %	
	inhalation: LC50 = 12 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = 2650 mg/kg			

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.  
In the event of persistent symptoms receive medical treatment.  
Take away from danger area and lay down affected person.

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours.

## ESKANOL PO SOLUTION

Revision date: 23.08.2022

Product code: 00359-1326

Page 3 of 11

Seek medical treatment immediately.

### After contact with skin

Wash off immediately with soap and plenty of water.  
Treat subsequently with skin cream.  
Consult a doctor if skin irritation persists.

### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Consult (eye) doctor immediately.

### After ingestion

Do not induce vomiting.  
Summon a doctor immediately.  
Rinse out mouth and give plenty of water to drink.  
Never give anything by mouth to an unconscious person.  
Induce vomiting only upon the advice of a physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause respiratory irritation.  
Causes damage to organs through prolonged or repeated exposure. (the ear)  
Suspected of damaging the unborn child.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

#### Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire may produce:  
carbon monoxide and carbon dioxide  
Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

### Additional information

Vapours are heavier than air and spread along ground.  
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.  
Cool containers at risk with water spray jet.  
Collect contaminated firefighting water separately, must not be discharged into the drains.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Ensure adequate ventilation.  
Remove persons to safety.  
Keep away sources of ignition.

## ESKANOL PO SOLUTION

Revision date: 23.08.2022

Product code: 00359-1326

Page 4 of 11

### For non-emergency personnel

Avoid contact with skin, eyes and clothing.  
Do not breathe vapours.

### For emergency responders

In case of vapour formation use respirator.  
Use personal protective clothing.

### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.  
Do not discharge into the subsoil/soil.

### 6.3. Methods and material for containment and cleaning up

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

#### For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).  
Shovel into suitable container for disposal.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).  
Informations for disposal look up chapter 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed.  
Vapours are heavier than air and spread along ground.  
Use only in thoroughly ventilated areas.  
Provide suitable extraction at the processing machines.

#### Advice on protection against fire and explosion

Keep away from heat and sources of ignition.  
Do not smoke.  
Take precautionary measures against static discharges.  
Use only explosion-proof equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.  
Pay attention to anti-explosion rules.  
Avoid temperatures above 25°C .

#### Hints on joint storage

Incompatible with:  
Oxidizing agents, Metal halogenides, Peroxides

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Mortar

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

## ESKANOL PO SOLUTION

Revision date: 23.08.2022

Product code: 00359-1326

Page 5 of 11

### Occupational exposure limits

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
100-42-5	Styrene	20	85		TWA (8 h)	
		40	170		STEL (15 min)	

### Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
100-42-5	Styrene	Mandelic acid plus phenylglyoxylic acid	400 mg/g	Creatinine	End of shift

## 8.2. Exposure controls

### Appropriate engineering controls

- Ensure adequate ventilation, especially in confined areas.
- Pay attention to explosion protection rules.

### Protective and hygiene measures

- Do not inhale vapours.
- Wash hands before breaks and immediately after handling the product.
- When using do not eat, drink or smoke.
- Treat subsequently with skin cream.
- Remove and wash contaminated clothes before re-use.

### Eye/face protection

- Eye wash bottle with pure water (EN 15154).
- Tightly fitting goggles (EN 166).

### Hand protection

- Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.
- This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
- Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.
- Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

### Skin protection

- Long sleeved clothing (DIN EN ISO 6530)
- Solvent-resistant apron (EN 467).

### Respiratory protection

- In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	Light yellow	
Odour:	Pungent	
pH-Value:		n. d.

### Changes in the physical state

Melting point/freezing point:		n. d.
Boiling point or initial boiling point and boiling range:		145 - 146 °C

## ESKANOL PO SOLUTION

Revision date: 23.08.2022

Product code: 00359-1326

Page 6 of 11

Sublimation point:	n.a.
Softening point:	n. d.
Flash point:	34 °C
Sustaining combustion:	Sustaining combustion

### Flammability

Solid/liquid:	n.a.
Gas:	n.a.

### Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	n. d.
Upper explosion limits:	n. d.
Auto-ignition temperature:	490 °C

### Self-ignition temperature

Solid:	n.a.
Gas:	n.a.

Decomposition temperature:	n. d.
----------------------------	-------

### Oxidizing properties

Not oxidising.

Vapour pressure: (at 20 °C)	6,24 hPa
Density (at 25 °C):	1,1 g/cm <sup>3</sup>
Bulk density:	n.a.
Water solubility: (at 20 °C)	Immiscible

### Solubility in other solvents

n. d.

Partition coefficient n-octanol/water:	n. d.
Viscosity / dynamic: (at 25 °C)	180 - 240 mPa·s
Viscosity / kinematic: (at 40 °C)	> 20,5 mm <sup>2</sup> /s
Flow time:	n. d.
Relative vapour density:	n. d.
Evaporation rate:	n. d.
Solvent separation test:	n. d.
Solvent content:	41 %

### 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No decomposition if stored and applied as directed.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

## ESKANOL PO SOLUTION

Revision date: 23.08.2022

Product code: 00359-1326

Page 7 of 11

Reactions with oxidising agents.

Reactions with peroxides.

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

Avoid temperatures above 50°C.

If heating up polymerisation.

### 10.5. Incompatible materials

Oxidizing agents, Metal halogenides, Peroxides

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

Fire may produce:

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

Carbon monoxide and carbon dioxide

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

No toxicological data available.

Styrene

LD50/oral/rat: 5000 mg/kg

LD50/dermal/rat: > 2000 mg/kg

LC50/inhalativ/rat: 11,8 mg/l/4h

#### **Irritation and corrosivity**

Causes skin irritation.

Causes serious eye irritation.

#### **Sensitising effects**

Based on available data, the classification criteria are not met.

#### **Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of damaging the unborn child. (Styrene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

May cause respiratory irritation. (Styrene)

#### **STOT-repeated exposure**

Causes damage to organs through prolonged or repeated exposure. (Styrene)

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

### 11.2. Information on other hazards

#### **Endocrine disrupting properties**

No data available

#### **Other information**

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006



### ESKANOL PO SOLUTION

Revision date: 23.08.2022

Product code: 00359-1326

Page 8 of 11

#### SECTION 12: Ecological information

##### 12.1. Toxicity

Ecological dates are not available.  
Harmful to aquatic life with long lasting effects.  
Styrene  
LC50/Pimephales promelas/96 h = 4,02 mg/l  
EC50/Daphnia magna/48 h = 4,7 mg/lg  
NOEC//Daphnia magna/21 d = 1,01 mg/l  
EC50/Selenastrum capricornutum/72 h = 4,9 mg/l  
EC10/Selenastrum capricornutum/96 d = 0,28 mg/l

##### 12.2. Persistence and degradability

No data available

##### 12.3. Bioaccumulative potential

No data available

##### 12.4. Mobility in soil

No data available

##### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

##### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

##### 12.7. Other adverse effects

Hazard to waters.  
Product is toxic to fish and their nutrient animals.

##### **Further information**

Do not flush into surface water or sanitary sewer system.

#### SECTION 13: Disposal considerations

##### 13.1. Waste treatment methods

###### **Disposal recommendations**

Can be incinerated, when in compliance with local regulations.  
Where possible recycling is preferred to disposal.

###### **List of Wastes Code - residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

###### **Contaminated packaging**

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.  
Packaging that cannot be cleaned should be disposed of like the product.

#### SECTION 14: Transport information

##### **Land transport (ADR/RID)**

**14.1. UN number:** UN 1866  
**14.2. UN proper shipping name:** Resin solution  
**14.3. Transport hazard class(es):** 3



## ESKANOL PO SOLUTION

Revision date: 23.08.2022

Product code: 00359-1326

Page 9 of 11

**14.4. Packing group:**

III

Hazard label:

3



Classification code:

F1

Limited quantity:

5 L / 30 kg

Excepted quantity:

E1

Transport category:

3

Hazard No:

30

Tunnel restriction code:

D/E

**Inland waterways transport (ADN)****14.1. UN number:**

UN 1866

**14.2. UN proper shipping name:**

Resin solution

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

III

Hazard label:

3



Classification code:

F1

Limited quantity:

5 L / 30 kg

Excepted quantity:

E1

**Marine transport (IMDG)****14.1. UN number:**

UN 1866

**14.2. UN proper shipping name:**

Resin solution

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

III

Hazard label:

3



Marine pollutant:

No

Limited quantity:

5 L / 30 kg

Excepted quantity:

E1

EmS:

F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number:**

UN 1866

**14.2. UN proper shipping name:**

Resin solution

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

III

Hazard label:

3



Limited quantity Passenger:

10 L

Passenger LQ:

Y344

## ESKANOL PO SOLUTION

Revision date: 23.08.2022

Product code: 00359-1326

Page 10 of 11

Excepted quantity:	E1	
IATA-packing instructions - Passenger:		355
IATA-max. quantity - Passenger:		60 L
IATA-packing instructions - Cargo:		366
IATA-max. quantity - Cargo:		220 L

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

### 14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC):	< 5 %; < 90 g/l
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS

#### National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
--------------------------	---

Water hazard class (D):	2 - obviously hazardous to water
-------------------------	----------------------------------

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 1,2,6,7,9,10,12,13,14,15.

### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses  
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure  
IMDG = International Maritime Code for Dangerous Goods  
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization  
MARPOL = International Convention for the Prevention of Pollution from Ships  
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

## ESKANOL PO SOLUTION

Revision date: 23.08.2022

Product code: 00359-1326

Page 11 of 11

GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals  
CAS = Chemical Abstract Service  
EN = European norm  
ISO = International Organization for Standardization  
DIN = Deutsche Industrie Norm  
PBT = Persistent Bioaccumulative and Toxic  
vPvB = Very Persistent and very Bio-accumulative  
LD = Lethal dose  
LC = Lethal concentration  
EC = Effect concentration  
IC = Median immobilisation concentration or median inhibitory concentration

### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 1; H372	Calculation method
Aquatic Chronic 3; H412	Calculation method

### Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

### Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*