

according to Regulation (EC) No 1907/2006



ESKANOL VE SF CONDUCTIVE GREY

Revision date: 09.07.2024

Product code: 00359-1361

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ESKANOL VE SF CONDUCTIVE GREY

Art.-No.

10801

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laminate resine

1.3. Details of the supplier of the safety data sheet

Company name:	TIP TOP Oberflaechenschutz Elbe GmbH	
Street:	Heuweg 4	
Place:	D-06886 Wittenberg	
Telephone:	+49(0)3491/635-50	Telefax:+49(0)3491/635-552
Responsible Department:	Responsible for the safety data sheet: sds@g	bk-ingelheim.de
1.4. Emergency telephone	INTERNATIONAL: +49 - (0) 6132 - 84463, GE	3K GmbH (24h - 7d/w - 365d/a)
<u>number:</u>	Public Poisons Information Line: +353 (0) 1 80 week)	09 2166 (8am-10pm 7 days a

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Tetramethylene dimethacrylate

Cobalt bis (2-ethylhexanoate)

2,2'-ethylenedioxydiethyl dimethacrylate

Signal word: Pictograms:



Hazard statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Precautionary statements

2	
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.



according to Regulation (EC) No 1907/2006



ESKANOL VE SF CONDUCTIVE GREY

Revision date: 09.07.2024

Product code: 00359-1361

Page 2 of 10

Special labelling of certain mixtures

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture containing following substances with additives :

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No	1272/2008)		
	Acrylated resin			< 60 %
	Skin Irrit. 2, Eye Irrit. 2; H315 H31	9		
2082-81-7	Tetramethylene dimethacrylate			< 50 %
	218-218-1		01-2119967415-30	
	Skin Sens. 1B; H317		•	
13463-67-7	titanium dioxide			< 5 %
	236-675-5	022-006-00-2	01-2119489379-17	
	Carc. 2; H351			
109-16-0	2,2'-ethylenedioxydiethyl dimethad		< 1 %	
	203-652-6		01-2119969287-21	
	Skin Sens. 1B; H317			
27253-31-2	Cobalt bis (2-ethylhexanoate)			< 0,5 %
	248-373-0	607-230-00-6	01-2119970733-31	
	Repr. 1B, Acute Tox. 4, Skin Sens	. 1, Aquatic Chronic 3; H36	0D H302 H317 H412	
79-10-7	Acrylic acid			< 1 %
	201-177-9	607-061-00-8	01-2119452449-31	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 2; H226 H332 H312 H302 H314 H318 H400 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. L	imits, M-factors and ATE	
27253-31-2	248-373-0	Cobalt bis (2-ethylhexanoate)	< 0,5 %
	oral: ATE = 500 mg/kg		
79-10-7	201-177-9 Acrylic acid		< 1 %
	inhalation: LC50 = 3,6 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = > 290 mg/kg; oral: LD50 = > 192 mg/kg STOT SE 3; H335: >= 1 - 100 Aquatic Acute 1; H400: M=1		



according to Regulation (EC) No 1907/2006



ESKANOL VE SF CONDUCTIVE GREY

Revision date: 09.07.2024

Product code: 00359-1361

Page 3 of 10

Further Information

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter < = $10 \mu m$.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately. In the event of persistent symptoms receive medical treatment. Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours. In case of the person being unconscious put him/her in a stable side position. If symptoms persist, call a physician.

After contact with skin

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult (eye) doctor immediately.

After ingestion

Do not induce vomiting. Summon a doctor immediately. Rinse out mouth and give plenty of water to drink. Never give anything by mouth to an unconscious person. Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray. Fire-extinguishing activities according to surrounding.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide and carbon dioxide

Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.



according to Regulation (EC) No 1907/2006



ESKANOL VE SF CONDUCTIVE GREY

Revision date: 09.07.2024

Product code: 00359-1361

Page 4 of 10

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation. Keep away sources of ignition. Remove persons to safety.

For non-emergency personnel

Do not breathe vapours.

Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator. Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Informations for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Use only in thoroughly ventilated areas. Provide suitable extraction at the processing machines. Avoid contact with skin, eyes and clothing. When using do not eat, drink or smoke.

Advice on protection against fire and explosion

No special protective measures against fire required.

Advice on general occupational hygiene

Do not inhale vapours. Wash hands before breaks and immediately after handling the product. When using do not eat, drink or smoke. Remove and wash contaminated clothes before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Hints on joint storage

Incompatible with: Peroxides Bases

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.



according to Regulation (EC) No 1907/2006



ESKANOL VE SF CONDUCTIVE GREY

Revision date: 09.07.2024

Product code: 00359-1361

Page 5 of 10

7.3. Specific end use(s)

Laminate resine

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
79-10-7	Acrylic acid	10	29		TWA (8 h)	
		20	59		STEL (1 min)	
13463-67-7	Titanium dioxide, respirable dust	-	4		TWA (8 h)	
13463-67-7	Titanium dioxide, total inhalable dust	-	10		TWA (8 h)	

Additional advice on limit values

This product does not contain any substances for which a Workplace Exposure Limit has been set in concentrations above the limits.

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.43 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril 732> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

•	i information on pasic physical and che	mear properties			
	Physical state:	Viscous			
	Colour:	Grey			
	Odour:	Characteristic			
				Test method	
	Changes in the physical state				
	Melting point/freezing point:		n. d.		
	Boiling point or initial boiling point and		> 200 °C		
	boiling range:				
	Sublimation point:		n.a.		
	Softening point:		n. d.		
	- ·				



according to Regulation (EC) No 1907/2006



ESK	ANOL VE SF CONDUCTIVE GREY	
Revision date: 09.07.2024	Product code: 00359-1361	Page 6 of 10
Pour point:	n.a.	
Flash point:	> 100 °C	
Flammability Solid/liquid:	n.a.	
Explosive properties The product is considered non-explosive	nethertheless explosive vapour/air mixture can b	e generated.
Lower explosion limits:	n. d.	
Upper explosion limits:	n. d.	
Auto-ignition temperature:	n. d.	
Self-ignition temperature Solid: Gas:	n.a. n.a.	
Decomposition temperature:	n. d.	
pH-Value:	n. d.	
Viscosity / dynamic: (at 25 °C)	1700 mPa·s	
Viscosity / kinematic:	n. d.	
Flow time:	n. d.	
Water solubility: (at 20 °C)	Immiscible	OECD 105
Solubility in other solvents n. d.		
Partition coefficient n-octanol/water:	n. d.	
Vapour pressure:	n. d.	
Density (at 20 °C):	1,15 g/cm³	
Bulk density:	n.a.	
Relative vapour density:	n. d.	
9.2. Other information		
Information with regard to physical hazard Oxidizing properties Not oxidising.	classes	
Other safety characteristics		
Solvent separation test:	n. d.	
Solvent content:	n. d.	
Evaporation rate:	n. d.	
Further Information		
No data available.		
SECTION 10: Stability and reactivity		

10.1. Reactivity

No decomposition if stored and applied as directed. If heating up polymerisation.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions



according to Regulation (EC) No 1907/2006



ESKANOL VE SF CONDUCTIVE GREY

Revision date: 09.07.2024

Product code: 00359-1361

Page 7 of 10

Reactions with peroxides. Reactions with alkalies.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

10.5. Incompatible materials

Peroxides Bases.

10.6. Hazardous decomposition products

No hazardous decomposition products known. Fire may produce: Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases). Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

No toxical dates available.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (Tetramethylene dimethacrylate; 2,2'-ethylenedioxydiethyl dimethacrylate; Cobalt bis (2-ethylhexanoate))

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecological dates are not available.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential



according to Regulation (EC) No 1907/2006



ESKANOL VE SF CONDUCTIVE GREY

Revision date: 09.07.2024

Product code: 00359-1361

Page 8 of 10

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazard to waters.

Further information

080409

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations. Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:14.2. UN proper shipping name:14.3. Transport hazard class(es):14.4. Packing group:

Inland waterways transport (ADN) <u>14.1. UN number or ID number:</u> 14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Marine transport (IMDG) <u>14.1. UN number or ID number:</u>

14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packing group:

Air transport (ICAO-TI/IATA-DGR) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.



according to Regulation (EC) No 1907/2006



ES	KANOL VE SF CONDUCTIVE GREY	
Revision date: 09.07.2024	Product code: 00359-1361	Page 9 of 10
14.4. Packing group:	No dangerous good in sense of this transport regulation.	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
14.6. Special precautions for user		
No dangerous good in sense of this trar		
14.7. Maritime transport in bulk according to		
No dangerous good in sense of this trar	nsport regulation.	
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regulation	ations/legislation specific for the substance or mixture	
EU regulatory information		
Restrictions on use (REACH, annex XVII):		
Entry 3, Entry 75		
Information according to Directive 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)	
National regulatory information		
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juven work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.	
Water hazard class (D):	2 - obviously hazardous to water	
15.2. Chemical safety assessment		
For this substance a chemical safety as	sessment has not been carried out.	

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

- ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
- IMDG = International Maritime Code for Dangerous Goods
- IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
- MARPOL = International Convention for the Prevention of Pollution from Ships
- IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

- REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
- CAS = Chemical Abstract Service
- EN = European norm
- ISO = International Organization for Standardization
- DIN = Deutsche Industrie Norm
- PBT = Persistent Bioaccumulative and Toxic
- vPvB = Very Persistent and very Bio-accumulative
- LD = Lethal dose
- LC = Lethal concentration
- EC = Effect concentration
- IC = Median immobilisation concentration or median inhibitory concentration



according to Regulation (EC) No 1907/2006



ESKANOL VE SF CONDUCTIVE GREY

Revision date: 09.07.2024

Product code: 00359-1361

Page 10 of 10

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H360D	May damage the unborn child.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)