

ESKANOL VE SOLUTION 430

Revision date: 23.08.2022

Product code: 00359-1325

Page 2 of 11

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe vapour.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P405 Store locked up.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture containing following substances with additives :

Hazardous components

CAS No	Chemical name	Quantity
	EC No Index No REACH No	
	GHS Classification	
100-42-5	Styrene	< 50 %
	202-851-5 601-026-00-0 01-2119457861-32	
	Flam. Liq. 3, Repr. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 3; H226 H361d H332 H315 H319 H335 H372 H304 H412	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
100-42-5	202-851-5	Styrene	< 50 %
		inhalation: LC50 = 12 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: LD50 = 2650 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
 In the event of persistent symptoms receive medical treatment.
 Take away from danger area and lay down affected person.

ESKANOL VE SOLUTION 430

Revision date: 23.08.2022

Product code: 00359-1325

Page 3 of 11

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
Seek medical treatment immediately.

After contact with skin

Wash off immediately with soap and plenty of water.
Treat subsequently with skin cream.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Consult (eye) doctor immediately.

After ingestion

Do not induce vomiting.
Summon a doctor immediately.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Harmful if inhaled.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
Causes damage to organs through prolonged or repeated exposure. (the ear)
Suspected of damaging the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide and carbon dioxide
Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Vapours are heavier than air and spread along ground.
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
Cool containers at risk with water spray jet.
Collect contaminated firefighting water separately, must not be discharged into the drains.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.

ESKANOL VE SOLUTION 430

Revision date: 23.08.2022

Product code: 00359-1325

Page 4 of 11

Remove persons to safety.
Keep away sources of ignition.

For non-emergency personnel

Avoid contact with skin, eyes and clothing.
Do not breathe vapours.

For emergency responders

In case of vapour formation use respirator.
Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.
Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Informations for disposal look up chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.
Vapours are heavier than air and spread along ground.
Use only in thoroughly ventilated areas.
Provide suitable extraction at the processing machines.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.
Do not smoke.
Take precautionary measures against static discharges.
Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.
Pay attention to anti-explosion rules.
Avoid temperatures above 50°C.

Hints on joint storage

Incompatible with:
Oxidizing agents, Metal halogenides, Peroxides

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Mortar

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ESKANOL VE SOLUTION 430

Revision date: 23.08.2022

Product code: 00359-1325

Page 5 of 11

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
100-42-5	Styrene	20	85		TWA (8 h)	
		40	170		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
100-42-5	Styrene	Mandelic acid plus phenylglyoxylic acid	400 mg/g	Creatinine	End of shift

8.2. Exposure controls

Appropriate engineering controls

- Ensure adequate ventilation, especially in confined areas.
- Pay attention to explosion protection rules.

Protective and hygiene measures

- Do not inhale vapours.
- Wash hands before breaks and immediately after handling the product.
- When using do not eat, drink or smoke.
- Treat subsequently with skin cream.
- Remove and wash contaminated clothes before re-use.

Eye/face protection

- Eye wash bottle with pure water (EN 15154).
- Tightly fitting goggles (EN 166).

Hand protection

- Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm, permeation time of approx. 480 minutes.
- This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
- Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.
- Pls. find examples in the protective gloves database under: <http://bestglove.com/site/chemrest/>

Skin protection

- Long sleeved clothing (DIN EN ISO 6530)
- Solvent-resistant apron (EN 467).

Respiratory protection

- In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Yellow
Odour:	Pungent

pH-Value: n. d.

Changes in the physical state

Melting point/freezing point: - 31 °C (*)

Test method

ESKANOL VE SOLUTION 430

Revision date: 23.08.2022

Product code: 00359-1325

Page 6 of 11

Boiling point or initial boiling point and boiling range:	145 °C (*)
Sublimation point:	n.a.
Softening point:	n. d.
Flash point:	31 °C ISO 3680
Sustaining combustion:	Sustaining combustion

Flammability

Solid/liquid:	n.a.
Gas:	n.a.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	1,1 vol. % (*)
Upper explosion limits:	6,1 vol. % (*)
Auto-ignition temperature:	490 °C (*)

Self-ignition temperature

Solid:	n.a.
Gas:	n.a.

Decomposition temperature:	n. d.
----------------------------	-------

Oxidizing properties

Not oxidising.

Vapour pressure: (at 20 °C)	6,7 hPa (*)
--------------------------------	-------------

Density (at 25 °C):	1,03 - 1,16 g/cm ³
---------------------	-------------------------------

Bulk density:	n.a.
---------------	------

Water solubility: (at 20 °C)	Immiscible
---------------------------------	------------

Solubility in other solvents

n. d.

Partition coefficient n-octanol/water:	n. d.
--	-------

Viscosity / dynamic: (at 25 °C)	350 - 500 mPa·s
------------------------------------	-----------------

Viscosity / kinematic: (at 40 °C)	> 20,5 mm ² /s
--------------------------------------	---------------------------

Flow time:	n. d.
------------	-------

Relative vapour density:	n. d.
--------------------------	-------

Evaporation rate:	n. d.
-------------------	-------

Solvent separation test:	n. d.
--------------------------	-------

Solvent content:	n. d.
------------------	-------

9.2. Other information

(*) Styrene

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

ESKANOL VE SOLUTION 430

Revision date: 23.08.2022

Product code: 00359-1325

Page 7 of 11

10.3. Possibility of hazardous reactions

Reactions with oxidising agents.
Reactions with peroxides.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.
Vapour/air mixtures are explosive at intensive warming.
Heating can release vapours which can be ignited.
Avoid temperatures above 50°C.
If heating up polymerisation.

10.5. Incompatible materials

Oxidizing agents, Metal halogenides, Peroxides

10.6. Hazardous decomposition products

No known hazardous decomposition products.
Fire may produce:
Irritant/corrosive, flammable as well as toxic distillation gases (carbonization gases).
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.
No toxicol dates available.
Styrene
LD50/oral/rat: 5000 mg/kg
LD50/dermal/rat: > 2000 mg/kg
LC50/inhalativ/rat: 11,8 mg/l/4h

Irritation and corrosivity

Causes skin irritation.
Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (Styrene)
Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Styrene)

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure. (Styrene)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the

ESKANOL VE SOLUTION 430

Revision date: 23.08.2022

Product code: 00359-1325

Page 8 of 11

product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological dates are not available.

Harmful to aquatic life with long lasting effects.

Styrene

LC50/Pimephales promelas/96 h = 4,02 mg/l

EC50/Daphnia magna/48 h = 4,7 mg/lg

NOEC//Daphnia magna/21 d = 1,01 mg/l

EC50/Selenastrum capricornutum/72 h = 4,9 mg/l

EC10/Selenastrum capricornutum/96 d = 0,28 mg/l

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Hazard to waters.

Product is toxic to fish and their nutrient animals.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN 1866

14.2. UN proper shipping name:

Resin solution

ESKANOL VE SOLUTION 430

Revision date: 23.08.2022

Product code: 00359-1325

Page 9 of 11

14.3. Transport hazard class(es): 3

14.4. Packing group: III

Hazard label: 3



Classification code: F1

Limited quantity: 5 L / 30 kg

Excepted quantity: E1

Transport category: 3

Hazard No: 30

Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1866

14.2. UN proper shipping name: Resin solution

14.3. Transport hazard class(es): 3

14.4. Packing group: III

Hazard label: 3



Classification code: F1

Limited quantity: 5 L / 30 kg

Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1866

14.2. UN proper shipping name: Resin solution

14.3. Transport hazard class(es): 3

14.4. Packing group: III

Hazard label: 3



Marine pollutant: No

Limited quantity: 5 L / 30 kg

Excepted quantity: E1

EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1866

14.2. UN proper shipping name: Resin solution

14.3. Transport hazard class(es): 3

14.4. Packing group: III

Hazard label: 3



Limited quantity Passenger: 10 L

ESKANOL VE SOLUTION 430

Revision date: 23.08.2022

Product code: 00359-1325

Page 10 of 11

Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:		355
IATA-max. quantity - Passenger:		60 L
IATA-packing instructions - Cargo:		366
IATA-max. quantity - Cargo:		220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC):	< 5 %; < 90 g/l
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water hazard class (D):	2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,6,7,9,10,11,12,13,14,15.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

ESKANOL VE SOLUTION 430

Revision date: 23.08.2022

Product code: 00359-1325

Page 11 of 11

GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)